September 17, 1991 BEI Job No. 88288

Cowell: Chies sete



Mr. Larry Seto
Alameda County Health Care Services Agency
Division of Hazardous Materials
Department of Environmental Health
80 Swan Way, Room 200
Oakland, CA 94621

Subject:

GI Trucking Company

1750 Adams Avenue, San Leandro, CA

Quarterly Groundwater Sampling

Dear Mr. Seto:

This documents the fourth quarterly groundwater sampling for the third year at the subject facility.

Four of the five existing monitoring wells (MW-2 through MW-5, Figure 1) were sampled on August 28, 1991. Well MW-1 contained a phase-separated hydrocarbon layer with a thickness of 0.09 feet. A water sample was not collected from this well.

Three well casing volumes of water were removed from each well prior to sampling. A representative sample was collected from each well using a Teflon bailer and placed in one-liter amber bottles provided by the laboratory. The Well Purging and Sampling Data forms for all wells are enclosed. The groundwater samples were placed in a cooler with blue ice and delivered via courier to NET Pacific, Inc., a California-certified laboratory.

The water samples were analyzed for Total Petroleum Hydrocarbons (TPH) as diesel using modified EPA Method 8015. As indicated in the enclosed analytical report, TPH as diesel was not found in samples from wells MW-2, MW-4, and MW-5 at or above the reporting limit of 0.05 parts per million (ppm). TPH as diesel was detected at a concentration of 0.24 ppm in well

This sampling event completes the third year of quarterly groundwater monitoring at this site. TPH as diesel was first detected in the groundwater sample from well MW-3 collected in February 1990, and, except in December 1990, has been detected in all groundwater samples from this well since February 1990, at concentrations ranging from 0.24 ppm to 1.3 ppm. TPH as diesel has not been detected in any groundwater samples from wells MW-2, MW-4, and MW-5. Blymyer Engineers will continue to perform quarterly groundwater sampling for wells MW-2 through MW-5 for another year.

If you have any questions, please contact me at (415) 521-3773.

Cordially,

Blymyer Engineers, Inc.

Michael S. L

Michael S. Lewis

Manager, UST Services

Enclosures

cc: Mr. Lester Feldman, RWQCB

Mr. Mike Bakaldin, San Leandro Fire Department


Mr. Curtis Carr, Carolina Freight Carriers Corporation

Mr. Bob Hogancamp, GI Trucking Company

Mr. Tom McGuire, GI Trucking Company

mf\88288.4Q3





DATE 8/28/91	PROJECT NUMBER 8828	PROJECT 8 NAME G	TRUCKING	_
WELL MW-1	BORING N/A	CASING DIAMETER	12"	<u>-</u>
Column of Liquid in Well		Volume to be Removed	= 0.17	
Depth to product (6' 2-5/		Gallon per foot of casing Column of water	х	
Depth to water (6' 3-6/)	8" <u>) 6.31</u> ft	Volume of casing Number of volumes		
Total depth of well		to remove Total volume to	х	
Column of water		removė		
Method of measuring liquid	OIL/WATER INTERF	ACE PROBE		-
Method of purging well	N/A		rate	-
Method of decon	ALCONOX AND DI W	ATER		-
Physical appearance of water (clari				
_				
- 				-
_ 				_
r mar				
Field Analysis	<u>Initial</u>	<u>During</u>	<u>Final</u>	
Time				
Conductivity (µs/em)				
p H				
Temperature ("F")				
Method of measurement				-
Total of volume purged				
Comments OBTAIN DEPT	H TO PRODUCT/DEP	TH TO WATER ONL	Y: PRODUCT LAYER	= 0.09f
Sample Number		Amount of Sample		-
Preservative (circle one)	None HCI	${ m HNO_3}$	H ₂ SO ₄	
Signed/Sampler	11 W Illow	Date	0/0/2/	-
Signed/Reviewer Much	all.To	Date	9/17/71	-

DATE 8/28/91	PROJECT NUMBER 8828	8 PRO-	JECT DE GITR	UCKING	
WELL MW-2 NUMBER MW-2	BORING DIAMETER N/A	CASI DIAM	ING METER	2"	
Column of Liquid in Well		Volume to be		0.17 gal/ft	
Depth to product	N/A	Gallon per foot Column of wat		<u>16.57</u> ft	
Depth to water (6 ' 8-1/8")	<u>6.68</u> ft	Volume of casi Number of vol		<u>2.8</u> gal	
Total depth of well	<u>23.25</u> ft	to remov e Total volume t	x o	3	
Column of water	<u>16.57</u> ft	remove	=	<u>8.4</u> ga1	
Method of measuring liquid 0 I L	/WATER INTERFA				
Method of purging well TEF	LON BAILER		<u> </u>	rateN/A	
Method of decon ALC	ONOX AND DI WA	TER			
Physical appearance of water (clarity Initial SLI	, color, particulates, odor) GHTLY SILTY, N	O ODOR			
	TY, NO ODOR				
V	TY, NO ODOR				
Field Analysis	<u>Initial</u>	<u>Dur</u>	ing	Final	
Time	1.2:08	12:22	12:30	12:37_	
Conductivity (µs/cm)	9420	9120	9040	9350	
pH	7.52	<u>7.51</u>	<u>7.49</u>	7.44	
Temperature (°F)	67.9	67.2	67.2	67_8	
Method of measurement HY	DAC METER				
Total of volume purged 8.	5 gal		<u></u>		
Comments				- ambar alace	hott1
Sample Number MW-3 MW	<u>-2</u>	Amount of San		er amber glass	DOLLI
Preservative (circle one)	None HCI	HNO	_		
Signed/Sampler	a Mllove		Date 8/3	28/91	
Simo & Province Machan	K1.70		Date 7	17/91	

DATE 8/28/91	PROJECT NUMBER 88288	Projec Name_	T GI TRUCK	ING	
WELL NUMBER MW-3	BORING DIAMETER N/A	CASING DIAMET			
Column of Liquid in Well		Volume to be Rei		0 171/56	
Depth to product	N/A	Gailon per foot of o Column of water	casing = x	$\frac{0.17 \text{ gal/ft}}{16.13}$ ft	
Depth to water $(6^{\circ} 7-1/2^{\circ})$	<u>6.62</u> ft	Volume of casing Number of volume	= 8	2.7 gal	
Total depth of well	22.75 ft	to remove Total volume to	x	3	
Column of water	<u>16.13</u> ft	remove	#	8.1	
Method of measuring liquid	OIL/WATER INTE	RFACE PROBE	<u> </u>		
Method of purging well	TEFLON BAILER		<u> </u>	rate_N/A	
Method of decon	ALCONOX AND DI	WATER			
Physical appearance of water (clarity	, color, particulates, odor)				
Initial	SLIGHTLY SILTY	NO ODOR			
During	SILTY, NO ODOR				
Final	SLIGHTLY SILTY	, NO ODOR			
Field Analysis	<u>Initial</u>	During		Final	
Time	<u>13:10</u>	<u>13:16</u>	13:21	13:28	
Conductivity (µs/cm)	816	889	909	920	
р Н	7.36	7.34_	7.13	7.10	
Temperature (°F)	69.9	70.1	69.5	69.3	
Method of measurement	HYDAC METER				
Total of volume purged	8.25				
Comments				1	1. a + 4 1 -
Sample Number MW-3		Amount of Sample		<u>amber glas</u> s	DOLLTE
Preservative (circle one)	None HCI	HNO ₃	H ₂ SO ₄	0.407	
Signed/Sampler tint	CV Mlove		Date 8/2	8/91	
Signed/Reviewer Mucha	XX.50		Date9/1	7/91	

8/28/91 DATE	PROJECT 88288	PROJECT NAME	GI TRUC	CKING	
WELL NUMBER MW-4	BORING DIAMETER N/A	CASING DIAMETE	MR	2"	
Column of Liquid in Well		Volume to be Rem		0.17 gal/ft	-
Depth to product Depth to water (5 ' 8-3/8")	N/A 5.70 ft	Gallon per foot of ca Column of water Volume of casing	x =	17.09 ft 2.90 gal	
Total depth of well	22.79 ft	Number of volumes to remove Total volume to	x	3	
Column of water	<u>17.09</u> ft	remov e	=	8.7 gal	
Method of measuring liquid					
Method of purging well				rate N/A	
Method of decon	ALCONOX AND DI	L WATER			
Physical appearance of water (clarity, Initial	CLEAR, NO ODOR	R			
During	SILTY, NO ODOR	R			
Final	SILTY, NO ODOF	R			
Field Analysis	<u>Initial</u>	During		<u>Final</u>	
Time	9:46	<u>9:54</u> 1	0:02	<u> 10:11</u>	
Conductivity (µs/cm)	957	1000 9	98	962	
pΗ	7.80	7.52 7	-40	7.43	
Temperature (°F)	68.7	69.6	8.6	69.6	
Method of measurement	HYDAC METER				
Total of volume purged	9.0 GAL				
Comments					7
Sample Number MW-4				er glass amber	bс
Preservative (circle one)	None HCI	нио3	$_{ m H_2SO}$	4 ⁷ 2 8 <i>f</i> 9 <u>1</u>	
Signed/Sampler Turk	and S. D		Date 9/17	/91	

DATE8/28/91	PROJECT 88288	PROJECT NAME	GI TRUCKING	
WELL NUMBER MW-5	BORING DIAMETER N/A	CASING DIAMETER	2"	
Column of Liquid in Well		Volume to be Removed		
Depth to product	N/A	Gallon per foot of casing Column of water	$= \frac{0.17 \text{ gal/ft}}{16.35 \text{ ft}}$	
Depth to water $(5^{\circ} 10-3/4^{\circ})$	<u>5.90</u> ft	Volume of casing Number of volumes	= 2.8	
Total depth of well	22.25 ft	to remove Total volume to	x <u>3</u>	
Column of water	<u>16.35</u> ft	remove	= 8.4 ga1	
Method of measuring liquid	OIL/WATER INTER	RFACE PROBE		
Method of purging well	TEFLON BAILER		rate_N/A	
Method of decon	ALCONOX AND DI	WATER		•
Physical appearance of water (clarity,	color, particulates, odor)			
Initial	CLEAR, NO ODOR			
During	SLIGHTLY SILTY	, NO ODOR		
Final	SILTY, NO ODOR			
Field Analysis	Initial	During	Final	
Time	11:17_	11:23 11:3	11:39	
Conductivity (µs/cm)	918	924 932	940	
p H	7.49	7.50 7.43	7,47	
Temperature (°F)	70.1	69.0	69.3	
Method of measurement	HYDAC METER			
Total of volume purged	8.5 GALS			
Comments			<u> </u>	
Sample Number MW-5		Amount of Sample $3-1$	<u>liter amber glas</u> s b	ottles
Preservative (circle one)	None HCl	HNO ₃	$^{\mathrm{H}_2\mathrm{SO}_4}$	
Signed/Sampler	10 Mbour	Date_	8/28/91	
Signed/Reviewer Muchan	45.J	Date	9/17/91	



NATIONAL ENVIRONMENTAL TESTING INC

NET Pacific, Inc. 435 Tesconi Circle Santa Rosa, CA 95401

Tel: (707) 526-7200 Fax: (707) 526-9623

Michael Lewis Carolina Freight Carriers c/o Blymyer Engineers, Inc 1829 Clement Ave. Alameda, CA 94501

Date: 09-09-91

NET Client Acct No: 619 NET Pacific Log No: 9559 Received: 08-30-91 0800

Client Reference Information

GI Trucking/San Leandro, Project: 88288

Sample analysis in support of the project referenced above has been completed and results are presented on following pages. Please refer to the enclosed "Key to Abbreviations" for definition of terms. Should you have questions regarding procedures or results, please feel welcome to contact Client Services.

Approved by:

Jules Skamarack) | Laboratory Manager

JS:rct Enclosure(s)



Client No: 619

@Client Name: Carolina Freight Carriers

Date: 09-09-91

NET Log No: 9559

Page: 2

Ref: GI Trucking/San Leandro, Project: 88288

Descriptor, Lab No. and Results

			MW-4 08-28-91 1020	MW-5 08-28-91 1147	
Parameter	Method	Reporting Limit	96118	96119	Units
PETROLEUM HYDROCARBONS					
EXTRACTABLE (WATER)					
DILUTION FACTOR *			1	1	
DATE EXTRACTED			08-31-91	08-31-91	
DATE ANALYZED			09-03-91	09-03-91	
METHOD GC FID/3510					
as Diesel		0.05	ND	ND	mg/L



Client No: 619

NET Log No: 9559

[®]Client Name: Carolina Freight Carriers

Date: 09-09-91

Page:

Ref: GI Trucking/San Leandro, Project: 88288

Descriptor, Lab No. and Results

					
			MW-2 08-28-91 1245	MW-3 08-28-91 1335	
		Reporting			
Parameter	Method	Limit	96120	96121	Units
		<u>.</u>		<u></u>	
PETROLEUM HYDROCARBONS					
EXTRACTABLE (WATER)					
DILUTION FACTOR *			1	1	
DATE EXTRACTED			08-31-91	08-31 - 91	
DATE ANALYZED			09-03-91	09-03-91	
METHOD GC FID/3510					
as Diesel		0.05	ND	0.24	mg/L



Client Acct: 619 ®Client Name: Carolina Freight Carriers NET Log No: 9559

Ref: GI Trucking/San Leandro, Project: 88288

QUALITY CONTROL DATA

Date: 09-06-91

Page: 4

Parameter	Reporting Limits	Units	Cal Verf Stand % Recovery	Blank Data	Spike % Recovery	Duplicate Spike % Recovery	RPD
Diesel	0.05	mg/L	103	ND	88	81	7.4



KEY TO ABBREVIATIONS and METHOD REFERENCES

: Less than; When appearing in results column indicates analyte not detected at the value following. This datum supercedes the listed Reporting Limit.

: Reporting Limits are a function of the dilution factor for any given sample. To obtain the actual reporting limits for this sample, multiply the stated Reporting Limits by the dilution factor (but do not multiply reported values).

ICVS : Initial Calibration Verification Standard (External Standard).

mean : Average; sum of measurements divided by number of measurements.

mg/Kg (ppm) : Concentration in units of milligrams of analyte per kilogram of sample,

(parts per million).

mg/L : Concentration in units of milligrams of analyte per liter of sample.

mL/L/hr : Milliliters per liter per hour.

MPN/100 mL : Most probable number of bacteria per one hundred milliliters of sample.

N/A : Not applicable.

NA : Not analyzed.

ND : Not detected; the analyte concentration is less than applicable listed

reporting limit.

NTU : Nephelometric turbidity units.

RPD : Relative percent difference, 100 [Value 1 - Value 2]/mean value.

SNA : Standard not available.

ug/Kg (ppb) : Concentration in units of micrograms of analyte per kilogram of sample,

(parts per billion).

ug/L : Concentration in units of micrograms of analyte per liter of sample.

umhos/cm : Micromhos per centimeter.

Method References

Methods 100 through 493: see "Methods for Chemical Analysis of Water & Wastes", U.S. EPA, 600/4-79-020, rev. 1983.

Methods 601 through 625: see "Guidelines Establishing Test Procedures for the Analysis of Pollutants" U.S. EPA, 40 CFR, Part 136, rev. 1988.

Methods 1000 through 9999: see "Test Methods for Evaluating Solid Waste", U.S. EPA SW-846, 3rd edition, 1986.

SM: see "Standard Methods for the Examination of Water & Wastewater, 17th Edition, APHA, 1989.

BLYMYER
ENGINEERS, INC.
1829 Clement Avenue

Alameda, CA 94501 (415) 521-3773

CHAIN OF CUSTODY RECORD

PAGE / OF /

JOB#	PROJECT NA	ME/LO	САПОН															5,
88288	GI	Tr	JC/c	cury / San Leandro CA			8015)											TURNAROUND TIME: Stan Cara Day(s)
SAMPLERS (SIGNATURE)	1			1		O)			8270)		_		İ	Ì				REMARKS:
SAMPLERS (SIGNATURE)	nh	Li	f	Mline	NERS)(1)/802	EL (MOD	14/8240	PA 625/	18.1)	020/602	ļ						
DATE	TIME	COMP	GRAB	SAMPLE NAME/LOCATION	# OF CONTAINERS	TPH AS GASOLINE + BTXE (MOD EPA 8015/8020)	TPH AS DIESEL (MOD EPA	VOC (EPA 624/8240)	SEMI-VOC (EPA 625/8270)	TRPH (EPA 418.1)	BTXE (EPA 8020/602)						HOLD	
8/28/91	9:24		×	BB-1	3												X	
15/B2/B			Y	MW-4	3	<u> </u>	X											
8/28/91	11:47		γ	MW-5	3		×											
8/28/91	12:45		× '	MLU-Z	3	<u> </u>	×											
8/28/91	13:35		Х	mw-3	3	<u> </u>	×											
/ /		ļ				ļ	ļ											
								ļ										
			ļ			\perp	<u> </u>	<u> </u>										
		ļ	igsqcup			ļ		_	_	ļ 						i		
		ļ				ļ	ļ	<u> </u>		ļ	ļ	<u> </u>				·		
	ļ		ļ					1					ĤΪ	١٧	4	<i> </i>	1	ED 8/29/91
	-	-	-				-	-	_	U.	C) (,		Lun F	104	
		1	<u> </u>		_		_	-	 	W	<u> </u>			19		0		* sealingaet
			<u> </u>					1	1	ļ	ļ	ļ <u>.</u>	ļ	ļ				
						Ber	SULTE A	LAID IND	OLCE TO	<u> </u>	<u> </u>	<u> </u>				<u> </u>	ļ	
REQUESTED BY:	, ,	,				KE		IND INV			_	. ,	,	1	_		دسده'	· Com cla pr
Mich						-		ar	0 (6	na	<i></i> ,	-21	g n	<u>-</u>	<u> </u>	-VI	ers	Gorp. C/O BEI
RELINQUISHED BY: (SIGN	nature) Milc	اسر		DATE / TIME RECEIVED BY: (SIGNATURE) 8/2491 15:05 Michael S. DATE / TIME RECEIVED FOR LABORATORY BY: (SIGNATURE)	6	Kt.	LINUU	XILO B		S/2	V A	2	_	8/2	DATE (9/4)	/ IIME //6.	105	RECEIVED BY: (SIGNATURE) Part 18/29/91 19:00 19:00
RELINQUISHED BY: [SIG	NATURE)	P		DATE / TIME RECEIVED FOR LABORATORY BY: SIG	GNATUXE)		DATE	Z/TIME	_	REA	MARKS:	k	. /5	- p=	17	<i>j</i>	10	14:00
Mucha	1.4	7		B/29/91 3:00 RECEIVED FOR LABORATORY BY SIG	de	9/2	24/0	3:	01 0m	_		e 14	- :	ر <u>ب</u>	1	-	<i></i>	19:00
WHITE: Accompany Sample		YELL	OW: BEI	, After Lub Signs PINK: Original Sumpler		V	T'		!		V	200	ck:	150	ing	198	د	2/30/9, 0803