EXON COMPANY, U.S.A.

P.O. BOX 4032 CONCORD, CA 94524-2032

ENVIRONMENTAL ENGINEERING MARLA D. GUENSLER SENIOR ENVIRONMENTAL ENGINEER (510) 246-8776 (510) 246-8798 FAX July 29, 1993

Mr. Safa Toma East Bay Municipal Utility District P. O. Box 24055 Oakland, CA 94623-1055

JUL 1993

RE: Exxon RAS #7-0104; 1725 Park Street, Alameda, CA/EBMUD System Discharge Permit #502-66631

Dear Mr. Toma:

Attached for your review and comment is a letter report entitled <u>Remediation System Quarterly Self-Monitoring</u>

Report for the above referenced site. This report, prepared by RESNA Industries, Inc., of Novato, California, details the data from the operations and performance of the groundwater remediation system located at the site as required by the East Bay Municipal Utility District Wastewater Discharge Permit, number 502-66631 during the Second Quarter 1993.

The attached report includes the certification page required by the permit's Section V, Paragraphs (a) 2 and (c) "Signatory Requirements". A letter dated July 26, 1993 authorizing myself as a representative signature of the statement from Mr. Gord Thomson, Exxon Marketing Vice President, was sent directly to your attention. A copy of the letter is attached.

If you have any questions or comments, or require additional information, please contact me at the above listed phone number.

Sincerely,

Marla D. Guensler

Senior Environmental Engineer

MDG/mdg

enclosure:

RESNA Quarterly Report dated July 26, 1993

cc: w/enclosure:

Mr. Richard Hiett - San Francisco Bay RWQCB Mr. John Margowski - Wickland Oil Company

Mr. John Margowski - Wickland On Company

Ms. Juliet Shin - Alameda County Health Department

w/o enclosure:

Mr. Gary Pischke - RESNA - Novato



73 Digital Drive Novato, CA 94949 Phone: (415) 382-7400 FAX: (415) 382-7415

REMEDIATION SYSTEM QUARTERLY SELF-MONITORING REPORT FOR EBMUD DISCHARGE PERMIT NO. 502-66631

Second Quarter 1993 Exxon Service Station No. 7-0104 1725 Park Street Alameda, California



73 Digital Drive Novato, CA 94949 Phone: (415) 382-7400 FAX: (415) 382-7415

July 26, 1993

Ms. Marla Guensler Exxon Company, U.S.A. P.O. Box 4032 2300 Clayton Road Concord, California 94524

Subject:

Remediation System Quarterly Self-Monitoring Report for EBMUD Discharge Permit No. 502-66631, Second Quarter 1993, Exxon Service Station No. 7-0104,

1725 Park Street, Alameda, California

Ms. Guensler:

At the request of Exxon Company, U.S.A. (Exxon), RESNA Industries Inc. (RESNA) performed operation and maintenance on the groundwater remediation system (GRS) operating at Exxon Service Station No. 7-0104, 1725 Park Street, Alameda, California. This report presents the results and findings of the self-monitoring activities performed during second quarter 1993. The purpose of the self-monitoring activities is to comply with the East Bay Municipal Utility District (EBMUD) Wastewater Discharge Permit (No. 502-66631) requirements. Information contained in this report pertains to the discharge requirements only. Additional information regarding other aspects of the GRS and site are included in other documents. A site vicinity map is shown on Plate 1

SYSTEM DESCRIPTION

The GRS was installed in February 1993 to treat dissolved petroleum hydrocarbons in groundwater extracted from the first water bearing zone beneath the site (Plate 2, Generalized Site Plan). The extraction system consists of five pneumatic pumps in on-site extraction wells EW-1 through EW-5, collection piping, and associated instrumentation and controls. The treatment system consists of two main modules: treatment (bioreactor) and post-treatment (filtration and carbon polishing). The treatment module consists of a bioreactor, two 200-pound vapor-phase granular activated carbon (GAC) canisters, and the associated air sparging, nutrient and caustic supply systems. The post-treatment consists of a dual-chamber sand filter, a bag filter, and three 200-pound liquid-phase GAC canisters connected in series. Effluent from the system is discharged to the sanitary sewer regulated by the EBMUD. Sampling ports were installed at various locations of the treatment system and are designated as follows:

0722mgue 170077.03



"Influent"	Composite sample from recovery wells
"Bioreactor"	Water sample from the first compartment of the bioreactor
"A"	Effluent from bioreactor, influent to first GAC canister
"B"	Effluent from second GAC canister, influent to third GAC canister
וינייי	Effluent from third GAC canister into sanitary sewer

FIELD PROCEDURES

Monitoring and maintenance of the GRS was conducted by RESNA in accordance with the Operation and Maintenance Manual for the system. RESNA personnel visited the site weekly during the month of April 1993 to assess smooth operation. Beginning in May 1993, operation and maintenance of the system was performed by RESNA on a bi-weekly basis. Throughout this quarter the GRS was shut down periodically for maintenance purpose.

Sampling of the system was performed monthly in accordance with the requirements and procedures of the self-monitoring program associated with the EBMUD wastewater discharge permit. A copy of the EBMUD wastewater discharge permit is included in Attachment A. Water samples were also collected from the bioreactor and submitted to RESNA's bioremediation laboratory in Los Angeles for biological evaluation (bio count) on a monthly basis.

On April 30, 1993, RESNA personnel collected groundwater samples from sampling ports "Influent", "A", "B", and "C". Samples were submitted to Pace Inc. (Pace), a California-certified laboratory in Novato, California, following proper preservation and Chain-of-Custody procedures. The samples were analyzed for the presence of total petroleum hydrocarbon as gasoline (TPHg), benzene, toluene, ethylbenzene, and total xylenes (BTEX) using modified Environmental Protection Agency (EPA) Methods 8015/8020.

RESNA received the laboratory results for the April 30 samples on May 12, 1993. Analytical results indicated that breakthrough of petroleum hydrocarbons had occurred in the second and third GAC canisters. However, TPHg and BTEX concentrations in the effluent sample were below the limitations of the wastewater discharge permit. On May 20, 1993 RESNA proceeded to shut down all five recovery well pumps which stopped discharge from entering the sanitary system. The bioreactor itself was kept in operation by maintaining air sparging and the input of caustic and nutrients.

The treatment system was back in full operation after the spent carbon was replaced with new carbon on June 14, 1993. RESNA collected water samples from all sampling ports two hours after effluent beginning discharged into the sewer. Samples collected were delivered to Pace and analyzed for the presence of TPHg and BTEX. Analytical results indicated that TPHg and BTEX concentrations in the effluent discharged were below the wastewater discharge permit limitations.

DISCUSSIONS OF RESULTS

Operation and performance data for the GRS including analytical results of water samples collected for the period of April through June, 1993 are summarized in Table 1. Copies of laboratory reports and chain-of-custody records are included in Attachment B. Attachment C contains copies



of the facility inspection logs. Results of the self-monitoring and sampling activities indicate the following:

- A cumulative total of 415,739 gallons of groundwater has been treated and discharged into the sanitary sewer during this monitoring period, ending June 29, 1993.
- TPHg and BTEX concentrations in effluent water discharged into the sewer were in compliance with the wastewater discharge permit.

RESNA recommends that signed copies of this report be forwarded to:

Mr. Safa Toma East Bay Municipal Utility District P.O.Box 24055 Oakland, California 94623-1055

Mr. Richard Hiett California Regional Water Quality Control Board San Francisco Bay Region 2101 Webster Street Oakland, California 94612

Ms. Juliett Shin Alameda County Department of Environmental Health Hazardous Materials Division 80 Swan Way, Room 200 Oakland, California 94621

Please call with any questions or comments regarding this report.

Sincerely.

RESNA Industries Inc.

Van Da De

Kin W. Leung Staff Engineer

Gary Pischke, C.E.G. 1501

Project Manager

Enclosures:

Plate 1, Site Vicinity Map

Plate 2, Generalized Site Plan

Table 1, Operation & Performance Data for Groundwater Treatment System

Attachment A: Wastewater Discharge Permit

Attachment B: Laboratory Reports and Chain-of-Custody Records

Attachment C: Facility Inspection Logs



STATEMENT OF CERTIFICATION


I certify under penalty of law that this document and all attachments are prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gathered and evaluated the information submitted. Based on my inquiry of the person or persons who managed the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge or belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.


EXXON COMPANY, U.S.A.

Maria Guensler

Senior Environmental Engineer

Date: 7-29-93







EXPLANATION

- MW-1 Monitoring well location
- EW-1 Extraction well location

Map Source: Site Map by Harding Lawson Associates, 1992; survey by Ron Archer, Civil Engineer, Inc., 1993





PROJECT NO. 170077.03

7/93

GENERALIZED SITE PLAN

Exxon Service Station No. 7-0104 1725 Park Street Alameda, California PLATE

2



TABLE 1 OPERATION AND PERFORMANCE DATA FOR GROUNDWATER REMEDIATION SYSTEM

Exxon Station No. 7-0104 1725 Park Street Alameda, California (Page 1 of 3)

	Total	Average	:					
Sample	Flow	Flow Rai	te Sample	В	T	${f E}$	X	TPHg
Date	(gal)	(gpd)	ID	(ppb)	(ppb)	(ppb)	(ppb)	(ppb)
02/16/93	NA	NA	"Bioreactor"	120	40	25	56	660
02/17/93	NA	NA	"Bioreactor"	23	5.3	2.8	9.3	140
02/18/93	NA	NA	"Bioreactor"	<0.5	<0.5	<0.5	<0.5	<50
02/22/93	0	NA	"Influent"	NS	NS	NS	NS	NS
			"A"	16	11	3.7	15	150
			"B"	NS	NS	NS	NS	NS
			"C"	<0.5	< 0.5	<0.5	< 0.5	<50
02/23/93	230	288	"Influent"	NS	NS	NS	NS	NS
32.23 , 2			"A"	12	7.4	2.7	14	110
			"B"	NS	NS	NS	NS	NS
			"C"	<0.5	<0.5	<0.5	< 0.5	<50
02/24/93	4,165	5,328	"Influent"	1,000	700	83	50	4,800
02,21,75	,,105	5,520	"A"	200	110	5.1	80	800
			"B"	NS	NS	NS	NS	NS
			"C"	<0.5	<0.5	<0.5	< 0.5	<50
02/25/93	10,130	4,752	"Influent"	930	820	130	740	3,800
V= 20,70		.,	"A"	11	2.9	< 0.5	33	300
			"B"	NS	NS	NS	NS	NS
			" C "	NS	NS	NS	NS	NS
02/26/93	15,440	5,328	"Influent"	NS	NS	NS	NS	NS
0220075	25,	0,0=0	"A"	NS	NS	NS	NS	NS
			"B"	NS	NS	NS	NS	NS
			"C"	NS	NS	NS	NS	NS
03/04/93	36,240	3,456	"Influent"	760	430	45	600	3,600
	,	-,	"A"	5.1	2.1	< 0.5	20	170
	•		"B"	<0.5	<0.5	<0.5	< 0.5	<50
			"C"	<0.5	<0.5	<0.5	<0.5	<50
03/11/93	80,000	6,192	"Influent"	480	390	84	600	3,800
J.J. Z.Z. J.J.	00,000		"A"	0.5	<0.5	<0.5	0.8	63
			"B"	< 0.5	<0.5	<0.5	< 0.5	<50
			"Č"	<0.5	<0.5	<0.5	< 0.5	<50



TABLE 1 OPERATION AND PERFORMANCE DATA FOR GROUNDWATER REMEDIATION SYSTEM

Exxon Station No. 7-0104 1725 Park Street Alameda, California (Page 3 of 3)

Sample Date	Total Flow (gal)	Average Flow Rate (gpd)	Sample ID	B (ppb)	T (ppb)	E (ppb)	X (ppb)	TPHg (ppb)
04/30/93	270,400	1,389	"Influent"	240	140	35	500	2,700
0 1130173	2.0,100	1,507	"A"	31	22	14	81	380
			"B"	1.3	<0.5	< 0.5	2.3	55
			"C"	1.5	0.9	<0.5	2.4	<50
05/11/93	308,640	3,476	"Influent"	ŃS	NS	NS	NS	NS
	-	•	"A"	NS	NS	NS	NS	NS
			"B"	NS	NS	NS	NS	NS
			"C"	NS	NS	NS	NS	NS
05/20/93	346,407	4,196	"Influent"	NS	NS	NS	NS	NS
			"A"	NS	NS	NS	NS	NS
			"B"	NS	NS	NS	NS	NS
			"C"	NS	NS	NS	NS	NS
06/14/93	346,407	0	"Influent"	540	340	88	730	3,300
			"A"	< 0.5	< 0.5	< 0.5	1.1	<50
			"B"	< 0.5	< 0.5	< 0.5	< 0.5	<50
			"C"	<0.5	<0.5	<0.5	<0.5	<50
06/24/93	393,810	4,740	"Influent"	NS	NS	NS	NS	NS
			"A"	NS	NS	NS	NS	NS
			'B''	NS	NS	NS	NS	NS
			"C"	NS	NS	NS	NS	NS
06/29/93	415,739	4,386	"Influent"	NS	NS	NS	NS	NS
			"A"	NS	NS	NS	NS	NS
			"B"	NS	NS	NS	NS	NS
			"C"	NS	NS	NS	NS	NS

Abbreviations:

B = benzene

E = ethylbenzene

TPHg = total petroleum hydrocarbons as gasoline

gal = gallons

NA = not applicable

T = toluene

X = total xylenes

gpd = gallons per day

ppb = parts per billion

NS = not sampled/not measured

ATTACHMENT A WASTEWATER DISCHARGE PERMIT



Exxon Service Station Account No. 501-66631 Page 1

STANDARD PROVISIONS AND REPORTING REQUIREMENTS

I. Exxon Service Station #7-0104, located at 1725 Park Street, in Oakland, shall comply with all items of the attached <u>STANDARD PROVISIONS AND REPORTING REQUIREMENTS</u>, 11/92 Revision.

REPORTING REQUIREMENTS

- I. Exxon Service Station #7-0104 shall notify EBMUD Source Control in writing, one week prior to start up. The District will conduct a site inspection before discharge may be initiated.
- II. Exxon Service Station #7-0104 shall monitor discharges per the schedule found in the Self-Monitoring and Reporting Requirements, Section IV, on page 3 of this permit and submit the reports as required below.
- III. Exxon Service Station #7-0104 shall submit quarterly reports as follows:

<u>Date Due</u>	Reporting Period
April 30, 1993	January 25 through March 31, 1993
July 30, 1993	April 1 through June 30, 1993
October 29, 1993	July 1 through September 30, 1993
January 28, 1994	October 1 through December 31, 1993

The quarterly report shall contain:

- 1. A summary of the treatment unit self-monitoring results, any other monitoring, and well sample results that occurred during the reporting period.
- 2. The estimated date that primary carbon canister breakthrough will occur, using current loading data.
- 3. Copies of the Facility Inspection Log. This log must include flow totalizer readings from each sample date, maintenance activities performed, description of operational changes, visual observations of the unit for leaks or fouling and off-haul of hazardous wastes.

3D - 30.6 6/90 N



Exxon Service Station Account No. 501-66631 Page 2

WASTEWATER DISCHARGE LIMITATIONS

Exxon Service Station #7-0104 shall not discharge wastewater from Side Sewer number 1 into the sanitary sewer if the strength of the wastewater exceeds the following:

REGULATED PARAMETER	DAILY MAXIM	UM, mg/L
Arsenic	2	mg/L
Cadmium	1	mg/L
Chlorinated Hydrocarbons		
(Total Identifiable)	0.5	mg/L
Chromium	2	mg/L
Copper	5	mg/L
Cyanide	5	mg/L
Iron	100	mg/L
Lead	2	mg/L
Mercury	0.05	mg/L
Nickel	5	mg/L
Oil and Grease	100	mg/L
Phenolic compounds	100	mg/L
Silver	1	mg/L
Zinc	5	mg/L
pH (not less than)	5.5	s.u.
Temperature	150	°F
Benzene	0.005	mg/L
Toluene	0.012	mg/L
Ethylbenzene	0.005	mg/L
Xylenes	0.011	mg/L



Exxon Service Station Account No. 501-66631 Page 3

SELF-HONITORING AND REPORTING REQUIREMENTS

- I. Exxon Service Station #7-0104 shall obtain representative samples of the wastewater discharge. The sampling shall be performed according to the frequency and methods outlined below and according to the methods and requirements found in STANDARD PROVISIONS AND REPORTING REQUIREMENTS, 11/92 Revision.
- II. Self-monitoring Reports shall contain:
 - 1. Laboratory results.
 - 2. Chain of custody documentation.
 - 3. Signatory requirements.
- III. Sample location "C", also known as Side Sewer number 1, shall be the sample port located on the effluent side of the final carbon vessel. Sample location "B" shall be the sample port located between the end two carbon vessels. Sample location "A" shall be the sample port located on the influent side of the first carbon vessel, after the retention tank. The sample locations are shown on Harding Lawson Associates Plate 2 in this Permit.
- IV. Sample locations "A", "B", and "C" per the following schedule:

Two hours after system start-up^{1,2} Daily for first three days^{1,2} Weekly for the first three weeks Monthly for the first year

Sample locations "A" and "C" only.

- ² Laboratory results to be available within 24 hours of sample collection and faxed to 510/287-1351.
- V. Parameters to be monitored and sample types:

EPA 8020 (as gasoline) - grab sample BTEX - grab sample

VI. All samples must be obtained using containers, collection methods, preservation techniques, holding times and analytical methods set forth in 40 CFR Part 136, except for the 8000 series methods, which are found in U.S. Environmental Protection Agency, Office of Solid Waste and Emergency Response, Test Methods for Evaluating Solid Waste, SW-846.

D - 30.6 6/90 N



Exxon Service Station No.7-0104 Account No. 502-66631 Page 4

MONITORING and TESTING CHARGES

Total EBMUD Inspections Per Year: 3 @ \$510.00 each =

\$1,530.00 /year

Total Analyses Per Year:

Parameter	Tests	Charge	Total Charge
	per year	per test	per year
EPA 624	3	\$156.00	\$468.00
EPA 625	1	\$199.00	\$199.00
Metals	1	\$111.00	\$111.00
	Monitoring and	l Testing Charge =	\$2,308.00 /year \$192.33 /month

WASTEWATER DISPOSAL CHARGE

All wastewater discharged will be charged for treatment and disposal service at the unit rate measured for other carbon treated groundwater discharges. Current unit rate: \$0.32 /Ccf

Volume discharged in Ccf/month =

292.8

\$93.70 /month

VASTEWATER CAPACITY FEE

The capacity fee is calculated by multiplying the monthly wastewater discharge volume by the applicable fee in effect at start-up. Each month, 1/36 of the capacity fee will be charged, until the entire fee has been paid in 3 years.

Discharge volume = 218880 gallons per month

Capacity fee rate = \$46.72 /Ccf-month

Capacity fee = \$13,671.22 \$379.76 /month or



WASTEWATER DISCHARGE PERMIT

Terms and Conditions

Exxon Service Station No.7-0104 Account No. 502-66631 Page No. 5

FEES AND WASTEWATER CHARGES

The following fees and charges are due when billed by the District:

Permit Fee (Paid \$2,260). Balance:	\$0.00
Monthly Monitoring Charges	\$192.33
Monthly Wastewater Disposal Charge	\$93.70
Monthly Wastewater Capacity Fee	\$379.76

Total Monthly Charges =

\$665.79

This Permit may be amended to include changes to rates and charges which may be established by the District during the term of this Permit.

AVERAGE WASTEWATER DISCHARGE *

LAST 12 MONTHS	PRECEDING 12 - 24 MONTHS
N/A	N/A
Gallons per calendar day.	'

Osnoris per calendar day

Effective Date: January 25, 1993

AUTHORIZATION

The above named Applicant is hereby authorized to discharge wastewater to the community sewer, subject to said Applicant's compliance with EBMUD Wastewater Control Ordinance, compliance conditions, reporting requirements and billing conditions.

MUCHALL SULLEY
MANAGER, WASTEWATER DEPARTMEN

1/22/53 DATE

ATTACHMENT B

LABORATORY REPORTS AND CHAIN-OF-CUSTODY RECORDS



May 10, 1993

MAY 1 2 1993

Mr. Kin Leung Resna 73 Digital Dr. Novato, CA 94949

RE: PACE Project No. 430430.519

Client Reference: Exxon 7-0104 (EE)

Dear Mr. Leung:

Enclosed is the report of laboratory analyses for samples received April 30, 1993.

Please note a peak eluting earlier than Benzene and suspected to be methyl tert butyl ether was present in your samples INFLUENT, A, and B (PACE #'s 70 0061733, 70 0061741, and 70 0061750).

Footnotes are given at the end of the report.

If you have any questions concerning this report, please feel free to contact us.

Sincerely,

Stephanie Matyor
Stephanie Matzo
Project Manager

Enclosures



Resna

73 Digital Dr.

May 10, 1993

PACE Project Number: 430430519

Novato, CA 94949

Attn: Mr. Kin Leung

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number:

Date Collected:

Date Received:

Client Sample ID:

Parameter

70 0061733 04/30/93

04/30/93 INFLUENT

2700

240

Units MDL DATE ANALYZED

ORGANIC ANALYSIS

PURGEABLE FUELS AND AROMATICS TOTAL FUEL HYDROCARBONS, (LIGHT):

Purgeable Fuels, as Gasoline (EPA 8015M) ug/L PURGEABLE AROMATICS (BTXE BY EPA 8020M): Benzene Toluene

Ethylbenzene

Xylenes, Total

ug/L

ug/L

0.5 0.5 ug/L ug/L 0.5

35

05/04/93 140 05/04/93

0.5

50

500

05/04/93

05/04/93

05/04/93

05/04/93

05/04/93

Kansas City, Missouri



Mr. Kin Leung

Page 2

May 10, 1993

PACE Project Number: 430430519

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number:

Date Collected: Date Received:

Client Sample ID:

Parameter

70 0061741

04/30/93

04/30/93 'A'

380

31

22

<u>Units</u> <u>MDL</u> <u>DATE ANALYZED</u>

ORGANIC ANALYSIS

PURGEABLE FUELS AND AROMATICS

TOTAL FUEL HYDROCARBONS, (LIGHT):

Purgeable Fuels, as Gasoline (EPA 8015M) ug/L PURGEABLE AROMATICS (BTXE BY EPA 8020M): Benzene ug/L

Toluene Ethylbenzene

Xylenes, Total

ug/L 0.5 ug/L 0.5

50

ug/L 0.5

ug/L

0.5140.581

05/04/93

05/04/93

05/04/93

05/04/93

05/04/93

05/04/93

05/04/93

Kansas City, Missouri



Mr. Kin Leung

Page 3 May 10, 1993

PACE Project Number: 430430519

05/04/93

05/04/93

05/04/93 05/04/93

05/04/93

05/04/93

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number:

Date Collected: Date Received:

Client Sample ID:

70 0061750

04/30/93 04/30/93

, B,

MDL Parameter DATE ANALYZED Units

ORGANIC ANALYSIS

PURGEABLE FUELS AND AROMATICS

TOTAL FUEL HYDROCARBONS, (LIGHT): Purgeable Fuels, as Gasoline (EPA 8015M) ug/L

PURGEABLE AROMATICS (BTXE BY EPA 8020M): Benzene

Toluene Ethylbenzene

Xylenes, Total

55 50 0.5 1.3 ug/L 0.5 ND ug/L ug/L 0.5 ND

0.5 ug/L

2.3 05/04/93



70 0061768

Mr. Kin Leung

Page

May 10, 1993

PACE Project Number: 430430519

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number:

Date Collected: Date Received:

Client Sample ID:

04/30/93 04/30/93 ·C'

Parameter Units MDL DATE ANALYZED

ORGANIC ANALYSIS

PURGEABLE FUELS AND AROMATICS				
TOTAL FUEL HYDROCARBONS, (LIGHT):			_	05/04/93
Purgeable Fuels, as Gasoline (EPA 8015M)	ug/L	50	ND	05/04/93
PURĞEABLE AROMATICS (BTXE BY EPA 8020M):	.		_	05/04/93
Benzene	ug/L	0.5	1.5	05/04/93
Toluene	ug/L	0.5	0.9	05/04/93
Ethylbenzene	ug/L	0.5	ND	05/04/93
Xvlenes. Total	ua/L	0.5	2.4	05/04/93

These data have, been reviewed and are approved for release.

Darrell C. Cain

Kansas City, Missouri



Mr. Kin_Leung

FOOTNOTES

May 10, 1993

Page 5

for pages 1 through

PACE Project Number: 430430519

Client Reference: Exxon 7-0104 (EE)

MDL

Method Detection Limit

ND Not detected at or above the MDL.

Pittsburgh, Pennsylvania

Denver, Colorado



Mr. Kin Leung

QUALITY CONTROL DATA

May 10, 1993

Page

PACE Project Number: 430430519

Client Reference: Exxon 7-0104 (EE)

PURGEABLE FUELS AND AROMATICS

Batch: 70 20912

Samples: 70 0061733, 70 0061741, 70 0061750, 70 0061768

METHOD BLANK:

Parameter TOTAL FUEL HYDROCARBONS, (LIGHT):	<u>Units</u>	MDL	Method Blank -
Purgeable Fuels, as Gasoline (EPA 8015M PURGEABLE AROMATICS (BTXE BY EPA 8020M)	ug/L	50	ND -
Benzene Toluene Ethylbenzene	ug/L ug/L ug/L	0.5 0.5 0.5	ND ND ND
Xylenes, Total	ug/L	0.5	ND

LABORATORY CONTROL SAMPLE AND CONTROL SAMPLE DUPLICATE:

		Reference		Dupl	
Units	MDL	Value	Recv		PD
1 ug/L	50	1000	90%	89%	1%
ug/L	0.5	40.0	104%	100%	3%
ug/L	0.5	40.0	104%	99%	4%
ug/L	0.5	40.0	106%	103%	27
ug/L	0.5	120	105%	99%	5⊁
	ug/L ug/L ug/L ug/L	ug/L 50 ug/L 0.5 ug/L 0.5 ug/L 0.5	Units MDL Value 1 ug/L 50 1000 ug/L 0.5 40.0 ug/L 0.5 40.0 ug/L 0.5 40.0	Units MDL 50 Value 1000 Recv 90% ug/L ug/L 0.5 40.0 104% ug/L ug/L 0.5 40.0 104% ug/L 0.5 40.0 106%	Units MDL stag/L Value stag/L Recv stag/L <th< td=""></th<>



Mr. Kin Leung

FOOTNOTES

May 10, 1993

Page 7

for page 6

PACE Project Number: 430430519

Client Reference: Exxon 7-0104 (EE)

MDL

Method Detection Limit

ND

Not detected at or above the MDL.

RPD

Relative Percent Difference

Kansas City, Missouri

PARTED THE ASSURANCE OF QUALITY

EXXON COMPANY, U.S.A.

430430.519

P.O. Box 4415, Houston, TX 77210-4415 CHAIN OF CUSTODY

Novato, CA, 11 Digital Drive, 94949 (415) 883-6100

Huntington Beach, CA, 5702 Bolsa Avenue, 92649 (714) 892-2565

Consultant's Name:	RES	MA																Page of
Address: 73	DIGIT	AL D	R.,	NO	VATO	C	Ą							Sit	e Loc	ation:	ΑL	-AMEDA
Project #:						Consu	ıltant P	roject #	: 17	100	<u>רר.</u>	ol		Co	nsulta	nt Wo	rk Rele	ase #:
Project Contact: KIN LEUNG Phone #: (415)382-7400 Fax #: 382-7415 Laboratory Work Release #: 09300238									ase #: 09300238									
EXXON Contact:	MARLA	<u></u>	X	EE [С&М	Phone	#:				Fax			E	XON	RAS	#: 7	-0104
Sampled by (print): KIN LEUNG Sampler's Signature: Lim Da. 38																		
Shipment Method:	148	CHEST	, 			Air B	ill#:							Sh	ipmen	t Date:		
TAT: 24 hr	48 hr	72 hr	\boxtimes	Standard	(5 day)					ANA	LYSIS	REQUI	RED					Sample Condition as Received Temperature ° C: <u>CUENT</u>
Sample Description	Collection Date/Time	Matrix Soil/Water	Prsv	# of Cont	PACE Sample #	TPH/GAS/BTEX EPA 8015/8020	TPH/Diesel EPA 8015	TRPH EPA 418.1										Cooler #: CURIER Inbound Seal Yes No Outbound Seal Yes No COMMENTS
	11/20/02			<u> </u>	/ Im- 7		TP	도 H										
INFLUENT	4/30/93	H20	HCI	2	6173,3	~												
`A'	4/30/93	-		1-	6174.1	✓		ļ										
`B'	4/30/93				6175,0	4												
`c '	4/30/93	<u> </u>	1	سد	6176.8	✓												
	44			ļ													· · · · · · · · · · · · · · · · · · ·	
				<u> </u>														
				<u> </u>					l									
Relinqu	ished by/Affil	iation		Date	Time			Accepte	d by/A	filiation	1		Date	e T	ime	Addi	tional C	Comments:
Kin Wa	21			4/30/93	1635													•
the	2			1/30/13	6:40	\mathcal{L}	LC	SA	nti	$\geq L$	PACE		4/30	5 6:	40			
/													<u> </u>					

Detribution



June 28, 1993

JUN 2 9 1993

Mr. Kin Leung Resna 73 Digital Dr. Novato, CA 94949

RE: PACE Project No. 430615.501

Client Reference: Exxon 7-0104 (EE)

Dear Mr. Leung:

Enclosed is the report of laboratory analyses for samples received June 15, 1993.

Footnotes are given at the end of the report.

If you have any questions concerning this report, please feel free to contact us.

Sincerely,

Michael Cohen Project Manager

Enclosures



70 0092566

Resna 73 Digital Dr.

Novato, CA 94949

June 28, 1993

PACE Project Number: 430615501

06/19/93

Attn: Mr. Kin Leung

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number: Date Collected: Date Received:

Client Sample ID:

Xylenes, Total

06/14/93 06/15/93 Influent MDL

0.5

730

Parameter DATE ANALYZED Units ORGANIC ANALYSIS PURGEABLE FUELS AND AROMATICS TOTAL FUEL HYDROCARBONS, (LIGHT): 06/19/93 Purgeable Fuels, as Gasoline (EPA 8015M) ug/L 50 3300 06/19/93 PURGEABLE AROMATICS (BTXE BY EPA 8020M): 06/19/93 Benzene 06/19/93 0.5 540 ug/L Toluene 06/19/93 uq/L 0.5 340 Ethylbenzene 0.5 06/19/93 ug/L 88

ug/L



Mr. Kin Leung

Page 2 June 28, 1993

PACE Project Number: 430615501

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number:

Date Collected: Date Received:

Client Sample ID:

70 0092574 06/14/93

06/15/93 'A'

Parameter Units MDL DATE ANALYZED

ug/L

ORGANIC ANALYSIS

PURGEABLE FUELS AND AROMATICS TOTAL FUEL HYDROCARBONS, (LIGHT):

Purgeable Fuels, as Gasoline (EPA 8015M) ug/L PURGEABLE AROMATICS (BTXE BY EPA 8020M): Benzene

Toluene Ethylbenzene

Xylenes, Total

06/21/93 ND 06/21/93 50 06/21/93 0.5 ND 06/21/93 ug/L 06/21/93 ND

1.1

ug/L 0.5 0.5 ug/L

0.5

ND 06/21/93

06/21/93



Mr. Kin Leung

Page 3 June 28, 1993

PACE Project Number: 430615501

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number:

Date Collected: Date Received:

Client Sample ID:

70 0092582 06/14/93

06/15/93 B'

MDL DATE ANALYZED Parameter Units

ug/L

ORGANIC ANALYSIS

PURGEABLE FUELS AND AROMATICS

TOTAL FUEL HYDROCARBONS, (LIGHT): Purgeable Fuels, as Gasoline (EPA 8015M) ug/L

PURGEABLE AROMATICS (BTXE BY EPA 8020M): Benzene

Toluene Ethylbenzene

Xylenes, Total

06/19/93 06/19/93 ND 50 06/19/93

06/19/93 0.5 ND ug/L 06/19/93 0.5 ND ug/L ND 06/19/93 0.5 ug/L

> 06/19/93 ND 0.5



Mr. Kin Leung

Page

June 28, 1993

PACE Project Number: 430615501

Client Reference: Exxon 7-0104 (EE)

PACE Sample Number:

Date Collected: Date Received:

Client Sample ID:

Parameter

70 0092590

06/14/93 06/15/93

'C'

Units MDL DATE ANALYZED

ug/L

ug/L

ug/L

ORGANIC ANALYSIS

PURGEABLE FUELS AND AROMATICS TOTAL FUEL HYDROCARBONS, (LIGHT):

Purgeable Fuels, as Gasoline (EPA 8015M) ug/L PURGEABLE AROMATICS (BTXE BY EPA 8020M): Benzene

Toluene Ethylbenzene

Xylenes, Total

06/19/93 ND 06/19/93 50 06/19/93

ND 06/19/93 0.5 0.5 ND 06/19/93 06/19/93 0.5 ND

ug/L 0.5 ND 06/19/93

These data have been reviewed and are approved for release.

well C. Cari Darrell C. Cain

Regional Director



Mr. Kin Leung Page 6 QUALITY CONTROL DATA

June 28, 1993

PACE Project Number: 430615501

Client Reference: Exxon 7-0104 (EE)

PURGEABLE FUELS AND AROMATICS

Batch: 70 22135

Samples: 70 0092566, 70 0092574, 70 0092582, 70 0092590

METHOD BLANK:

Parameter	Units	MDL	Method Blank
TOTAL FUEL HYDROCARBONS, (LIGHT): Purgeable Fuels, as Gasoline (EPA 8015M	ug/L	50	ND
PURGEABLE AROMATICS (BTXE BY ÈPA 8020M) Benzene	ug/L	0.5	- ND
Toluene	ug/L	0.5	ND
Ethylbenzene	ug/L	0.5	ND
Xylenes, Total	ug/L	0.5	ND

LABORATORY CONTROL SAMPLE AND CONTROL SAMPLE DUPLICATE:

			Reference		Dupl	
Parameter	Units	MDL	Value	Recv	Recv	RPD
Purgeable Fuels, as Gasoline (EPA 8015M	ug/L	50	1000	89%	92%	3%
Benzene	ug/L	0.5	40	104%	111%	6%
Toluene	ug/L	0.5	40	99%	105%	5%
Ethylbenzene	uq/L	0.5	40	95%	101%	6-
Xylenes, Total	uq/L	0.5	120	97%	103%	6%

Les Annales California



Mr. Kin Leung

FOOTNOTES

Page 7

for page

June 28, 1993 PACE Project Number: 430615501

Client Reference: Exxon 7-0104 (EE)

MDL

Method Detection Limit

ND

Not detected at or above the MDL.

RPD

Relative Percent Difference



EXXON COMPANY, U.S.A.

P.O. Box 4415, Houston, TX 77210-4415 CHAIN OF CUSTODY 430615.501

X

Novato, CA, 11 Digital Drive, 94949 (415) 883-6100

Huntington Beach, CA, 5702 Bolsa Avenue, 92649 (714) 892-2565

Consultant's Name	RES	AA														-	Page	
Address: 73	CA								Site Location: ALAMERA									
Project #:		Consultant Project #: 170077, 01								Consul	tant Wo							
Project Contact: KIN LEUNG							Phone #: (415)382-7400 Fax #: 382-7415							Labora	tory Wo	rk Rele	ease #: 09306238	
EXXON Contact: MARLA EE C&M							Phone #: Fax #:								EXXON RAS #: 7- 0/04			
Sampled by (print):	KIN	LEUNC	4			Samp	ler's Si	gnature	<u> </u>	Kin	Wa	- 2		-				
Shipment Method:	ICE C	HEST				Air B	ill#:							Shipme	nt Date	•		
TAT: 24 hr	48 hr	72 hr	X :	Standard	(5 day)	ANALYSIS REQUIRED								Sample Condition as Received				
Sample Description	Collection Date/Time	Matrix Soil/Water	Prsv	# of Cont	PACE Sample #	TPH/GAS/BTEX EPA 8015/8020	PH/Diesel PA 8015	TRPH EPA 418.1									Temperature © C:CICAT Cooler #: COURIER Inbound Seal Yes No Outbound Seal Yes No COMMENTS	
INFLUENT	6/14/93	H20	HU	2	2256,6		는 E	<u>⊢</u> ⊞			<u> </u>	 					•	
`A'	15 155	1	,	-	7257.4	×				 			 	_				
`B'				 	1258.2	X		ļ				 	-		 			
<u> </u>		1	1	1	9259,0	×						 -		_	-			
					12710						<u> </u>		 - - - - - - - - - -		<u> </u>			
										 			 		<u> </u>			
								<u> </u>						+	 			
															 			
	- n./-					- <u>W-2-02</u>				<u> </u>				+				
										 		<u> </u>		+-				
Relingu	ished by/Affili	ation		Date	Time			Accepte	d by/A	[ffiliatio	<u> </u>	<u> </u>	Date	Time	Addi	ional C	omments:	
Kin Wai 5		EUNG		6/15/93	 	Óη.	er	ex	K	VOI	M		6/15	135			ommones.	
manufaction 10/	White	Diminal	-	Yallow			Uink	Lab			Col.			A 10 . 45°				

ATTACHMENT C FACILITY INSPECTION LOGS

DAILY	FIELD REPORT
Project No.	170077.01 Project Name EXXON 7-0104 By K. LEWIG To Date 3-31-93
Main Activity	
cle Type	☐ Rent ☐ WGR ☑ Personal Odometer IN Odometer OUT Total Mileage
Time	Description
	Depart Home M Office Hotel
12:05	Arrive at Job Site . System was Off upon arrival
	Inspected Instrumentation:
	Control Panel: ON Nutrient Pump: ON 7H: 6.30
	Coustic Pump 1 and AUTO Transfer Pump : AUTO
	Sand Filter Pressure: O psi Bag Filter Pressure: 10 psi
	1 Et Carbon Pressure a O Psi
	Flowmetter Reading: 184321 Flow rate: 0 gpm
	Compressor: ON (back up unil) Hour meter: 597.85
	Air Spargly Flow Rate: 1-9 scfm Pressure. 25 psi
	AT Supply Pressure: 65 psi
	Casatic Cerel: -5 gal Mutrient Cerel: 100 gal
` -	S. AND REPORT FOR THE PROPERTY OF THE PROPERTY
-	- Backward Sand filter
	- Backward carbon drums
	- Refil courter tenk
	- Regione bay filter
17.57	Control Panel: ON Nutrient Pump: ON 1H: 6.4
	Control Panel: ON Nutrient pump: ON pH: 6.4 Courtic Rump: Auto Transfer Pump: MITO
	Sand Falter Pressure. 17.0ps; Bay Filler Pressure " 16.2 ps;
	1 St Carbon Pressure : 12 ps;
	Flowmeter reality: 184780 Flowrate: 7.5 spm
	Compressor: ON (Backup) Hour mete: 597.85
	Air Spangily Flow Rute , 1.9 scfm Bressme 20 ps;
	Air Supply Pressure: 65 ps;
	Air Supply Pressure: 65 ps; Caustic Unel, 20 gol Nutried level: 100 pol
	- Measure vapor emission from carbon down.
	Depart Job Site
	Arrive Home Office Hotel

	170077.01 Project Name EXX6N 7-0104 BY K. LEWS TO Date \$	- 2.
ctivity	0 & M	
Түре	Rent WGR Personal Odometer IN Odometer OUT Total Mileage	
	Description	
	Depart 🔀 Home 🗋 Office 🗋 Hotel	
0	Arrive at Job Site - System was on upon worl.	
	Inspect Instrumentation:	
_	Control Panel: ON Nutrient Pump: ON pH:	7.4
	Constic Pump: Auto Transfer Pump: Auto	
_	Sand Filter Pressure: 0 psi Bag Filter Pressure: 0 psi	<u> </u>
	1 St Carbon Pressure: 0 ps.	
_	Flow meter Reading: # 192674 Flow rate: 0 gpm	
	Compressor = ON (backup unil) Hour meter 597-95	
_	Air Sparging How rate: 1.9 sctm Pressure 25 psi	
_	Coustic Level: 15 gels Nutrient Level: 90 pals	
	Ast Supply Pressure . 65 psi	
	- Backwarh sand filters - Backwart carbon hedo - Replaced Bay Filter	10 se
_	- Backward control hedo - Replaced Bay Filter	
_	- Backward control heds - Replaced Bay Filter Instrumentation Readings:	7.16
_	- Backward control hedo - Replaced Bay Filter Instrumentation Readings: Control Panel: OH Nutrient Pump: OH pH:	7.16
_	- Backward control hads - Replaced Bay Filter Instrumentation Readings: Control Panel: ON Nutrient Runp: ON pH: Caustic Rung: AUTO Transfer Runp: AUTO	7.16
_	- Backward control hedo - Replaced Bay Filter Instrumentation Readings: Control Panel: OH Nutrient Aunp: OH pH: Courtic Rung: Auro Transfer Phap: Auro Sand Fille Pressure: 17.1 psi Bas Filta Pressure: 16,0 psi	7.16
_	- Replaced Bay Filter Instrumentation Readings: Control Panel: ON Nutrient Pump: ON pH: Countic Rung: Auru Transfer Pump: Auro Sand Fille Pressure: 17.1 psi Bay Filter Pressure: 16.0 psi 152 Carbon Pressure: 12.0 psi	7.16
_	- Backwart conton bads - Replaced Bay Filter Instrumentation Readings: Control Panel: ON Nutrient Aury: ON pH: Courtic Runy: Auro Transfer Phap: Auro Sand Fille Pressure: 17.1 psi Bay Filta Pressure: 16.0 psi 1st Carbon Pressure: 12.0 psi Flow mete Reading: 193207 Flow rate: 8.2 gpm	7.16
_	- Backwart conton hedo - Replaced Bay Filter Instrumentation Readings: Control Panel: OH Nutrient Pump: OH pH: Countic Runy: Auro Transfer Pump: Auro Sand Filly Pressure: 17.1 psi Bas Filty Pressure: 16.0 psi 1St Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95	7.16
_	- Replaced Bay Filter Instrumentation Readings: Control Penel: ON Nutrient Pump: ON pH: Countic Rung: Auro Transfer Pump: Auro Sand Fille Pressure: 17.1 psi Bas Filter Pressure: 16.0 psi 1st Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95 Air Sparging Flow rate: 1.9 scfm. Pressure: 25 psi	7.16
_	- Backwart conton hedo - Replaced Bay Filter Instrumentation Readings: Control Panel: OH Nutrient Pump: OH pH: Countic Runy: Auro Transfer Pump: Auro Sand Filly Pressure: 17.1 psi Bas Filty Pressure: 16.0 psi 1St Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95	7.16
_	- Replaced Bay Filter Instrumentation Readings: Control Penel: ON Nutrient Pump: ON pH: Countic Rung: Auro Transfer Pump: Auro Sand Fille Pressure: 17.1 psi Bas Filter Pressure: 16.0 psi 1st Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95 Air Sparging Flow rate: 1.9 scfm. Pressure: 25 psi	7.16
_	- Replaced Bay Filter Instrumentation Readings: Control Penel: ON Nutrient Pump: ON pH: Countic Rung: Auro Transfer Pump: Auro Sand Fille Pressure: 17.1 psi Bas Filter Pressure: 16.0 psi 1st Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95 Air Sparging Flow rate: 1.9 scfm. Pressure: 25 psi	7.16
_	- Replaced Bay Filter Instrumentation Readings: Control Penel: ON Nutrient Pump: ON pH: Countic Rung: Auro Transfer Pump: Auro Sand Fille Pressure: 17.1 psi Bas Filter Pressure: 16.0 psi 1st Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95 Air Sparging Flow rate: 1.9 scfm. Pressure: 25 psi	7.16
_	- Replaced Bay Filter Instrumentation Readings: Control Penel: ON Nutrient Pump: ON pH: Countic Rung: Auro Transfer Pump: Auro Sand Fille Pressure: 17.1 psi Bas Filter Pressure: 16.0 psi 1st Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95 Air Sparging Flow rate: 1.9 scfm. Pressure: 25 psi	7.76
_	- Replaced Bay Filter Instrumentation Readings: Control Penel: ON Nutrient Pump: ON pH: Countic Rung: Auro Transfer Pump: Auro Sand Fille Pressure: 17.1 psi Bas Filter Pressure: 16.0 psi 1st Carbon Pressure: 12.0 psi Flow meta Reading: 193207 Flow rate: 8.2 gpm Compressor: ON (backup) Hour meter: 597.95 Air Sparging Flow rate: 1.9 scfm. Pressure: 25 psi	7.16

	FIELD REPORT	To To	Date
Main Activity		K. LEUNG TO	Date 4-5-93
	0 R M 30 ±		
cle Type	Rent WGR MC Personal Odometer IN	Odometer OUT	Total Mileage
Time	Description		
	Depart Home Office Hotel		
17.45	Arrive at Job Site		
	Inspect Instrumentation:	/ 12 1	
	Control Panel (CP): OH Nutrient	Pump (P-1) 2	h .H. 6.57
	Courtie Pump (P-2): AUTO Transfer	Pump (P-3):	Auto
	Sand Filter Pressure: 0 ps; Bag F	ilter Pressure:	o psi
	1st Carbon Pressure (PI-9): o psi		
	Flowmeter Peading, 208161 Flow	rate: 0 gpm	
	Air Compressor: ON (backup) Hour me	Tex: 597.95	
	Air Spanging Flow rate: 1.9 sofm	Pressure: 25 1	PSÍ
	Air Supply Pressure: 65 psi Caustic Level: 8 gal Nutrier	85	
	Caustic Level: 8 gal nutries	t Level : too go	d
	- Backwarh Sand Filter - Backwart Carlon Drums - Replace boy follow Control Panel: ON Nutrient Courtie Pump (P-2): Auto. Transfer Sand Filter Pressure: 18 psi B 1 St Carbon Pressure: 13 psi Flow meter Reading: 208238 F Air Compressor: ON (backup) Air Spanging How Rate: 19 scfm Atr Supply Pressure: 65 psi	Rimp (P-3). A ag Filter Pressure 600 Pate: 6.5 Hour meter: 59	9pm
	Courtic cerel: 8 gal 1	utriest (evel:	35 gal
		- 12	
0.777	Depart Job Site		
	Arrive Home Diffice Hotel		

	170077. 01 Project Name EXXON 7-0104 BY K. LEWAG TO Date 4-7-9
lain Activity	
cle Type	
ime	Description
	Depart Home Office Hotel
1215	Arrive at Job Site ·
	Control Panel: on Mutrient Pump (P-1), ON pH: 6.65
	Caustic Pamp: Acto Transfer Pump: Auto
	Sand Filter Pressure, 19 psi Bag Filter Pressure: 19 psi
	1 St Carbon Pressure: 13 psi
	Flow meter Rendry: 214604 Flow rate: 3.5 gpm
	Air Compressor : ON
	Air Sparging Flow Rate: 1.9 scfm Pressure: 25 psi
	Countrie level: 8 gel Nutrient level: 85 gel
	Caustic level: & gel Nutrient level: B5 gol
	- Backward Sand Filter
	- Backwark carbon downs
	- Refill cautic & fank
	- regitt success and favor
830	
-	control panel: in Nutrent lung: on mil: 6.63
-	Control panel: on Nutrient Pump: on pf: 6.65 Countie Pump: Auto Transfer Pump: Auto
	The state of the s
	Sand Filter Pressure: 19 psi Bag Filter Pressure: 19 psi
	Sand Filter Pressure: 19 psi Bag Filter Pressure: 19 psi
	Sand Filter Pressure: 19 psi Bag Filter Pressure: 19 psi
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 1st Carbon Pressure: 8 psi Flow meter Readry: 214692 Howrate: 511 5pm
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 13t Carbon Pressure: 8 psi Flow meter Readry: 214692 Howrate: 511 5pm Air compressure: on
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 1st Carbon Pressure: 8 psi Flow meter Readry: 214692 Howrate: 5:1 5pm Air compressure: on Air Sparphy Flow Rote: 19, spfm, Pressure: 25 psi
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 13t Carbon Pressure: 8 psi Flow meter Readry: 214692 Flowrate: 5:1 Spm Air compressure: on Air Sparging Flow Rote: 19 spfm, Pressure: 25 psi Air Supply Pressure: 65 psi
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 13t Carbon Pressure: 8 psi Flow meter Readry: 214692 Flowrate: 5:1 Spm Air compressure: on Air Sparging Flow Rate: 19 spfm, Pressure: 25 psi Air Supply Pressure: 65 psi
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 13t Carbon Pressure: 8 psi Flow meter Readry: 214692 Flowrate: 5:1 Spm Air compressure: on Air Sparging Flow Rate: 19 spfm, Pressure: 25 psi Air Supply Pressure: 65 psi
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 13t Carbon Pressure: 8 psi Flow meter Readry: 214692 Flowrate: 5:1 5pm Air compressure: on Air Sparging Flow Rote: 19 spfm, Pressure: 25 psi Air Supply Pressure: 65 psi
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 13t Carbon Pressure: 8 psi Flow meter Readry: 214692 Flowrate: 5:1 5pm Air compressure: on Air Sparging Flow Rote: 19 spfm, Pressure: 25 psi Air Supply Pressure: 65 psi
	Sand Filter Pressure: 19 psi Bay Filter Pressure: 19 psi 1st Carbon Pressure: 8 psi tlaw meter Readry: 214692 Howarde: 5:1 5pm Air compressure: on Air Sparging Flow Rote: 19 spfm, Pressure: 25 psi Air Supply Pressure: 65 psi

DAILY F	TELD REPORT	
Project No.	170077, 01 Project Name EXXON 7-0164 BY K. LEUNG TO	Date 4-9-93
Main Activity	ORM	
icle Type	☐ Rent ☐ WGR ☐ Personal Odometer IN Odometer OUT	Total Mileage
Time D	Description	
	Depart Home Office Hotel	
10:15 A	Arrive at Job Site	
	Comprol Panel: ON Nutrent Pump: or	pH: 6.81
	Courtis Pump: Auto Transfe Pump: Anto	
	Sand Filter Pressure, 18,2 psi Bag Filter Pressure.	1Bzps:
-	1st Carbon Pressure: 11 psi	
	Flowerder Reading: 223530 Flow rate: 6.0 g	PM
	Bir Spanging Flow rate: 1.9 scfm, Pressure 2	c eti
	Aft Supply Pressure: 65 psi	1
	Caustic Level: 50 gel Hutrient level: 78	eal.
=	Backwash: Sand filters, Carbon knums	
=	- Replace bas filter	
-		
-		II
		TO THE STATE OF TH
		2 2
	47	2 200
		2.3
De	Depart Job Site	
Ar	Arrive	

DAILY	FIELD REPORT
Project No.	170077.01 Project Name EXXOLI 7-0104 By K. LEUNG TO Date 4-13-9
Main Activity	
cle Type	
Time	Description
	Depart Home M Office Hotel
1400	Arrive at Job Site
	Control Panel: ON Nutrient Pump: ON pH: 6.97
	Courtie Purp; Auto Transfer Purp; Auto
	Sand Filter Pressure: 19,2 ps; Bag Filter Pressure: 19,2 psi
	1st Carlon Pressure: 15.8 psi
	Flow meter Reading: 238370 Flow rate: 2.4 gpm
	Air Compressor: ON Air Sparging: Flow Rate: 1.9 scfm, Pressure: 25 ps/
	Caustic level: 46 get Nutrient level: 75 pal
	Ar Supply Pressure: 65 psi
	- Backwash: Sand filter, carbon drung
	Control Panel: ON Nutrient Pump: ON PH: 6.88
	Send Filly Pressure: 18.4 psi Bay Filte Pressure: 18.2 ps
	Sand Faller Pressure: 18.4 psi Bag Fitte Pressure: 18.2 ps
	Flow meter Readily 238450 Flowrede: 5.5 gpm
	Air Compressor: ON
	Air Sparging Flow Rate: 1.4 cfm Pressure: 25 ps;
	Constic Level: 46 gal Nutrent Level: 75 mil
	Air supply Pressure, 65 psi
100000	Description Sire
	Depart Job Site
	Arrive Home Office Hotel

DAILY	FIELD REPORT
Project No.	170077. 01 Project Name EXXON - 7 - 0104 BY K. LEYNG TO Date 4-16-93
Main Activity	O long
icle Type	
Time	Description
	Depart Home Office Hotel
950	Arrive at Job Site ·
	Control Panel: on Hutlent Pump: ON pH: 7.19 Eaustic Pump: Ando Transfer Pump: Austo
	Bootso Sand Filter Pressure: 19.5 pri Bay Filter Pressure: 19.5 psi
	12 Carbon Pressure ! 17 più
	Flow meter Reading: 250960 Flow rate: 3.0 5pm
	Air Compressur : ON
	Air Spanging How rate: 1.9 cfm Pressure: 25 psi
	Atr Supply Pressure: 65 psi
	cautic level: 44 gal Nutrient level: 5 gd
	, was and
	- Back wach Sand filters, carbon drums.
	- Replace buy filler
	- Aprile
·	
-	
-	

	Described Dis
Acceptance	Depart Job Site
	Arrive Home Office Hotel

roject No.	170077.01 Project Na	PASCON	1-7-0104	BY K. LEWY TO	Date 4/30/1
lain Activity	0 4 M	1985	· ·		
icle Type	Rent WGR	☐ Personal	Odometer IN	Odometer OUT	Total Mileage
me	Description			4	
	Depart 🗋 Home 🙇 Of	flice 🔲 Hotel			
1617	Arrive at Job Site · Su	ctem do	un upon a	mivel	
	Control Panel:	on	Nutrient	Pump: on	pH: 11.86
	Courtie Pump:	Auto	Transfer	Punyo : Anto	
	Sand Filter Pr	essure,	O psi	Bag Fiter Presure	129 0 3
	1st carbon Pres	ssure,	O pci		
	Flournetter Rea	idry:	270400	Flowrate: 0 gp	m
	Air Compression				
	1000			Pressure.	25 psi
	Air Supply P	ressure.	65 psi		
	Caustic lave	e :	\$ 25 gel	Nutrient les	el: 60 gel
_	- Backward son	d filler	, corbon o	lowers	
134	Combrol Barel:	, on	Nutri	ent sump; on	p# : 11.84
	Control Band: Caustic Pump: Sand Filter	ON Auto Pressure	Nutrie Transf	ent lump: ON ier Pump: Auto	pH: 11.84 ressure: 18 ps
	Control Barel: Caustic Pump: Sand Filter 1 SI Cartron P	Auto Pressure Pressure	Nutri Transf 185 pri 13 psi	ent Sump: ON Ex Pump: Auto Bag Filter P	ressure: 18 p
	Control Barel: Caustic Pump: Sand Filter 1 St Cartron P Flowmeter Res	Auto Pressure Pressure:	Nutri Transf 185 pri 13 psi	ent Sump: ON Ex Pump: Auto Bag Filter P	ressure: 18 p
	Control Barel: Caustic Pump: Sand Filter 1 St Cartron P Flowmeter Rea Air compress	Auto Pressure: Pressure: Juzy 2	Nutrie Transf 185 pri 13 psi 70411 F	ex Pump: ON Ex Pump: Auto Bag Filter P Warracle: 6.1 gp	versue: 18 p
	Control Parel: Caustic Pump: Sand Filler 1 St Cartron P Flowmeter Rea Air compress Air Sparging	Auto Pressure Pressure: Us. 2	Nutrie Transf 185 pri 13 pri 70411 F	ex Pump: ON Ex Pump: Auto Bag Filter P Warracle: 6.1 gp	ressure: 18 p
	Control Barel: Caustic Pump: Sand Filter 1 St Cartron P Flowmeter Rea Air compress	Auto Pressure Pressure: Us. 2	Nutrie Transf 185 pri 13 pri 70411 F	ex Pump: ON Ex Pump: Auto Bag Filter P Warracle: 6.1 gp	versue: 18 p
	Control Parel: Courtie Pump: Sand Filter 1 St Cartron P Flowmeter Rea Air compress Air Sparging Air Supply P Caustic level - COLLECTED	Anto Pressure Pressure: Liz. 2 Mr. 2 Mr. 2 Mr. 1 Plan R. Plan R. Plan R. Plan R. Plan R. SAMPLES	Nutria Transf 185 pri 13 psi 70411 F Sur 20 0 65 pri gel 7	ex Pump: ON ex Pump: Auto Bag Filter P lowrate: 6.1 gp Im Pressure Nutrical ler	ressure: 18 pm
	Control Parel: Courtie Pump: Sand Filter 1 St Cartron P Flowmeter Rea Air compress Air Sparging Air Supply P Caustic level - COLLECTED	Anto Pressure Pressure: Liz. 2 Mr. 2 Mr. 2 Mr. 1 Plan R. Plan R. Plan R. Plan R. Plan R. SAMPLES	Nutrie Transf 185 pri 13 psi 70411 F 50 0	ex Pump: ON ex Pump: Auto Bag Filter P lowrate: 6.1 gp Im Pressure Nutrical ler	ressure: 18 pm
	Control Parel: Courtie Pump: Sand Filter 1 St Cartron P Flowmeter Rea Air compress Air Sparging Air Supply P Caustic level - COLLECTED	Anto Pressure Pressure: Liz. 2 Mr. 2 Mr. 2 Mr. 1 Plan R. Plan R. Plan R. Plan R. Plan R. SAMPLES	Nutria Transf 185 pri 13 psi 70411 F Sur 20 0 65 pri gel 7	ex Pump: ON ex Pump: Auto Bag Filter P lowrate: 6.1 gp Im Pressure Nutrical ler	ressure: 18 pm
	Control Parel: Courtie Pump: Sand Filter 1 St Cartron P Flowmeter Rea Air compress Air Sparging Air Supply P Caustic level - COLLECTED	Anto Pressure Pressure: Liz. 2 Mr. 2 Mr. 2 Mr. 1 Plan R. Plan R. Plan R. Plan R. Plan R. SAMPLES	Nutria Transf 185 pri 13 psi 70411 F Sur 20 0 65 pri gel 7	ex Pump: ON ex Pump: Auto Bag Filter P lowrate: 6.1 gp Im Pressure Nutrical ler	ressure: 18 p
	Control Parel: Courtie Pump: Sand Filter 1 St Cartron P Flowmeter Rea Air compress Air Sparging Air Supply P Caustic level - COLLECTED	Anto Pressure Pressure: Liz. 2 Mr. 2 Mr. 2 Mr. 1 Plan R. Plan R. Plan R. Plan R. Plan R. SAMPLES	Nutria Transf 185 pri 13 psi 70411 F Sur 20 0 65 pri gel 7	ex Pump: ON ex Pump: Auto Bag Filter P lowrate: 6.1 gp Im Pressure Nutrical ler	ressure: 18 pm

DAILY	FIELD REPORT
Project No.	170077.01 Project Name Exton 7-0104 By K. LEWIL To Date 5-6-93
Main Activity	
.cle Type	☐ Rent ☐ WGR ☑ Personal Odometer IN Odometer OUT Total Mileage
Time	Description
	Depart Home Office Hotel
1030	Arrive at Job Site -
	RECEIVED CALL FROM DAVE DE MENT & GARY PISCHKE THAT THE
	SYSTEM MALFUNCTIONED AND WATER WAS OBSERVED OVERFLOWING PROM
	THE BY TRESTMENT COMPOUND INTO THE STORM DRAIN, UPON ARRIVED
	AT NOB SITE, THE CARBON DRUMS WERE FOUND CLOUGING UP
	DISCHARG RATE WAS VERY SLOW (< 1 GPM) APPARENTLY THE
	EXTRACTION RATE OF THE WELL PUMPS WERE FASTER THAN THE
	DISCHARGE RATE, & PARTIALLY TREATED WATER WAS OVERFLOWER
	FROM THE BIO REACTOR INTO THE POUBLE CONTRIUMENT, THE
	CONTAINMENT WAS FULL OF WATER AND WATER WAS OVERFLOWED
	THE TOP OF THE BERM INTO THE STREET.
1035	SHUT AFF BOWN THE SYSTEM AND BEGAN TO MYSTALL A' SUMP
	PUMP TO PUMP WATER FROM THE CONTAINMENT BACK TO THE
1000	BIOREACTOR
1050	TURN ON POWER TO THE TRANSFER IN PUMP AND BEGAN BACKWALA
	THE CARBON DRUMS
1125	THE DISCHARGE RATE WAS BACK TO ABOVE 6 GPM. BEGAN
	PUMPING OVERFLOWER WATER BACK TO & THE BIOREACTOR FAME
1613	REMOVED ALL WATER FROM THE FLOUR OF THE DOUBLE CONTAMINENT
· Las	INSPECTED SYSTEM TO LOCATED THE CAUSE OF MAILFULTION,
100	JERRY WILSKI WAR ON SITE TO HELP DETERMINE THE CAUSE OF
w-172n	SYSTEM MALPUNGON. RESULTS PETROLE OF THE CIRCUIT, INDICATED THE CAUSE WAS THE
49 1120	A THE CIRCUITY INDICATED THE CAMPE WAS THE
	TO THE CONTROLLING THE FLOW OF COMPRESSED ALR
	TO THE EXTRACTION PUMPS. RECORD THE MODEL NO. AND
	MAKE OF THE UNIT THE UNIT APPEARED PUNCTIONINGS
	OUP WITH EXTRACTION PATE, ANOTHER OVERFOW COME OCCUR.
	JERRY RECOMMENDED REPLACEMENT OF THE VALVE
1810	LALL SITE.
	Depart Job Site
	Arrive 🗍 Home 🗐 Office 🗐 Hotel

DAILY FIELD REPORT	
Project No. 170077.01 Project Name EXX ON 7-0104 By K. LEWIG To Date 5-1	1-93
Main Activity O &M	
icle Type	
Time Description	
Depart Home Office Hotel	
1430 Arrive at Job Site ·	
Control Panel: ON Nutrient Rump: ON pH: 11	.66
Cautic Pump: Auto Transfer Pump: Auto	
Sand Filte pressure: 19 ps; Bej Fille Pressure: 17 ps;	i entre
Tiespare) (6 pts	
Air Compressor: on them mater 917.62	
Air Spargity Plowrate: 2 cfm, Pressure: 25 psi	
Dir Supply Pressure: 65 psi	
Courtie level: 15 gol Nutrient Cevel: 55 gol.	
- Backwarh and filters, carbon down.	
- Replace box friter,	
1600 Control paul: on Hutriest Pemp: ON pH; 12.	54
Caudic Pump: Auto Transfer Pump: Auto	40.00
Sand Fitter Pressure: 19 psi Bay Fille Pressure: 17 ps	Ĺ.
1 th Carbon Pressure: 16 psi	
Flow meter Ready: 309098 Flow rate: 6 spn	
Air Sparsing Pressure: 65 psi Flow rate: 2 cfm	
Air Supply Pressur: 65 psi	= 3
Canotic level: 15 gal. Nutrient level: 55 cal.	
Depart Job Site	
Arrive Home Office Hotel	

TRANSFER PUMP: AUTO PAG FILTER DESIGNE 16.0 PS; FLOW PLATE: 6.3 EPM HOUR METER 1297 PRESSURE: 25 PS; UTRIENT LEVEL! 35 GAL	CONTROL PANEL: ON CANSTIC PUMP: ON/ANTO SAND FILTER PRESSURE: 18.2 FS? 1 SS CARBON PRESSURE: 16.7 PSI FLOW METER PERDING: 346407 AIR COMPRESSOR: ON AIR SPARGING FLOW RATE: 2 CFA AIR SUPPLY PRESSURE: 65 PSI CAUSTIC LEVEL: 13 GAT - REPLACED SOLENOID VALVE
FLOW PLATE: 6.3 EPM HOUR METER 1297 PRESSURE: 25 PSI UTRIENT LEVEL: 35 GAL	FLOW METER PERDING: 346407 AIR COMPRESSOR: ON AIR SPARGING PLOW RATE: 2 CFA AIR SUPPLY PRESSURE: 65 PSI CAUSTIC LEVEL: 13 GAT
HOUR METER 1297 PRESSURE: 25 PSI UTRIENT LEVEL 1 35 GAL ON DRUMS	FLOW METER BEADING: 346407 AIR COMPRESSOR: ON AIR SPARGING FLOW RATE: 2 CFA AIR SUPPLY PRESSURE: C5 PSI CAUSTIC LEVEL: 13 GAL
PRESSURE: 25 PSI UTRIENT LEVEL 1 25 GAL ON DRUMS	AIR SPARGING FLOW RATE: 2 CFM AIR SUPPLY PRESSURE: 65 PSI CAMSTIC LEVEL: 13 GAL
UTRIENT LEVEL / 35 GAL	ATR SUPPLY PRESSURE: 65 PSI CAUSTIC LEVEL: 13 GAL
on prums	CAUSTIC LEVEL: 13 GAC
	- REPLACED SOLENOID VALVE
	- BACKWASH SAND FILTER 4 CAR - ONE CARSH DRUM WAS LEA - SHUT DONN SYSTEM BEFORE
	- NO SAMPLE WAS CALLECTED
	_

roject# [7	1007701	Project Name Ex	XON 7-0	104 By	K. LEUNG	To	Date 6/14/
lain Activity	0 & M	/ REPLACE	E C	ARBON	CAHISTER	.	
ehicle Type	☐ Rent	☐ RESNA ☐ P	ersonal 0	dometer IN	Odo	meter OUT	Total Mileage
ime	Description			Ģ			
720	ARRIVE	ON SITE	<u>,</u> 54	STEM W	AS POWA	1, REFIT	HOSES
145	NEW C	ARBON D	RUMS	ARRIVED	BEGAN	HOUK UP	
2	The Australia	/N.541 4 . m		a h			
		MASH CAR N SYSTER		DRUMS.	 -		
733	1444 0	74 01070					
	CONT	ROL PANEL	: 01		NUTRIEN	T PUMP: 0	N pH: 7.2
	CAUST	TE PLIMP:	Aun	٠	TRANSFE	c pump:	AUTO
	-	FILTER					
							E: 6.3 GPM
							1298
						*	'URE : 25 PSI
_		Supply			•		75 GAL
	<u> </u>	me level	7	GAL_	NUTR	TENT CLIEB	, , , , , , , , , , , , , , , , , , , ,
_							
	-						
-							
	-						
	-						
							
	-						
	-						

6/93

DESMA

Page

d

	FIELD REPORT	
	10077.01 Project Name EXON 7-010 Y & LEUNG TO	Date 6/24/2
Aain Activity	064	Total Mileage
ehicle Type	Rent RESNA Personal Odometer IN Odometer OUT	Total Mileage
ime	Description	
520	ARRIVE ON SITE	
	CONTROL PANEL : ON NUTRIENT PUMP : ON	r#: 6.5
	CANSTIC PUMP: ANTO TRANSFER PUMP ANT	
	SAND FILTER PRESSURE: 18 PS BAG FILTER	PRESILE: 16.
	155 CARBOH 15.2 PSI	20 000
		E: 2.8 GPM
	The contract of	1503.7
	Mile Marchae Con Luic's	€ · 25 ps,
	CAUSTIC LEVEL 10 GAL KUTFIGHT LEVEL	CB CAC
	- BACKWASH SAND FILTERS, CAPBON DRUMS	
		1000000 1000 <u>0</u> 00
		FILTER: 167
	154 CAR-50H : 8.0 PS.	
	•	
	54.	
	Depart Job Site	
	Arrive	

DAILY	FIELD REPORT	
roject# (7	70077.01 Project Name Effon 7 - 0104 By K. CEUNG To Date	6 pefe
Main Activity	OLM	
/ehicle Type	The second secon	eage
Time	Description	
10:10	APPLIVE AT SITE SYSTEM RUNNING FINE	
	CONTROL PANEL: ON NUTRIENT PLMP; ON	pH: 6.88
	CAUSTIC PUMP: AUTO TRANSFER PUMP: AUT	
	SAND FILTER: 19.2 PSI BAG FILTER: 17.8	PSI
	1 S CARBON: 13.0 PS1	
	FLOW METER PEADING: 415 739 FLOW PLATE: 65	
	MR COMPRESSOR: ON HOUR: 16021	
	AIR SPARGING FLOW FAME. 2 CFM PRESSURE.	الم يع
	ATR SUPPLY: 65 psi	* M
_	CANSTIC LEVEL: 45 GAL. NUTRIENT: 50	GAL
	- BACKWASH SAND FILTER & CARBON	**
	PM: 6-81 SAND FILTER 18.4 PVI	
	ONG FILTER: 17.0 PS1 15 CARBON: 7.2 P1	
-	From this: 6-3 BPM.	
	Depart Job Site	
	Arrive Home Office Hotel	