



76 Broadway
Sacramento, California 95818

May 11, 2006

RECEIVED

By loppjectop at 11:41 am, May 18, 2006

Mr. Don Hwang
Alameda County Health Agency
1131 Harbor Bay Parkway
Alameda, California 94502

Re: **Report Transmittal
Quarterly Report
First Quarter – 2006
76 Service Station #0843
1629 Webster Street
Alameda, CA**

Dear Mr. Hwang:

I declare under penalty of perjury that to the best of my knowledge the information and/or recommendations contained in the attached report is/are true and correct.

If you have any questions or need additional information, please contact

Shelby S. Lathrop (Contractor)
ConocoPhillips
Risk Management & Remediation
76 Broadway
Sacramento, CA 95818
Phone: 916-558-7609
Fax: 916-558-7639

Sincerely,

Thomas Kosel
Risk Management & Remediation

Attachment



Solving environment-related business problems worldwide

www.deltaenv.com

3164 Gold Camp Drive • Suite 200
Rancho Cordova, California 95670 USA

916.638.2085 800.477.7411
Fax 916.638.8385

RECEIVED
By lopprojectop at 11:41 am, May 18, 2006

May 16, 2006

Mr. Donald Hwang
Alameda County Health Agency
1131 Harbor Bay Parkway, Suite 250
Alameda, California 94502

Re: Quarterly Summary Report – First Quarter 2006
Delta Project No. C102349011

Dear Mr. Hwang:

On behalf of ConocoPhillips (COP), Delta Environmental Consultants, Inc. (Delta) is forwarding the quarterly summary report for the following location:

Service Station

Location


76 Service Station No. 0843

1629 Webster Street
Alameda, California

Sincerely,
Delta Environmental Consultants, Inc.

Ben Wright
Staff Geologist

Daniel J. Davis, R.G.
Senior Project Manager



Forward: TRC - Quarterly Monitoring Report

cc: Ms. Shelby Lathrop, ConocoPhillips (electronic copy)

QUARTERLY SUMMARY REPORT
First Quarter 2006
76 Service Station No. 0843
1629 Webster Street
Alameda, California

PREVIOUS ASSESSMENT

June 1998 - Tosco Marketing Company (Tosco, now ConocoPhillips) removed two 10,000-gallon gasoline underground storage tanks (USTs), one 550-gallon used oil UST, product lines, and dispensers. Two holes approximately ¾-inch in diameter were observed in the used oil tank during removal. Approximately 338 tons of hydrocarbon impacted soil and backfill were removed from beneath the former USTs, dispensers, and product lines during the UST removal activities.

March 1999 – Four soil borings (B1 through B4) were advanced at the site and converted to monitor wells MW-1 through MW-4. Groundwater was encountered from 8 to 15 feet below ground surface (bgs). Static water was observed between 4 and 6 feet bgs subsequent to well installation.

December 1999 – Two offsite soil borings (B5 and B6) were advanced and subsequently converted to monitor wells MW-5 and MW-6. Groundwater was initially present at approximately 10 feet below ground surface (bgs). Static water was observed at 7 feet bgs subsequent to well installation.

March 2001 - An underground utility survey was conducted to identify and locate underground utilities beneath and in the vicinity of the site that could provide potential preferential pathways for groundwater flow.

May 2001 - Five direct-push soil borings (GP-1 through GP-5) were installed to evaluate whether underground utilities in the vicinity of the site are providing preferential pathways for groundwater flow and the migration of dissolved hydrocarbons. The results of the investigation indicated insufficient evidence that underground utility lines were providing preferential pathways for the off-site migration of dissolved petroleum hydrocarbons.

December 2001 - Twelve direct-push soil borings (GP-6 through GP-17) were completed to further assess the extent of residual hydrocarbons in the vadose zone beneath the site. The results of the investigation indicated that the extent of the residual hydrocarbon impact detected in the previous investigations was limited.

December 2002 - One on-site monitoring well (MW-2) was destroyed during remedial excavation of hydrocarbon-impacted soil. This well was completed in the vicinity of the former eastern dispenser island and was replaced with on-site backfill monitoring well MW-2A. Approximately 292 tons of hydrocarbon-impacted soil was removed from beneath the former eastern dispenser island.

September 2003 - A *Request and Work Plan for Closure* prepared by ERI was submitted to the Alameda County Health Care Services Agency, dated September 10, 2003. The report summarized why no further action is needed for the site; the report also included plans to destroy the existing wells upon regulatory acceptance for no further action.

June 2004 – A work plan was submitted for two monitor wells downgradient of MW-5.

May 2005 – A work plan titled *Work Plan Addendum – Site Assessment Activity* dated May 17, 2005 was prepared by ATC Associates Inc. for the installation of two offsite monitor wells.

September 2005 – A work plan was prepared by ATC Associates Inc., titled *Work Plan Subsurface Investigation*, for the installation of one onsite monitor well.

September 2005 – Site environmental consulting responsibilities were transferred to Delta.

SENSITIVE RECEPTORS

June/July 2002 - A groundwater receptor survey was conducted. Three irrigation wells are located within a one-half mile radius of the site. The wells are located approximately 1,980 feet west and 2,245 feet southwest of the site, crossgradient and upgradient of the site.

GROUNDWATER MONITORING AND SAMPLING

Quarterly groundwater monitoring and sampling was initiated in March 1999. During the most recent groundwater sampling event conducted on February 24, 2006, depth to groundwater ranged from 5.08 feet (MW-5) to 6.60 feet (MW-1) below top of casing (TOC). The groundwater flow direction was north at a gradient of 0.02 foot per foot (ft/ft). Maximum dissolved groundwater concentrations were present as follows: total purgeable petroleum hydrocarbons (TPPH) (910 micrograms per liter ($\mu\text{g/l}$) in MW-1), benzene (0.51 $\mu\text{g/l}$ in MW-2A), and MTBE (5,100 $\mu\text{g/l}$ in MW-1).

REMEDIATION STATUS

Approximately 338 tons of hydrocarbon impacted soil and backfill were removed from beneath the former USTs, dispensers, and product lines during UST removal activities. Approximately 292 tons of hydrocarbon-impacted soil was removed from beneath the former eastern island during the December 2002 excavation.

CHARACTERIZATION STATUS

Based on the most current (February 24, 2006) and historic groundwater analytical data, MTBE is not defined offsite cross-gradient (east-west) of MW-6 and downgradient (north) of onsite well MW-4. Additional assessment is required to define the dissolved MTBE offsite and downgradient of the site.

Monitor well MW-1 is sampled annually. The most recent TPPH concentration in the groundwater sample from MW-1 was 910 $\mu\text{g/l}$, an increase from <50 $\mu\text{g/l}$ one year ago. The MTBE concentration in the same sample was 5,100 $\mu\text{g/l}$, an increase from 27 $\mu\text{g/l}$ one year ago. Groundwater samples from a Shell service station located approximately 75 feet south (upgradient) of the site show very high concentrations of TPPH and MTBE and it appears that MW-1 is showing impacts from offsite migration of these constituents.

Monitor well MW-6 continues to show a decline in TPPH and MTBE concentrations, and samples from MW-5 remain below laboratory detection limits for TPPH, benzene, and MTBE.

RECENT CORRESPONDENCE

No recent correspondence was documented during this reporting period.

THIS QUARTER ACTIVITIES (First Quarter 2006)

1. TRC conducted the quarterly monitoring and sampling event at the site on February 24, 2006.
2. Delta prepared a site conceptual model (SCM) for the site.

WASTE DISPOSAL SUMMARY

No waste was disposed of from the site during this reporting period.

NEXT QUARTER ACTIVITIES (Second Quarter 2006)

1. TRC will conduct quarterly groundwater monitoring and sampling at the site.
2. Delta will submit a SCM for the site and submit a work plan for downgradient characterization.

CONSULTANT: Delta Environmental Consultants, Inc.