If IBI and IB-3 are due to 415 te

SE 1:04 17 PH 3: 15

Resideral PAH in Soil not a health risk.

contamination, then water sample

from 1349 should also be impacted, but water was not impacted.

November 16, 1998

UST Local Oversight Program Alameda County Health Agency Department of Environmental Health 1131 Harbor Bay Parkway, 2nd Floor Alameda, CA 94502

Attention:

Eva Chu

Subject:

Report of Soil and Groundwater Investigation

1347 Park Street UST Site, Alameda, California

Alameda County Site ID 5511

GA Project No. 144-01-01

Investigation from the removal meda, California Chromotopans bid not shell new tight on case

God 1541 goes SE geneally. Mayke foot to instruct now rear AB-1

Dear Ms. Chu;

Gribi Associates is pleased to submit this report on behalf of Mr. Jim Russi documenting a recentlycompleted soil and groundwater investigation at the 1347 Park Street underground storage tank (UST) site in Alameda, California (see Figure 1 and Figure 2). The investigation included the drilling and sampling of three soil borings immediately adjacent to a heating oil underground storage tank (UST) formerly located in the Park Street sidewalk at the project site. The purpose of the soil boring investigation was to assess soil and groundwater quality adjacent to the former UST in order to address regulatory site closure.

BACKGROUND

One 1,500-gallon heating oil UST, which apparently had been unused for a long time, was removed from the project site on November 1995. Following removal of the UST, the Alameda County Department of Environmental Health inspector noted holes in the tank and hydrocarbon odors and sheens in the excavation. Soil samples collected at about 11 feet in depth from the UST excavation sidewalls at each end of the tank contained elevated levels of diesel-range hydrocarbons, and one soil sample collected at about 14 feet in depth from the center of the UST excavation cavity contained no detectable hydrocarbons. The UST excavation cavity was overexcavated in early December 1995, and three of the four soil samples collected from the four excavation sidewalls at about 12 feet in depth contained elevated levels of diesel-range hydrocarbons. After completion of overexcavation activities, the excavation cavity was backfilled with clean imported fill material and re-surfaced to match existing grade.

On August 27, 1998, Gribi Associates submitted a workplan to Alameda County UST Local Oversight Program proposing the drilling and sampling of three hand auger borings adjacent to the former project site UST. Alameda County granted approval to implement the workplan on August 31, 1998.

LIMITATIONS

The services provided under this contract as described in this report include professional opinions and judgments based on data collected. These services have been provided according to generally accepted environmental protocol. The opinions and conclusions contained in this report are typically based on information obtained from:

- 1. Observations and measurements made by our field staff.
- 2. Contacts and discussions with regulatory agencies and others.
- 3. Review of available hydrogeologic data.

DESCRIPTION OF FIELD ACTIVITIES

The three soil borings were drilled and sampled by Mr. Jim Gribi on September 16, 1998.

Prefield Activities

Prior to beginning field activities, Gribi Associates marked proposed boring locations and notified Underground Services Alert (USA). In addition, Gribi Associates obtained a drilling permit from Alameda County Public Works Department and obtained an Excavation Permit and an Encroachment Permit from the City of Alameda. Copies of these permits are contained in Appendix A.

Location of Soil Borings

Locations of the investigative soil borings, IB-1, IB-2, and IB-3, are shown on Figure 2. IB-1 was sited immediately southeast from the former UST in the Park Street parking lane. IB-2 and IB-3 were sited in the project site basement, west and southwest, respectively, from the former UST.

Drilling and Sampling of Soil Borings

Investigative boring IB-1, located in the Park Street parking lane at about ground surface elevation, was drilled to a depth of about 13 feet below grade. Investigative borings IB-2 and IB-3, located in the project site basement approximately 8.5 feet below surface grade, were drilled to a depth of about three feet below the basement floor (approximately 11 feet below ground surface grade). All borings were drilled using hand auger equipment. During hand augering, retrieved soil cuttings were logged by Mr. Jim Gribi, a California-registered geologist. Boring logs for the three borings are contained in Appendix B. All hand auger and sampling equipment was thoroughly cleaned and

decontaminated between each sample collection by triple rinsing first with water, then with dilute tri-sodium phosphate solution, and finally with distilled water. Following completion, the investigative borings were grouted to match existing grade.

One soil sample was collected from IB-1 at a depth of about 8.5 feet below ground surface grade. Soil samples were collected from IB-2 and IB-3 at depths of 2.0 ft and 1.5 feet, respectively, below basement grade (approximately 10.5 feet and 10.0 feet, respectively, below ground surface grade). Each of the soil samples was collected using the following method: (1) Exposed soil was scraped away; (2) A clean 2-inch by 6-inch brass tube was completely filled with undisturbed soil, taking care to minimize excess void in the tube; (3) The tube was then quickly sealed with aluminum foil and plastic end caps, wrapped tightly with tape and labeled; and (4) The sealed tube was immediately placed in cold storage for transport to the laboratory.

A grab groundwater sample was collected from each of the three investigative borings using a clean disposable PVC bailer. Each water sample was collected in three 40-ml VOA vials and two half liter amber jars by completely filling each container from the bailer, and then tightly sealing each container with teflon-lined septum, making sure that no air bubbles were present. Each container was then labeled and immediately placed on ice for transport to the analytical laboratory.

Laboratory Analysis of Soil and Groundwater Samples

A total of three soil samples and three grab groundwater samples were analyzed for the following parameters:

USEPA 8015M Total Petroleum Hydrocarbons as Gasoline (TPH-G)
USEPA 8020/602 Benzene, Toluene, Ethylbenzene, Xylenes (BTEX)
USEPA 8020/602 Methyl-t-butyl Ether (MTBE)
USEPA 8015M Total Petroleum Hydrocarbons as Diesel/Motor Oil (TPH-D/MO)

In addition to the above analyses, the soil sample from IB-1 was analyzed for the following parameters:

USEPA 8270 Polynuclear Aromatic Hydrocarbons (PNAs)

All laboratory analyses were conducted by Acculabs, Inc., a California-certified analytical laboratory, with two-week turn around on lab results.

RESULTS OF INVESTIGATION

General Subsurface Conditions

Subsurface soils in the three borings were similar, consisting primarily of reddish brown silty loose sands throughout. Grey green hydrocarbon staining, with moderate to strong hydrocarbon odors, was noted in soils from eight to 12 feet below ground surface grade in IB-1 and from just below the basement concrete slab (approximately nine feet below ground surface grade) to about two feet below the basement surface (about 10.5 feet below ground surface grade) in IB-1. No hydrocarbon odors or staining were noted in soil or groundwater samples from IB-2. Groundwater was encountered at about 11 feet below ground surface grade in IB-1, and at about 1.5 feet below the basement surface (10.0 feet below ground surface grade) in IB-2 and IB-3.

Results of Laboratory Analyses

Soil and water laboratory analytical results are summarized in Table 1. The laboratory data report for soil and water samples is contained in Appendix C.

Table 1 SUMMARY OF SOIL AND GROUNDWATER ANALYTICAL RESULTS 1347 Park Street UST Site								
			Pagagagagaga da da da	ation (parts p	72767A-1-0-0-0-0		i tentrakianan	
	A CHARLES OF THE COLUMN		and the second		J)		ing thousands and a	
	SC/16	WATER	SOL.	WATER	SOIL	WATER	PRG	
	854	(114)	1059	(9.5 ft)	10:0 A	(9.5 ft)		
ТРН-D	4,900	730	<1.0	0.12	3,500	65		
трн-мо	1,900	300	<10	0.97	1,400	30		
TPH-G	200¹	34 ¹	<1.0	<0.050	140¹	0.12		
Benzene	0.11	0.012	<0.0050	<0.0005	<0.10	<0.0005	1.4	
Toluene	0.25	0.029	<0.0050	<0.0005	<0.10	<0.0005	880	
Ethylbenzene	0.60	0.047	<0.0050	<0.0005	<0.10	<0.0005	230	
Xylenes	1.4	0.094	<0.0050	<0.0005	0.11	<0.0005	320	
МТВЕ	<1.0	<0.100	<0.050	<0.0050	<1.0	<0.0050		
PNAs								
Napthalene	7.4						240	
2-Methylnaphthalene	28							
Acenaphthylene	<3.4		<u></u>	•••				
Acenaphthene	<3.4			-		-	T 10	

Table 1 SUMMARY OF SOIL AND GROUNDWATER ANALYTICAL RESULTS 1347 Park Street UST Site Goncentration (parts per million)							
	\boldsymbol{u}		J.	L2 -1116	ge same as a L	3-3	
	\$0/II 85 #		SQIL 10 5 A	WATER 1954)	SOIL 10.0 A	W (T F.R. 79 S A)	PRG
Fluorene	<3.4						90
Phenanthrene	8.3						
Anthracene	<3.4						3.7
Fluoranthene	<3.4						27,000
Pyrene	5.0						100
Benzo(a)anthracene	<3.4		••••				2.6
Chrysene	5.1						72
Benzo(b)fluoranthene	<3.4		••••				2,6
Benzo(k)fluoranthene	<3.4		***				26
Benzo(a)pyrene	<3.4						0.26
Indeno(1,2,3-cd)pyrene	<3.4						2.6
Dibenz(a,h)anthracene	<3.4	<u> </u>				<u> </u>	0.26
Benzo(g,h,i)perylene	<3.4		***			***	

TPH-D = Total Petroleum Hydrocarbons as Diesel

TPH-MO = Total Petroleum Hydrocarbons as Motor Oil

TPH-G = Total Petroleum Hydrocarbons as Gasoline

MTBE = Methyl-t-butyl Ether

PNAs = Polynuclear aromatic hydrocarbons

PRG = Preliminary Remediation Goals for soil at industrial sites, established by USEPA, Region 9 (August 1, 1996). PRGs are chemical concentrations that correspond to fixed levels of human health and environmental risk (either one-in-one million cancer risk or a noncarcinogenic hazard quotient of one) for exposure in soil.

<0.10 = Not detected above the expressed value.

- 1 = Acculabs, Inc. laboratory report states " Product is not typical gasoline."
- -- = Not analyzed for this analyte.
- --- = No PRG listed.

CONCLUSIONS

Soil and groundwater samples from investigative boring IB-2, located west from the former project site UST, contained no significant levels of diesel-range hydrocarbons. Both field screening and laboratory analytical results from investigative borings IB-1 and IB-3 showed detectable levels of diesel- and motor oil-range hydrocarbons in soil and groundwater immediately southeast to

southwest from the former heating oil UST. However, results of PNA analysis for the IB-1 soil sample, which showed low levels of some PNA compounds, seem to indicate that residual hydrocarbons present in subsurface soils adjacent to the former project site UST pose no significant risk to public health and the environment.

Laboratory chromatograms from IB-1 and IB-3 soil and water samples, which are included in the laboratory report contained in Appendix C, show separate diesel- and motor oil-range hydrocarbon peaks, and the chromatogram from the IB-2 water sample shows only a motor oil-range hydrocarbon peak. Thus, it appears that offsite sources have contributed to hydrocarbons encountered beneath the project site. The project site is located in a commercial area of Alameda, with at least one identified UST located in the Park Street sidewalk immediately north from the project site. In addition, numerous buried utilities are present in Park Street immediately adjacent to the former UST, including a buried sewer line, which apparently services the project site and is connected to a floor drain in the project site basement, running along the north side of the former project site UST excavation cavity.

We appreciate the opportunity to present this report for your review. Please call if you have questions or require additional information.

Very truly yours,


James E. Gribi Registered Geologist California No. 5843


JEG/ct

GA-23/Russi.rp1

c Jim Russi







APPENDIX A CITY AND COUNTY PERMITS



APPLICANT'S NONATURE_

ALAMEDA COUNTY PUBLIC WORKS AGENCY

510 TO 917078645543

WATER RESOURCES SECTION 951 TURNER COURT, SUITE 300, HAYWARD, CA 94345-2651 PHONE (510) 670-8575 ANDREAS GODPREY FAX (510) 670-5262 (\$10) 670-5248 ALVIN KAN

	_
DRILLING PERI	MIT APPLICATION
FOR APPLICANT TO COMPLETE LOCATION OF PROJECT 1347 PARK STREET ALAMEDA 14	FOR OFFICE USE PERMIT NUMBER 98W2377 WELL NUMBER
California Coordinates Source ft. CCE ft.	PERMIT CONDITIONS
CCN APN CLIENT Name JIM RUSS Address U79 JOPKSHIPP ED Phone 519 36-2100 Cny Alexand CA Zip 34-501 APPLICANT Name JIM GRIB RG # 58 4-7 Address BOH HAPBER AVE Phone SAME City Sulsum CA Zip 94-501 TYPE OF PROJECT Well Construction (1 Geotechnical Investigation Cathodic Protection (1 General U Water Supply (1 Contamination Well Destruction (1 Well Destruction (1 Well Destruction (1 Municipal U Well Destruction (1 Municipal U Well Destruction (1 Municipal U Infigation (1 Municipa	Circled Permit Requirements Apply A GENERAL I. A permit application should be submitted so as to arrive at the ACPWA office five days prior to proposed starting date. 2) Submit to ACPWA within 60 days after completion of permitted work the original Department of Water Resources Water Well Drillers Report or equivalent for well projects, or drilling logs and location skatch for gentechnical projects. 3) Permit is void if project not begun within 90 days of approval date. B. WATER SUPPLY WELLS 1. Minimum surface soal thickness is two inches of cement grout placed by tremic. 2. Minimum seal depth is 50 feet for municipal and industrial wells or 20 feet for domestic and irrigation wells unless a lesser depth is specially approved. C. GROUNDWATER MONITORING WELLS I. Minimum surface seal thickness is two inches of cement grout placed by tremic. 2. Minimum surface seal thickness is two inches of cement grout placed by tremic. 2. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet D. GEOTECHNICAL Backfill bore hole with compacted cuttings or heavy bentonities and upper two feet with compacted material. In steas of known at suspected contamination, stended cement grout shall be used in place of compacted guttings E. CATHODIC Fill hole above anode zone with concrete placed by tremic to the compact of the compact
Number of Borings 3 Maximum Hole Diameter 31/4 in. Denth 13 ft. ESTIMATED STARTING DATE 9-4-98 FSTIMATED COMPLETION DATE 9-4-98	APPROVED DATE 9/2/3
I hereby agree to comply with all requirements of this permit and Alamena County Ordinance No. 73-68	

CITY OF ALAMEDA ENCRUACHMENT PERM Permit No: EN98-073 ENGINEERING OFFICE STATUS: APPROVED 2250 Central Ave., Room 250 Applied : 09/11/98 Alameda, CA 94501 748-4614 or 748-4518 Approved : 09/11/98 JUB AUDRESS : 1347 PARK ST Parcel number : 071 -0204-009-04 : RUSSI JAMES F & ARLEEN M TRS UWNER 428 YORKSHIRE RD ALAMEDA CA 94501 APPLICANT : GRIBI ASSOC.(J.GRIBI) 884 VINTAGE AVE BUISUN, CA 94585 207-864-5543 JOB DESCRIPTION: 2 METERED SPACES/2 SIGNS 9/16 Project Desc. : 2 METERED SPACES/2 SIGNS 9/16 Fee description Units Fee/Unit Ext fee Data , 10 th and the section of the secti PERMIT FILING FEE 1.00 32,00 ENCROACHMENT - METERS "NO PARKING" SIGNS

*** Fees Required *** *** Fees Collected & Credits 13.59Account No. Receipt No. Date Payment 224-37330 R9804281 09/11/98 R9804281 09/11/98 13.50 4240-33410 2.00TOTAL THIS DATE **** 15.50Fees: 47.58 .00 47.50 Hdjustments: lotal Credits:

32.00 15.5U

. 86

CALL 248-4614 OR 248-4518 FOR INSPECTION.

ALL CONSTRUCTION WITHIN THE PUBLIC RIGHT OF WAY MUST HAVE BARRICADES UTE: WITH FLASHERS FOR NIGHT TIME PROTECTION.

Total Payments: Balance Due:

HIS IS TO CERTIFY THAT THE ABOVE WORK HAS BEEN COMPLETED TO MY ATISFACTION AND APPROVAL.

INSPECTOR

CALL 748-4614 OR 748-4518 FOR INSPECTION

lotal Fees:

CITY OF ALAMEDA Permit No: EX98-102 EXCAVATION PERMIT ENGINEERING OFFICE STATUS: APPROVED 2250 Central Ave., Room 250 Applied : 09/02/98 Alameda, CA 94501. 748-4614 or 748-4518 : 09/11/98 Approved JOB ADDRESS : 1342 PARK ST Parcel number : 021 -0204-009-04 CWNER : RUSSI JAMES F & ARLEEN M TRS 428 YURKSHIRE RD ALAMEDA CA 94501 APPLICANT : GRIBI ASSUC.(J.GRIBI) 884 VINTAGE AVE SUISUN, CA 94585 202-864-9943 JOB DESURIPTION: BOARING FOR SAMPLES FROM TANK Project Desc. : BUARING FOR SAMPLES FROM TANK Fee description Units fee/Unit Ext fee Data FILING FEE 31.12 1.00ADDITIONAL MICRUFICHE FEE 2.982.98 EXCAVATION PERMIT FEE..... 54.2U 54.20 TUTAL. 88.80 *** fees Required *** *** Fees Collected & Credits Account No. Receipt No. Date Payment 001-300-4240-3292 R9804280 09/11/98 2,99 001-300-4210-3320 R9804280 097/1179994.70 UU1-3UU-424U-3245 R98U4280 0971179813.18001-300-4240-3290 R9804280 99711798 5.28 510-500-9409-3290 R9804280 8.44 09/11/**9**8 001-300-4240-3292 R9804280 09/11/98 4.22 TUTAL THIS DATE 88.80 88.80 Fees: Adjustments: . 00 Total Credits: .ប្រ Total Fees: 88.80 lotal Payments: 88.80 Balance Due:

CALL 748-4614 OR 748-4518 FOR INSPECTION.

NOTE: ALL CONSTRUCTION WITHIN THE PUBLIC RIGHT OF WAY MUST HAVE BARRICADES WITH FLASHERS FOR NIGHT TIME PROTECTION.

.00

THIS IS TO CERTIFY THAT THE ABOVE WORK HAS BEEN COMPLETED TO MY SATISFACTION AND APPROVAL.

Date		
	**	INSPECTOR

APPENDIX B SOIL BORING LOGS

BORING NUMBER: IB-1

LOG OF BORING

SHEET _1_ OF _1_

BORING LOCATION:

SOUTHEAST OF FORMER UST

BORING TYPE: INVESTIGATIVE BORING

PROJECT NAME:

1347 PARK STREET UST SITE

PROJECT NUMBER: 144-01-01

GRIBI Associates

START DATE: 09/16/98

COMPLETION DATE: 09/16/98

DRILLING CONTRACTOR:

DRILLING METHOD: HAND AUGER

BOREHOLE DIAMETER: 3-1/4 INCHES

BORING TOTAL DEPTH: 13 FEET

COMPLETION METHOD: GROUTED

				_					_	
	DEPTH SCALE (FEET)	SAMPLE NO.	Sample Depth	INTERVAL	RECOVERY	BLOWS PER 6 IN.	USCS	LOG OF MATERIAL		PIEZOMETER\ WELL INSTALLATION
Î								0.0 - 1.0 Ft, Asphalt and base rock.		
	_						SM	1.0 - 2.0 Ft. Brown silty SAND, fine, loose, moist to wet, no hydrocarbon odors or staining.		
	5 -						SM	2.0 - 8.0 Ft. Reddish buff SAND, silty, fine to medium grained, moist, no hydrocarbon odors or staining.	- - -	
١	_								1	
	_	IB-1.1	8.5 FT						1	
	10-	IB-1,	0,5 F1				SM	8.0 - 12.0 Ft. Grey green silty SAND, fine to medium grained, loose, moist, moderate to strong hydrocarbon odors.]	
	_	:							_	
	_								-	
							SM	12.0 - 13.0 Ft. Reddish buff silty SAND, fine to medium grained, loose, wet, no hydrocarbon odors or staining.		
								TOTAL DEPTH: 13 FEET GROUNDWATER DEPTH: APPROX. 11 FEET	-	
	15—								\exists	
	_								-	
	_								\exists	
	_									
	=								\exists	
	20 –								-	
	_								-	
	_								\dashv	
									\dashv	
	_				1				\dashv	
Ì	_								\exists	
	_								\dashv	
	_						1			

BORING NUMBER: IB-2

LOG OF BORING

SHEET _1_ OF _1_

BORING LOCATION:

NORTHWEST OF FORMER UST

BORING TYPE: INVESTIGATIVE BORING

PROJECT NAME:

1347 PARK STREET UST SITE

PROJECT NUMBER: 144-01-01

GRIBI Associates

START DATE: 09/16/98

COMPLETION DATE: 09/16/98

DRILLING CONTRACTOR:

DRILLING METHOD: HAND AUGER

BOREHOLE DIAMETER: 3-1/4 INCHES

BORING TOTAL DEPTH: 11.5 FEET

COMPLETION METHOD: GROUTED

DEPTH SCALE (FEET)	SAMPLE NO.	SAMPLE DEPTH	INTERVAL	RECOVERY	BLOWS PER 6 IN.	USCS	LOG OF MATERIAL	PIEZOMETER! WELL INSTALLATION	
5 -							BASEMENT DOWN TO 8.5 FT BELOW SURFACE GRADE		
-							8.5 - 9.0 Ft. Concrete and base rock.		
10-	IB-2.1	10.5 FT				SM	9.0 - 11.5 Ft. Reddish buff silty SAND, fine to medium grained, loose, moist to wet, no hydrocarbon odors or staining.		
-									
-							TOTAL DEPTH: 11.5 FEET GROUNDWATER DEPTH: APPROX. 10 FEET		
15-								_	
_									
_								-	
20 -								_	
_	-							-	
	-					!		_	
-	-							4	
	-								
_	_								

BORING NUMBER: IB-3

LOG OF BORING

SHEET _1_ OF _1_

BORING LOCATION:

SOUTHWEST OF FORMER UST

BORING TYPE: INVESTIGATIVE BORING

PROJECT NAME:

1347 PARK STREET UST SITE

PROJECT NUMBER: 144-01-01

GRIBI Associates

START DATE: 09/16/98

COMPLETION DATE: 09/16/98

DRILLING CONTRACTOR:

DRILLING METHOD: HAND AUGER

BOREHOLE DIAMETER: 3-1/4 INCHES

BORING TOTAL DEPTH: 12.0 FEET

COMPLETION METHOD: GROUTED

	COMPLETION DATE. 09/10/90								
DEPTH SCALE (PEET)	SAMPLE NO.	SAMPLE DEPTH	INTERVAL	RECOVERY	BLOWS PER 6 IN.	USCS	LOG OF MATERIAL	PIEZOMETER	WELL INSTALLATION
5 -							BASEMENT DOWN TO 8.5 FT BELOW SURFACE GRADE		
_	ļ — ·						8.5 - 9.0 Ft. Concrete and base rock.		
10-	IB-3.1	10.0 FT				SM	9.0 - 10.5 Ft. Grey green sitty SAND, fine to medium grained, loose, moist to wet, moderate hydrocarbon odors.	4	
_	12 0.1					SM	10.5 - 12.0 Ft. Reddish buff silty SAND, fine to medium grained, loose, wet, no hydrocarbon odors or staining.	4	
15— 							TOTAL DEPTH: 12.0 FEET GROUNDWATER DEPTH: APPROX. 10 FEET		

APPENDIX C LABORATORY DATA REPORT



Davis

1046 Olive Drive, Suite 2, Davis CA 95616 ■ 530-757-0920 ■ Fax 753-6091

Sample Log 19039 October 05, 1998

Jim Gribi Gribi Associates 884 Vintage Suisun, CA 94585

Subject:

3 Water and 3 Soil samples

Project Name :

Russi Site

Project Number:

144-01-01

Dear Mr. Gribi,

Chemical analysis on the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. USEPA protocols for sample storage and preservation were followed.

Acculabs - Davis is certified by the State of Arizona (AZ0583) and the State of California (# 1346). If you have any questions regarding procedures or results, please call me at 530-757-0920.

Sincerely,

Tom Kwoka



Davis

1046 Olive Drive, Suite 2, Davis CA 95616 ■ 530-757-0920 ■ Fax 753-6091

Subject :

3 Water and 3 Soil samples

Project Name : Project Number : Russi Site 144-01-01 Sample Log 19039

October 05, 1998

Case Narrative

PNA's by 8270C

SAmple extract would not concentrate to the normal final volume of 2.0 ml and was brought to 10 ml (1:5 dilution). At this level there was a lot of interference from non-target organics causing surrogates 5 and 6 to have high recoveries.

Stewart Podolsky

Tempe/Phoenix ■ Tucson ■ North Phoenix ■ Davis/Sacramento ■ Durango ■ Golden ■ Sparks/Reno



Davis

1046 Olive Drive, Suite 2, Davis CA 95616 ■ 530-757-0920 ■ Fax 753-6091

PNAs by 8270C

Sample Log 19039 October 05, 1998

Sample Name : IB-1.1 (8.5')

Project Name : Russi Site
Project Number : 144-01-01
Sample Date : 09/16/98

Date Extracted : 09/29/98 Extr. Method : EPA 3550

QC Batch

: BS980907

Date Analyzed

: 10/02/98

Date Received Dilution

: 09/17/98 : 1:5

Sample Matrix

: Soil

Lab Number

: 19039-01

	MDI	Measured	Units
<u>Parameter</u>	MRL	Conc.	•
Naphthalene	3.4	7.4	mg/Kg
2-Methylnaphthalene	3.4	28	mg/Kg
Acenaphthylene	3.4	<3.4	mg/Kg
Acenaphthene	3.4	<3.4	mg/Kg
Fluorene	3.4	<3.4	mg/Kg
Phenanthrene	3.4	8.3	mg/Kg
Anthracene	3.4	<3.4	mg/Kg
Fluoranthene	3.4	<3.4	mg/Kg
Pyrene	3.4	5.0	mg/Kg
Benzo(a)anthracene	3.4	<3.4	mg/Kg
Chrysene	3.4	5.1	mg/Kg
Benzo(b)fluoranthene	3.4	<3.4	mg/Kg
Benzo(k)fluoranthene	3.4	<3.4	mg/Kg
Benzo(a)pyrene	3.4	<3.4	mg/Kg
Indeno(1,2,3-c,d)pyrene	3.4	<3.4	mg/Kg
Dibenz(a,h)anthracene	3.4	<3.4	mg/Kg
Benzo(g,h,i)perylene	3.4	<3.4	mg/Kg
2-Fluorophenol		81	% Recovery
Phenoi-d5		77	% Recovery
Nitrobenzene-d5		117	% Recovery
2-Fluorobiphenyl		106	% Recovery
2,4,6-Tribromophenol		131	% Recovery
Terphenyl-d14		147	% Recovery

MRL = Method Reporting Limit

Conc. = Concentration

E = Concentration exceeded calibration range.

Approved By

Tom Kwol

Tempe/Phoenix ■ Tucson ■ North Phoenix ■ Davis/Sacramento ■ Durango ■ Golden ■ Sparks/Reno



September 21, 1998 Sample Log 19039

MTBE (Methyl-t-butyl ether) By EPA Method 8020/602

From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98 Received: 09/17/98

Matrix : Soil

SAMPLE	Macrix . Soil	Date Analyzed	(MRL) mg/kg	Measured Value mg/kg
IB-1.1	(8.5′)	09/23/98	(1.0)	<1.0
IB-2.1	(2.0/10.5')	09/18/98	(.050)	<.050
IB-3.1	(1.5/10.0')	09/23/98	(1.0)	<1.0

Approved By:

Stewart Podolsky Senior Chemist



September 21, 1998 Sample Log 19039

MTBE (Methyl-t-butyl ether) By EPA Method 8020/602

From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98 Received: 09/17/98

Matrix : Water

SAMPLE	Date Analyzed	(MRL) ug/E	Measured Value ug/L
IB-1W	09/18/98	(100)	<100
IB-2W	09/21/98	(5.0)	<5.0
IB-3W	09/18/98	(5.0)	<5.0

Approved By:

Stewart Podolsky Senior Chemist



Sample Log 19039


Sample: IB-1.1 (8.5')

From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98

Dilution: 1:20 Run Log: 4177F

Parameter	(MRL) mg/kg	Measured Value mg/kg
Benzene	(.10)	.11
Toluene	(.10)	.25
Ethylbenzene	(.10)	.60
	(.10)	1.4
Total Xylenes TPH as Gasoline	(20)	200 *
Surrogate Recovery	103 %	





Sample Log 19039

13053


Sample: IB-2.1 (2.0/10.5')

From : Russi Site (Proj. # 144-01-01)

Sampled : 09/16/98

Dilution: 1:1 Run Log: 4177D

Parameter	(MRL) mg/kg	Measured Value mg/kg
Benzene Toluene Ethylbenzene Total Xylenes TPH as Gasoline	(.0050) (.0050) (.0050) (.0050) (1.0)	<.0050 <.0050 <.0050 <.0050 <1.0
Surrogate Recovery	y	98 %



Phoenix ■ Tucson ■ North Phoenix ■ Davis/Sacramento ■ Durango ■ Golden ■ Sparks/Reno



Sample Log 19039


Sample: IB-3.1 (1.5/10.0')

From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98

Dilution: 1:20 Run Log: 4177F

Parameter	(MRL) mg/kg	Measured Value mg/kg
Benzene Toluene	(.10) (.10)	<.10 <.10 <.10 <.10
Ethylbenzene Total Xylenes TPH as Gasoline	(.10) (.10) (20)	.11 140 *
Surrogate Recovery * Product is not typical gasoline.		80 %



Phoenix ■ Tucson ■ North Phoenix ■ Davis/Sacramento ■ Durango ■ Golden ■ Sparks/Reno



Sample Log 19039

Sample: IB-1W


From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98

Dilution: 1:20 Run Log: 4177D

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
Benzene Toluene Ethylbenzene Total Xylenes TPH as Gasoline	(10) (10) (10) (10) (1000)	12 29 47 94 34000 *
Surrogate Recovery * Product is not typical gasoline.		116 %





Sample Log 19039

Sample: IB-2W


From : Russi Site (Proj. # 144-01-01)

Sampled : 09/16/98

Dilution: 1:1 Run Log: 4177E

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
Benzene Toluene Ethylbenzene Total Xylenes TPH as Gasoline	(.50) (.50) (.50) (.50) (50)	<.50 <.50 <.50 <.50 <50
Surrogate Recovery	У	99 %



Phoenix ■ Tucson ■ North Phoenix ■ Davis/Sacramento ■ Durango ■ Golden ■ Sparks/Rene



Sample Log 19039 19039-06

Sample: IB-3W


From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98

Run Log : 4177D Dilution: 1:1

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
Benzene Toluene Ethylbenzene Total Xylenes TPH as Gasoline	(.50) (.50) (.50) (.50) (.50)	<.50 <.50 <.50 <.50 120
Surrogate Recovery	У	101 %



Date Analyzed: 09-18-98 Column: 0.53mm ID X 60m Restek Rtx-1701

Stewart Podolsky Senior Chemist

September 21, 1998 Sample Log 19039

QC Report for EPA 8020 & Modified EPA 8015

Run Log: 4177D

From: Russi Site (Proj. # 144-01-01)
Sample(s) Received: 09/17/98

Parameter	Matrix Spike % Recovery	Matrix Spike Duplicate % Recovery	RPD *
P	100	100	0
Benzene	-		-
Ethylbenzene	99	103	4
TPH as Gasoline	112	113	1

* RPD = Relative Percent Difference

Parameter	Laboratory Control Sample % Recovery	
Benzene Ethylbenzene Gasoline	99 100 113	
Parameter	Method Blank	
Benzene Toluene Ethylbenzene Total Xylenes	<0.005 mg/Kg <0.005 mg/Kg <0.005 mg/Kg <0.005 mg/Kg	
TPH as Gasoline	<1.0 mg/kg	

Stewart Podolsky Senior Chemist

September 23, 1998 Sample Log 19039

QC Report for EPA 8020 & Modified EPA 8015

Run Log: 4177F (Methanol Extracts)
From: Russi Site (Proj. # 144-01-01)
Sample(s) Received: 09/17/98

Parameter	Laborato Spike % Recovery	ry Control Duplicate % Recovery	RPD *
Benzene	100	100	0
Ethylbenzene	102	103	1
TPH as Gasoline	128	130	2

Parameter	Method Blank	
Benzene	<0.10mg/Kg	
Toluene	<0.10mg/Kg	
Ethylbenzene	<0.10mg/Kg	
Total Xylenes	<0.10mg/Kg	
TPH as Gasoline	< 20mg/Kg	

QC Report for EPA 602 & Modified EPA 8015

Run Log: 4177A

From: Russi Site (Proj. # 144-01-01) Sample(s) Received: 09/17/98

Parameter	Matrix Spike % Recovery	Matrix Spike Duplicate % Recovery	RPD *
Benzene	101	107	6
Ethylbenzene	103	107	4

No gasoline spike recovery due to high gas in spiked sample.

* RPD = Relative Percent Difference

Parameter	Laboratory Control Sample % Recovery 98 100 110	
Benzene Ethylbenzene Gasoline		
Parameter	Method Blank	
Benzene Toluene Ethylbenzene Total Xylenes	<0.50 ug/L <0.50 ug/L <0.50 ug/L <0.50 ug/L	
TPH as Gasoline	<50 ug/L	

Stewart Podolsky Senior Chemist



Sample Log 19039


Sample: IB-1.1 (8.5')

From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98

Extracted: 09/18/98 QC Batch : DS980903 Dilution : 1:125 Run Log : 7418A

Parameter	(MRL) mg/kg	Measured Value mg/kg
TPH as Diesel	(130)	4900
TPH as Motor Oil	(250)	1900





Sample Log 19039 19039-02

Sample: IB-2.1 (2.0/10.5')

From : Russi Site (Proj. # 144-01-01)

Sampled: 09/16/98

Extracted: 09/18/98 Dilution: 1:1

QC Batch : DS980903 Run Log : 7418A

Matrix : Soil

Date: 09-19-98 Time: 03:14:13 Column: 0.53mm ID X 15m DB1 (J&W Scientific)

Parameter	(MRL) mg/kg	Measured Value mg/kg
TPH as Diesel TPH as Motor Oil	(1.0) (10)	<1.0 <10

긓 2 EPA Mod 8015 Stewart Podolsky Senior Chemist

Popenix v Tucson v North Phoenix v Davis/Sacramento v Durango v Golden v 👢 💯



Sample Log 19039


Sample: IB-3.1 (1.5/10.0')

From : Russi Site (Proj. # 144-01-01)

Sampled : 09/16/98

Extracted: 09/18/98 QC Batch : DS980903 Dilution : 1:125 Run Log : 7418A

Parameter	(MRL) mg/kg	Measured Value mg/kg
TPH as Diesel	(130)	3500
TPH as Motor Oil	(250)	1400





Sample Log 19039 19039-04

Sample: IB-1W

From : Russi Site (Proj. # 144-01-01)


Sampled : 09/16/98

Extracted: 09/21/98

QC Batch : DW980903 Run Log : 7418C Dilution: 1:118

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
TPH as Diesel	(5900)	730000
TPH as Motor Oil	(12000)	300000



Phoenix ■ Tucson ■ North Phoenix ■ Davis/Sacramento ■ Durango ■ Golden ■ Sparks Store



Sample Log 19039 19039-05

Sample: IB-2W


From : Russi Site (Proj. # 144-01-01)

Sampled : 09/16/98

Extracted: 09/21/98 QC Batch : DW980903 Dilution : 1:1 Run Log : 7418C

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L			
TPH as Diesel TPH as Motor Oil	(50) (100)	120 970			





Sample Log 19039

Sample: IB-3W


From : Russi Site (Proj. # 144-01-01)

Sampled : 09/16/98

Extracted: 09/21/98 QC Batch : DW980903 Dilution : 1:10 Run Log : 7418D

Matrix : Water

Parameter	(MRL) ug/L	Measured Value ug/L
TPH as Diesel	(500)	65000
TPH as Motor Oil	(1000)	30000



QC Report TPH Diesel by 8015 Mod

QC Batch: DS980903

Matrix: Soil

Spike and Spike Duplicate Results

Parameter	Matrix Spike (%Rec)	Matrix Spike Dup. (%Rec)	RPD %		
TPH as Diesel	NC	NC	NC		
* Possible matrix	x interference.	See LCS data below.			
Laboratory Contro	ol Spike				
Parameter	Laborat Spik	cory Control ke (%Rec)			
TPH as Diesel		100			

Method Blank

Parameter	MDL(mg/Kg)	Measured Value(mg/Kg)
TPH as Diesel	(1.0)	<1.0
TPH as Motor Oil	(2.0)	<2.0

Stewart Podolsky Senior Chemist QC Report TPH Diesel/Motor Oil by 8015 Mod

QC Batch DW980903

Matrix: Water

Spike and Spike Duplicate Results

Parameter	Matrix	Matrix	RPD
	Spike (%Rec)	Spike Dup. (%Rec)	%
TPH as Diesel	Not enough s See duplicat	ample for spiking. e LCS Data.	

Laboratory Control Spike

	Labora	RPD	
Parameter	Spike (%Rec)	tory Control Spike Dup. (%Rec)	્ર
TPH as Diesel	91	91	0

Method Blank

Parameter	MDL(ug/L)	Measured Value(ug/L)
TPH as Diesel	(50)	<50
TPH as Motor Oil	(100)	<100

Stewart Podolsky

Senior Chemist

•								breek.	Contract of	Lab No	mar de	3 (34)
aqualab inc									4.55	10.00	ggq.	
[] 3902 E. University Dr. Ph		34					37-0826		-			
[] 710 E. Evans Blvd. Tucso							84-5812 on 7605	100 E 100 E	oort • Date			
[] 2020 W. Lone Cactus Dr.							8 0-769 5 55-0817	B			**************************************	THE RESERVED OF
[] 992 Spice Islands Dr. Spa [] 75 Suttle St. Durango CO	21301 281301	•					47-4227					
							P	JELIC)	NATER	SUPPLY	INFORM	ATION
Client GRIBI AGGORIATES	۵.						Syste	m Name				
Address 884 VINTAGE AV							PWS			Percet	to State/EF	AYN
City, State & Zip Sulful CH	9458	<u> </u>					+			 		
Contact) M		•			i		POE	No.	-	DWR N	10.	
Phone 707/864 -59+3	Project Nam	ie Ru	421	5	10		Colle	ction Poi	nt			
Fax (i II	Project Num	ber 14	1-01	-0	<u> </u>		Colle	ctor's Na	me			
P.O. Number	Fax Results	(Y) N	ı F	age	0	<u>f </u>	Local	ion (City)	 , .	,	, , , ,
SAMPLE TYPE GODES		9 X	S.			lyses	77	1 1	/ /	//	///	/ / /
DW = drinking water TB = travel blank	Complia	223	a	C T	Requ	ested	اللا	//	//	/ / /	' / /	//
WW = waste water SD = solid	Monito	ring	m_	n				/ /	//	//	//	///
MW = monitoring well SO = soil	Y	N	?	t a		-/\s			/ /	//	/ /	/ / /
HW = hazardous waste SL = sludge TURNARGUND TIME REQU	ieeren		e			/ it	Ty.	//		///	/ / /	' / /
		in the second of		n		\X\),	X -	[[//	'	//	//
Standard	Lab Dire Appro	3	T Y	# e ⊙ r :		S	N /	/ /	/ /		//	/ /
RUSH	-	8	P	8	/5		7 /	//	′ /	/ /	/ / /	/ /
Special			e		//	17	' /	/ /	//	/ / /	' / /	
CLIENTS SAMPLE ID/LOCATION	/ Date	Time			{		{		++	-1-(-{-{-	多加度 (基本)
18-14 (85)	9/16		5	1	X	X			 			01
1B-2.1 (20/10.5)	ÌΙ	ĺ	5	1	X	1	<u> </u>			_		02
13-3.1 (1.5/100)	i ₁		5		*	$\langle \downarrow \rangle$	_				_	08:
B-IW	11		w	5	X	4						74
1B-7h	- ()		W	5	X	$\langle \cdot $			\perp			<u>05</u>
12-21	Ħ		W	6	X	X						06
										_		
	_				-	 		┼-┼-	+-+			
								 				
							1			1 1	1	
	- 		_ _	 -	 	\vdash						
				L			l					1000
instructions/Comments/Special Requirer	nents:											
nioa abata sa			-									
	Date	Time "		(* 15) C	iee'	all of	pishec	A.		Sample	s Receiv	ed By
SAMPLE RECEIPT				Parit		17	\cap		12	Dac	IM	
Received Cold	9/17/98		1	Mr4.1	<u>~C.</u>	-	*			M VVCC	MIKE C	
Custody Seals 1 Y N	9/17/98	1695	28	A) W	COL	114			12	one	N/E	11/4
Seals intact	4			- •-	- <u>r</u>	,						7
	90-4	<u> </u>								9		
No. of Containers	and and a second									Fanor Alex	ount le vo	io) = a = a
aqualabis terms are Net 4	0 (Paymen	t must be	recen	red by	tne	uate s	HOWN O	Hardeall	ANICO	and charge	Marie SAN	Marie Control