AGENCY



DAVID J. KEARS, Agency Director

ENVIRONMENTAL HEALTH SERVICES
ENVIRONMENTAL PROTECTION
1131 Harbor Bay, Park, av Suite 250
Alamedal CA 94502-6517
(510) 567-6700
FAY (510) 587-9335

REMEDIAL ACTION COMPLETION CERTIFICATION

StID 4102 - PARKS RFTA, Dublin, CA

March 28, 2001

Mr. Marshall Marik PARKS RFTA 5701 8th Street Dublin, CA 94568

Dear Mr. Marik:

This letter confirms the completion of site investigation and corrective action for the underground storage tanks formerly located at the above-described location. Thank you for your cooperation throughout this investigation. Your willingness and promptness in responding to our inquiries concerning the former underground storage tanks are greatly appreciated.

Based on information in the above-referenced file and with the provision that the information provided to this agency was accurate and representative of site conditions, this agency finds that the site investigation and corrective action carried out at your underground storage tank site is in compliance with the requirements of subdivisions (a) and (b) of Section 25299.37 of the Health and Safety Code and with corrective action regulations adopted pursuant to Section 25299.77 of the Health and Safety Code and that no further action related to the petroleum release(s) at the site is required.

This notice is issued pursuant to subdivision (h) of Section 25299.37 of the Health and Safety Code. Please contact our office if you have any questions regarding this matter.

Sincerely,

Mee Ling Tung, Director

cc: Chuck Headlee, RWQCB Allan Patton, SWRCB files-ec (campparks-8)

HEALTH CARE SERVICES

AGENCY



ENVIRONMENTAL HEALTH SERVICES

ENMIPONITENTAL PROTECTION 1131 Harbor Bay Parkita, Sure 250

Alemeda | DA 94502-657 | 1510) | 567-6700

FAX 510 38T-9335

DAVID J KEARS, Agency Director

StID 4102

March 28, 2001

Mr. Marshall Marik PARKS RFTA 5701 8th Street Dublin, CA 94568

Re: Fuel Leak Site Case Closure for PARKS RFTA, Dublin, CA

Dear Mr. Marik:

This letter transmits the enclosed underground storage tank (UST) case closure letter in accordance with Chapter 6.75 (Article 4, Section 25299.37[h]). The State Water Resources Control Board adopted this letter on February 20, 1997. As of March 1, 1997, the Alameda County Environmental Protection Division is required to use this case closure letter for all UST leak sites. We are also transmitting to you the enclosed case closure summary. These documents confirm the completion of the investigation and cleanup of the reported release at the subject site. The subject fuel leak case is closed.

SITE INVESTIGATION AND CLEANUP SUMMARY

Please be advised that the following conditions exist at the site:

- up to 4100ppm TPH as diesel exists in soil beneath the site; and,
- up to 3500ppb TPHd exists in groundwater beneath the site

If you have any questions, please contact me at (510) 567-6762.

eva chu

Hazardous Materials Specialist

enlosures: 1. Case Closure Letter

c: Dennis Carrington, City of Dublin, 100 Civic Plaza, Dublin, CA 94568 files (campparks-9)

2. Case Closure Summary

CASE CLOSURE SUMMARY Leaking Underground Fuel Storage Tank Program

I. AGENCY INFORMATION

Date: August 1, 2000

Agency name: Alameda County-HazMat

Address: 1131 Harbor Bay Pkwy

City/State/Zip: Alameda, CA 94502

Phone: (510) 567-6700

Responsible staff person: Eva Chu Title: Hazardous Materials Spec.

II. CASE INFORMATION

Site facility name: PARKS RFTA

Site facility address: PARKS RFTA, Building 790, Dublin, CA 94568

RB LUSTIS Case No: N/A

Local Case No./LOP Case No.: 4102

URF filing date: 3/17/93

SWEEPS No: N/A

	•			
Respo	nsible Parties:	<u>Add</u>	resses:	Phone Numbers:
Marsh Parks	all Marik RFTA	5701 8 ^t Dublin, (Street CA 94568	925/803-5638
<u>Tank</u> <u>No:</u>	Size in gal.:	Contents:	Closed in-place or removed?:	<u>Date:</u>
<u>Buildir</u>	ng 888			
1 2 3	10,000 10,000 500	Diesel Gasoline Waste Oil	Removed "	7/2/96 "
<u>Buildir</u>	ng 200			
1	275	Diesel	Removed	3/97
<u>Buildir</u>	ng 109			
1	2,500	Fuel Oil	Removed	3/94
Buildir	<u>ng 732</u>			
1 2	18,000 1,000	Gasoline Diesel	Removed	3/93 3/93

Tank No:	Size in gal.:	Contents:	Closed in-place or removed?:	<u>Date:</u>
Buildin	g 334			
1	1,000	Gasoline	Removed	11/18/98
<u>Buildin</u>	g 770			
1	700	Gasoline	Removed	12/94
<u>Buildín</u>	g 514			
1	100	Gasoline	Removed	3/97

III. RELEASE AND SITE CHARACTERIZATION INFORMATION

Cause and type of release: Unknown cause; Diesel release to groundwater

Site characterization complete? YES

Date approved by oversight agency: 7/11/2000

Monitoring Wells installed? Yes Number: 3 by Building 109

Proper screened interval? Yes, 12 to 22 feet bgs

Highest GW depth below ground surface: 10.6' Lowest depth: 14.1' in MW-1

Flow direction: SE to SW

Most sensitive current use: Commercial

Are drinking water wells affected? No Aquifer name: NA Is surface water affected? No Nearest affected SW name: NA

Off-site beneficial use impacts (addresses/locations): None

Report(s) on file? YES Where is report(s) filed? Alameda County

1131 Harbor Bay Pkwy Alameda, CA 94502

Treatment and Disposal of Affected Material:

<u> Material</u>	<u>Amount</u>	Action (Treatment	<u>Date</u>
	<u>include units)</u>	or Disposal w/destination)	
Tank	10 USTs	Disposed by H&H, in San Francisco, or Erickson, in	Richmond, CA
		from 1993 to 1998	
Soil	320 tons (Bldg 888)	Disposed at Vasco Rd LF, in Livermore, CA	2/98
	100 tons (Bldg 888)	Reused as backfill material for excavation	Ukn
Product/Rinseate	e 4,800 gal.	Disposed at PRC in Patterson, CA	3/94

Maximum Documente	ed Contaminant Co	ncentrations Be	fore and After Clea	anup
Contaminant	Soil (p	pm)	Water	(ppb)
	Before ¹	After ²	Before ³	After ⁴
TPH (Gas)	211	36	<50	<50
TPH (Diesel)	4,100 ⁵	4,100 ⁵	5,900	3,500
Benzene	.164	<.01	2.5	<.5
Toluene	.695	.042	1,2	<.5
Ethylbenzene	2.94	.045	2.5	<.5
Xylenes	16.3	.234	8.0	<.5
MTBE	NA	NA	ND	ND
TOG	28			

NOTE: 1 soil sample collected from Building 888 (7/96)

2 soil sample from Bldg 888 after dispenser area was overexcavated, 2/98

maximum groundwater concentration from wells at Bldg 109
most recent groundwater data from wells at Bldg 109, 11/96

5 soil sample collected from Bldg 200, 3/97

IV. CLOSURE

Does completed corrective action protect existing beneficial uses per the Regional Board Basin Plan?

Does completed corrective action protect potential beneficial uses per the Regional Board Basin Plan?

Does corrective action protect public health for current land use? YES

Site management requirements: A site safety plan must be prepared for construction workers in the event excavation/trenching is proposed in the vicinity of residual soil and groundwater contamination.

Should corrective action be reviewed if land use changes? YES

Monitoring wells Decommissioned: None, pending site closure
Number Decommissioned: 0 Number Retained: 3

List enforcement actions taken: **NA**List enforcement actions rescinded: **NA**

LOCAL AGENCY REPRESENTATIVE DATA

Name: Eva Chu

Title: Haz Mat Specialist

Signature:

8/1/00 Date:

Reviewed by

Name: Don Hwang

Title: Haz Mat Specialist

Date: 8/1/0 0

Thomas Peacock

Title: Supervisor

VI. **RWOCB NOTIFICATION**

RB Response: Coseun

Date Submitted to RB:

Title: AEG

RWQCB Staff Name: Chuck Headlee Cand Headlos

Date: 10/24/06

Signature:

VII. ADDITIONAL COMMENTS, DATA, ETC.

oct 23,2000

Camp Parks RFTA (PRFTA) was a former military training facility. PRFTA is located in the northeast quadrant of the intersection of Interstates 580 and 680, in Dublin, CA. PRFTA occupies approximately 2800 acres and is bounded by multiple entities, including Federal Correctional Institution, Santa Rita Rehabilitation Center, Santa Rita Jail, Tassajara Creek Regional Park, local business, and residential districts. Tenant organizations that lease buildings or space at PTFTA include Federal entities, private companies, and private and public organizations. A multitude of underground storage tanks (USTs) has been uncovered at the site between 1993 through 1999. Below is a brief description of activities conducted related to the closure of the USTs.

Building 888

Building 888 is located at the intersection of Monroe and 4th Streets. The site had operated a fuel service station consisting of two pump dispensers, one oil-water separator, 1-10K diesel, 1-10K gasoline, and i-500 gallon waste oil USTs.

On July 2, 1996, the three USTs and associated piping and dispensers were removed. An older generation of product lines was discovered between the two pump islands during tank closure activities and was also removed. One soil sample was collected beneath the waste oil tank and soil samples were collected below each end of the two fuel USTs. Soil samples were collected in the two generations of pipeline trench and beneath the dispensers. A maximum of 1,510ppm TPHd and 211ppm TPHg were identified in the soil samples.

A total of approximately 150cy of soil was removed from the fuel tank excavation. Approximately 25 cubic yards appeared to be contaminated with petroleum hydrocarbons. Limited soil contamination remains in the southwest end of the fuel tank excavation at 14.5 feet bgs and in the product line trenches. Limited overexcavation was conducted in the vicinity of the fuel dispenser island. Approximately 20cy of soil was excavated. Confirmatory soil samples (S-5-DP-1, S-6-OGP-1, and S-6-OGP-2) were collected. Only sample S-5-DP-1 contained petroleum hydrocarbon constituents (370ppm TPHd, 36ppm TPHg, and trace BTEX and MTBE).

Five soil borings (B1 through B5) were advanced around the former fuel tank excavation to delineate the extent of soil and possible groundwater contamination. Soil samples were collected at 5 feet intervals. Sediments beneath the site consist primarily of clayey silt. Groundwater was encountered in boring B1, B2, and B3 at 15 to16 feet bgs. Groundwater was not encountered in boring B4 or B5, which were drilled to only 14.5 feet bgs. A soil sample from boring B2, at 11.5 feet bgs, was ND for TPHd, but a duplicate sample contained 23,000ppm TPHd. However, the fuel pattern did not resemble the diesel standard and hydrocarbons appeared heavier than indicated in the standard. A soil sample from boring B2 at 14.5 feet bgs was ND for petroleum hydrocarbons. PAHs and hydrocarbon constituents were not detected in any of the other boreholes. Groundwater was collected from Boring B1 and B2. Groundwater from boring B1 contained 320ppb TPHd. No other hydrocarbon constituents were above the laboratory detection limits. Groundwater from Boring B2 did not contain detectable hydrocarbon constituents. It appears the fuel release at Building 888 did not significantly impact groundwater quality beneath the site. No further action is required at this area.

Building 200

Building 200 is located at the western border of Parks RFTA at the intersection of Dougherty Road and 5th Street. A UST was formerly located north of the security building, which is currently a police station for Parks RFTA.

In March 1997 a 275-gallon diesel fuel tank was removed. Hydrocarbon staining was observed in the excavation and in the road base approximately 30 feet southwest of the UST. Soil sample B1, collected in the pit at 7 to 9 feet bgs, contained up to 4,100ppm TPHd. Soil sample O4CC, taken from the road base northwest of the police station, at 1 to 2 feet bgs, contained 270ppm TPHd. Benzene was not detected in any of the soil samples.

To further delineate the extent of soil and possible groundwater contamination, five soil borings were drilled to depths ranging from 21 to 25 feet bgs. Boring B2 was drilled through the former UST pit. And borings B1, B3, B4, and B5 were drilled adjacent to the UST pit. Groundwater was encountered at approximately 22 feet bgs. Grab groundwater samples were collected from boring B3 and B4. Unremarkable or non-detectable levels of hydrocarbons and PAHs were in the soil and groundwater samples. It appears the diesel release at this site was limited in extent and groundwater has not been significantly impacted. No further action is required in this area.

Building 109

Building 109 formerly housed a trash incinerator. During building demolition activities in March 1994, a 2,500-gallon UST was discovered under the building floor. It is suspected that the tank held fuel oil, possibly as a supplemental fuel for the incinerator. In March 22, 1994, the UST was punctured, resulting in the release of product into the excavation. Approximately 442 gallons of product were removed from the excavation and another 1,077 gallons removed from the tank. Additional water and fuel was removed from the excavation pit of six subsequent dates from March 28 through April 25, 1994.

After the UST was removed, soil samples (West and East) were collected beneath each end of the UST. Up to 490ppm TPHg, 2,300ppm TRPH, 2,000ppm TPHmo and trace to non-detect BTEX were detected. A material which appeared to be ash from the incinerator was also discovered during demolition along the excavation walls on the south side of the building at approximately 4 feet bgs. Ash samples were collected from three areas and a composite sample was prepared for PCDD, PCDF, SVOC, and metal analysis. Calculated toxicity equivalency for dioxins and furans did not exceed residential and industrial USEPA Region IX Preliminary Remediation Goals. Lead, at 1190ppm, was the only metal detected in the ash sample at concentrations above the TTLCs. DTSC is the lead agency for oversight of the ash issue.

In January 1995, three groundwater monitoring wells (MW-1 through MW-3) were installed to a total depth of approximately 22 feet bgs. Groundwater was encountered at depths ranging from 12.5 to 16 feet bgs. Boring MW-1 was drilled through a lens of ash at approximately 4 feet bgs. A sample of the ash material from the boring was collected and analyzed for hydrocarbons as well as Lead and PCDD/PCDFs (polychlorinated dioxins/furans).

In May 1995, nine borings, B-1 through B-9 were drilled to depths ranging from 6 to 12 feet bgs to assess the lateral and vertical extent of ash constituents. None of the borings encountered an ash lens similar to what was seen in the tank pit. Soil samples were collected from boring B-2 and B-9 for STLC metals analysis by CWET. Elevated concentration of soluble lead was detected in the soil sample from MW-1 at 4 feet bgs (319ppm lead (CWET) and from boring B-2 at 6 feet bgs (78.9ppm). PCDD/PCDFs were not detected at levels of concern. Soil from each borehole did not contain TPHd and only trace or non-detectable levels of TPHmo and BTEX. Groundwater samples collected from all three wells contained low levels of TPHd, ranging from 62 to 1,200ppb. The groundwater sample from well MW-1 did not contain detectable lead.

Quarterly groundwater monitoring commence in May 1996. After four quarters of sampling, low levels of TPHd continue to be detected in each well (up to 3,300ppb). However, BTEX, MTBE, and PNAs have not been detected (except for trace levels of xylenes in well MW-3). Maximum TPHd detected to date in groundwater should not pose a risk to construction workers (based on RWQCB's Tier 1 Look Up Tables) It appears that the fuel release from the former UST did not significantly impact groundwater quality beneath this area.

Building 732

Building 732 was a former vehicle maintenance building for PARKS.

In March 1993 two USTs (1-18K gallon gasoline, 1-1K gallon diesel) in separate pits and their associated piping were removed. The gasoline tank pit measured 35'x30'x14' deep. Groundwater was observed in the pit at ~13'bgs. No odor or staining was noted from the pit and/or soil samples. The native soil comprised primarily of clay with some sandy silt. The diesel tank pit measured 12'x8'x8' deep. Groundwater encountered in the pit had mixed with rainwater, which drained into both the excavation and piping trenches. Stained soil was noted at approximately one feet bgs in the excavation and trenches.

Soil samples collected from both excavations and water from the gasoline tank pit did not contain elevated hydrocarbon constituents. However, the grab groundwater/rainwater sample from the diesel pit contained up to 13,500ppb TPHg and 36,000ppb TPHd. This rain/ground-water was subsequently pumped from the excavation and another water sample collected. The final water sample did not contain elevated levels of petroleum hydrocarbon constituents.

Additional subsurface investigations were conducted around the former diesel tank excavation. Three soil borings (CP-1 through CP-3) were drilled to ~14.5 to 16 feet bgs. Soil samples were collected at 2, 5, 10, and 14 feet bgs. A water sample was also collected from each boring. Laboratory analytical results confirmed that there was minimal fuel release to the subsurface from the diesel UST. No further action is required in this area.

Building 334

A 1,000-gallon gasoline UST and all associated piping were removed by Building 334 on 11/18/98. Two soil samples (SE-10-01 and NE-10-02) were collected beneath each end of the UST and analyzed for TPHg, BTEX, MTBE, TPHd, and lead. No hydrocarbon constituents were identified. Lead levels were within acceptable geogenic levels.

Building 770


A 700-gallon gasoline tank was removed in December 1994. A soil sample was collected at 16 feet bgs (3 feet directly beneath the center of the UST). Analytical results did not reveal TPHg or BTEX above the laboratory detection limits.


Building 514


A 100-gallon gasoline UST was removed in March 1997. The tank appeared in good condition. The tank was on a concrete pad. A soil sample was collected at the edge of the concrete slab. Hydrocarbon constituents were not detected in the soil sample.


In summary, case closure is recommended because:

- the leak and ongoing sources have been removed;
- the site has been adequately characterized;
- the hydrocarbon concentrations in groundwater appears to have stabilized;
- no preferential pathways exist at the site;
- no water wells, deeper drinking water aquifers, surface water, or other sensitive receptors are likely to be impacted; and,
- the site presents no significant risk to human health or the environment.









Analytical Results of Soil Samples Collected During Tank Removal Activities, July 2, 1996, POL Point Building 888, Parks RFTA, Dublin, California. All results are in mg/Kg (parts per million-ppm).

Sample Number	Location	Depth in Feet (bgs)	TPH as Diesel (1)	TPH as gasoline (1)	Benzene (2)	Toluene (2)	Ethyl- benzene (2)	Xylenes (2)	Lead (3)
CPD-1	South end Diesel UST	14.5	nor in		. 4 (#)				
CPD-2	North end Diesel UST	14.5	937 (4)	, NA	<0.1 (5)	<0.1	2.94	16.3	NA
CPG-1		15	<10	NA	<0.002	<0.002	<0.002	<0.002	NA
	South end Gasoline UST	16	<10	0.071	<0.002	<0.002	<0.002	<0.002	7
CPG-2	North end Gasoline UST	_, 16	<10	0.141	<0.002	<0.002	<0.002	<0.002	8
MOP-1	West en d gas pipeline	1.5	<10	<0.05	<0.002	<0.002	<0.002	<0.002	7.1
MOP-2	East end gas pipeline	1.5	<10	<0.05	<0.002	<0.002	<0.002	<0.002	
DP-1	West end diesel pipeline	2	1510	40.2	<0.01				10.4
DP-2	East end diesel pipeline	. 2	<10			0.173	0,207	0,857	11.3
	Edot ond diodol pipeline		~10	0.14	<0.002	<0.002	<0.002	<0.002	5.8
OGP-1	West end old gas pipeline	. 4	<10	20.6	<0.002	0.055	0.0775	0.192	10.1
OGP-2	Center of ald gas pipeline	4	87.6	211	0.164	0.695	1.73	2.6	11
OGP-3	East end of old gas pipeline	' 4	<10	<0.05	<0.002	<0.002	<0.002	<0.002	9.7
DSTP-1	Diocal Stankalla		70 ď						
GPSTP-1	Diesel Stockpile		76.8	NA	<0.002	<0.002	<0.002	<0.002	NA
=	Old gas pip eline Stockpile		35.7	1.38	<0.002	0.0173	<0.002	0.0317	10.1
GPSTP-2	"	I	<10	<0.05	<0.002	<0.002	<0.002	<0.002	11
		i							

Notes

¹⁾ Total Petroleum Hydrocarbons (TPH) as diesel and as gasoline using modified EPA Method 8015.

²⁾ Benzene, Toluene, Ethylbenzene, Xylenes (BTEX) using EPA Method 8020.

³⁾ Total Lead using EPA Method 6010.

⁴⁾ Shaded cells highlight concentrations detected at or above the analytical laboratory reporting limit.

^{5) &}lt;0.1 = Not detected at or above analytical laboratory reporting limit.

Table 2 Analytical Results of Soil Sample WO-1 Collected Below Waste Oil UST (8.5 feet bgs), July 2, 1996, POL Point Building 888, Parks RFTA, Dublin, California. All results are in mg/Kg (parts per million-ppm).

Volatile	Extractable	Oil and	TPH as	TPH as	BTEX (5)					
Halocarbons (1)	Organics (2)	Grease (3)	Diesel (4)	gasoline (4)	Compounds	Cadmium	Chromium	Lead	Nickel	Zinc
ND (8)	ND	28 (7)	<10 (9)	<0.05	ND	7.51	35.9	<10	38,4	48,7
Notes										


- 1) Volatile Halocarbons using EPA Method 8010
- 2) Acıd/Base-Neutral Extractable Organics uşing EPA Method 8270B
- 3) Extractable Hydrocarbons (Oil and Grease) using SM 503E/5520F.
- 4) Total Petroleum Hydrocarbons (TPH) as diesel and as gasoline using modified EPA Method 8015.
- 5) Benzene, Toluene, Ethylbenzene, Xylenes (BTEX) using EPA Method 8020.
- 6) LUFT Metals using EPA Method 6010.
- 7) Shaded cells highlight concentrations detected at or above the analytical laboratory reporting limit.
- 8) ND = Not detected at or above analytical laboratory reporting limit for all analytes reported.
- 9) <10 = Not detected at or above analytical aboratory reporting limit.

SUMMARY TABLE FOR SITES UNDERGOING INVESTIGATION

SUMMARY OF SOIL AND GROUNDWATER RESULTS Camp Parks Reserve Forces Training Area, Dublin, California

					Analyte (mg/kg.for soil and mg/L for groundwater)								
Sampling Location	Sample Description	Sample Date	Media	Analytical Method	Lend	TPH (diestl)	TPH (hydraulic floid)	TPH (gas)	миве	Benzene	Tohiene	Ethyl- benzene	Total Xylenex
Building 200 B200-P1 B200-O1CC B200-O4CC B200-B1 B200-C1	Under piping, 2-3 ft bgs In road base on E tide of Bldg, 1-2 ft bgs In road base on NW corner of Bldg, 1-2 ft bgs Bottom of excavation, 7-9 ft bgs Composite sample of excavated soil	35517 35517 35517 35517 35517 35517	Soil Soil Soil Sail Soil	EPA 8015M/8020 EPA 8015M/8020 EPA 8015M/8020 EPA 8015M/8020 EPA 8015M/8020	1 1 1	ND ND 270 4100 670		-	ND ND ND ND ND	NO NO NO NO NO	25 26 26 26 26 26	ND ND 006 023 ND	ND ND 036 096 006
B888-1GW B888-1S-11SW B888-2S-19SW	Groundwater sample collected from excavation 24hrs after detection 5 sidewall sample at 11 ft bgs 5 sidewall sample at 19 ft bgs Composite sample of excavated soil (gas & diesel excavation) Composite sample of excavated soil (hydraulion) lift excavations) Gas trench bottom sample, N side, 8-9 ft bgs Gas trench bottom sample, S side, 8-9 ft bgs Diesel trench bottom sample, 4-5 ft bgs	35521 35521 35521 35521 35521	Water Sail Soil Soil Sail Sail Soil	EPA 8015M/8020/6010 PPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010	13 14 11 11 14 14	0.84 % NO	5100	82 ND 16 130 ND 56 160	Manus Ma Manus Manus Manus Manus Manus Ma Manus Ma Manus Ma Ma Manus Ma Ma Ma Ma Ma Ma Ma Ma Ma Ma Ma Ma Ma	ND 0.0018 ND ND ND ND ND 0.0052	0.58 0.0037 0.042 0.089 0.0035 0.0055 0.004	17 ND 0.12 0 22 	10.1 ND 1.02 4 6 ND 0.042 0.033

General Notes
"---" = Not analyzed
ND = Not detected






Table 2
Analytical Results of Organic Constituents
Of Soil and Groundwater Samples Collected From Building 888: Soil Borings
Camp Parks RFTA

Dublin, California

		,	'	, x		Ethyl-	m,p-			Total	
Sample ID	Matrix	TPHG	TPHD	Benzene	Toluene	benzene	Xylene	o-Xylene	PAH	Lead	MTBE
S-11 5-B1	Soil	<1.3	<1.3	<0.0065	<0.0065	<0.0065	<0.0065	<0.0065	ND**	10.0	<0.026
S-16.5-B1	Soil	<1.2	<1.2	<0.0061	<0.0061	<0.0061	<0.0061	< 0.0061	ND**	5.5	<0.024
S-11.5-B2	Soil	<1.3	<1.3	< 0.0067	<0.0067	< 0.0067	< 0.0067	< 0.0067	ND**	11.0	<0.027
S-11.5-B2 dup	Soil	<1.3	23000	<0.0067	<0.0067	<0.0067	< 0.0067	< 0.0067	ND**	10.0	< 0.027
S-14.5-B2	Soil	<1.3	<1.3	< 0.0063	< 0.0063	< 0.0063	< 0.0063	< 0.0063	ND**	5.6	<0.025
S-11 5-B3	Soil	<1.3	<1.3	< 0.0063	< 0.0063	< 0.0063	<0.0063	< 0.0063	ND**	9.1	<0.025
S-14.5-B3	Soil	<1.2	<1.2	<0.0061	<0.0061	<0.0061	<0.0061	< 0.0061	ND**	6.3	<0.024
S-11.5-B4	Soil	<1.4	<1.4	<0.0068	<0.0068	<0.0068	<0.0068	<0.0068	ND**	9.4	<0.027
S-14.5-B4	Soil	<1.3	<1.3	< 0.0063	< 0.0063	< 0.0063	< 0.0063	< 0.0063	ND**	7.5	< 0.025
S-11.5-B5	Soil	<1.3	<1.3	<0.0065	<0.0065	<0.0065	<0.0065	< 0.0065	ND**	9.7	< 0.026
S-14.5-B5	Soil	<1.3	<1.3	<0.0064	<0.0064	<0.0064	<0.0064	< 0.0064	ND**	8.1	< 0.026
S-0519-1A,B	Soil	<1.4	<1.4	<0.0068	<0.0068	<0.0068	<0.0068	<0.0068	ND**	8.9	<0.027
W-16-B1 *	Water	<50	320	<0.5	<0.5	<0.5	<0.5	<0.5	ND**	22.0	<2
W-16-B1 dup₩	Water	<50	81	<0.5	<0.5	<0.5	<0.5	<0.5	ND**	39.0	<2
W-15-B2 <i>∱</i>	Water	<50	<50	<0.5	<0.5	<0.5	<0.5	<0.5	ND**	5.2	<2
rinsate blank ∦	Water	<50	NA	<0.5	<0.5	<0.5	<0.5	< 0.5	ND**	ND	<2
W-14-B3 🗡	Water	<50	<47	<0.5	<0.5	<0.5	<0.5	<0.5	ND**	61	<2

Notes.

Results measured in milligrams per kilogram

NA = Not Analyzed

TPHG = Total petroleum hydrocarbons as gasoline motor oil by EPA Method 8015 M

TPHD = Total petroleum hydrocarbons as diesel by EPA Method 8015 M

BTEX analyzed by EPA Method 8020A

PAH=Polynuclear Aromatic Hydrocarbons by EPA Method 8310

Total Lead by EPA Method 6010A

Soil Sample Notation Legend:

S-11-B1:

S =soil sample

W =water sample

11 =depth

B1 =Boring No.

^{* =} measured in micrograms per liter (µg/L)

^{** =} All analyte below laboratory detection limits.

Table 2

Analytical Results of Organic Constituents

Of Soil and Groundwater Samples Collected From Building 888: Stockpile Soils and Former Product Line

Camp Parks RFTA

Dublin, California

						Ethyl-	m,p-					Oil &
Sample ID	Matrix	TPHG	TPHD	Benzene	Toluene	benzene	Xylene	o-Xylene	MTBE	HVOC	semiVOC	Grease
S-1218-1A-1D	Soil	<1	2	<0.005	<0.005	<0.005	<0.005	<0.005	<0.020	NA	NA	NA
S-1218-2A-2D	Soil	<1	9.4	<0.005	< 0.005	<0.005	<0.005	<0.005	<0.020	NA	NA	NA
S-1218-3A-3D	Soil	<1	15	<0.005	<0.005	<0.005	<0.005	<0.005	<0.020	NA	NA	NA
S-1218-4A-4D	Soil	<1	620	<0.005	<0.005	<0.005	<0.005	<0.005	<0.020	ND	ND	170
						Ethyl-	m,p-			Total	•	Oil &
Sample ID	Matrix	TPHG	TPHD	Benzene	Toluene	benzene	Xylene	o-Xylene	MTBE	Lead	PAH	Grease
S-6-OGP2	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	<0.020	8.1	NA	NA
S-6-OGP2D												
3-0-0GFZD	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	<0.020	6.6	NA	NA
S-5-DP1	Soil Soil	<1 36	<1 370	<0.005 <0.010	<0.005 0.042	<0.005 0.045	<0.005 0.074	<0.005 0.160	<0.020 <0.040	6.6 9.6	NA NA	NA NA

Notes.

Results measured in milligrams per kilogram

NA = Not Analyzed

TPHG = Total petroleum hydrocarbons as gasoline motor oil by EPA Method 8015 M

TPHD = Total petroleum hydrocarbons as diesel by EPA Method 8015 M

BTEX analyzed by EPA Method 8020A

PAH=Polynuclear Aromatic Hydrocarbons by EPA Method 8310

Total Lead by EPA Method 6010A

HVOC = EPA method 8010 by 8260

semiVOA = EPA method 8270

Soil Sample Notation Legend:

S-11-B1:

S =soil sample


W =water sample


11 =depth


B1 =Boring No.

^{* =} measured in micrograms per liter (µg/L)

^{** =} All analyte below laboratory detection limits.







SUMMARY TABLE FOR SITES UNDERGOING INVESTIGATION

SUMMARY OF SOIL AND GROUNDWATER RESULTS Camp Parks Reserve Forces Training Area, Dublin, California

					Analyte (mp/kg for soil and mg/L for groundwater)								
Sampling Location	Sample Description	Sample Date	Media	Analytical Method	Lead	TPH (diesel)	TPH (hydraulic fluid)	TPH (gus) .	мιвε	Benzene	Toluent	Ethyl- benzene	Total Xylenes
Building 200 B200-P1 B200-OICC B200-O4CC B200-B1 B200-C1	Under piping, 2-3 ft bgs In road base on E ride of Bldg, 1-2 ft bgs In road base on NW comer of Bldg, 1-2 ft bgs Bottom of excavation, 7-9 ft bgs Composite sample of excavated soil	35517 35517 35517 35517 35517 35517	Soil Soil Soil Soil Soil	EPA 8015M/8020 EPA 8015M/8020 EPA 8015M/8020 EPA 8015M/8020 EPA 8015M/8020	1111	ND ND 270 4100 670	-	-	ND ND ND ND	25 25 25 25 25 25 26 25 25 26 25 25 26 25 25 26 25 25 26 26 26 26 26 26 26 26 26 26 26 26 26 26 26 26 26 26 26 2	25 25 25 25 25 25 25 25 25 25 25 25 25 2	ND ND 0.06 0.23 ND	ND ND 0.36 0.96 0.06
BinIding 888 B888-1GW B888-1S-11SW B888-2S-19SW B888-1C-GD B888-2C-HF B888-3S-GT8 B888-4S-GT8 B888-4S-GT8	Groundwater sample collected from exervation 24hrs after detection 5 sidewall sample at 11 ft bgs 5 sidewall sample at 19 ft bgs Composite tample of excavated soil (gas & diesel excavation) Composite sample of excavated soil (hydraulic lift excavations) Gas trench bottom sample, N side, 8-9 ft bgs Gas trench bottom sample, S side, 8-9 ft bgs Diesel trench bottom sample, 4-5 ft bgs	35521 35521 35521 35521	Water Soil Soil Soil Soil Soil Soil	EPA 8015M/8020/6010 PPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010 EPA 8015M/8020/6010	13 14 11 14 14 14	0,84 ND ND 7.3 	5100	82 ND 16 130 — ND 56 160		ND 0.0018 ND ND ND ND ND ND ND	0.58 0.0037 0.042 0.089 0.0035 0.0055	1.7 ND 0.12 0.22 ND 0.021 0.35	10.1 ND 1.02 4.6 ND 0.042 0.033

General Notes
"---" = Not analyzed
ND = Not detected




Table 2

Analytical Results of Organic Constituents

Of Soil and Groundwater Samples Collected From Building 200: Soil Borings

Camp Parks RFTA

Dublin, California

					1	Ethyl-	m,p-	1		Total	
Sample ID	Matrix	TPHG	TPHD	Benzene	Toluene	benzene	Xylene	φ-Xylene	PAH	Lead	MTBE
S-11-B1	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	ND**	5.8	<0.020
S-11-B1D	Soil	<1	<1	<0.005	<0.005	< 0.005	<0.005	<0.005	ND**	6.1	< 0 020
S-21-B1	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	ND**	5	< 0.020
S-12-B2	Soil	<1	1.2	<0.005	<0.005	<0.005	<0.005	<0.005	ND**	5.7	< 0.020
S-21-B2	Soil	<1	8.1	<0.005	<0.005	< 0.005	< 0.005	< 0.005	ND**	5.2	< 0.020
S-11.5-B3	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	< 0.005	ND**	6.5	< 0.020
S-20.5-B3	Soil	<1	<1	<0.005	<0.005	<0.005	< 0.005	< 0.005	ND**	6.9	< 0.020
S-11.5-B4	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	ND**	5.2	< 0.020
S-20.5-B4	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	ND**	5 .9	< 0.020
S-11.5-B5	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	ND**	6.1	< 0.020
S-20.5-B5	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	< 0.005	ND**	6 .6	< 0 020
S-0218-1A,B	Soil	<1	<1	<0.005	<0.005	<0.005	<0.005	<0.005	ND**	6	< 0.02
W-22-B3*	Water	<50	58	<0.5	<0.5	<0.5	<0.5	<0.5	ND**	<3	<2
W-22-B3D*	Water	<50	<50	<0.5	<0.5	<0.5	<0.5	<0.5	ND**	<3	<2
W-22-B4*	Water	<50	<50	<0.5	<0.5	<0.5	<0.5	<0.5	ND**	<3	<2
W-22-B4D*	Water	NA	<50	NA	NA	NA	NA	NA	NA	NA	NA
Rinsate Blank*	Water	<50	NA	<0.5	<0.5	<0.5	<0.5	<0.5	NA	NA	<2

Notes:

Results measured in milligrams per kilogram

NA = Not Analyzed

TPHG = Total petroleum hydrocarbons as gasoline motor oil by EPA Method 8015 M

TPHD = Total petroleum hydrocarbons as diesel by EPA Method 8015 M

BTEX analyzed by EPA Method 8020A

PAH=Polynuclear Aromatic Hydrocarbons by EPA Method 8310

Total Lead by EPA Method 6010A

Soil Sample Notation Legend:

S-11-B1:

S =soil sample


W =water sample

11 =depth

B1 =Boring No.

^{* =} measured in micrograms per liter (µg/L)


^{** =} All analyte below laboratory detection limits.



CAL	•	SERVICES	J08 NUMBER: 2809	DRAWN BY: JWB	DATE: 9/17/98
VACAVILLE, CA.95688		INC 707-446-7996	REVISIÓN: 10/5/98	CAD FILENAME: 2809FG5R.DWG	SCALE: AS SHOWN
		GIC CRO		CTION	DWG HO.:

5

BLDG 200: GEOLOGIC CROSS SECTION CAMP PARKS IN DUBLIN ALAMEDA COUNTY, CALIFORNIA



OPEN PIT

(FORMER LOCKETION OF B-109)

O TANK

O TANK

TO TON

EAST T-109

WEST

SAMPLE

TEXAMORDO BEPTHIE

SAMPENE LOCATIONS FOR T-109, PORKS PATA.

N

(SCALE: 1"= 5 FEET

	TRPH (PPM)	TPH- Motor Oil (PPM)	Benzene (PPM)	Toluene (PPM)	Ethyl- Benzene (PPM)	Xylene (PPM)
WEST	1400	320	N.D.	N.D.	N.D.	N.D.
EAST	2300	2000_	N.D.	N.D.	.91	3.9

THE

Table 2 Petroleum Soil Sampling Results for Tank 109

<u>'</u>	Cadmium (PPM)	Chromium (PPM)	Lead (PPM)	Nickel (PPM)	Zinc (PPM)
WEST	.72	38	11	44	55
EAST	.65	36	11	45	61

Table 3 Metals Soil Sampling Results for Tank 109




TABLE 3
SOIL SAMPLES ANALYTICAL RESULTS
BUILDING 109-UST

Sample I.D.		EPA Modified	Method 8015/8020		TPH by	EPA Modified Me	thod 8015	
(depth)	Benzen e	Toluene	Ethylbenzene	Xylenes	Diesel	Motor Oil	Kerosene	CWET Lead
MW-1 (4')	ND	ND	ND	ND	ND	29	ND	319(1)
MW-1 (10')	ND	ND	ND	ND	ND	ND	ND	
MW-1 (14')	ND	ND	ND	ND	ND	ND	ND	
MW-2 (5')	ND	ND	ND	ND	ND	ND	ND	
MW-2 (10')	ND	ND	ND	ND	ND	ND	ND	
MW-2 (15')	ND	ND	ND	ND	ND	ND	ND	
MW-3 (5')	ND	ND	ND	ND	ND	ND	ND	
MW-3 (10')	ND	ND	ND	ND	ND	ND	ND	
MW-3 (15')	0.057	0,11	0.30	1.0	ND	ND	ND	

						Total	Metals	by EPA	Method	6010A	(7471 fo	r Hg)					
	Sb	As	Ba	Be	Cd	Cr	Co	Cu	Pb	Hg	Mo	Ni	Se	Ag	Tl	v	Zn
MW-1 (14')	ND	5.1	112	ND	ND	19.6	9.0	15.6	5.6	ND	ND	26.5	ND	ND	ND	31.0	32.9
MW-2 (15')	ND	3.9		ND	ND	15.0		10.7	4.3	ND		19.4	ND	ND	ND	-	23.4
MW-3 (15')	ND	4.4	86	ND	ND	16.5	7.5	11.6	4.4	ND	ND	19.3	ND	ND	ND	27.9	28.0

NOTES: All results are in mg/kg

ND = not detected -- = not analyzed

⁽¹⁾ MW-1-4 appeared to be ash, results reported in mg/L

TABLE 3 ASH AND SOIL SAMPLES METALS ANALYTICAL RESULTS BUILDING 109-ASH

		Total Metals by EPA Method 6010A (7471 for Hg) ¹															
	Sb	As	Ba	Be	Cd	Cr	Co	Cu	Pb	Hg	Mo	Ni	Se	Ag	Tl	v	Zn
ASH-1	ND^2	7.6	1220	ND	19.2	80.1	14.2	501	11904	ND	ND	72	ND	8.3	ND	29.9	1540
MW-1 (14')	ND	5.1	112	ND	ND	19.6	9.0	15.6	5.6	ND	ND	26.5	ND	ND	ND	31.0	32.9
MW-2 (15')	ND	3.9	3	ND	ND	15.0		10.7	4.3	ND		19.4	ND	ND	ND		23.4
MW-3 (15')	ND	4.4	86	ND	ND	16.5	7.5	11.6	4.4	ND	ND	19.3	ND	ND	ND	27.9	28.0

					Soluble (STLC) N	Metals by	y CWE	f and E	PA Method	6010A	(7471	for Hg)	5			
	Sb	As	Ba	Be	Cd	Cr	Co	Cu	Pb	Hg	Mo	Ni	Se	Ag	Tl	v	Zn
MW-1 (4')				48					3196								
B-2 (6')	ND	0.49	2.6	ND	0.064	0.34	ND	4.7	78.9°	. 0.0030	ND	5.1	ND	ND	ND	0.81	80.1
B-9 (5.5')	ND	ND	13.3	ND	ND	ND	0.53	ND	ND	0.00044	ND	0.98	ND	ND	ND	0.59	ND

¹ Results are in mg/Kg

 $^{^{2}}$ ND = not detected

 ^{3 -- =} not analyzed
 4 Exceeds Lead TTLC regulatory limit of 1000 mg/Kg

⁵ Results are in mg/L

⁶ Exceeds Lead STLC regulatory limit of 5 mg/L

TABLE 4

GROUNDWATER SAMPLES ANALYTICAL RESULTS BUILDING 109-UST

	I	EPA Modified	Method 8015/8020		TPH by Modif	ied Method 8015	6010-A	8290 PCDD/	
Sample I.D.	Date Sampled	Ben zene	Toluene	Ethylbenzene	Xylenes	Diesel	Kerosene	Lead	PCDF
MW-1	1/25/95	ND	ND	ND	ND	62	ND	ND	ND
MW-2	1/25/95	ND	ND '	ND	ND	300	ND		
MW-3	1/25/95	2.5	1.2	2.5	8.0	1200	820		

NOTES: All results are in μ g/kg

ND = not detected -- = not analyzed

TABLE 2

DETECTED PCDD/PCDF AND TEQ CALCULATION
ASH-1 COMPOSITE

DIOXINS:		ntration g/g)	Toxicity Equivalency Factors (TEF)	Toxicity Equivalency (TEQ)
2,3,7,8-TCDD	ND		1	
Total TCDD		ND	NA	_
1,2,3,7,8-PeCDD	ND		0.5	~
Total PeCDD		ND	NA	_
1,2,3,4,7,8-HxCDD	ND		0.1	-
1,2,3,6,7,8- <u>H</u> xCDD	ND		0.1	~
1,2,3,7,8,9-HxCDD	ND		0.1	-
Total HxCDD		22	NA	-
1,2,3,4,6,7,8-HpCDD	94		0.01	0.94
Total HpCDD		160	NA	-
OCDD		460	0.001	0.46
,		642		
FURANS:				
2,3,7,8TCDF	4.4		0.1	0.44
Total TCDF		90	NA	J
1,2,3,7,8-PeCDF	ND		0.05	~
2,3,4,7,8-PeCDF	ND		0.5	-
Iotal PeCDF		27	NA	-
1,2,3,4,7,8-HxCDF	ND		0.1	-
1,2,3,6,7,8-HxCDF	ND		0.1	-
2,3,4,6,7,8-HxCDF	ND_		0.1	
1,2,3,7,8,9-HxCDF	ND		0.1	
Total HxCDF		ND	NA	-
,2,3,4,6,7,8-HpCDF	34		0.01	0.34
,2,3,4,7,8,9-HpCDF	ND		0.01	_
Total HpCDF		49	NA	*
OCDF		ND	0.001	-
		166		
TOTAL PCDD/PCDF:		808	TOTAL TEQ:	2.96

Notes:

Residential PRG for 2,3,7,8-TCDD = 3.8 pg/g
Industrial PRF for 2,3,7,8-TCDD = 24 pg/g
Adult EMEG for 2,3,7,8-TCDD = 700 pg/g
Child EMEG for 2,3,7,8-TCDD = 50 pg/g

Table 2 Analytical Results for Groundwater Samples Collected at Building 109, Camp Parks RFTA, Dublin, California.

All results are in parts per million (mg/L).

	•			BTEX(1)							
Sample Location	Date Collect ed	MtBE	Benzene	Toluene	Ethyl- benzene	Xylene	TPH as Diesel(2)	TPH as Kerosene(2)	TPH as Fuel Oil #4 (2)	Semi-Volatiles PNAs (3)	TPH as gasoline (4)
MW-1	1/25/9 5	NA	< 0.0005	< 0.0005	< 0.0005	< 0.0005	0.062	< 0.050	NA	NA	NA
	5/21/9 6	< 0.005 (5)	< 0.0005	< 0.0005	< 0.0005	< 0.005	< 0.050	< 0.050	< 0.050	NA	NA
	8/21.9 6	< 0.005	< 0.0005	< 0.0005	< 0.0005	< 0.005	0.073	< 0.050	NA	NA	NA
	11/21/9 6	<0.005	< 0.0005	< 0.0005	< 0.0005	< 0.0005	0.075	NA	NA	NA	NA
	2′20⁄9 7	<0.005	<0.0005	< 0.0005	<0.0005	<0.0005	0.081	NA ,	NA	NA	< 0.050
MW-2	1/25/9 5	NA	< 0.0005	< 0.0005	< 0.0005	< 0.0005	0.003	< 0.050	NA	NA	NA
	5/21/9 6	< 0.005	< 0.0005	< 0.0005	< 0.0005	< 0.005	0.55	< 0.050	< 0.050	NA	NA
	8/21/96	< 0.005	< 0.0005	< 0.0005	< 0.0005	< 0.005	0.38	< 0.050	NA	NA.	NA
	11/21/9 6	<0.005	< 0.0005	< 0.0005	< 0.0005	< 0.0005	0.52	NA	NA	NA.	NA
	2/20/9 7	<0.005	<0.0005	< 0.0005	<0.0005	<0.0005	0.77	NA	NA	NA	<0.050
MW-3	1/25/9 5	NA	0.0025	0.0012	0.0025	0.008	1.2	0.820	NA	NA	NA
	5/21/96	< 0.005	< 0.0005	< 0.0005	< 0.0005	0.0012	3,6	< 0.10	< 0.10	NA NA	NA NA
	8/21/96	< 0.005	< 0.0005	< 0.0005	< 0.0005	< 0.005	5.9	< 0.25	NA	NA NA	NA NA
	11/21/9 6	< 0.005	< 0.0005	< 0.0005	< 0.0005	< 0.0005	3,5	NA	NA	ND	0.43 ##
	2/20/97	< 0.005	< 0.0005	< 0.0005	<0.0005		1.94	NA	NA		0.2 ##
MW-1*	5/21/96	< 0.005	< 0.0005	< 0.0005	< 0.0005	0.001	0.61	< 0.050	< 0.050	NA	NA
	8/21/96	< 0.005	< 0.0005	< 0.0005	< 0,0005	< 0.005	7.3	< 0.25	NA	NA NA	NA NA
	11/21/96	< 0.005	<0,0005	<0.0005	< 0.0005	< 0.0005	0.43	NA	NA	NA NA	NA NA
	2/20/97	<0.005	< 0.0005	<0.0005		0.00073	3.3	NΛ	NΛ	NA	0.47 ##
		0.035 (6)	0.001 (6)	0.15 (6)	0.7 (6)	1.75 (6)					

Notes

¹⁾ MtBE (Methyl tert-Butyl Ether), Benzene, Toluene, Ethylbenzene, Xylenes (BTEX) using modified EPA Method 8021.

²⁾ Total Petroleum Hydrocarbons (TPH) as Diesel, as Kerosene, and as Fuel Oil #4 using modified EPA Method 8015.

³⁾ Semi-Volatile Organics-Polynuclear Aromatic partial using EPA Method 8270.

⁴⁾ Total Petroleum Hydrocarbons as gasoline using modified EPA Method 8015.

⁵⁾ All less than values indicate not detected at or above laboratory reporting limits.

⁶⁾ California Maximum Contaminant Levels

^{* =} duplicate of sample MW-3 for 5/21/96, 8/21/96, 2/20/97sampling events. Duplicate of MW-2 for 11/21/96 sampling event. NA = Not analyzed

ND = Not detected at or above laboratory reporting limit for all requested analytes.

^{## -} chromatogram pattern does not resemble a typical gasoline chromatogram pattern. See Analytical Data Review.

	dward-Clyde Consultants	. PRO	OJECT N	AME.	Co	imp	45	<u>~></u>	NO. 413.6
į.	IG LOCATION CPT BIDG: 109. 1	L'east of	MW-1	1	ELEVA	NOITE	AND	DATUM	
DRILL	ING AGENCY RUITHAND	DRILLER	ed Furt	W	DATE	START	ED (5/8/9	36
	ING EQUIPMENT 13-53 Molake	ENC.			сомр	LETION	DEP		SAMPLER. 'S' CA IN
DRILL	ING METHOD Hollow Stem Auger	DRILL BIT	6"			OF PLES	DIST		UNDIST.
SIZE A	AND TYPE OF CASING			- 1	WA	TER EV.	FIRS	T	COMPL. 24 HRS
TYPE	OF PERFORATION	FROM	то	FT.		ED BY	L		CHECKED BY:
SIZE A	AND TYPE OF PACK	FROM	то	FT.	٠.,				
TYPE	of seal Portland Coment	FROM O	10 16	FT.		ue			·
DEPTH IFEET)	. DESCRIPTION		GRAPH	Prezon Installa		Control Percometer Data	2	Penetial Sarah	REMARKS (Orill Rate, Fluid loss, Odor, etc.)
2	Clayer graves Rubble — FI Brown today prown aggregate Medium stiff, low plastically to moist, or some matter of becomes very stiff, non plast brown, stiff, shight plast to low plasticity, coloble up to 2", moist, some I Ash Rubble Rush Staurs, various colo asgresate, hostly brown I glass fagments, porce chips, slag, pebbles, in	nic nicky es	GN CZ					12 268 5 7 2 18 3 2 1	Begin Drill 0910 Redo due to poor recovery wil Noss system
9 1	becomes wet	• • • • • • • • • • • • • • • • • • • •	CI/NY				X	8 4 8 22	
10	Yellowish brown, some fine a aggregate at top, damp	and kilt of	\ <u>W</u>	,					Bottom of Borry 1070
	F	HELD LOG	OF BOR	ING 1	10 _	8-1			STEET 1 of 1

	dward-Clyde Consultants 4	OJECT N	AME	Can	P P	ark	S	No. <u>7</u>	136
	NG LOCATION BIDGIOG 5'W 1 20'S R	MW-1		ELEVA					
DRILL	ING AGENCY I NO UO DRILLER T	Rodfur	law	DATE S DATE F	INISH	EÐ	5/8/9		-
L				COMPLE			16	SAMPLER Z.	5"CA 10
SIZE	HOLLOW STEM ALAPY AND TYPE OF CASING 3	6"		SAMP	LES_	DIST.		UNDIST.	
J	OF PERFORATION IFROM	то	FT.	WATE ELE LOGGE	v	FIRS	···	CHECKED BY:	4 HRS
SIZE	AND TYPE OF PACK FROM	το	FT.					CHECKED BY:	
TYPE	OF SEAL PORTLAND COMENT FROM C	7 TO 13	FT.	281	uk	≥			
7	(Critical Cyrical)		IIC LOC	<u> </u>	, l	SAM	PLES		
DEPTH (FEET)	DESCRIPTION	Lithology	Piezon		Piezumet Data	# -	- 1 × 1 × 1	REMAR	
	Challant O grad		Install	ation > 0	8	[4]	Penetta Hesist (Blows/ 6 in 1	(Orill Flate, Fluid lo	ss, Odor, etc.)
	clayer gravel - FILL-	GM/				: [Begindri	11 1055
]	Gray to brown, various colors of	GC						' '	
1	lissregate, aggregate up to 211,					-	}		
							10		
2						-	12		
]	Ash Rubble					-	14	boon le	ecovery
	various color ascrepate and matrix, clayey and sandy matrix, peoples glass and metal farmonts some				‡	X	30	1	7
	glass and retal farmouts some						B		
4	- ASH Chess percent Rubble franci B-1 and B-2)] [_	16		
1	-flancia 184 and 18-2)						24		
]	-				[X	20	1	
1							7	-	
, ‡	Accomes black, coal like natter. fine				Ī		10		
6	scromes black, coal like watter, fine sand 913e, some aggregate					$\overline{}$			
‡	becomes as above					Δ	20	B-Z-6	11/5
$oxed{\exists}$					‡	.	7		
‡					‡		4		j
න †	becomes moist,		_	ł 			4	_	_
†	,			Į.	ţ	X	,0		
1	_				#			-	
1	becomes met, black				†	•	7		
		Ī	-		‡-	abla	8		
16	•				Ŧ	\triangle	11		
Ŧ					#	_	6		
1					1	4	5		
‡	CLAN	CL			Ŧ	X	5		
12	adark brown-gray brown, redun						18		
\	CLAY brown-gray brown, medundence, Stiff, Shigh ploshaly	-			7			Bottom	1130
1		ļ			‡		 	` `	-
+					+]
‡					†				
+	-				1				ا قر
<u>‡</u>									. 1
	FIELD LCG	OF BORI	NG N	10 <u>B</u>	-3			. HEET	_ of(

		OJECT N			_			NO. 7136
BOR	NG LOCATION BIDD 109 30 SON MI	W-1	-1	ELEVAT	100	ONA	MUTAC	
DRIL	LING AGENCY KUI WAVE	ON FA	lan !	DATE ST	TART	ĒD.	5/8	195
DRIL	LING EQUIPMENT B-53 Mobile Dril	<u> </u>	(COMPLE			TH 17	Y
DRIL	LING METHOD HOllow Stem Augus DRILL BIT	1 1	 }	NO.C)F	DIST.	10	UNDIST.
SIZE	AND TYPE OF CASING	64	-+	SAMPL	<u>.ES.</u>	FIRS		<u> </u>
J	OF PERFORATION IFROM	то		<u>ELE</u> \	<u>/i</u>	CINS	<u> </u>	
L				LOGGE	DBY			CHECKED BY:
<u> </u>		то	FT.	1	BiL	10		
TYPE	OF SEAL Portland Coment FROM O	1017	FΤ	·	ひし	110		,
		GRAPI	IIC LOG		=	SAN	APLES .	
DEPTH (FEET)	DESCRIPTION	Lithology	Piezom	Water Content	3 3 3 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	۽ و	= ===	REMARKS
ے ت			Installa	tion ≥3	Prezomes Data	Type No	Penetra Resist (Blows/ 6 in)	(Drill Rate, Fluid loss, Odor, etc.)
	Clayer grave -FILL-	0.11			-	- 1		
] :	gray to brown, various color acquegate	GM/		-	Į			Besin Drill
]	dry dough of the day of the	GC.	ĺ		‡			1140
	dry, dense, sandy clargey maker, nonplastic, peobles up to 1 cm				†	٠) ~
]]	Chot like B-1, B-2) No ash detail		1		ŀ		<u></u>	
12-	CIO 2002 B-1, B-2) No as a concert				+	12	N/I	
[]	with more Sand-SINA	ŀ			Ŧ	14	X	
	Will Mark Said The		İ		Į	. 1		
-	trace glass fragments, coal		1		#	20		poor Recovery
]	like farments			1 1	t	12	\mathbb{N}	Poor Patricy
	· • • · ·		i		ł		X	
4 -	<u>-</u>				Ŧ	14		
	becomes 10054, some glass			1 1	1	7	1 1	
-	sectives 100 2 -, some just				‡	8		
7	fragments and churks up to				+			
1	15cm				Ţ	2		
6	_				‡	2	1 1	
"					+	2	1 1	
]					Ł	3	\sim	
	becomes wet				1	5	\mathbb{N}/\mathbb{I}	
]	. Decomes wer				Ŧ	3	$\perp X \mid$	
1	•				‡	_ 1	$\angle \lambda$	
×-1	<u>.</u>		}-	1	- 🛓	3	1 1	
		ļ			+	y		
					Ŧ			Į
1		}			1	ろ		
<u> </u>	-				‡.	4		
Ŧ	trace of	- 1			t	ان		
107	porcelain fragments up to Icm	- 1			┢	7-	<u> </u>	
` ‡					Ŧ	6	N/I	
1					‡,	6	X	
+	CIAN Brown to double and I				+	-	I/V	
+	Brown to dark grey, moist - dama	CL			1	-	<u>/</u> }	\
121	Brown to dark grey, noist-damp, medium deux, stight preshaly			1 1	1	>		`
+							T	
1					‡	ì		Bottom \$210
7	-	j			1	-		
, ‡					ł	ſ		
1					Ŧ	}	1	
-	-				+			
+					‡			
		1		1 1	1	1	1	ì

Woodward-Clyde Consultants

PROJECT NAME CAMP PARKS 109 UST NO. 7137-0100

			IC LOG		1	544	PLES	NO. 110 1 - 10
DEPTH	DESCRIPTION	Lithalogy		i i	meter 1.			REMARKS
ā≟		2.15.03,	Installation	Conten	Paramet	VIN NO	Penerica Resist (Blows/ 6 at 1	(Drill Rate, Fluid Joss, Odor, etc.)
15	becomes mast Silly sand becomes met, brown to hight brange rust color, medium Sand with fines	SM/ SC		5-10		X		MW-3-15 0900 strang product
17	Clay gray to light brown nation clense, shight plasticity	MY				,		product oday
21 + + + + + + + + + + + + + + + + + + +					+++++++++++++++++++++++++++++++++++++++			product odor
++++ ++++	10@22				**************************************		{	TOC 0745 Monument well protectal placed at surface Stickup
#								
+++++++++++++++++++++++++++++++++++++++					1			

FIELD LOG OF BORING NO MW-3

S-EET 2012

PROJECT NAME CAMP Parks 109 UST Woodward-Clyde Consultants BORING LOCATION WID' NOTTE On excausted pile. 12/20/94 KVILH AUG SAMPLER JUCA COMPLETION DEPTH DRILLING EQUIPMENT ID. B-53 Mobile Dril UNDIST. DRILL BIT Hollon Stem Anger FIRST 16 WATER Sch: 40 4" PVC CHECKED BY: TO 22 LOGGED BY TYPE OF PERFORATION 0.020-inch TO 22 SIZE AND TYPE OF PACK FROM Lonester 412 SBILIR 10 FROM TYPE OF SEAL Portland Cement Bentante 9-10 Conference Presometer Data OŁP CH (FEET) Penutra Hesisi (Blows/ 6 in) REMARKS DESCRIPTION (Drill Rate, Fluid loss, Odor, etc.) Installation Begin drill 0815 Clayey gravel GM (Rubble) Dankbrown vanors color aggregate, moist (due to vain), agreeds up to tem, stight plastical Clay
Dankbown, pockets of medium
and fine sand (wanter to not
Colored stains), some gravels MW-3-5 0836 45 becomes Mostly clay, distribed texture (compacted) becomes nottled with gray, low plasticity, medium dense MW-3-10 0850 10 9 and stiff, damp 15 17 E FET 1 of 2

FIELD LOG OF BORING NO .

Woodward-Clyde Consultants PROJECT NAME Camp PACKS 109 UST NO. 7137 TOLOO

DESCRIPTION Lino agy Piezometer No installation MUCL SILTY / CLAYEN SANDS SOLTY / CLAYEN SANDS			UPAP	-IC LOG	hich.	,	929		102 / NO. 1131 DI
SILTY/CLANEY SANDS Sight to mun, very soft, non plastic, what, some sand, portects of clay CLANY light to medium brown, made and CL	£ P.T.	DESCRIPTION		<u> </u>	1				REMARKS
INJUST JOHN SANDS SITY/CLAYEN SANDS Injust brown, very soft, non plastic, whet, some sand, portects a clay If CLEAN Light to medium brown, medium Stiff dense, sand and soit at top 20 TD@ 22 TD@ 22 Hornweat well protector placed at surface Stick up	a ±				183] = [¥ .	2 E S S S S S S S S S S S S S S S S S S	(Drill Rate, Fluid loss Odor, etc.)
TD@ ZZ' Monument wetu probetor placed at surface Strick up	+	light brown, very soft, non plastic, wet, some sand, porkets of clay	SM/ SC				1	3 3 3	MW-2-15 1220
protector placed at surface Stick up	20 + + + + + + + + + + + + + + + + + + +	top				***			
		TD@ Z2'		_		+ + + + + + + + + + + + + + + + + + +		}	protector placed at surface
FIELD LOG OF BORING NO MW-2 SIEET Zof 2	1	FIELD LOG	DE BOD		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				

FIELD LOG OF BORING NO


Woodward-Clyde Consultants PROJECT NAME CAMP PANKS 109 UST NO. 7137-0100


		GRAPH	40 LOG	OVA	Ξ.		VPLES	
04.P1H (FFLT)	DESCRIPTION	Lithology	Plezameter Instalfation	AVO X	Prezonal Data	Type No	Penerica Densi (Blown) 6 m)	REMARKS (Drift Rate, Fruid loss, Odor, etc.)
15	Some assregate	CYML						
17+								
19+					† † † †			
21 + 22 + +	TD@22							T1 @ 1145
++++					**************************************			Monument well protector placed at surface Stick up
+#\+++#.++						-	-	1
}					† † † † † † †			I
-+ + ++-+-+ + + + -+ +		The company of the special party of the special par						
		OF BOBI			$\frac{1}{M}$		11	SEST 2-06 2

FIELD LOG OF BORING NO MW-1 S-EET 2 of 2

CAMP PAYES USTITIS Woodward-Clyde Consultants PROJECT NAME. NO.7137-0100 BORING LOCATION - 30 SOUTH & Incureated from DRILLERA DATE STARTED DATE FINISHED KULHAUG 12/20/94 COMPLETION DEPTH DRILLING EQUIPMENT SAMPLER "CA. ID. B-53 Mobile Drill Hollow Stem Auger NO. OF DRILL BIT CASING 4" PVC WATER FIRST 13.5 40 24 HRS TYPE OF PERFORATION 0.0 20 - inch FROM TO22 FT. LOGGED BY CHECKED BY: 12 SIZE AND TYPE OF PACK STOW 412 TO 22 FT. SBilin TYPE OF SEAL FROM Parlland Gment 0 Confession Presonneter GRAPHIC LOG SAMPLES 9-10 Bentonite REMARKS DESCRIPTION IOnili Rate, Fluid loss, Odor, etc.) CLANEY GRAVEL - RUBBIE GM) Begin dill 1025 Darkbrown, various color assessate GC brick-fragments, damp(Rain), 2 Clothay with brown, medium dense CL 10 and stift, low plasheity 11 MW-1-4 1040 DSH Rubble 45 Rush stains and varous color 6 aggregate, mostly black-brown, glass fragments, pebbles up to 9 15 17 Darkbrown, Some fine Sand/sitt ML packets and aggregate, slightly plustic, damp, motium dense becomes light brown to brown MW-1-10 1110 10 puplicate ۲5 12 19 becomes silly and damp 24 13 MW-1-14 130 5 V becomes wet 6 6


-EET 1 of 2






CAMP PARKS (ECS-30)

PLOT PLAN B-732 SKETCH #2



LEGEND;

&- SOIL SAMPLE LOCATIONS



CAMP PARKS (ECS-30)

AMPLING LOCATIONS FOR PIT B-732-1 AND B-731-1 PITS AND ASSOCIATED PIPING

SKETCH # 4

TABLE 1

SUMMARY OF ANALYTICAL RESULTS FOR SOIL AND WATER TESTED FOR LEAD, PURGEABLE AROMATICS AND TOTAL PETROLEUM HYDROCARBONS FOR TANK NO. B-732-1 (18,000 GALS) AND ITS ASSOCIATED PIPING.

SOIL SAMPLE DATE	LOCATION	SAMPLE NO.	<u>DETECTED</u> CONSTITUENTS	CONCENTRATIONS (PPM)
	Pit 732-1			
3/17/93	East	93-03-195	None	None
11	West	11	TPH-D	51
•	Piping trans	hs		
11	732-A1	11	None	None
21	732-A2	18	None	None
11	732-A3	en .	None	None
tī	732-A4	11	None	None
11	732-A5	**	None	None
11	732-A6	**	None	None
11	732-A7	11	None	None
11	732-B1	**	TPH-D	60
11	732-B2	19	None	None
11	732-B3	97	None	None
11	732-B4	39	None	None
11	732-B5	11	None	None
##	732-B6	11	None	None
P1	732-B7	16	None	None
STOCKPILE SOIL SAMPLE	LOCATION	SAMPLE NO.	DETECTED CONSTITUENTS	CONCENTRATIONS (PPM)
2/23/93		93-02-208	None	None
11	Composite 2A,B,C,D	11	None	None
	Composite			
WATER SAMPLE DATE	LOCATION	SAMPLE NO.	<u>DETECTED</u> CONSTITUENTS	CONCENTRATIONS MG/L(PPM)
2/23/93	Pit 732-1	93-02-208	Ethyl Benzene	.0006
			Xylene	.0023
			TPH-G	.065
3/17/93	Pit 732-1A	93-03-195	None	None

Note:

- 1. Pit 732-1 East and West sample (soil from the tank pit) were tested for Lead, Purgeable Aromatics, TPH.
- 2. Samples 732-A1 to A7 and 732-B1 to B7 (soil from the excavation of its associated piping trench) were tested for Lead, Purgeable Aromatics and TPH.
- 3. Stockpile samples 1A,B,C,D and 2A,B,C,D Composite (soil from the excavated tank pit 732-2) were tested for Purgeable Aromatics and TPH.
- 4. Water sample 732-1 (from the pit of tank 732-1) and sample 732-1A (taken on 3/17/93 for verification) were tested for Purgeable Aromatics and TPH.

SUMMARY OF ANALYTICAL RESULTS FOR SOIL AND WATER TESTED FOR O&G, TPH, BTEX, OTHER METALS, CHLOROHYDROCARBONS AND LEAD FOR TANK NO. B-732-2 (1,000 gals)


TABLE 2

SOIL SAMPLE DATE	LOCATION	SAMPLE NO.	<u>DETECTED</u> CONSTITUENTS	CONCENTRATIONS (PPM)
5/6/93	1A South	93-05-068	1,2-Dichloro Ben 1,3-Dichloro Be Mexochloroethan Tetrachlorobenz Pentachloroetha Lead Toluene Xylene	nzene .203 e .013 ene .002
11	2A North	16	None	None
5/14/93	1A South	93-05-172	Lead	8.8
11	2A North	Ħ	Lead	7.4
STOCKPILE SOIL SAMPLE	LOCATION	SAMPLE NO.	<u>DETECTED</u> CONSTITUENTS	CONCENTRATIONS (PPM)
2/23/93	3A,B,C,D Comp.	93-02-208	Chromium Nickel Zinc Lead Cadmium Ethyl Benzene Xylene TPH-G	20.7 28.2 39.2 12.9 .19 .159
			TPH-D TRPH	13.5 32

WATER SAMPLE DATE	LOCATION	SAMPLE NO.	<u>DETECTED</u> CONSTITUENTS	CONCENTRATIONS MG/L(PPM)
INITIAL WAT	ER SAMPLE			
2/23/93	Pit 732-2	93-02-208	Chromium Zinc Lead Ethyl Benzene Toluene Xylene TPH-G TPH-D	.007 .085 .054 .196 .118 .939 13.5
FINAL WATER	SAMPLE			
5/3/93	Pit 732-2	93-05-012	Zinc	.02
5/6/93	Pit 732-2	93-05-071	None	None

Note:

- 1. 1A South and 1A North samples (soil from the tank pit) were tested for O&G, Lead, Purgeable Aromatics, TPH and Chlorinated Hydrocarbon. Samples were taken again at the same location on 5/14/93 for verification.
- 2. Stockpile 3A,B,C,D Composite sample (soil from the excavation) was tested for Metals, Total Recoverable Petroleum Hydrocarbons, Purgeable Aromatics, TPH and Chlorinated Hydrocarbons. The stockpiled soil was placed on and covered by plastic. This soil will be disposed in accordance with Federal and State regulations.
- 3. The initial water sample Pit 732-2 (water from the pit after the tank was removed) and the final water samples (verified before disposal) were tested for Metals, Purgeable Aromatics and TPH.
- 4. Water sample Pit 732-2 which was taken on 5/3/93 was tested for Chlorinated Hydrocarbon, O&G, Metals and Purgeable Aromatics.
- 5. Water sample from pit 732-2 which was taken on 5/6/93 was tested for TPH and Purgeable Aromatics.



Woodward-Clyde Federal Services

CESPK-ED-EC Ray Zimny Corps of Engineers, Sacramento District October 20, 1994 Page 5

ANALY	TABLE 1 ANALYTICAL RESULTS FOR PARAMETERS DETECTED IN SOIL CAMP PARKS, DUBLIN, CALIFORNIA							
Soil Boring Number	Depth	EPA METHOD 7420 Total Lead ¹	MODIFIED EPA . METHOD 8015 TPH reported as Motor Oil ²					
: 	(feet)	(mg/Kg)	(mg/Kg)					
CP-1	2	9 .						
	5	12						
	10	16	·					
	14	10						
CP-2	1	12	213					
	5	12						
ļ	10	11						
	14	11						
CP-3	2	11	27³					
	5	11						
	10	15						
	15	11						

- -- Sample analyzed for TPH-diesel, neither diesel nor motor oil was detected
- 1 Sample preparation using EPA 3050
- 2 Sample preparation using EPA 3550
- 3 TPH found in samples were in the heavier, motor oil range.

Each soil sample was 6 inches. Number denoted represents the top of the soil sample

Woodward-Clyde Federal Services

CESPK-ED-EC Ray Zimny Corps of Engineers, Sacramento District October 20, 1994 Page 6

TABLE 2 ANALYTICAL RESULTS FOR DETECTED PARAMETER IN GROUNDWATER CAMP PARKS, DUBLIN, CALIFORNIA						
Soil Boring Total Lead ¹ Number						
	(mg/L)					
CP-1	0.26					
CP-2	0.22/0.222					
CP-3	0.065					

- $\frac{\underline{\text{Note:}}}{1 \ \text{Sample preparation using EPA 3005.}}$
- 2 Duplicate sample

	Ward-Clyde Consultants							DATUM	29732NO. 7128
	CYTILL NEW VOI	TOL LERA	- L)cen	KY I	DATE	TAPT	Ē		-10:1
	NG EQUIPMENT 1 1-1 D 21 R FO	K	aturk	w i	DATE P	INISH	ED		SAMPLER A C.
	Mobile Unit 6-5-		, ,,		NO.		DIST		UNDIST.
	HOWOW TEM DUCER		6"		SAMP	LES :	i		<u> </u>
	IC A		то	FT.	ELE		LIK?	14.25	
					LOGGE		_		CHECKED BY:
	- IA		TO	FT	SI	SIL	11R		M. Castula-
YPE O	F SEAL Portland Neat grout FROM	<u>' 0</u>	TO14.	5					
DEPTH (FEET)	DESCRIPTION		- GRAP1 Lithology	Person		Duta	SA ##	MPLES /Sep	REMARKS
				HNI	i V	1 -	E	\$ 5±50	tom hate, Field loss, Odor, etc.
‡	CLAYEY /SILTY GRAVEL		611/			1 1			Started 1200
. ‡	light gray (10 yr=1/1), up to (ocm	GC	1	ĺ	1 1			HALL CAL 074
1 ‡	gravel isubrounded to augular	j		1]	- 4	100	Prili to I'
 	anviloose		}		1	1		X 12	Poor Recovery
‡	ha more darkyellowith brown	١.						בי ע	
‡	becomes darkyellowith brown (10 yr 44) with motificationed gr	ucb,	1]		1	X	10	CP-1-2 1210
‡	iron oxide slains		1	Ì		1 1			Drill to 4.5'
+			 	1		1	-		1.0
‡	CLAY	1	CL					1	
<u></u>	(54 2.5/1) BLACK, LOW Plash	روان	t 	<u> </u>		\ <u>}</u>			1
1	drymedium dense, medium st	i `(€]]			
Ŧ			<u> </u>	1				XE	1
5Ŧ	becomes nottled wolve gray			-5		4		45	Was JEANCE
7 🚶	(5/4/2)		[ļ		X	9	theadspace CP-1-5 1220
1	•					1		14	CF-1-0 1000
Ŧ				1			-		1
‡			ļ				-	}	Drill to 9.5'
1	as above, trace gravel dsan	d		-		1	-		C.L. 01 11117
‡	, 0						.		1
‡							.		
‡	•		}				-		
+						1 1			
‡						1 1	_		
‡						1	:		
‡	land aft it would	1/. >				 			Headspace
10+	becomes Soft, ohive gray (54)	12)		41				5	,
1	9 .					1	\triangle	7	CP-1-10 1230
<u> </u>							_]	12	-
Ŧ						1	-		Drill to 13'
1								1	
+						1 1	-		1
Ī							r	'	
+ +	becomes day & gray (544/1), inc	teas					.	-	
+	in Ame sand+ coarse sitt anade	\mathbf{v}^{-1}			!	‡	- :	-	†
‡	to subvounded, slight plashial	,			i	+	ţ	5	111-1 m=0
4 +	becomes dayf gray(544/1), inc in fine sand+ coarse silt, angula to subvounded, slight plashick, morst, loose				,]		. 5	Headspace
, †	be comes NET	ļ		2	Y] }	\times	6	CP-1-14 1245
+				<u></u>		<u> </u>			

_			-245-	iic Log	. 1	ia la	SA	MPLES	BCN10::5
(FEET)	DESCRIPTION		Lithalogy	HNU	Marit	Piezum	Signality.	fector (c Penetra Hessa (Blovo)	REMARKS E (Drill Rate, Fluid loss Odor, etc.)
1 ‡						-	-		
1	TO@ 14.5'								TO @ 1245
+	•								HOU readings
<u> </u>]			HAU readures of cores unless otherwise noted
+									otherwise noted
+						-	-		Retrievable
‡									screen + tip vs
<u>†</u>						-			Retrievable screen + tip vs on hydroporch
Ţ	-			ļ					,
1						-	-		
‡			j [
‡						-			
1						_			
- + + + + + + + + + + + + + + + + + + +									
<u>‡</u>						-	-		
 									
† 						-			
 									
‡						-			
‡									
<u> </u>						-	<u> </u>		
‡		_				-			
Ŧ						-			
†						-			
++++				:		-			
+ +									
-							-		
+++++++++++++++++++++++++++++++++++++++								. ;	
‡							<u>.</u>	. !	
<u> </u>						-		†	
+++++		:				-			
‡							-		


BORING	LOCATION (P-1)	(9' NW of	priver of	1167 7	A'/ 11	LEVAT	ION AND	DATUM		
DRILLIN	G AGENCY KUIL HA		DRILLER	ad furl	טע פ	ATE ST	ARTED	71	15/94	
DRILLIN	G FOUIDMENT		-53		C	OMPLE	TION DE	PTH45	SAMOLEO	IOD. CA
DRILLIN	CMETHOD	tem Duaer	DRILL BIT	6"		NO. C	F DIS		UNDIST. 1	1
SIZE AN	D TYPE OF CASING	417	- A			WATE	R FIF	₹\$7 4	COMPL.	24 HRS
TYPE OF	PERFORATION	N/J	FROM	TO	FT.	LOGGE	<u>· </u>		CHECKED BY	<u> </u>
	D TYPE OF PACK	۸(۸	FROM	то	FT.	~0	• .	. ¬		
TYPE OF	SEAL Portland Ne	eat Grout	FROM (<u>5</u>	2'R	ilik		M. Cast	Uhao
DEPTH (FEET)		RIPTION		Lithology	LOG LOUSILING HWI	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Piezumater Data	Penetra Herov II Penetra Hessist (Blows/	REMA	
1 1	SILTY GRAV Lightgray (It gravets, subre loose, dry becomes mult oxide stains	ounded to an	gulan	GM/ GC			X	13 11 11	Start I HNU CAI Drill to CP-2-1 Poor R	16.074 11 1425
+++++++++++++++++++++++++++++++++++++++	CLAY Black (54 2 dry, stiff, tra	5/1), tow place		CL			+ + + + + + + + + + + + + + + + + + + +		Drill to	·
5 + + + + + + + + + + + + + + + + + + +	as above, we gray (54 4/-	the a with a 2)	blive		ーち		X	5812	Headspa CP-Z-5 Drill to	
+++++++++++++++++++++++++++++++++++++++	becomes olw	c guay 054	4/Z) —				+			
10-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	becomes light 574), mediums gray (54 4/1)	olive brown (.h.fl., with d ,damp,56fi	2.5Y ak		<1			0 & C	CP-Z-ID Headspa Drill to	
H+++++++++++++++++++++++++++++++++++++	becomes medic Soft becomes wet, increase in ver	very soft			۷١	Y	 	10.00	Headspo	ece 1450


PROJECT NAME CAMPPANKS Blog 732 NO. 7128 Woodward-Clyde Consultants DI PTH (FEET) REMARKS Perometer P Lithology DESCRIPTION (Drift Rate Fruid loss Odor, etc.) 刊主 TO @ 14.5' TD @ 1450 HNU readured of cores onless otherwise noted. Retrievable screen vsed in hydropurch


JEET Laf C

PROJECT NAME Camp Parks - Blog 732 NO. 7128 Woodward-Clyde Consultants BORING LOCATION ELEVATION AND DAT (9' S of center UST 732-2) DRILLER ROd Forlow DATE STARTED DRILLING AGENCY 7/15/94 KVILHAUG COMPLETION DEPTHO DRILLING EQUIPMENT B-53 Mobile drill MOD. Hollow Stem Auger DRILL BIT NO.OF DRILLING METHOD DIST. 4 SIZE AND TYPE OF CASING WATER FIRST 4.25 COMPL. **24 HRS** 1 A TYPE OF PERFORATION nA FROM CHECKED BY: LOGGED BY S.Bilir ŦŌ SIZE AND TYPE OF PACK FROM nla M. Castellanos TYPE OF SEAL PORTLAND FROM TO Neat anout SRAPHIC LOG SAMPLES DEPTH (FEET) A STATE OF THE STA Penetra Resist (Blows/ 6 in) DESCRIPTION TIN IX (Drill Rate, Fluid loss, Odor etc.) SILTY/CLAYEY GROUEL Lightgray (1048=11), up to 6'cm, loose, any, angular Start, 0900 Restart 0908 HNU CALIBR. 0740 GH/ GC Drill to 1' poorrecovery GRAVELLY CLBY
GRAVISH Brown and very dark gray brown
(10) K 5/2 and 10 YK 3/2) some savd/gravely CL Ю 48 CP-3-2 0910 low plastically divi, metium stiff LI MUJ 9 grayish brown and very dark grayish 6 brown (10 y R 512 are 10 y R 312) 16W Plasticity, dampy Medium Gense 1 stiff CL Headspace 41 becomes black (104R 21), hace gravel, roots જ Headspace 5 becomes dark gray (5441), CP-3-5 0925 41 trace coarse sand 10 18 as above, notified with olive brown (2.5 y 413), various colors, pockets of sand (medium), stiff, some roots 5 41 9 17 as above 5 8 41 darkgray (544/1), medium plasticity, 15 10 CP-3-10 6955 5 8 2-5 Olive brown (2.5 V4/3) mothed with dark gray (5 V4/1), olive brown is medium stiff / low plasticity, dark gray is coff medium plasticity Headspace 11 5 8 10 becomes dark grayish brown 12.5 y 4/2), some mediums and, high 5 plasticity, molet, soft 6 becomes wet +EET ! of FIELD LCG OF BORING NO.

_		GRAP-	ic roc		5	SA	MPLES	
15 15 17	DESCRIPTION	Lithology	Latomere. Introduce HNU		Prezumet	the sta	Herry 11 Penchal Hesist (filoss/	REMARKS (Drift Rate, Fluid loss, Odor, etc.)
+		m)						
++	as above, increase in medium	CL					3	CP-3-15 102
+	sand, very soft					X	335	CP-5-15 102
+	TO @ 16'			_				TO@ 1025
+					-	-		HALL readings
‡					-			of core unless otherwise noted
Ţ †					-			[_
+	•				-	- 1		Retrievable screen did not
╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸╸					-	_		retrieve when
‡							1	
 + + + + + + + + + + + + + + + + + + +						-		
† † †								
+					1		:	
† +					-			
_					-			
† + + +					-	-		
 								
† † †								
+					1	-		
+						. !	}	
÷ †					-		i (
- +			ļ			- 1		
+			ļ			. '	1	
+ ++-+			V anglitzer pringing and a state of the stat				į	
-					-	_ '	}	
┤╌╬╌╬╌╬╌╬╌╬╌╬┾╬╸╬╶╬╌╬╌╸╛╺┩╍╬╌ ┆╶╸┾╌┿╌╬╸╸╸ ┆╸╸╸╸ ┆╸╪ ╶╸╸╸	FIELD LO				*		-3	_







DRAFT

4.2.2 The soil samples were analyzed for: 1) Benzene, Toluene, Ethylbenzene and Xylene (BTE & X); 2) Total Petroleum Hydrocarbons (TPH) using diesel and gasoline as a standard; 3) Methyl Tertiary - Butyl Ether (MTBE); and 4) Lead.

Table 1A. Analytical Results of Samples taken at the Bottom of Excavation


Analyte.	Soil Sample Number Camp Parks-334-SE-10-01 mg/kg (ppm)	Soil Sample Number Camp Parks-334-NE-10-02 mg/kg (ppm)	US EPA Method Number
Benzene	ND	ND	5030A/8020A
Toluene	ND	ND	5030A/8020A
Ethylbenzene	ND	ND	5030A/8020A
Xylenes (total)	ND	ND	5030A/8020A
TPH (diesel)	ND	ND	8015M
TPH (gasoline)	ND	ND	8015M
MTBE	ND	ND	5030A/8020A
Lead	7.6	15	7420

Table 1B. Analytical Results of Samples taken at the Excavated Soil Piles

Analyte	Soil Sample Number Camp Parks-334-Piles-01 & 02 mg/kg (ppm)	Soil Sample Number Camp Parks-334-Pile-03 mg/kg (ppm)	US EPA Method Number
Benzene	ND	ND	5030A/8020A
Toluene	ND	ND	5030A/8020A
Ethylbenzene	ND	ND	5030A/8020A
Xylenes (total)	ND	ND	5030A/8020A
TPH (diesel)	ND	ND	8015M
TPH (gasoline)	ND	ND	8015M
MTBE	ND	ND	5030A/8020A
Lead	7.4	15	7420

Notes.

- 1 All soil samples were taken on November 18, 1998
- 2 ND Not Detected at the laboratory reporting limit







Table 2. Summary of Laboratory Results, PRFTA, Dublin, California

Sample Identification	TPH-Diesel (ppm)	TPH-Gasoline (ppm)	BTEX (ppm)	Total Lead (ppm)
T1135-S1	ND	NT	ND	NT
T1136-S1	2,000	NT	ND	NT
SP1135-S1	350	NT	ND	NT
SP1136-S1	NID	NT	ND	NT
SP1135-S2	ND	NT	ND	NT
T770-1	NT	ND	ND	6.4
SP770123	NT	ND	ND	6.1
E1136-S1	ND	NT	ND	NT
E1136-S2	ND	NT	ND .	NT
E1136-S3	ND	NT	ND	NT
E1136-S4	ND	NT	ND	NT
E1136-S5	ND	NT	ND	NT
SP1136-1109	240	NT	ND	NT

Note: ND - Not detected at or above detection limits for the analysis (see Appendix C for detection limits)
NT - Not Tested

7112/FTANKCL FB2 (01/16/96) SAC



Parks Reserve Forces

Training Area

MAR STATION

DUBLIN REVO

SUMMARY TABLE FOR CLOSURE

SUMMARY OF SOIL AND GROUNDWATER RESULTS Camp Parks Reserve Forces Training Area, Dublin, California

				:		Analyte (mg/kg for soil and mg/L for groundwater)								
Sampling Location	Sample Description	Samp	le Date	Media	Analytical Method	Lead	TPH (diesel)	TPH (hydraulic (luid)	TPH (gas)	MtBE	Benzene	Toluene	Ethyl- benzene	Total Xylenes
Building 514 B514-B1 B514-C1	Bottom of excavation, 3-5 ft bgs Composite sample of excavated soil		6/97 6/97	Soil Soil	EPA 8015M/8020/6010 EPA 8015M/8020/6010	49 22	ND ND		ND ND	-	ND ND	ND ND	ND ND	ND ND
Building 1105 B1105-B1 B1105-C1	Bottom of excavation, 5-7 ft bgs Composite sample of excavated soil		5197 5197	Soil Soil	EPA 8015M EPA 8015M/8020		ND 1100J	-		R	R	Ř	0.051	 0.46J
Building 1108 B1108-B1	Bottom of full end of tank to close in place, 3-5 ft bgs	3/2	<i>\$1</i> 97	Soil	EPA 8015M/8020	~~	660		ND	סמ	ND	0,03	0.09	0,47
Building 1137 B1137 B1 B1137-C1 B1137-C2	Bottom of excavation, 7-9 ft bgs Composite sample of top 4 ft of excavated soil Composite sample of stained soil, excavated below 4 ft bgs	3/2	15197 15197 15197	Soil Soil	EPA 8015M EPA 8015M EPA 8015M/8020	-	ND ND 390		- -	. ND	- ND	 ND	 ND	 0,16
Buiding 1139 B1139-B1 B1139-C1	Bottom of excavation, 3-5 ft bgs Composite sample of excavated soil		25/97 25/97	Soil Soil	EPA 8015M EPA 8015M	_	260J 100J		-			_	₹ -	-

General Notes

"--" = Not analyzed

ND = Not detected

R = Rejected

J = Estimated