

5500 Shellmound Street. Emeryville, CA 94608-2411

Fax: 510-547-5043 Phone: 510-547-5420

January 14, 1994

101

HAZMAT 94 JAN 27 PH 2: 23

Re: ACDEH STID #1107 Shell Service Station WIC #204-6001-0109 29 Wildwood Avenue Piedmont, California WA Job #81-463-203

Dear Ms. Eberle:

Jennifer Eberle

Alameda County Department of Environmental Health Hazardous Materials Division 80 Swan Way, Room 200 Oakland, CA 94621-1426

This letter describes recently completed and anticipated activities at the Shell service station referenced above (Figure 1). This status report satisfies the quarterly reporting requirements prescribed by California Administrative Code Title 23 Waters, Chapter 3, Subchapter 16, Article 5, Section 265.d. Included below are descriptions and results of activities performed in the fourth quarter 1993 and proposed work for the first quarter 1994.

Fourth Quarter 1993 Activities:

- Blaine Tech Services, Inc. (BTS) San Jose, California measured ground water depths in five of the six wells and collected water samples from all six wells. The ground water depth was not measured in well E-4 since it is a flowing artesian well. BTS' report describing these activities and the analytic report for the ground water samples are included as Attachment A.
- Weiss Associates (WA) compiled the ground water elevation and analytic data (Tables 1 and 2, respectively) and prepared a ground water elevation contour map (Figure 2).
- BTS measured dissolved oxygen concentrations in ground water in all site wells (Table 2). The dissolved oxygen concentrations are similar to last quarter and are more than sufficient to support natural hydrocarbon biodegradion. BTS will continue to be measure dissolved oxygen concentrations.

Anticipated First Quarter 1994 Activities:

WA will submit a report presenting the results of first quarter 1994 ground water sampling
and ground water depth measurements. The report will include tabulated ground water
elevation and analytic data, dissolved oxygen concentrations and a ground water elevation
contour map.

Conclusions and Recommendations

The dissolved oxygen concentrations appear adequate for biochemical oxidation. According to Barker et al, approximately 20 μ g dissolved oxygen are required for complete biochemical oxidization of 1 μ g BETX in naturally occurring ground water. Based on the 3,820 to 5,750 μ g/ ℓ dissolved oxygen measured in ground water beneath the site, biochemical oxidation of about 170 to 290 μ g/ ℓ BETX is possible. Since BETX concentrations in ground water from all site wells fall within this range, there appears to be more than sufficient dissolved oxygen for biochemical oxidation of the hydrocarbons. Therefore, as we discussed in previous reports, WA recommends continued measurement of dissolved oxygen concentrations in ground water to monitor the progress of hydrocarbon biodegradation by naturally occurring microorganisms.

Barker, J.F., et al, 1987, Natural Attenuation of Aromation Hydrocarbons in a Shallow Sand Aquifer, Ground Water Monitoring Review, (7(1):64-71.



Please call if you have any questions.

No. 5747

Sincerely,

Weiss Associates

J. Michael Asport Technical Assistant

N. Scott MacLeod, R.G.

Project Geologist

JMA/NSM:jma

J:\SHELL\450\QMRPTS\463QMDE3.WP

Attachments:

Figures

Tables

A - BTS' Ground Water Monitoring Report

Dan Kirk, Shell Oil Company, P.O. Box 5278, Concord, California 94520-9998
John Jang, Regional Water Quality Control Board - San Francisco Bay, 2101
Webster Street, Suite 500, Oakland, California 94612




Figure 1. Site Location Map - Shell Service Station WIC #204-6001-0109, 29 Wildwood Avenue, Piedmont, California




Figure 2. Monitoring Well Locations and Ground Water Elevation Contours - October 19, 1993 - Shell Service Station, WIC #204-6001-0109, 29 Wildwood Avenue, Piedmont, California

TABLE 1. Ground Water Elevations - Shell Service Station WIC #204-6001-0109, 29 Wildwood Avenue, Piedmont, California

Well ID	Date	Top-of-Casing Elevation (ft above msl)	Depth to Water (ft)	Ground Water Elevation (ft above msl)
MW-1	07/12/89	37.96	2.76	35.20
	01/30/90		3.10	34.86
	04/27/90		3.24	34.72
	07/31/90		4.26	33.70
	10/30/90		4.25	33.71
	01/31/91		3.66	34.30
	04/30/91		3.46	34.50
	07/30/91		4.14	33.82
	10/29/91		3.96	34.00
	01/20/92		3.59	34.37
	04/14/92		3.18	31.71
	07/21/92		4.17	33.79
	10/02/92		4.29	33.67
	01/20/93		2.32	35.64
	05/03/93		3.50	34.46
	06/28/93		3.76	34.20
	07/21/93		4.09	33.87
	10/19/93		3.58	34.38
MW-2	07/12/89	34.89	3.66	31.23
	01/30/90	•	3.49	31.40
	04/27/90		3.79	31.10
	07/31/90		4.03	30.86
	10/30/90		4.21	30.68
	01/31/91		4.09	30.80
	04/30/91		3.95	30.94
	07/30/91		4.07	30.82
	10/29/91		4.11	30.78
	01/20/92		3.86	31.03
	04/14/92		3.66	34.30
	07/21/92		3.92	30.97
	10/02/92		4.45	30. 44
	01/20/93		3.74	31.15
	05/03/93		3.77	31.12
	06/28/93		3.96	30.93
	07/21/93		4.39	30.50
	10/19/93		3,92	30.97
MW-3	07/12/89	35.00	3.83	31.17
	01/30/90		3.24	31.76

⁻ Table 2 continues on next page --

TABLE 1. Ground Water Elevations - Shell Service Station WIC #204-6001-0109, 29 Wildwood Avenue, Piedmont, California (continued)

Well	-	Top-of-Casing Elevation	Depth to Water	Ground Water Elevation
ID	Date	(ft above msl)	(ft)	(ft above msl)
				40.00
	04/27/90		4.02	30.98
	07/31/90		4.31	30.69
	10/30/90		4.52	30.48
	01/31/91		4.33	30.67
	04/30/91		3.79	31.21
	07/30/91		4.37	30.63
	10/29/91		4.00	31.00
	01/20/92		3.87	31.13
	04/14/92		3.15	31.85
	07/21/92		4.17	30.83
	10/02/92		4.43	30.57
	01/20/93		2.20	32.80
	05/03/93		3.50	31.50
	06/28/93		4.08	30.92
	07/21/93		4.12	30.88
	10/19/93		4,20	30.80
MW-4	01/30/90	33.73	4.50	29.23
AVA. () - 1	04/27/90	55.15	3.62	30.11
	07/31/90		4.19	29.54
	10/30/90		4.19	29.54
	01/31/91		4.49	29.24
	04/30/91		4.02	29.71
	07/30/91		4.39	29.34
	10/29/91		3.75	29.98
	01/20/92		3.94	29.79
	04/14/92		3.71	30.02
	07/21/92		4.02	29.71
	10/02/92		4.13	29.60
	01/20/93		3.10	30.63
	05/03/93		3.70	30.03
	06/28/93		3.81	29.92
	07/21/93		3.81	29.92
	10/19/93		3.94	29.79
	#8.86.50508-10.01 0.11 40.151-11.66.704.5951010	s. v. s. v. et e.		.
MW-5	01/30/90	31.38	7.12	24.26
	04/27/90		4.19	27.19
	07/31/90		4.09	27.29
	10/30/90		4.39	26.99
	01/31/91		4.49	26.89

TABLE 1. Ground Water Elevations - Shell Service Station WIC #204-6001-0109, 29 Wildwood Avenue, Piedmont, California (continued)

Well ID	Date	Top-of-Casing Elevation (ft above msl)	Depth to Water (ft)	Ground Water Elevation (ft above msl)
	04/30/91		4.27	27.11
	07/30/91		4.32	27.06
	10/29/91		3.79	27.59
	01/20/92		4.09	27.29
	04/14/92		4.12	27.26
	07/21/92		4.13	27.25
	10/02/92		4.30	27.08
	01/20/93		3.12	28.26
	05/03/93		4.07	27.31
	06/28/93		4.08	27.30
	07/21/93		4.05	27.33
•	10/19/93	enulingum jaget kan in 17 valdiga <mark>tessessesse</mark> Luna tura jahan menerarah dala m disebes 1888 1	4.20	27.18
E-4	07/12/89	34.63	a	>39.13
	01/30/90	31.03	b	>34.63
	04/27/90		b	>34.63
	07/31/90		b	>34.63
	10/30/90		b	>34.63
	01/31/91		b	>34,63
	04/30/91		ь	>34.63
	07/30/91		b	>34.63
	10/29/91		b	>34.63
	01/20/92		b	>34.63
	04/14/92		ъ	>34.63
	07/21/92		ь	>34.63
	10/02/92		Ъ	>34.63
	01/20/93		b	>34.63
	05/03/93		b	>34.63
	06/28/93		b	>34.63
	07/21/93		Ъ	>34.63
	10/19/93	ng Properties Destation (1980) (1980) (1980) (1980)	b	> 34.63

a = Well E-4 is a flowing artesian well. The potentiometric surface was greater than 4.5 ft above the top of the well casing.

b = Well E-4 potentiometric surface was higher than the top of the well casing.

ell D	Date Sampled	Depth to Water (ft)	TPH-G	В	E	Ţ	×	HVOCs	Dissolved Oxygen ^a
			<	**********	р	arts per billion	(ug/L)		
W-1	07/12/89	2.76	<50	<0.5	<1	<1	<3	b	•••
	01/30/90	3.10	<50	<0.5	<0.5	<0.5	<0.5		
	04/27/90	3.24	<50	<0.5	<0.5	<0.5	<0.5		
	07/31/90	4.26	<50	<0.5	<0.5	<0.5	<0.5		
	10/30/90	4.25	<50	<0.5	<0.5	<0.5	<0.5		
	01/31/91	3.66	<50	<0.5	<0.5	<0.5	<0.5		
	04/30/91	3.46	<50	0.8	0.6	<0.5	1.2		
	07/30/91	4.14	<50	<0.5	<0.5	<0.5	<0.5		
	10/29/91	3.96	<50	<0.5	<0.5	<0.5	<0.5		
							<0.3		
	01/20/92	3.59	<30	<0.3	<0.3	<0.3			
	04/14/92	3.18	<50	<0.5	<0.5	<0.5	<0.5		
	07/21/92	4.17	<50	<0.5	<0.5	<0.5	<0.5		
	10/02/92	4.29	<50	<0.5	<0.5	<0.5	<0.5		
	01/20/93	2.32	<50	<0.5	<0.5	<0.5	<0.5		
	05/04/93	3.50	<50	<0.5	<0.5	<0.5	<0.5		1,930
	07/21/93	4.09	<50	<0.5	<0.5	<0.5	<0.5		4,640
	10/19/93	3.58	50	<0.5	<0.5	<0.5	<0.5		4,310
W-2	07/12/89	3.66	60	2.7	<1	<1	<3	b	
	01/30/90	3.49	<50	6.6	0.54	<0.5	0.93		
	04/27/90	3.79	60	2.1	<0.5	<0.5	<0.5		
	07/31/90	4.03	70	1.5	<0.5	<0.5	<0.5		
	10/30/90	4.21	70	<0.5	<0.5	0.7	1.6		
	01/31/91	4.09	80	<0.5	0.9	<0.5	1.9		
		3.95	100	5.9	0.7	0.6	2.0	•••	
	04/30/91			<0.5			<0.5		
	07/30/91	4.07	<50		<0.5	<0.7			
	10/29/91	4.11	<50	<0.5	<0.5	<0.5	<0.5		
	01/20/92	3.86	<30	0.84	<0.41	<0.3	<0.48		
	04/14/92	3.66	70	16	3.1	<0.5	2.1		***
	07/21/92	3.92	<50	<0.5	<0.5	<0.5	<0.5		
	10/02/92	4.45	<50	<0.5	<0.5	<0.5	<0.5		
	01/20/93	3.74	<50_	3.8	0.52	<0.5	<0.5		
	05/04/93	3.77	680°	2.8	<0.5	<0.5	<0.5		900
	07/21/93	4.39	<50	8.0	1.8	1.2	7.9		5,880
	10/19/93	3.92	<50	<0.5	<0.5	<0.5	<0.5		5,700
W-3	07/12/89	3.83	3,900	380	99	41	30	d	
M., 3		3.24	5,500	440	79 79	35	130	***	
	01/30/90		4 E00	310	37	26	110	***	
	04/27/90	4.02	4,500			17		111	
	07/31/90	4.31	3,500	210	8.4		62		•••
	10/30/90	4.52	2,300	610	<0.5	<0.5	28	***	
	01/31/91	4.33	4,100	300	19	20	81	777	
	04/30/91	3.79	3,800	370	8.6	19	60	***	

⁻⁻ Table 2 continues on next page --

Well	Date Sampled	Depth to Water (ft)	TPH-G	6	E	T	x	HVOCs	Dissolved Oxygen
			ç		ре	arts per billion	(ug/L)		
	07/30/91	4.37	3,300	160	15	13	87		
	10/29/91	4.00	1,000	35	2.9	2.8	8.1		•••
	01/20/92	3.87	6,900	380	47	18	48		
	04/14/92	3.15	6,000	480	41	38	55		
	07/21/92	4.17	3,700	330	30	13	23		***
	10/02/92	4.43	4,200	260	13	10	12		
	01/20/93	2.20	4,200	360	32	15	26		
	01/20/93 ^{dup}	2.20	3,900	370	32	15	26		
	05/04/93	3.50	12,000	290	120	520	620		630
	07/21/93	4.12	2,000	170	<10	12	11		4,340
	07/21/93 ^{dup}	4.12	2,000	170	<10	10	14		`
	10/19/93	4.20	2,000	240	<0.5	<0.5	<0.5		5,740
MW-4	01/31/90	4.50	<50	<0.5	<0.5	<0.5	<0.5		***
110 7	04/27/90	3.62	130°	<0.5	<0.5	<0.5	<0.5	2000	49.0
	07/31/90	4.19	<50	<0.5	<0.5	<0.5	<0.5		
	10/30/90	4.19	<50	<0.5	<0.5	<0.5	<0.5	***	***
	01/31/91	4.49	50°	<0.5	<0.5	<0.5	<0.5		
	04/30/91	4.02	<50	<0.5	<0.5	<0.5	<0.5	e	
	07/30/91	4.39	<50	<0.5	<0.5	<0.5	<0.5	•••	
	10/29/91	3.75	<50	<0.5	<0.5	<0.5	<0.5		
	01/20/92	3.94	<30	<0.3	<0.3	<0.3	<0.3		
	04/14/92	3.71	<50	<0.5	<0.5	<0.5	<0.5		
	07/21/92	4.02	<50	<0.5	<0.5	<0.5	<0.5		
	10/02/92	4.13	<50	<0.5	<0.5	<0.5	<0.5		
	01/20/93	3.10	<50	<0.5	<0.5	<0.5	<0.5		
	05/04/93	3.70	<50	<0.5	<0.5	<0.5	<0.5		1,740
	07/21/93	3.81	<50	0.56	<0.50	<0.50	<0.50		4,510
	10/10/93	3.94	<50	<0.5	<0.5	<0.5	<0.5	1999	5,750
MW-5	01/31/90	7,12	<50	<0.5	<0.5	<0.5	<0.5		
MM-7	04/27/90	4.19	210°	<0.5	<0.5	<0.5	<0.5		***
		4.09	90	<0.5	<0.5	<0.5	<0.5		***
	07/31/90			0.8	0.6	0.7	1.4	•••	***
	10/30/90	4.39	100 80 ^c	<0.5	<0.5	<0.5	<0.5		***
	01/31/91	4.49							***
	04/30/91	4.27	90	<0.5	<0.5	<0.5	<0.5	f	
	07/30/91	4.37	90	<0.5	<0.5	<0.5	<0.5	2004	
	10/29/91	3.79	<50	<0.5	<0.5	<0.5	<0.5	7.55	
	01/20/92	4.09	<30	<0.3	<0.3	<0.3	<0.3		
	04/14/92	4.12	<50°	<0.5	<0.5	<0.5	<0.5	***	
	07/21/92	4.13	74°	<0.5	<0.5	<0.5	<0.5		***
	10/02/92	4.30	76°	<0.5	<0.5	<0.5	<0.5		***

Well ID	Date Sampled	Depth to Water (ft)	TPH-G	8	E	τ	×	HVOCs	Dissolved Oxygen ⁸
			<		ра	rts per billion	(ug/L)	***********	*******
	01/20/93	3.12	72 ^c	<0.5	<0.5	<0.5	<0.5		122
	05/04/93	4.07	70°	<0.5	<0.5	<0.5	<0.5		1620
	05/04/93 dup	4.07	80°	<0.5	<0.5	<0.5	<0.5		***
	07/21/93	4.05	<50	<0.50	<0.50	<0.50	<0.50		3,460
	10/19/93	4.20	51	<0.5	<0.5	<0.5	<0.5		3,820
	Speak of Street, 11.1								
E-4	07/12/89	g	<50	<0.5	<1	<1	<3	* * *	
	01/31/90	9	<50	<0.5	<0.5	<0.5	<0.5		
	04/27/90	g	120°	<0.5	<0.5	<0.5	<0.5		***
	07/31/90	g	<50	<0.5	<0.5	<0.5	<0.5		***
	10/30/90	g	<50	<0.5	<0.5	<0.5	<0.5		
	01/31/91	g	<50	<0.5	<0.5	<0.5	<0.5		• • •
	04/30/91	g	<50	<0.5	<0.5	<0.5	<0.5	b	
	07/30/91	g	<50	<0.5	<0.5	0.6	<0.5		
	10/29/91	g	<50	<0.5	<0.5	<0.5	<0.5		
	01/20/92	g	<30	<0.3	<0.3	<0.3	<0.3		
	04/14/92	9	<50	<0.5	<0.5	<0.5	<0.5		
	07/21/92	g	<50	<0.5	<0.5	<0.5	<0.5		
	10/02/92	g	<50	<0.5	<0.5	<0.5	<0.5		
	01/20/93	9	<50	<0.5	<0.5	<0.5	<0.5		630
	05/04/93	9	<50	<0.5	<0.5	<0.5	<0.5		5,440
	07/21/93	g	<50	5.4	1.0 <0.5	0.72 <0.5	4.4 <0.5		5,630
	10/19/93	g	<50	<0.5	V.,J.	~U,J	15045		بببيه
Trip	07/12/89		<50	<0.5	<1	<1	<3		•••
Blank	01/31/90		<50	<0.5	<.5	<0.5	<0.5		
	04/27/90		<50	<0.5	<0.5	<0.5	<0.5		
	07/31/90		<50	<0.5	<0.5	<0.5	<0.5		
	10/30/90		<50	<0.5	<0.5	<0.5	<0.5	***	
	01/31/91		<50	<0.5	<0.5	<0.5	<0.5		
	04/30/91		<50	<0.5	<0.5	<0.5	<0.5		
	07/30/91		<50	<0.5	<0.5	<0.5	<0.5		
	10/29/91		<50	<0.5	<0.5	<0.5	<0.5	•••	
	10/02/92		<50	<0.5	<0.5	<0.5	<0.5		603
	01/20/93		<50	<0.5	<0.5	<0.5	<0.5	***	***
	05/03/93		<50	<0.5	<0.5	<0.5	<0.5	***	***
	07/21/93		<50	<0.50	<0.50	<0.50	<0.50 <0.5	222	
	10/19/93		<50	<0.5	<0.5	<0.5	4.5		
Bailer	04/27/90		110°	<0.5	<0.5	<0.5	<0.5	***	***
Blank	01/31/91		<5	<0.5	<0.5	<0.5	<0.5	944	>++
D.COLIK	10/02/92		ND	ND	ND	ND	ND	222	***


⁻⁻ Table 2 continues on next page --

Well ID	Date Sampled	Depth to Water (ft)	TPH-G	В	E	т	x	HVOCs	Dissolved Oxygen ^a
10	sampted	water (It)	<			parts per bill	ion (ug/L)		>
DTSC MCLs			NE	1	680	100 ^h	1750	i	NA
8015	- l Petroleum Hydro	ocarbons as Gasoli	ne by Modified	EPA Method	b = No H	VOCs detected.	of dissolved oxyge ined discrete peak		
= Ethylber = Toluene	zene by EPA Metho by EPA Method 602 by EPA Method 602	od 602 or 8020 2 or 8020			gaso d = BETX	line	.41, 0.097, 0.036	•	
	genated volatile alyzed	organic compounds	by EPA Method	601 or 624	(TCE f = 0.22) and 0.0034 pp ppm PCE, 0.022	proethene (PCE), 0 om trans-1,2-dichl 2 ppm TCE and 0.01	oroethene (DCE) 7 ppm DCE detec	detected ted
	•	tment of Toxic Sub ls for drinking wa		maximum		sian well; pote ation.	entiometric surfac	e above top-of-	casing
ı = Not det	ected above deter	ction limit of n p	ppb			recommended ad blished.	ction level for dr	inking water; M	CL not
					i = DISC	MCLs for PCE :	= 0.005 ppm; TCE =	0.005 ppm: DCE	= 0.01 ppm



ATTACHMENT A

BLAINE TECH'S GROUND WATER MONITORING REPORT



BLAINE TECH SERVICES INC.

985 TIMOTHY DRIVE SAN JOSE, CA 95133 (408) 995-5535 FAX (408) 293-8773

November 9, 1993

Shell Oil Company P.O. Box 5278 Concord, CA 94520-9998

Attn: Mr. Daniel T. Kirk

SITE: Shell WIC #204-6001-0109 29 Wildwood Avenue Piedmont, California

QUARTER: 4th Quarter of 1993

QUARTERLY GROUNDWATER SAMPLING REPORT 931019-L-1

This report contains data collected during routine inspection, gauging and sampling of groundwater monitoring wells performed by Blaine Tech Services, Inc. in response to the request of the consultant who is overseeing work at this site on behalf of our mutual client, Shell Oil Company. Data collected in the course of our field work is presented in a TABLE OF WELL GAUGING DATA. The field information was collected during our preliminary gauging and inspection of the wells, the subsequent evacuation of each well prior to sampling, and at the time of sampling.

Measurements taken include the total depth of the well and the depth to water. The surface of water was further inspected for the presence of immiscibles which may be present as a thin film (a sheen on the surface of the water) or as a measurable free product zone (FPZ). At intervals during the evacuation phase, the purge water was monitored with instruments that measure electrical conductivity (EC), potential hydrogen (pH), temperature (degrees Fahrenheit), and turbidity (NTU). In the interest of simplicity, fundamental information is tabulated here, while the bulk of the information is turned over directly to the consultant who is making professional interpretations and evaluations of the conditions at the site.

STANDARD PROCEDURES

Evacuation

Groundwater wells are thoroughly purged before sampling to insure that the sample is collected from water that has been newly drawn into the well from the surrounding geologic formation. The selection of equipment to evacuate each well is based on the physical characteristics of the well and what is known about the performance of the formation in which the well has been installed. There are several suitable devices which can be used for evacuation. The most commonly employed devices are air or gas actuated pumps, electric submersible pumps, and hand or mechanically actuated bailers. Our personnel frequently employ USGS/Middleburg positive displacement pumps or similar air actuated pumps which do not agitate the water standing in the well.

Normal evacuation removes three-case volumes of water from the well. More than three-case volumes of water are removed in cases where more evacuation is needed to achieve stabilization of water parameters and when requested by the local implementing agency. Less water may be removed in cases where the well dewaters and does not recharge to 80% of its original volume within two hours and any additional time our personnel have reason to remain at the site. In such cases, our personnel return to the site within twenty four hours and collect sample material from the water which has recharged into the well case.

Decontamination

All apparatus is brought to the site in clean and serviceable condition. The equipment is decontaminated after each use and before leaving the site. Effluent water from purging and on-site equipment cleaning is collected and transported to Shell's Martinez Manufacturing Complex in Martinez, California.

Free Product Skimmer

The column headed VOLUME OF IMMISCIBLES REMOVED (ml) is included in the TABLE OF WELL GAUGING DATA to cover situations where a free product skimming device must be removed from the well prior to gauging. Skimmers are installed in wells with a free product zone on the surface of the water. The skimmer is a free product recovery device which often prevents normal well gauging and free product zone measurements. The 2.0" and 3.0" PetroTraps fall into the category of devices that obstruct normal gauging In cases where the consultant elects to have our personnel pull the skimmers out of the well and gauge the well, our personnel perform the additional task of draining the accumulated free product out of the PetroTrap before putting it back in the well. This

recovered free product is measured and logged in the VOLUME OF IMMISCIBLES REMOVE column. Gauging at such sites is performed in accordance with specific directions from the professional consulting firm overseeing work at the site on Shell's behalf.

Sample Containers

Sample material is collected in specially prepared containers which are provided by the laboratory that performs the analyses.

Sampling

Sample material is collected in stainless steel bailer type devices normally fitted with both a top and a bottom check valve. Water is promptly decanted into new sample containers in a manner which reduces the loss of volatile constituents and follows the applicable EPA standard for handling volatile organic and semi-volatile compounds.

Following collection, samples are promptly placed in an ice chest containing pre-frozen blocks of an inert ice substitute such as Blue Ice or Super Ice. The samples are maintained in either an ice chest or a refrigerator until delivered into the custody of the laboratory.

Sample Designations

All sample containers are identified with a site designation and a discrete sample identification number specific to that particular groundwater well. Additional standard notations (e.g. time, date, sampler) are also made on the label.

Chain of Custody

Samples are continuously maintained in an appropriate cooled container while in our custody and until delivered to the laboratory under a standard Shell Oil Company Chain of Custody. If the samples are taken charge of by a different party (such as another person from our office, a courier, etc.) prior to being delivered to the laboratory, appropriate release and acceptance records are made on the Chain of Custody (time, date, and signature of the person releasing the samples followed by the time, date and signature of the person accepting custody of the samples).

Hazardous Materials Testing Laboratory

The samples obtained at this site were delivered to Sequoia Analytical Laboratory in Redwood City, California. Sequoia Analytical Laboratory is a California Department of Health Services certified Hazardous Materials Testing Laboratory and is listed as DOHS HMTL #1210.

Objective Information Collection

Blaine Tech Services, Inc. performs specialized environmental sampling and documentation as an independent third party. In order to avoid compromising the objectivity necessary for the proper and disinterested performance of this work, Blaine Tech Services, Inc. performs no consulting and does not become involved in the marketing or installation of remedial systems of any kind. Blaine Tech Services, Inc. is concerned only with the generation of objective information, not with the use of that information to support evaluations and recommendations concerning the environmental condition of the site. Even the straightforward interpretation of objective analytical data is better performed by interested regulatory agencies and those engineers and geologists who are engaged in the work of providing professional opinions about the site and proposals to perform additional investigation or design remedial systems.

Reportage

Submission of this report and the attached laboratory report to interested regulatory agencies is handled by the consultant in charge of the project. Any professional evaluations or recommendations will be made by the consultant under separate cover.

Please call if we can be of any further assistance.

Richard C. Blaine

RCB/cf

Attachments: Table of Well Guauging Data

Chain of Custody

Certified Analytical Report

cc: Weiss Associates

5500 Shellmound Street Emeryville, CA 94608-2411

ATTN: Michael Asport

TABLE OF WELL GAUGING DATA

WELL I.D.	DATA COLLECTION DATE	MEASUREMENT REFERENCED TO	QUALITATIVE OBSERVATIONS (sheen)	DEPTH TO FIRST IMMISCIBLES LIQUID (FPZ) (feel)	THICKNESS OF IMMISCIBLES LIQUID ZONE (feet)	VOLUME OF IMMISCIBLES REMOVED (ml)	DEPTH TO WATER (feet)	DEPTH TO WELL BOTTOM (feet)
MW-1	10/19/93	TOC	<u></u>	NONE		-	3,58	13.12
MW-2	10/19/93	TOC	-	NONE		-	3.92	11.52
MW-3	10/19/93	тос	<u></u>	NONE	-	-	4.20	9.00
MW-4	10/19/93	тос	-	NONE		-	3.94	12,66
MW-5	10/19/93	тос	<u></u>	NONE	_		4.20	15.96
EW-4	10/19/93	*4	-	NONE	**	-	-	34.21

^{*}Sample DUP was a duplicate sample taken from well MW-3.

^{**} Water was flowing out of the well pipe opening.

RETAIL	LL OI L ENVIR	ONME	NTA.L	ENGI	NEERIN	۷G -	WE	ST			Cł	A - \$\$	N C)F (No:_	CUS	TO	DΥ	RE	CORD	Dale: Page	10/11/13
29 VIC#:	Wildwoo	d Aven	ue, P	iedmo	nt .					An	aly	sis R	equ	ulre	d				LAB: Sequoi		
204	-6001-0	109														Τ	T .	Τ	CHECK OH! (1) LOX OH!A	CI/DI	TURN AROUND TIME
hell Engineer: Dan Kirk Consultant Name of Blaine Tech Se 985 Timothy Dr Consultant Conlact Jim Keller Comments:	rive S	an Jos	<u>e, CA</u>	951 Phone	No.: (168 675-6 33 No.: (4535-8	160	Mod. Gas)	5 Mod, Diesel).	8020/602)	iles (EPA 8240)	70	PH 8015 & BTEX 8020					pa	-	Sis investigation lot Cheatry/Disposal Water Cheatry/Disposal Int/Ar Rom or Sys. O B M	Peris	24 hours
	Dole			Water		io. of	TPH (EPA 8015	TPH (EPA 80)S	208 A93) X318	Volatile Organics	Test for Disposal	Combination TPH			Asbeslos	Container Size	Preparation Use	Composite Y/N	MATERIAL DESCRIPTION	c	SAMPLE ONDITION/ OMMENTS
MW-1	19/19			γ		3						х			·	40	HLL	-	93/0811	-01	· Ûci
MW-Z	10/19			x		3						Х				Т			0.001		
MW-3	10/19			x		3						ኦ				1	-			<i>-</i> ℃	
MW-4	10/19			X		3						χ					+			<i>_65</i> ⊃	· · · · · · · · · · · · · · · · · · ·
MW-5	10/19	•		X		3						×			-}	-	-			704	
E-4	10/19			x		- 							_			+-	-			705	<u>-</u>
		•		 -		3 3	-	_				*	_			\perp	4		· · · · · · · · · · · · · · · · · · ·	705	<u> </u>
DUP	10/19			X						_		X	_		_					-0)
EB sy (Agnobut and the By (Agnobut and By (Agn	(0)	Pilnie	d Nome	130 i	VER		Dale Time Dale	: 11 : 101 : [1	//2_		bevi	< 7-	olure.):		<u></u>		riniec	Name: S. O.IV small I Name:	-0	Dole: /c/20/63 Time: //// Dole: Time:
					AUST PRO	i	Ilme	_	11115	1 1	ιw	/ Car			NYOI	CEA	- 1		HUPANO		Dale: D-20-G

SHE RETAIL	LL OI ENVIR	L CC	MP NTAL	ENG!	Y Neerin	۷G -	WE	ST			CI	IAI se	N C	OF C	cus	TO	DΥ	RE	CORD		10: 10/11/13
WIC/: 29	Wildwoo	d Aven	ue, P	iedmo	nt '					An	aly:	sls F	pe?	ılre	d d				LAB: Sequot		
204	-6001-0	109											T	1.		Π	Τ.	Γ	CHECK OHE (I) FOX OHLY	C1/01	TURH AROUND THE
Shell Engineer: '				Phone	No.: (510)	ł					ĺ) 441	
Dan Kirk				575-6	No.: (. 168 675-6	160		-)]	24 hours 🔲
Consultoni Nome . Blaine Tech Se	TVICES	Inc				Ť00						BTEX 8020							_) H41	41 hours
985 Timothy Dr Consultant Contac	ive S	an Jos	e, CA	951	33		ļ	١.		2		ไล๊							Wales) нц	16 days XXX (Hosmo
Jim Keller	···.			995-5	No.: (8 35 293-81	408)	_ ≅	Dle se 1)		8240)	١.	& B.			}						Oly+1
Comments:				rox I:	293-8	7.7.3	Gos)			(EPA 1		8015 8	'	ľ		ĺ	ĺ		Waler Beam of Sys.	£412	HOIT: Holky Lab or
							Mod,	Ö.	602			8					_		ern. C	HH2	24/41 hm. 1A1,
Sompled by: 🗾	1130	2/-4		· · · · ·	· ·		LO .	8015 Mod.	8020/602)	울	पू	E					1 2	λ/γ	O(PP)	1	
Printed Name:	CADI	3 02	151	<u>.</u>			(EPA 801	(EPA 80)	STEX (EPA 80	lle Organics	or Disposal	Combination IPH			105	Container Sizo	Preparation Used		MATERIAL		SAMPLE
Sample ID	Dale	Sludge	Soli	1elo?/		lo. ol conts.) Hat	PH C	ME ME	Volaille	Test for	Com			Asbestos	Se Se	Pre PO	Composite	DESCRIPTION	}	CONDITION/
TB.	10/19			X		Z					-	X			•	40 ML	Hα		9310811-	+	
										 -	_	-	 			170		· ·	1210011-	<u> </u>	•
									_		ļ										•
· · · · · · · · · · · · · · · · · · ·																					
	1		٠							-	_						-			╁╌	1167
	 																				
		<u>.</u>																			
٠,						•			-	_	•									- 	·
																			<u> </u>		
* '							į	,					!								
										-					-				· · · · · · · · · · · · · · · · · · ·	 	-
Mongki), ya berkinpnilei		Pilnie	d Nam	<u> </u>			Dale): /o	1249	3 Řec	9 Y e C	(1)07	· Nalvie	1:	ـــِـا		<u>: : </u>		l Nome:	L	· · · · · · · · · · · · · · · · · · ·
cellnquished By (signaly		Pilole	A-D d Nome	30	VER	-	Dol:	P: /	1112	7	•	4</td <td>)</td> <td></td> <td></td> <td></td> <td></td> <td>. 1</td> <td>5. 07) mn</td> <td>u</td> <td>Dale: 10/10/2</td>)					. 1	5. 07) mn	u	Dale: 10/10/2
	~~>		<u>5, 87</u>	ry nec	1		Πm	<u>: 1/</u>	126/93	Tree.	P0 V14	(HÖL	וטונטו);			· P	iniec	Name:		Dole:
njoudr) Ag poutinbulle	10);	Printe	d Nom	•:			Dale Time			Reci	bevie	(1)00	olure); ;			P	In e	Name:	<u></u>	Ilme: Dale:
		IHI	LABOR	Alory	AUSI PRO	YIDE A	CO	PY OF	THIS	CHAI	N-Of	CUST	ODY	unte i	NVOI	~ ·	10.00	<u> </u>	<u>.</u>		ilme:



Blaine Tech Services, Inc. 985 Timothy Drive San Jose, CA 95133 Attention: Jim Keller

Project: Shell, 29 Wildwood Ave.

Enclosed are the results from 9 water samples received at Sequoia Analytical on October 20,1993. The requested analyses are listed below:

SAMPLE #	SAMPLE DESCRIPTION	DATE OF COLLECTION	TEST METHOD
3JB1101	Water, MW-1	10/19/93	EPA 5030/8015/8020
3JB1102	Water, MW-2	10/19/93	EPA 5030/8015/8020
3JB1103	Water, MW-3	10/19/93	EPA 5030/8015/8020
3JB1104	Water, MW-4	10/19/93	EPA 5030/8015/8020
3JB1105	Water, MW-5	10/19/93	EPA 5030/8015/8020
3JB1106	Water, E-4	10/19/93	EPA 5030/8015/8020
3JB1107	Water, DUP	10/19/93	EPA 5030/8015/8020
3JB1108	Water, EB	10/19/93	EPA 5030/8015/8020
3JB1109	Water, Trip Blank	10/19/93	EPA 5030/8015/8020

Please contact me if you have any questions. In the meantime, thank you for the opportunity to work with you on this project.

Very truly yours,

SEQUQIA ANALYTICAL

Project/Manager

Blaine Tech Services, Inc.

985 Timothy Drive San Jose, CA 95133 Attention: Jim Keller Client Project ID:

Shell, 29 Wildwood Ave.

Sampled:

Oct 19, 1993

Sample Matrix: Analysis Method:

Water EPA 5030/8015/8020 Received: Reported: Oct 20, 1993 Oct 28, 1993

First Sample #:

3JB1101

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

Analyte	Reporting Limit μg/L	Sample I.D. 3JB1101 MW-1	Sample I.D. 3JB1102 MW-2	Sample I.D. 3JB1103 MW-3	Sample I.D. 3JB1104 MW-4	Sample I.D. 3JB1105 MW-5	Sample I.D. 3JB1106 E-4
Purgeable Hydrocarbons	50	N.D.	N.D.	2,000	N.D.	51	N.D.
Benzene	0.50	N.D.	N.D.	240	N.D.	N.D.	N.D.
Toluene	0.50	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Ethyl Benzene	0.50	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Total Xylenes	0.50	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.
Chromatogram Pat	ttern:	••		Gas + Discrete Peak		Discrete Peak	
Quality Control Da	ata		·				

Report Limit Multiplication Factor:	1.0	1.0	20	1.0	1.0	1.0
Date Analyzed:	10/22/93	10/22/93	10/22/93	10/22/93	10/22/93	10/22/93
Instrument Identification:	GCHP-2	GCHP-2	GCHP-2	GCHP-2	GCHP-2	GCHP-2
Surrogate Recovery, %: (QC Limits = 70-130%)	78	84	86	85	91	83

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard. Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

3JB1101.BLA <1>

Blaine Tech Services, Inc.

985 Timothy Drive

San Jose, CA 95133 Attention: Jim Keller

Client Project ID:

Shell, 29 Wildwood Ave.

Water

Sample Matrix: Analysis Method: EPA 5030/8015/8020

First Sample #: 3JB1107 Sampled:

Oct 19, 1993

Received:

Oct 20, 1993

Reported: Oct 28, 1993

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

Analyte	Reporting Limit μg/L	Sample I.D. 3JB1107 DUP	Sample I.D. 3JB1108 EB	Sample I.D. 3JB1109 Trip Blank		
Purgeable Hydrocarbons	50	2,100	N.D.	N.D.		
Benzene	0.50	250	N.D.	N.D.		
Toluene	0.50	13	N.D.	N.D.		
Ethyl Benzene	0.50	N.D.	N.D.	N.D.		
Total Xylenes	0.50	N.D.	N.D.	N.D.		
Chromatogram Pa	ttern:	Gas + Discrete Peak		 .		

Quality Control Data

1
Date Analyzed: 10/22/93 10/22/93 10/22/93
Instrument Identification: GCHP-2 GCHP-2 GCHP-2
Surrogate Recovery, %: 91 93 80 (QC Limits = 70-130%)

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard. Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

3JB1101.BLA <2>

Blaine Tech Services, Inc.

985 Timothy Drive San Jose, CA 95133 Attention: Jim Keller

Client Project ID:

Shell, 29 Wildwood Ave.

Matrix:

Water

QC Sample Group: 3JB1101-09

Reported: Oct 28, 1993

QUALITY CONTROL DATA REPORT

ANALYTE			Ethyl-		
	Benzene	Toluene	Benzene	Xylenes	
Method:	EPA 8020	EPA 8020	EPA 8020	EPA 8020	
Analyst:	A. Miraftab	A. Miraftab	A. Miraftab	A. Miraftab	
Conc. Spiked:	10	10	10	30	
Units:	μg/L	μg/L	µg/L	μg/L	
LCS Batch#:	BLK102293	BLK102293	BLK102293	BLK102293	
Date Prepared:	-	-	-	•	
Date Analyzed:	10/22/93	10/22/93	10/22/93	10/22/93	
Instrument I.D.#:	GCHP-2	GCHP-2	GCHP-2	GCHP-2	
LCS %			•		
Recovery:	94	94	95	93	
Control Limits:	80-120	80-120	80-120	80-120	
MS/MSD					
Batch #:	3JA3902	3JA3902	3JA3902	3JA3902	
	3JA3902 -	3JA3902 -	3JA3902	3JA3902	
Batch #: Date Prepared: Date Analyzed:	3JA3902 - 10/22/93	•	3JA3902 10/22/93	3JA3902 - 10/22/93	
Date Prepared:	-	3JA3902 10/22/93 GCHP-2	-	-	
Date Prepared: Date Analyzed: Instrument I.D.#:	- 10/22/93	- 10/22/93	- 10/22/93	- 10/22/93	
Date Prepared: Date Analyzed:	- 10/22/93	- 10/22/93	- 10/22/93	- 10/22/93	
Date Prepared: Date Analyzed: Instrument I.D.#: Matrix Spike % Recovery:	- 10/22/93 GCHP-2	- 10/22/93 GCHP-2	10/22/93 GCHP-2	- 10/22/93 GCHP-2	
Date Prepared: Date Analyzed: Instrument I.D.#: Matrix Spike % Recovery: Matrix Spike	- 10/22/93 GCHP-2	- 10/22/93 GCHP-2	10/22/93 GCHP-2	- 10/22/93 GCHP-2	
Date Prepared: Date Analyzed: Instrument I.D.#: Matrix Spike % Recovery:	- 10/22/93 GCHP-2	- 10/22/93 GCHP-2	10/22/93 GCHP-2	- 10/22/93 GCHP-2	
Date Prepared: Date Analyzed: Instrument I.D.#: Matrix Spike % Recovery: Matrix Spike Duplicate % Recovery:	10/22/93 GCHP-2 100	- 10/22/93 GCHP-2 99	10/22/93 GCHP-2 100	10/22/93 GCHP-2 100	
Date Prepared: Date Analyzed: Instrument I.D.#: Matrix Spike % Recovery: Matrix Spike Duplicate %	10/22/93 GCHP-2 100	- 10/22/93 GCHP-2 99	10/22/93 GCHP-2 100	10/22/93 GCHP-2 100	

SEQUOIA ANALYTICAL

Please Note:

The LCS is a control sample of known, interferent free matrix that is analyzed using the same reagents, preparation and analytical methods employed for the samples. The LCS % recovery data is used for validation of sample batch results. Due to matrix effects, the QC limits for MS/MSD's are advisory only and are not used to accept or reject batch results.