

1500 So. Union Avenue Bakersfield, California 93307 Phone: (805) 835-7700

FAX: (805) 835-7717

No seal

August 3, 1992

Eva Chu Alameda County Department of Environmental Health 80 Swan Way, Rm. 200 Oakland, CA 94621

Re: Scotsman Corp., Dublin CA Groundwater Remediation Second Quarter Report

#### Dear Ms. Chu:

This letter is an update on the groundwater remediation project underway at the Scotsman Corporation facility, 6055 Scarlett Ct., Dublin. As of July 9, 1992, the groundwater treatment system has treated 1,087,100 gallons of water. The only monitoring wells that have detectable hydrocarbon concentrations are MW-1 and MW-6 (see Plate 1). The plume has remained centered around these two wells throughout the project. These wells are in the heart of the plume and have historically had the highest concentrations. Below is a tabulation of the well concentrations reported for the samples collected on July 10, 1992. All samples were analyzed for BTX&E and TPH (gasoline). Enclosed are the analysis results from the samples collected from the wells.

7-10	-92
Benzene	TPH
(ppb)	(ppb)
79	31000
ND	ND
ND	2900
ND	ND
	(ppb) 79 NO

ND = Not detected



Eva Chu Alameda County Department of Environmental Health August 3, 1992 Page Two

Depth to groundwater measurements were recorded on July 9, 1992 and calculated to Mean Sea Level as follows:

WELL	WELL ELEVATION	WATER ELEVATION	DEPTH TO WATER
MW-1	328.86	320.00 ft msl	8.86 ft
MW-2	329.50	323.40 ft msl	6.10 ft
MW-3	327.69	323.27 ft msl	4.42 ft
MW-4	329.19	322.89 ft msl	6.30 ft
MW-5	**	**	7,09ft
MW-6	328.16	318.86 ft msl	9.30 ft
MW-7	**	**	7.49 ft
MW-8	**	**	6.61 ft
RW-3	**	**	10.22 ft

<sup>\*\*</sup> Well not surveyed

Calculations indicate the direction of the groundwater gradient to be 39 degrees west of South with a slope of approximately 1.66 feet per 100 feet (see Plate 3).

The excavation work proposed in the April 13, 1992 Work Plan has been scheduled for the week of August 10, 1992. The work will consist of the excavation and disposal of the soil around MW-1 and MW-6. The well head elevations for the remaining monitoring wells will be surveyed to mean sea level. I will contact your office later this week to confirm the date work will begin.

If you have further questions or require additional information, please give me a call at (805) 835-7700.

Sincerely,

Timothy C. Reed

Project Geologist

Rex J. Young

State Registered Geologist

Encl. Plot Plan


Plot Detail

Gradient Map

Laboratory Analysis

cc: Ms. Amanda Howard, First Interstate Bank

Mr. Marc Selover, RESNA






Project Number: 55018

8-3-92

SCOTSMAN CORP. DUBLIN, CA.

**PLOT PLAN** 

**PLATE** 






environmental/geotechnical services

Project Number: 55018

6-4-91

SCOTSMAN CORP. DUBLIN, CA.

DETAIL OF WELLS AND REMEDIATION EQUIPMENT LOCATIONS PLATE





Project Number: 55018

8-3-92

# SCOTSMAN CORP. DUBLIN, CA.

SHALLOW GROUNDWATER GRADIENT MAP July 9, 1992 PLATE



# CHAIN OF CUSTODY RECORD AND ANALYSIS REQUEST

PROJECT NO. PROJECT NAME/SITE								ANALYSIS REQUESTED P.O. #:						-											
33018 Scotsman								S				7	/	7	7	1	7	7	Τ	7	7	11	7		· · · · · · · · · · · · · · · · · · ·
SAMPLERS (SIGN) /								E E	m	THEMARKS															
Ten Moore (PRINT) TEM MOORE						CONTAINERS	Σ				18					Ι.	/	Ι.	Ι.	/ /	,				
SAMPLE IDENTIFI		DATE	TIME	COMP	GRAB	PRES. USED	CED	NO. CO	SAMPLE TYPE	1/4			100/01/01		0100/15	(						<i> </i> -	F	EMARKS	
Influent	•	7/10/93	8:25		χ	No	X	<u> </u>	CH		X	$f^-$								$\overline{}$	$\Box$	w		7158	
Effluent		1	37,30	<u> </u>	1	1	1	1	Ĭ	1	<u> </u>	$I^-$							$\vdash$				1	159	
Mw-1	·*··		11:00				$\sqcap$	H	H	$\Pi$	$\prod$												1	140	
MW-2			8:55	1			11		1	11	$\dagger \dagger$	1											1	141	· · ·
Mw-3	· · · · · · · · · · · · · · · · · · ·		9:20				11			$\sqcap$	11	1											1	162	
Mw-4			8:15				11				11	1												163	
MW-5			10:30							11	$\prod$													165	1
MW-6			10:42							П	17													165	
Mw-7			11:10					$\prod$		$\prod$	1			-										166	•
WM-8			10120		1					11	11													167	,
RW-3		1	11:35		1	1	1	1	1	1	1			-								•	1/	168	
														•				· · · · · ·					<b>V</b>		
			]																<u> </u>						
RELINQUISHED BY:	DATE	1	IE F	RECEI	VED	BY:			LA	BOR	OTA	RY:							PL	EASI	E SEI	ND RES	SULTS	TO:	
10 Mar	<i>0 </i> 7	192 17	40				·-··			,	0			_		1					_				c 11
RELINQUISHED BY:	DATE	7 7	4E F	RECE	VED	BY:				Q	₹e	25n	A-	Fre	240	ont	2			1	€:	514	-12	nkers	field
RELINQUISHED BY:	DATE	TIN	AE F	RECEI	VED	BY:			RE	QUE	STE	D TUF	RNAR	OUN	ID TII	ME:									
		上			1				Namal																
RELINQUISHED BY:	DATE			RECE	· .	BY KABO	1 1	•		CEI	PT C		TION:		D				1			IANAG			
}	7/10	192 /	:40	111	11	ary	TR	thi					TI		1					lim	1	<u> ۲ و د</u>	d		



## **ANALYSIS REPORT**

Attention: Project:	RESN 1500 Baker	South Union rsfield, CA 9 19514-L, Pr		Da BT TP. TP.	te Sampled: te Received: EX Analyzed: Hg Analyzed: Hd Analyzed:	1020tab.frm 07-10-92 07-10-92 07-15/16-92 07-15/16-92 NR Water		
Detection L	imit:	Benzene ppb 0.5	Toluene ppb 0.5	Ethyl- benzene ppb 0.5	Total Xylenes ppb 0.5	<b>TPHg</b> <u>ppb</u> 50	<b>TPHd</b> <u>ppb</u> 50	
SAMPLE Laboratory Ide	ntificati	on						
Influent W1207158		ND	ND	ND	ND	ND	NR	
Effluent W1207159		ND	ND	ND	ND	ND	NR	
MW-1 W1207160		79	32	26	84	31000	NR	
MW-2 W1207161		ND	ND	ND	ND	ND	NR	
MW-3 W1207162		ND	ND	ND	ND	ND	NR	

ppb = parts per billion =  $\mu g/L$  = micrograms per liter.

#### ANALYTICAL PROCEDURES

BTEX-- Benzene, toluene, ethylbenzene, and total xylene isomers (BTEX) are measured by extraction using EPA Method 5030 followed by analysis using EPA Method 8020/602, which utilizes a gas chromatograph (GC) equipped with a photoionization detector (PID) and a flame-ionization detector (FID) in series.

TPHg-Total petroleum hydrocarbons as gasoline (low-to-medium boiling points) are measured by extraction using EPA Method 5030, followed by analysis using modified EPA Method 8015, which utilizes a GC equipped with an FID.

TPHd-Total petroleum hydrocarbons as diesel (high boiling points) are measured by extraction using EPA Method 3550 for soils and EPA Method 3510 for water, followed by modified EPA Method 8015 with direct sample injection into a GC equipped with an FID.

Laboratory Representative

July 24, 1992
Date Reported

RESNA ENVIRONMENTAL LABORATORY IS CERTIFIED BY THE STATE OF CALIFORNIA DEPARTMENT OF HEALTH SERVICES AS A HAZARDOUS WASTE TESTING LABORATORY (Certification No. 1211)

ND = Not detected. Compound(s) may be present at concentrations below the detection limit.

NR = Analysis not requested.



## **ANALYSIS REPORT**

Attention: Mr. Tim Reed RESNA 1500 South Union Ave. Bakersfield, CA 93307 Project: AGS 19514-L, Project #33018 Scotsman				Dat BT: TP: TP:	te Sampled: te Received: EX Analyzed: Hg Analyzed: Hd Analyzed: trix:	1020lab.frm 07-10-92 07-10-92 07-15/16-92 07-15/16-92 NR Water		
Detection L	imit:	Benzene ppb 0.5	Toluene <u>ppb</u> 0.5	Ethylbenzene ppb 0.5	Total Xylenes <u>ppb</u> 0.5	TPHg ppb 50	<b>TPHd</b> <u>ppb</u> 50	
SAMPLE Laboratory Ide	entificati	on						
MW-4 W1207163		ND	ND	ND	ND	ND	NR	
MW-5 W1207164		ND	ND	ND	ND	ND	NR	
MW-6 W1207165		ND	1.7	1.5	1.1	2900	NR	
MW-7 W1207166		ND	ND	ND	ND	ND	NR	
MW-8 W1207167		ND	ND	ND	ND	ND	NR	

ppb = parts per billion =  $\mu g/L$  = micrograms per liter.

#### **ANALYTICAL PROCEDURES**

BTEX- Benzene, toluene, ethylbenzene, and total xylene isomers (BTEX) are measured by extraction using EPA Method 5030 followed by analysis using EPA Method 8020/602, which utilizes a gas chromatograph (GC) equipped with a photoionization detector (PID) and a flame-ionization detector (FID) in series.

TPHg-Total petroleum hydrocarbons as gasoline (low-to-medium boiling points) are measured by extraction using EPA Method 5030, followed by analysis using modified EPA Method 8015, which utilizes a GC equipped with an FID.

TPHd-Total petroleum hydrocarbons as diesel (high boiling points) are measured by extraction using EPA Method 3550 for soils and EPA Method 3510 for water, followed by modified EPA Method 8015 with direct sample injection into a GC equipped with an FID.

Laboratory Representative

July 24, 1992
Date Reported

RESNA ENVIRONMENTAL LABORATORY IS CERTIFIED BY THE STATE OF CALIFORNIA DEPARTMENT OF HEALTH SERVICES AS A HAZARDOUS WASTE TESTING LABORATORY (Certification No. 1211)

ND = Not detected. Compound(s) may be present at concentrations below the detection limit.

NR = Analysis not requested.



# **ANALYSIS REPORT**

Attention: Project:	RESI 1500 Bake	South Unions rsfield, CA 9 19514-L, Pr		Dat BTI TPI	e Sampled: e Received: EX Analyzed: Ig Analyzed: Id Analyzed:	07-10-9 07-10-9 07-15/1 07-15/1 NR Water	5-92	
Detection I	.imit:	Benzene ppb 0.5	Toluene ppb 0.5	Ethyl- benzene <u>ppb</u> 0.5	Total Xylenes ppb 0.5	<b>TPHg</b> <u>ppb</u> 50	TPHd ppb 50	
SAMPLE Laboratory Ide	entificati	ion					<del></del>	
RW-3 W1207168		ND	ND	ND	ND	ND	NR	

#### ANALYTICAL PROCEDURES

BIEX- Benzene, toluene, ethylbenzene, and total xylene isomers (BTEX) are measured by extraction using EPA Method 5030 followed by analysis using EPA Method 8020/602, which utilizes a gas chromatograph (GC) equipped with a photoionization detector (PID) and a flame-ionization detector (FID) in series.

TPHg-Total petroleum hydrocarbons as gasoline (low-to-medium boiling points) are measured by extraction using EPA Method 5030, followed by analysis using modified EPA Method 8015, which utilizes a GC equipped with an FID.

TPHd-Total petroleum hydrocarbons as diesel (high boiling points) are measured by extraction using EPA Method 3550 for soils and EPA Method 3510 for water, followed by modified EPA Method 8015 with direct sample injection into a GC equipped with an FID.

Laboratory Representative

July 24, 1992
Date Reported

RESNA ENVIRONMENTAL LABORATORY IS CERTIFIED BY THE STATE OF CALIFORNIA DEPARTMENT OF HEALTH SERVICES AS A HAZARDOUS WASTE TESTING LABORATORY (Certification No. 1211)

ppb = parts per billion =  $\mu g/L$  = micrograms per liter.

ND = Not detected. Compound(s) may be present at concentrations below the detection limit.

NR = Analysis not requested.