SONNENSCHEIN NATH & ROSENTHAL

1301 K STREET N.W.
SUITE 600, EAST TOWER
WASHINGTON, D.C. 20005

(202) 408-6400 FACSIMILE (202) 408-6399

John S. Hahn (202) 408-6430

June 18, 1997

VIA FEDERAL EXPRESS

Ms. Juliet Shin
Hazardous Materials Specialist
Alameda County Department of
Environmental Health
80 Swan Way, Room 200
Oakland, California 94621

Re: STID 3856; 1055 Eastshore Highway, Albany, CA

Dear Ms. Shin:

Enclosed is AllWest's Groundwater Monitoring Report for the first quarter of 1997. Please call me if you have any questions.

Sincerely,

John S. Hahn

Enclosure

cc: John Frank (w/enclosure)

Marc Cunningham (w/o enclosure)
John T. Lynch (w/o enclosure)
Craig Denny (w/enclosure)

8072302

CHICAGO KANSAS CITY LONDON LOS ANGELES NEW YORK SAN FRANCISCO ST LOUIS WASHINGTON, D.C.



AllWest Environmental, Inc.

Specialists in Environmental Due Diligence and Remedial Services

One Sutter Street, Suite 600 San Francisco, CA 94104 Tel 415 391.2510 Fax 415.391 2008

GROUNDWATER MONITORING REPORT First Quarter 1997

1055 Eastshore Highway Albany, California

ALLWEST PROJECT 96208.28 June 9, 1997

PREPARED BY:

12/31/97

Long Ching, PE Senior Project Manager

REVIEWED BY:

Marc D. Cynningham, REA

Fresident

TABLE OF CONTENTS

I.	INTRODUCT	INTRODUCTION .						
II.	SITE HISTORY							
III.	GROUNDWA	ATER SAMPLING ACTIVITIES	Page 2					
IV.	LABORATO	RY TEST RESULTS	Page 2					
V.	CONCLUSIO	ONS	Page 3					
VI.	REPORT LIMITATIONS							
	TABLES	Table 1 - Summary of Groundwater Elevation Measurements Table 2 - Summary of Groundwater Chemical Analyses Results						
	FIGURES	Figure 1 - Site Regional Map Figure 2 - Site Vicinity Map Figure 3 - Well Location Map Figure 4 - Groundwater Contour Map						
	APPENDICE	ES Appendix A - Groundwater Sampling Protocol Appendix B - Groundwater Sampling Field Logs Appendix C - Laboratory Test Results and Chain-of-Custody Re	ecords					



MONITORING WELLS SAMPLING REPORT First Quarter 1997

1055 Eastshore Highway Albany, California

I. INTRODUCTION

This report presents the First Quarter 1997 results of a quarterly groundwater monitoring program performed by AllWest Environmental at 1055 Eastshore Highway, Albany, California. The monitoring program was initiated in response to an Alameda County Department of Environmental Health (ACDEH) request for quarterly sampling. The objective of the sampling program was to investigate the groundwater in the vicinity of the former underground storage tank (UST).

The scope of AllWest's services included sampling of four wells (MW-1 through MW-4), the measuring of groundwater levels in all four wells, and the submittal of the samples to a state certified laboratory, Global Environmental Laboratory, Inc. (Global Lab). The samples were submitted for analysis of total petroleum hydrocarbons as gasoline (TPH-g), Benzene, Toluene, Ethylbenzene, and Xylenes (BTEX). After receipt of the analytical results, a written report was prepared to present the results.

II. SITE HISTORY

The subject property lies in the western-most area of Albany, Alameda County, California in an industrial area (See Figures 1 and 2). The subject property is located on the east side of Eastshore Highway, approximately 200 feet south of the Albany off-ramp from Highway I-80. San Francisco Bay is located approximately 2,000 feet west of the subject property.

The subject property facility currently is occupied by the City of Albany Corporation Yard. One underground storage tank (UST) containing gasoline was removed by *Resna Industries* on September 2, 1992. The former UST was located south of the building. A generalized site plan with the former UST location is presented on Figure 3.

Soil near the UST excavation was removed in September 1992. A preliminary site assessment (PSA) was conducted in July 1994. The PSA consisted of the advancement of seven boreholes, the installation of three groundwater monitoring wells (MW-1 through MW-3), and the submittal of soil and groundwater samples to an analytical laboratory for analyses. The PSA indicated that gasoline constituents were present in soil and groundwater at the site.

In June 1995, monitoring well MW-4 was installed and sampled. All four monitoring wells were sampled in June, September and December of 1995, March, June, and September of 1996, and January of 1997 as requested by the *ACDEH*. Additionally, groundwater elevations were measured each quarter as part of the quarterly groundwater monitoring program.

III. GROUNDWATER SAMPLING ACTIVITIES

Activities for the First Quarter 1997 monitoring event included sampling and measuring the groundwater elevation of all four monitoring wells (MW-1 through MW-4). The work was conducted by *AllWest* personnel on April 11, 1997.

AllWest's groundwater sampling protocols, presented in Appendix A of this report, were followed. Groundwater parameters including conductivity, temperature, and pH were collected at three gallon intervals and recorded on the sampling logs (See Appendix B). At least three well casing volumes were purged prior to sampling. After purging, three 40-milliliter samples were collected from each of the four monitoring wells. No product sheen was noted.

The April 11, 1997 groundwater levels as well as the cumulative groundwater level measurements from wells MW-1 through MW-4 are presented in Table 1. Groundwater flow direction was calculated to be towards the northwest with an average gradient of 0.005 ft/ft. A groundwater surface elevation contour map is presented in Figure 4.

IV. LABORATORY TEST RESULTS

The four collected water samples were submitted to a State of California certified analytical laboratory, *Global Environmental Laboratory, Inc.* (*Global Lab*), of Fremont, California. All water samples were analyzed for total petroleum hydrocarbons as gasoline (TPH-g) and Benzene, Toluene, Ethylbenzene, and Xylene (BTEX).

The laboratory results indicated concentrations of TPH-g at 4,000 μ g/L (approximately equivalent to parts per billion [ppb]) in well MW-2 only. No TPH-g was detected in samples from MW-1, MW-3, and MW-4 at or above the laboratory reporting limit of 50 ppb. BTEX concentrations for MW-2 were reported as 520 ppb Benzene, 4.8 ppb Toluene, 120 ppb Ethylbenzene, and 180 ppb Xylene. No BTEX concentrations were detected in MW-1, MW-3, and MW-4 at or above the laboratory reporting limit of 0.5 ppb.

A review of the laboratory internal quality assurance/quality control (QA/QC) information indicates the spike data were within the laboratory recovery limits. The sample was analyzed within the acceptable EPA holding time. Therefore, the laboratory results reported by *Global* are considered to be representative and of good quality.

A cumulative summary of analytical results for wells MW-1 through MW-4 to date are presented in Table 2. A copy of the laboratory test reports and Chain-of-Custody documents of this quarterly monitoring event are included as Appendix C.

V. CONCLUSIONS

As indicated by the laboratory test results, low levels of TPH-g and BTEX were detected in groundwater samples from monitoring well MW-2. The concentrations of TPH-g and BTEX in well MW-2 are within the historical range of previous sampling results. The non-detectable results from MW-1, MW-3 and MW-4 continue to indicate the extent of contaminated groundwater is stable and limited to the immediate vicinity of MW-2.

VI. REPORT LIMITATIONS

The work described in this report has been performed accordance with generally accepted engineering principles an practices. The conclusions and recommendations contained herein are presented based on environmental conditions of the site and laboratory test results of the groundwater sample. It must be recognized that changes can occur in groundwater conditions due to seasonal variations, or other reasons. Furthermore, the distribution of chemical concentrations in the groundwater can vary both temporally and spatially. The chemical analyses results are valid as of the date and at the sampling location only. *AllWest* cannot be held accountable for the accuracy of the test data from an independent laboratory, nor for any analyte quantities falling below the recognized standard detection limits for the method utilized by the independent laboratory.

R96208.28E

TABLE 1 CUMULATIVE SUMMARY OF GROUNDWATER ELEVATION MEASUREMENTS

1055 Eastshore Highway Albany, California

Well Number and Sampling Date	Well Casing Elevation	Depth to Water (In feet)	Groundwater Elevation (Assumed Datum equals 12')	Change Since Last Measurement (In feet)	Average Hydraulic Gradient
MW-1					
		- 2-			0.009 ft/ft SSE
6/28/94	6.62 feet	6.06	0.56 0.58	+0.02	0.004 ft/ft WNW
6/29/94		6.04	0.54	-0.04	0.004 fbft WKW
7/20/94		6.08 4.85	1.77	+1.53	0.004 ft/ft SW
6/9/95		4.79	1.77	+0.13	0.005 ft/ft SW
6/29/95 9/7/95		5.90	0.72	-1.18	0.003 ft/ft SW
1 ' ' 1	}	3.98	2.64	+1.92	0.005 ft/ft SW
12/20/95		3.55	3.07	+0.43	0.007 ft/ft SE
3/22/96 6/21/96		5.20	1.42	-1 65	0.005 ft/ft W
9/17/96	}	5.86	0.76	-0.66	0.003 ft/ft NW
9/17/96 1/17/97		3.35	3.27	+2.51	0.005 ft/ft SW
4/11/97		4.88	1.74	-1.53	0.005 ft/ft NW
4/11/7/					
MW-2					
6/28/94	6.92 feet	6.26	0.66		0.009 ft/ft SSE
6/29/94	0.75 .00	6.34	0.58	-0.08	0.004 ft/ft WNW
7/20/94		6.33	0.59	+0.01	0.003 ft/ft S
6/9/95		5.13	1.79	+1.20	0.004 ft/ft SW
6/29/95		4.99	1.93	+0.14	0.005 ft/ft SW
9/7/95		6.23	0.69	-1.24	0.004 ft/ft SW
12/20/95		4.12	2.80	+2.11	0.005 ft/ft SW
3/22/96		3.70	3.33	+0.42	0.007 ft/ft SE
6/21/96		5.44	1.48	-1.85	0.005 ft/ft W
9/17/96		6.11	0.81	-0.67	0.003 ft/ft NW
1/17/97		3.51	3.41	+2.60	0.005 ft/ft SW
4/11/97		5.15	1.77	-1.64	0.005 ft/ft NW
MW-3					
6/28/94	7.02 feet	6.30	0.72		0.009 ft/ft SSE
6/29/94		6.29	0.73	+0.01	0.004 ft/ft WNW
7/20/94		6.36	0.66	-0.07	0.003 ft/ft S
6/9/95		5.16	1.86	+1.20	0.004 ft/ft SW
6/29/95		5.03	1.99	+0.13	0.005 ft/ft SW
9/7/95		6.42	0.60	-1.39	0.004 ft/ft SW
12/20/95		4.02	3.00	+1.61	0.005 ft/ft SW
3/22/96		3.67	3.35	+0.35	0.007 ft/ft SE
6/21/96		5.45	1.57	-1.78	0.005 ft/ft W
9/17/96		6.17	0.85	-0.72	0.003 ft/ft NW
1/17/97		3.46	3.56	+2.71	0.005 ft/ft SW
4/11/97	H	5.13	1.89	-1.67	0.005 ft/ft NW

Well Number and Sampling Date	nd Sampling Elevation		Groundwater Elevation (Assumed Datum equals 12')	Change Since Last Measurement (In feet)	Average Hydraulic Gradient
MW-4				i	
6/29/95 9/7/95 12/20/95 3/22/96 6/21/96 9/17/96 1/17/97 4/11/97	6.46 feet	4.60 5.79 3.66 3.29 4.93 5.62 3.07 4.60	1.86 0.64 2.80 3.17 1.53 0.84 3.39 1.86	-1.22 +2.16 +0.37 -1.64 -0.69 +2.55 -1.53	0.005 ft/ft SW 0.004 ft/ft SW 0.005 ft/ft SW 0.007 ft/ft SE 0.005 ft/ft W 0.003 ft/ft NW 0.005 ft/ft SW 0.005 ft/ft NW

Note: MW-1 through MW-3 were installed in June 1994, MW-4 was installed in June 1995.

TABLE 2 CUMULATIVE SUMMARY OF GROUNDWATER ANALYTICAL RESULTS


1055 Eastshore Highway Albany, California


Monitoring Well No. and Sampling Date	TPH- Gasoline	Benzene	Toluene	Ethylbenzene	Xylenes
MW-1					
6/23/94 6/29/95 9/7/95 12/20/95 3/22/96 6/21/96 9/17/96 1/17/97	ND (<50)	ND (<0.3) 0.8 ND (<0.5)	0.60 ND (< 0.5) ND (< 0.5) ND (< 0.5) 2.5 ND (< 0.5) ND (< 0.5) ND (< 0.5) ND (< 0.5)	2.5 1.3 ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)	9.0 3.2 ND (<0.5) ND (<0.5) 2.2 ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)
6/23/94 6/29/95 9/7/95 12/20/95 3/22/96 6/21/96 9/17/96 1/17/97 4/11/97	330 3,800 2,700 1,500 4,500 1,100 190 9,700 4,000	130 260 100 170 920 140 9.0 1,200 520	11 9.8 1.9 50 30 1.6 8.2 140 4.8	20 190 92 30 360 62 10 440 120	10 310 210 170 1,300 160 26 1,300 180
MW-3	52.0	ND (<0.3)	ND (<0.3)	4.0	13
6/23/94 6/29/95 9/7/95 12/20/95 3/22/96 6/21/96 9/17/96 1/17/97 4/11/97	ND (<50)	ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)	ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)	ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)	ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)


Monitoring Well No. and Sampling Date	TPH-Gasoline	Benzene	Toluene	Ethylbenzene	Xylenes
MW-4					
6/29/95 9/7/95 12/20/95 3/22/96 6/21/96 9/17/96 1/17/97 4/11/97	ND (<50) ND (<50) ND (<50) 60 ND (<50) ND (<50) ND (<50) ND (<50)	ND (<0.5) ND (<0.5) ND (<0.5) 0.8 ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)	ND (<0.5) ND (<0.5) ND (<0.5) 2.8 ND (<0.5) 2.3 ND (<0.5) ND (<0.5)	ND (<0.5) ND (<0.5) ND (<0.5) 1.1-ppb ND (<0.5) ND (<0.5) ND (<0.5) ND (<0.5)	ND (<0.5) ND (<0.5) ND (<0.5) 4.7 ND (<0.5) 1.4 ND (<0.5) ND (<0.5)

Notes:

- 1. ND = Not-detected at or above the laboratory reporting limit indicated in parenthesis.
- 2. All numerical values are in units of μ g/L, approximately equivalent to ppb.
- 3. MW-4 installed June 1995.







₩ ₩-4

WELL LOCATION MAP

EXPLANATION



1055 EAST SHORE HIGHWAY


ALBANY, CALIFORNIA

FIGURE 3

SOURCE: ALLWEST

DRAWN BY: S. POON PROJECT NO. 96208.28

DATE: 4/28/97



Appendix A

GROUNDWATER SAMPLING PROCEDURES

Upon arriving at the groundwater monitoring well site, each monitoring well vault and well casing are first examined for damage which could render the well inoperable. Any water collected during the recent rains were purged from the well vault to avoid contamination from rain water. The upper end-cap was then removed and an organic vapor meter (OVM) was used to detect hydrocarbon vapor that might exist inside the well casing. The reading of the OVM was then recorded onto the groundwater sampling field log. After an appreciable time for groundwater levels to equilibrate, electric water level sounder was lowered into the well casing to measure the depth to water to the nearest 0.01 feet. A clear polyethylene bailer was then lowered into the well casing and partially submerged. Upon retrieval of the clear bailer, the surface of the water column retained in the bailer was carefully examined for floating product or product sheen.

After initial measurements were completed and recorded, each monitoring well was purged by an electrical submersible pump or decontaminated teflon bailer. A minimum of 3 well volumes of groundwater was purged. Groundwater quality parameters (temperature, pH, and conductivity) were monitored with a combination meter after each well volume was removed. Purging was considered complete when purging indicators were stabilized (consecutive readings within 10% of each other) or the purged water was relatively free of sediments. All purged water was temporarily stored on-site in labeled 55-gallon drums pending test results to determine the proper disposal method. If no contamination was found then the purge water was disposed of as nonhazardous.

Groundwater sampling was conducted after the water level in the well recovered to at least 80% of the initial level that was recorded before purging. The groundwater sample was collected using a disposable bailer, which was discarded after the sampling event. Upon retrieval of the disposable bailer, the retained water was carefully transferred to appropriate glass container(s) (three 40-ml VOAs) furnished by the analytical laboratory. A bottom emptying device was placed on the bailer to minimize the loss of volatile organic compounds during transfer. All sample containers were fitted with teflon lined septum/cap and filled such that no headspace was present. After the water sample was properly transferred to the appropriate containers, the containers were labeled and immediately placed on ice in an insulated cooler to preserve the chemical characteristics of the sample.

To prevent cross contamination, all groundwater sampling equipment that came into contact with the groundwater was thoroughly cleaned by washing in Alconox (a non-phosphate detergent) solution and double rinsed with distilled water prior to each well sampling event. Groundwater samples were stored and transported in an insulated cooler filled with crushed ice. The analytical laboratory collected the samples from the site or from the *AllWest* office. The samples were delivered to the analytical laboratory by a special courier of the laboratory. All samples were transported under strict Chain-of-Custody document protocol from the time of sample collection to the time of arrival at the laboratory.



GROUNDWATER MONITORING WELL SAMPLING FIELD LOG

Project No.:	96208.28		Pro	Project Name: Albany			
Well No.: _	MW-1		We	Vell Location:			
Well Depth:	(f	t.)	Cas	sing Diameter: _	_2(in.)	
Depth to Wa	ter: <u>4.88</u>	(ft.)	Date: <u>04/11/97</u>	7 Tim	e: <u>9:32</u>		
Water Colum	nn in Well:	(ft.)	We	ell Volume:2	2.6 (gal.)		
Odor? <u>no</u>	F	ree Product?	n/a	Thickness	s: <u>n/a</u>		
Purging Met	hod: Hand P	ump Su	ıbmersible Pump	Baile	er <u>X</u>	Other	
Time	рН	Conduc.	Water Temp (F°)	Water Level	Volume Removed	Remarks	
9:45	8.01	1648	68.1		2.5		
9:50	7.79	1640	67.8		5.0		
9:55	7.68	1632	67.3		7.5		
9:58	7.57	1646	66.9		8.5		
Purging Star	rt Time:	9:40		Purging Stop 7	Time:9;	58	
Total Volum	ie Purged:	8.5 (gal	l.)	Well Dewater?	no no		
Water Level	Prior to Samp	ling: <u>4,97</u> (ft.)	Time:	10:05		
Sampling M	ethod: Teflo	n Bailer	Disposable Ba	iler <u>X</u> S	Sampling Pump		
Sample Coll	ected:	3 X 40 - ml		Sample No.	:MW	7-1	
Remarks:		-					
				·			
Compler	I Chin	σ		Date/Time:	4/11/9	7 10:15	




GROUNDWATER MONITORING WELL SAMPLING FIELD LOG

Project No.:	96208.28		Pro	oject Name:A	Albany	
Well No.: _	MW-2		We	ell Location:		M-W
Well Depth:	(f	t.)	Ca	sing Diameter: _	2 (in.)
Depth to Wa	ter: <u>5.15</u>	(ft.)	Date: <u>04/11/9</u>	7 Tim	e: <u>9:34</u>	
Water Colum	nn in Well:	(ft.)	We	ell Volume:2	2.5 (gal.)	
Odor? <u>yes</u>	F	ree Product? _	n/a	Thicknes	s: <u>n/a</u>	
Purging Met	thod: Hand Pu	ımp Sı	ıbmersible Pump	Baile	er _X_	Other
Time	рН	Conduc. (µS)	Water Temp (F°)	Water Level	Volume Removed	Remarks
12:20	7.21	1130	69.1		2.5	
12:25	7.13	1095_	68.6		5.0	
12:30	6.99	1088	68.2		7.5	
distribution of the state of th						
	rt Time:				Fime: 12	:30
	Prior to Sampl				12:35	
	-					
			Disposable Ba		:MW	
Remarks:	 					
Sampler:	L. Chins			Date/Time:	4/11/9	7 12:50



GROUNDWATER MONITORING WELL SAMPLING FIELD LOG

Project No.:	96208.28		Pro	oject Name:A	lbany	
Well No.: _	MW-3		We	ell Location:		
Well Depth:	(f	t.)	Cas	sing Diameter: _	2 (in.)
Depth to Wa	ter: <u>5.13</u>	(ft.)	Date: <u>04/11/9</u> 2	7 Tim	e: <u>9:30</u>	
Water Colum	nn in Well:	(ft.)	We	ell Volume:2	2.5 (gal.)	
Odor? <u>no</u>	F	ree Product? _	n/a	Thickness	s:n/a	
Purging Met	thod: Hand P	ump Su	ıbmersible Pump	Baile	er <u>X</u>	Other
Time	рН	Conduc. (µS)	Water Temp (F°)	Water Level	Volume Removed	Remarks
11:25	7.58	1361	69.1		2.5	
11:30	7.63	1348	68.8		5.0	
11:35	7.62	1336	68.5		7.5	
]						
Purging Star	rt Time:	11:20		Purging Stop T	ime:1	:35
Total Volum	ne Purged:	7.5 (gal	.)	Well Dewater?	no _	
Water Level	Prior to Samp	ling: <u>5.20</u> (ft.)	Time:	11:40	
Sampling M	ethod: Teflo	n Bailer	Disposable Ba	iler <u>X</u> S	ampling Pump	
Sample Coll	ected:	3 X 40 - ml	<u> </u>	Sample No.	:	7-3
	I Chin			Date/Time:	4/11/9	7 12:00



Project No.:	96208.28		Pro	Project Name: <u>Albany</u>				
Well No.:	MW-4		We	ell Location:				
Well Depth:	(f	t.)	Ca	sing Diameter: _	(in.)		
Depth to Wa	ter: 4.60	(ft.)	Date: <u>04/11/9</u>	7 Tim	e: <u>9:28</u>			
Water Colum	nn in Well:]	<u>9.40</u> (f	t.) We	ell Volume:3	3.2 (gal.)			
Odor? <u>no</u>	F	ree Product?	n/a	Thicknes	s:n/a			
Purging Met	hod: Hand Pu	ımp Su	ibmersible Pump	Baile	er _X_	Other		
Time	рН	Conduc. (µS)	Water Temp (F°)	Water Level	Volume Removed	Remarks		
10:35	7.72	1396	67.4		2.5			
10.40	7.68	1335	67.1		5.0			
10:45	7.71	1364	66.8		7.5			
10:50	7.59	1330	66.5		10.0			
Purging Star	rt Time:	10:30		Purging Stop 7	Гіте: <u>10</u>	:50		
Total Volum	ne Purged:	10 (gal.)	Well Dewater	?no			
Water Level	Prior to Sampl	ing: <u>4.73</u> (ft.)	Time:	10:55			
Sampling M	ethod: Teflo	n Bailer	Disposable Ba	iler <u>X</u> S	Sampling Pump			
Sample Coll	ected:	3 X 40 - ml		Sample No.	:MV	7-4		
Remarks:	<u> </u>							
Compler	I Chine	T		Date/Time:	4/11/9	7 11:10		

4118 CLIPPER COURT, FREMONT, CA 94538

PHONE (510) 498-1991

FAX (510) 498-1994

April 18, 1997

All West Environmental, Inc. One Sutter Street, Suite 600 San Francisco, CA 94104

Regarding:

Analytical Results

Client Project: 96208.28

Global Lab Project: 970414A

Dear Mr. Long Ching:

Enclosed are the lab results for the samples submitted to Global Lab for the project above. The samples will be disposed of by the laboratory after 30 days from the time they were received.

We appreciate the opportunity to be of assistance to you. If you have any questions or comments, please feel free to contact me at (510) 498-1991.

Sincerely,

Lisheng Wu
Laboratory Manager

4118 CLIPPER COURT, FREMONT, CA 94538

PHONE (510) 498-1991

FAX (510) 498-1994

DHS (LUFT) TPH-BTEX REPORT

(ug/L)

Client:

Long Ching

All West Environmental, Inc.

Date Sampled: Date Received: 04-11-97

One Sutter Street, Suite 600

Date Analyzed:

04-14-97 04-17-97

San Francisco, CA 94104

Date Reported:

04-18-97

Project:

96208.28

Matrix:

Lab Job #:

970414A

Water

Client I.D.	Lab. I.D.	Benzene	Toluene	Ethyl Benzene	Total Xylenes	Dilution Factor
MW-1	970414A01	ND	ND	ND	ND	1
MW-2	970414A02	520	4.8	120	180	1
MW-3	970414A03	ND	ND	ND	ND	1
MW-4	970414A04	ND	ND	ND	ND	1
Reporting Limi	it I	0.5 ug/L	0.5 ug/L	0.5 ug/L	0.5 ug/L	

ND Not Detected. All analytes recorded as ND were found to be at or below the Reporting Limit.

Reviewed By:

ELAP#: 2132

Lisheng Wu, Laboratory Mnager

4118 CLIPPER COURT, FREMONT, CA 94538

PHONE (510) 498-1991

FAX (510) 498-1994

DHS (LUFT) TPH-GASOLINE REPORT

(ug/L)

Client:

Long Ching

All West Environmental, Inc.

One Sutter Street, Suite 600 San Francisco, CA 94104

Project:

96208.28

Matrix:

Water

Date Sampled:

Date Received:

04-14-97 04-17-97

04-11--97

Date Analyzed: Date Reported:

04-17-97

Lab Job #:

970414A

Client I.D.	Lab.	8015M Gasoline	Dilution Factor
1.0.	I.D.	Gasonne	ractor
MW-1	970414A01	ND ND	1
MW-2	970414A02	4000	1
MW-3	970414A03	ND ND	1
MW-4	970414A04	ND	1

50 ug/L

ND Not Detected. All analytes recorded as ND were found to be at or below the Reporting Limit.

Reviewed By:

Reporting Limit

Lisheng Wu, Laboratory Mnager

ELAP#: 2132

EPA METHOD TEST QA/QC TABLE

GLOBAL PROJECT #: 970414A

Lab I.D.:

970414A-MSP

Project:

96208.28

Ext/Prep. Method:

EPA 5030

Date:

04-17-97

Analytical Method:

EPA M8015

Analysis date:

04-17-97 Water

Matrix: Unit:

ug/L

Analyte	Sample Result	Spike Level	Matrix Spike Result	MS Recovery %	Matrix Spike Dul. Result	MSD Recovery %	Average Recovery %R	LCL %R	UCL %R	RPD %	UCL %RPD
									407.0	4.7	44.0
Benzene	0.0	20.0	19.95	99.8	19.03	95.2	97.5	76.0	127.0	4.7	11.0
Toluene	0.0	20.0	16.57	82.9	15.70	78.5	80.7	76.0	125.0	5.4	13.0
Chlorobenzene	0.0	20.0	16.69	83.5	15.99	80.0	81.7	75.0	130.0	4.3	13.0
Gasoline	0.0	1000.0	827	82.7	836	83.6	83.1	70.0	130.0	1.1	30.0

Notes:

Sample Result-Concentration of Sample which is to used for Sample Spike & Sample Spike Duplicate

Spike Level- Level of Concentration Added to the Sample

MSP Result- Matrix Spike Result

MSP %R- Matrix Spike Percent Recovery

MSPD Result- Matrix Spike Duplicate Result

MSPD %R- Matrix Spike Dublicate Percent Recovery

AVG. %R - Average Recovery for MSP & MSPD % Recovery

LCL- Lower Criteria Level

UCL- Upper Criteria Level

RPD- Relative Percent Difference

CHAIN OF CUSTODY

LOG NO. 1075

	: (510) 498-1991 Fax:	(510) 498-199	4																
ADDRESS A TO	CLIE			ANAL	YSIS R	EQUES	FIELD C	ONDITIO	NS:										
ONE S	UTTER ST, #60	94104		208.7		PRES					20.7% 28.00				_				
SAN	DESTINA	ESERVATIVES	£. 30,000					COMPOSITE:											
1 AL	GE 4118 Clipper Court Fremont, CA 94538				5965			, 1 2 2 2 3 3 4 3 4 3 4 3 4 3 4 3 4 3 4 3 4			The state of		*		·				
PROJECT MANAGER LONG CHING PHONE H SAMPLED BY L. CHING				/		2.7	<u>.</u>	1,620											
SAMPLED BY				BIEX		(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)			SPECIAL INSTRUCTIONS										
JOB DESCRIPTION									į										
											Tre-								
SITÉ LOCATION					-6				FA. UJA	1	TURN AROUND TIME . NOTE / FIELD READINGS								
							Ho		200			24 HOURS	48 HOURS	1 WEEK	OTHERS				
DATE TIM	E IDENTIFICATION	SAMPLE METHOD	MATRIX	CONT NO.	AINER IVPE	N	1F	90 LAP 10 AP	M.			모	1 × Z ·	_ ≥	5	ļ			
4/11/97	MM-1		WATER	う	40ML	1,3	X			i de la companya de l			12.5	区					
4/11/97	MM-5		WATER	3	40ML	1,3	X				S.C.		, (°),	X					
4/1/97	WW-3		WATER	3	40ML	1,3	X		19.) 24.)		1967		5 3	X				····	
4/11/97	MW-4		WATER	3	40ML	1,3	X	50m 7007	\$4.45 \$4.50	75 (S)			2.75	Х					
	TRIP BLANK		WATER		40ML	- 3		(1) (1) (清)	- Total	ix X	N.		`,~;}`						
				,				学者 外媒	15 m	100			(0.) (1)					<u>.</u>	
															3.75				
	carrent finding page to the									¥*	流		\$ Y		1				
	the state of the s	A Section 1							S)	Š.	\$ F	T	5 8 Y		3 3				
									21.5 14.6	0	100) 100)		2.7		,, °				
	AND DESIGNATION								`	Ř					,				
		460						100	20 ° 1 20 ° 1		```		, ,						
								s ,1	,										
SUSPECTED CONSTITUE		<u></u>		<u> </u>		<u>- </u>	SAME	PLE RET	TENTION TI	ME	PF	ESERVATIV	/ES [.]	(1) H (2) H		(3) = COLI (4))		
RELINQ	JISHED BY (SIGN)	PRINT	NAME / COMP	ANY-		D/	TE/A	ME			REC	CEIVED E	Y (SIGI	y)		PRINT	ME/COMPA	NY \	
Lins		LONG CH				14/	97	9=9	50	199		M	4	2	, ,	Bret	FISS	e:	
2.36.002	7					· · · / · ·					- 32					Bret	+ 9 997	<u> </u>	
				en al le res		167.53b 167.53b		(it)		I AND			Ž		*	13:40	· def.	14/97	
REC'D AT LAB BY:	1.164 W. 1.12 W. 1.4. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1.	- NO. A. 40. 78.38.2311332552	DATE / TIN	Æ:		- 1775		1 THEO				COND	TIONS/C	OMMEN	TS:				
SHIPPED VIA	JPS	PS 🖫 OTHI				ER						AIR BILL #							