DAVID J. KEARS, Agency Director

AGENCY



Alameda County CC4580 Environmental Protection Division 1131 Harbor Bay Parkway, Room 250 Alameda CA 94502-6577

REMEDIAL ACTION COMPLETION CERTIFICATION

July 8, 1996

Attn: Steve Nelson Tharco 2222 Grant Ave San Lorenzo CA 94580

Dear Mr. Nelson:

UNDERGROUND STORAGE TANK (UST) CASE Tharco 2222 Grant Ave San Lorenzo CA 94580 SITE NO. 1794

This letter confirms the completion of site investigation and remedial action for the underground storage tanks formerly located at the above-described location. Enclosed is the Case Closure Summary for the referenced site for your records.

Based upon the available information, including the current land use, and with the provision that the information provided to this agency was accurate and representative of site conditions, no further action related to the underground storage tank release is required.

This notice is issued pursuant to a regulation contained in Title 23, California Code of Regulations, Division 3, Chapter 16, Section 2721 (e). If a change in land use, structural configuration, or site activities are proposed such that more conservative exposure scenarios should be evaluated, the owner must promptly notify this agency.

Please telephone Amy Leech at (510)567-6700 if you have any questions regarding this matter.

Sincerely,

Mee Ling Tung, Director of Environmental Health Services

ATTACHMENT

c: Frances Maroni, HET, Inc., 2363 Mariner Square Dr, Suite 243, Alameda CA 94501
Kevin Graves, RWQCB
Mike Harper, SWRCB w/attachment
Acting Chief of Environmental Protection Division
Files(ALL)

HEALTH CARE SERVICES









ENVIRONMENTAL HEALTH SERVICES 1131 Harbor Bay Parkway

Alameda, CA 94502-6577 (510)

REMEDIAL ACTION COMPLETION CERTIFICATION

June 13, 1996

Attn: Steve Nelson Tharco 2222 Grant Ave San Lorenzo CA 94580

Dear Mr. Nelson:

UNDERGROUND STORAGE TANK (UST) CASE Tharco 2222 Grant Ave San Lorenzo CA 94580 SITE NO. 1794

This letter confirms the completion of site investigation and remedial action for the underground storage tanks formerly located at the above-described location. Enclosed is the Case Closure Summary for the referenced site for your records.

Based upon the available information, including the current land use, and with the provision that the information provided to this agency was accurate and representative of site conditions, no further action related to the underground storage tank release is required.

This notice is issued pursuant to a regulation contained in Title 23, California Code of Regulations, Division 3, Chapter 16, Section 2721 (e). If a change in land use, structural configuration, or site activities are proposed such that more conservative exposure scenarios should be evaluated, the owner must promptly notify this agency.

Please telephone Amy Leech at (510)567-6700 if you have any questions regarding this matter.

Sincerely,

Mee Ling Tung, Director of Environmental Health Services

ATTACHMENT

Frances Maroni, HET, Inc., 2363 Mariner Square Dr, Suite 243, Alameda CA 94501 c: Kevin Graves, RWQCB Mike Harper, SWRCB w/attachment Acting Chief of Environmental Protection Division Files(ALL)

CASE CLOSURE SUMMARY Leaking Underground Fuel Storage Tank Program Page 1 of 4

I. AGENCY INFORMATION

Agency name: Alameda County-HazMat

Date:City/State/Zip: Alameda, CA 94502

Responsible staff person: Amy Leech

Date: March 22, 1996

Address: 1131 Harbor Bay Pkwy

Phone: (510) 567-6700

Title: Hazardous Materials Spec.

II. CASE INFORMATION

Site facility name: Tharco

Site facility address: 2222 Grant Ave., San Lorenzo, CA 94580

RB LUSTIS Case No: N/A

Local Case No./LOP Case No.: 1794

URF filing date: 06/15/94

SWEEPS No: N/A

Responsible Parties:

Address:

Phone Numbers:

Attn: Steve Nelson

2222 Grant Ave.

(51)276-8600

Tharco

٠.

San Lorenzo, CA 94580

Tank Size in

Contents:

Closed in-place

Date:

No: gal.:

2,000 Diesel

or removed?:

removed

07/19/93

III. RELEASE AND SITE CHARACTERIZATION INFORMATION

Cause and type of release: Leak and/or overfilling

Site characterization complete? Yes

Date approved by oversight agency: 03/13/96

Monitoring Wells installed? Yes

Number: 3

Proper screened interval? Yes (4-9 ft bgs)

Highest GW depth below ground surface: 5.02 ft Lowest depth: 6.46 ft (MW-1)

Flow direction: Has varied from SE, NW; SE to SW. May be tidally influenced.

Most sensitive current use: Commercial

Are drinking water wells affected? No

Aguifer name: N/A

Is surface water affected? No Nearest affected SW name: N/A

Off-site beneficial use impacts (addresses/locations): Not Known

Report(s) on file? YES Where is report(s) filed?

Alameda County, 1131 Harbor Bay Pkwy, Alameda, CA 94502

96 APR 18 PM 1: 25

ENAL ON THE NIAL

III. RELEASE AND SITE CHARACTERIZATION INFORMATION (cont'd)

Treatment and Disposal of Affected Material:

<u>Material</u>	Amount	Action (Treatment	<u>Date</u>
Tanks	(include units) I - UST	or Disposal w/destination) H&H Ship 220 China Basin St., San Francisco	07/93
Product/ Rinsate	70 gallons	PRC Patterson Inc. 13331 North Hwy 33, Patterson, CA	07/93
Soil	40 c.y.	May have been disposed at BFI	12/93

Maximum Documented Contaminant Concentrations - - Before and After Cleanup

Contaminant	Soil (pp	m)		Water (ppb)		
	Before ¹	After ²	After ³	Before4	After ⁵	
TPH (Gasoline)	ND	350	700	460	ND	
TPH (Diesel)	26	39	200	1,000	1,700	
Benzene	ND	2.8	2.1	8.4	ND	
Toluene	ND	0.11	3.4	0.6	ND	
Ethylbenzene	ND	0.86	2.8	3.4	ND	
Xylene	ND	0.99	5.1	1.6	ND	

I "Before" soil sample collected at 6 ft bgs from the diesel UST pit prior to overexcavation.

Comments (Depth of Remediation, etc.):

See comments under Additional Comments section.

IV. CLOSURE

Does completed corrective action protect existing beneficial uses per the Regional Board Basin Plan? **Undetermined**

Does completed corrective action protect potential beneficial uses per the Regional Board Basin Plan? Undetermined

Does corrective action protect public health for current land use? YES

Site management requirements:

A safety assessment for potential exposure risks should be completed and the appropriate regulatory agencies must be notified prior to construction and/or excavation in the affected area at this site.

Should corrective action be reviewed if land use changes? YES

Monitoring wells Decommissioned: No

Number Decommissioned: Pending case closure concurrence. Number Retained:3

List enforcement actions taken: n/a
List enforcement actions rescinded: n/a

^{2 &}quot;After" soil sample collected at 6 ft bgs from the diesel UST pit after overexcavation.

^{3 &}quot;After" soil sample collected from boring B-2 @ 8 - 10 ft bgs.

^{4 &}quot;Before" water sample collected from MW-2 on 3/29/94.

^{5 &}quot;After" water sample collected from MW-2 on 8/9/95.

CASE CLOSURE SUMMARY Leading Underground Fuel Storage Tank Page 3 of 4

V. LOCAL AGENCY REPRESENTATIVE DATA

Name: Amy Leech

Signature: Office

Reviewed by

Name: Eva Chu Signature:

Name: Thomas Peacock

Signature:

VI. RWOCB NOTIFICATION

Date Submitted to RB:

RWQCB Staff Name: Kevin Graves, P.E.

Title: Assoc. Water Resources Control Engineer

Title: Hazardous Materials Spec.

Date: 3/89/96

Title: Hazardous Materials Spec.

Date: 3/29/96

Title: Supervising, Hazardous Materials Spec.

ate: 3-28-96

RB Response

Signature:

Date: 6

VII. ADDITIONAL COMMENTS

On July 19, 1993, one 2,000-gallon diesel underground storage tank (UST) was removed from 2222 Grant Avenue, San Lorenzo, CA. (See attachment 1 for site location.) Groundwater was observed seeping into the tank pit at approximately 9.0 ft bgs and a strong gasoline odor was noted during the UST removal. Initial analytical results of the two soil samples collected from the pit bottom in native soil at approximately 10 feet bgs were unremarkable. On August 27, 1993, after groundwater was pumped from the tank pit and allowed to recharge, a "grab" groundwater sample was collected and the sandy "backfill" material believed to be contaminated was excavated from the tank pit.

Analytical results of the August 27th "grab" groundwater sample identified 850 ppb TPHg and 110 ppm xylenes. Confirmatory soil samples collected from each sidewall at approximately 6-9 feet bgs in the overexcavated tank pit identified up to 350 ppm TPHg, 39 ppm TPHd, and 2.8 ppm benzene. (See attachment 2.)

On March 25, 1994, three monitoring wells were installed in the vicinity of the UST pit. Groundwater was encountered from 4.81 to 5.41 feet bgs. A soil sample collected at 6.5 ft bgs from boring B-2/MW-2 (located approximately 8-10 feet northwest of the tank pit) identified 710, 200, and 2.1 ppm of TPHg, TPHd, and benzene, respectively. (See attachment 3 for soil results and boring logs.)

Groundwater was sampled five times from 3/24/94 through 8/9/95. Groundwater gradient is relatively flat and the flow direction has fluctuated from northwest to southwest and southeast which may indicate tidal influences. The maximum concentration of TPHg, TPHd, and BTEX detected in groundwater during the 3/94 to 8/85 sampling period was 460; 1,700; and 37/0.7/3.4/3.6 ppb, respectively. TPHg and BTEX were non-detect in all three wells in August 1995 and TPHd was detected at 1,700 ppb in monitoring well MW-2. In addition, total dissolved solids (TDS) ranged from 1,240 to 5,910 ppb during the August 1995 sampling event. (See attachment 4 for historical groundwater data.)

It appears that residual soil contamination left in place is located within predominantly clay sediments that contain sand from approximately 6 to 7 feet bgs in the vicinity of the UST pit. Based on the TDS levels measured at the site, groundwater is not suitable for drinking water.

A review of the potential risk to human health from exposure to contaminants left in place was completed using ASTM E1739-95 Tier 1 RBCA. The possible pathways of exposure evaluated were soil and groundwater volatilization to outdoor air; other routes of exposure (e.g., risk from indoor air inhalation and soil leachate to groundwater) were not considered since currently, it appears that there are no building structures located over the residual soil and groundwater contamination and groundwater is not used as a drinking water source. In addition, significant contaminant migration in groundwater is not expected due to the low permeable clays soils present at the site.

VII. ADDITIONAL COMMENTS (cont'd)


The maximum concentration of benzene reported to be left in soil and groundwater at the site is 2.1 ppm and 37 ppb, respectively. These concentrations do not exceed the Tier 1 RBCA commercial exposure of 1x10⁻⁴ cancer risk of 13.25 ppm for soil volatilization to outdoor air or 53.4 ppb for groundwater volatilization to outdoor air. The Tier 1 RBCA commercial exposure of 1x10⁻⁴ cancer risk is exceeded for the indoor inhalation pathways for the expected maximum concentrations of contaminants left in soil and groundwater; however, as indicated above, there are no building structures currently over the area of residual contamination. These pathways should be considered and evaluated accordingly prior to completing any excavation or construction in the vicinity of the former UST pit.

No further investigations are recommended since this site appears to meet the San Francisco RWQCB's definition of a low risk groundwater case:


- 1. The source of contamination was abated by removal of the UST. Overexcavation of the contaminated backfill soil was reportedly completed; however, analytical data indicates that residual soil contamination remains in the vicinity of the UST pit.
- 2. The extent of impact to soil and groundwater has been evaluated at this site by analysis of multiple soil and groundwater samples collected within the UST pit and from three soil borings/monitoring wells installed in the vicinity of impacted area.
- 3. Analytical groundwater data collected over one complete hydrologic cycle (5 consecutive quarters) has shown that the dissolved hydrocarbon plume is not significantly migrating and that TPHg and BTEX compounds appear to be attenuating.
- 4. This site is located one-half mile east of San Francisco Bay, and drainage canals which empty to the Bay are located approximately 2,000 feet to the north and south of the site. The residual contamination left in soil and groundwater at this site is not expected to significantly impact these sensitive receptors.
- 5. No significant risk to human health was found for outdoor inhalation exposure to benzene from soil and groundwater contamination using the ASTM E1739-95 Tier 1 RBSL Look-up Table for 1×10^{-4} cancer risk. The cancer risk of 1×10^{-4} was exceeded for indoor inhalation exposure to benzene from soil and groundwater contamination using the Tier 1 RBSL Look-up Table; however, at this time, the area impacted by hydrocarbon contamination is located underneath a parking lot and the nearest building structure is located approximately 30 feet to the north. There is currently no scientific data or methodology available to determine if there are any other potential human health risks associated with the residual levels of TPHg and TPHd left in soil and groundwater.

The current property owner, Tharco, manufactures corrugated cardboard boxes at the site. A risk analysis should be performed if any change in land use or plans for construction/excavation in the affected area is planned.

6. Since it appears that site specific exposure pathways will not affect any currently recognized sensitive ecological receptors, an environmental risk analysis was not performed.



EW 2 8.4/0.72 JP - stockpile b-q - below grade Sample locations Clab composite) *6W1 collected 8/30.



ENVIR & NMENTAL TECHN & LOGIES, INC.

2222 Grant Avenue San Lorenzo, California

7-282 1/95

Table 1

SUMMARY OF SOIL SAMPLE ANALYTICAL RESULTS

Tharco Corporation 2222 Grant Avenue San Leandro, CA

Sample I.D. #	Sampling Depth (feet)		TPHg (ppm)	B (ppm)	T (ppm)	E (ppm)	X (ppm)	TPHd (ppm)
B-1	6.5	3/25/94	ND<1.0	ND<0.005	0.022	ND<0.005	ND<0.005	ND<5:0
B-2	6.5	3/25/94	7 10	2.1	3.4	2.8	5.1	200
B-3	8.5	3/25/94	ND<1.0	ND<0.005	ND<0.005	ND<0.005	ND<0.005	ND<5.0
Notes:								

TPHg:

Total petroleum hydrocarbons as gasoline by EPA Method 8015 (DHS modified)

TPHd:

Total petroleum hydrocarbons as diesel by EPA Method 3550/8015

BTEX:

Benzene, toluene, ethylbenzene and total xylenes by EPA Method 8020 (DHS-modified)

ppm:

Parts per million

ND:

Not detected in concentrations exceeding method detection limits

STE/LOCATION BEGUN Tharco, San Lorenzo 3/25/94					8 Inches	ANGLE/BEARING	BORING NO				
DRILLING CONTRACTOR COMPLI)	FIRST ENCOUNTERED	90 Degrees WATER DEPTH	B-1 BOTTOM OF BORING		
Bayland Drilling 3/25/94							7 Feet	· · · · · · · · · · · · · · · · · · ·	19 Feet		
DRILLMAKE MODEL OPERATOR LOGGED BY CM 70 Adam Huajardo Ruary Alla							STATIC WATER DEPTH 5.41 Feet - 3/29		MM-1		
	material CH 40 PV	c	SLOT SIZ	28	SAMPLING				BOTTOM OF WELL		
FILTE	R PACK	<u>. </u>	WELL SE	AL					19 Feet FLANNED USE		
#2/12 sand Neat cement over hydrated						ted bento	nite pellets		Monitoring		
FCOT FOOT	PID FIELD HEADSPACE (ppm)	DEPTH S	WATER LEVEL	WELL CONSTR.	GRAPHIC LOG	MATERI	MATERIAL CLASSIFICATION & PHYSICAL DESCRIPTION				
6	10	3	¥	ACTION AC			rete pad. .AY (CL); gray	, soft, high plast	icity; damp.		
4	3	6 —				Charralls	· loon CI AV ·	with cond (CI), o	ware maddle of black		
4	0.2	,	Ţ			soft, hig	h plasticity; a	pproximately 30	ray mottled black, % fine grained rse grained sand;		
	}		1			wet.			0		
10	\$	K						y, firm, salt cryst	als in cavities;		
		11		THE			coarse grained	.); gray, firm, low	v plasticity.		
15	0	16				intermi	ttent iron-stai:		o medium graine	:d	
Clayey GRAVEL with sand (GC); multicolored, fine to coarse grained (up to 2" diameter), angular to rounded; approximately 15% clay; approximately 25% fine to coarse grained sand.									rse		
	_	20			~~~~~~						
HYDR & - ENVIR & NMENTAL TECHN & LOGIES, INC.				{ !	A LL CONSTRU	RING LOG .ND ICTION DIAGR IW-1	PLATE C-2 SHEET 1 OF	F1			
						긔	Th	iarco	JOB NO.	,	
DAT	E: June 1, 19	94						int Avenue	7-282		
APPROVED BY: Gary Pischke, C.E.G.						7	San Lo	renzo CA	1-202		

STE/LOCATION Tharco, San Lorenzo					BEGUN		BORING DIAMETER	A. E/BEARING	BORING NO			
DRILLING CONTRACTOR					3/25/94		8 Inches	90 Degrees	B-2			
	land Dri				COMPLETED		FIRST ENCOUNTERED WATER DEPTH		BOTTOM OF BORING			
DRILL MAKE & MODEL OPERATOR					3/25/94		6 Feet		19 Feet			
CM				Huajardo	LOGGED BY		STATIC WATER DEPTH/	DATE	WELL NO.			
WELL MATERIAL SLOT SIZE SAVER POLYTICE MW-2												
	CH 40 PV	VC	0.020			odified spli	it spoon		BOTTOM OF WELL			
	PACK 12 sand		WELL SE						19 Feet PLANNED USE			
	PID		iveat	cement over	er hydr	ated bento	nite pellets		Monitoring			
BLOWS/ ROOT	FIELD HEADSPACE (ppm)	DEPTH XX	WATER LEVEL	WELL CONSTR	GRAPHIC LOG	MATERI	DESCRIPTION					
2	0	3	> :- 1		00000000000000000000000000000000000000	6" Conc Pea gra	rete pad.		,			
0	11	5 7 8 8 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9 9	Ţ		Lean CLAY (CL); light-gray, soft, high plasticity; trace of medium to coarse grained sand; wet. (1)							
7	0.2	10 11 12 13			Lean CLAY (CL); dark-gray, firm, low plasticity, trace of plant debris and organic material, salt crystals in cavities; trace of medium to coarse grained sand; trace of fine grained, angular, gray gravel; wet. (2)							
		"-			////	rinorogy i	(1) to uthology					
Lean CLAY (CL); gray, very stiff, low plasticity, red iron-staining; approximately 10% silt and fine grained sand.												
Lean CLAY with sand (CL); gray, firm, light red iron-staining; approximately 50% silt and fine grained sand; wet.									ht red fine grained			
20												
HYDR & - ENVIR & NMENTAL WE						WELL	SOIL BORIN		PLATE C-3			

TECHN LOGIES, INC.

DATE: June 1, 1994

APPROVED BY: Gary Pischke, C.E.G.

WELL CONSTRUCTION DIAGRAM
MW-2

Tharco
2222 Grant Avenue
San Lorenzo CA

PLATE
C-3

SHEET 1 OF 1

JOB NO.
7-282

Tharco, San Lorenzo Beggi						·	BORING DIAMETER	ANGLE/BEARING	BORING NO		
							8 Inches	90 Degrees	B-3		
Bay	land Dri	lling			3/25/94		FIRST ENCOUNTERED WATER DEPTH BOTTOM OF BOR 9 Feet (uncertain) 20.5 Feet				
	DRILL MAKE & MODEL OPERATOR LOCCED BY						STATIC WATER DEPTH	DATE	WELL NO.		
	CM 70 Adam Huajardo Ruary A						5.34 Feet - 3/29/		MW-3		
	WELL MATERIAL SLOT SIZE SAMPLING N 2" SCH 40 PVC 0.020" CA-mod						tenoon		BOTTOM OF WELL		
FILTE	R PACK		WELL SE	AL					19 Feet PLANNED USE		
#2/	12 sand		Neat	cement ov	<u>er hydra</u>	ted bento	nite pellets		Monitoring		
BLOWS/ ROOT	PID FIELD HEADSPACE (ppm)	DEPTH X	WATER LEVEL	WELL CONSTR.	GRAPHIC LOG			TION & PHYSICAL I	DESCRIPTION		
		3	> ;-				rete pad.	: 4.5' - 5 '; sampler l	plocked by cobble.		
0		6 — 7 —				Lean CL. grained :	AY (CL); dark sand; moist.	gray; trace of med	ium to coarse		
7	0	9 10 11	¥	Titutuminintalianintal		Lean CLAY (CL); dark gray, soft, high plasticity, salt crystals in cavities, red iron-staining, grading into light gray, firm, moderately plastic; trace of medium grained sand; wet.					
14	0	12 ————————————————————————————————————		A THE	I	Lean CLAY (CL); tan, stiff, moderate plasticity; approximately 30% silt; trace of fine grained sand.					
	Poorly-graded SAND (SP); yellow to brown, 5 to 10% black organic material, fine grained, loose.										
E	HYDR & - ENVIR & NMENTAL TECHN & LOGIES, INC.					WEL	MV	ID TION DIAGRAM V-3	SHEET 1 OF 1		
DATE	DATE: June 1, 1994					7	Tha		JOB NO.		
						-{	2222 Gran	· 	7_200		
WLLK!	APPROVED BY: Gary Pischke, C.E.G.					San Lorenzo CA 7-282					

,