

June 1, 1993

Mr. Ted Klink City of Pleasanton Fire Department P.O. Box 320 Pleasanton, California 94566-0802

30-0065-10

Subject:

Quarterly Ground Water Monitoring and Sampling Report

Former Mobil Station 04-H6J

1024 Main Street Pleasanton, California

Dear Mr. Klink:

The enclosed report presents the results of quarterly ground water monitoring and sampling performed April 5, 1993, by Alton Geoscience at former Mobil Station 04-H6J, 1024 Main Street, Pleasanton, California.

Please call if you have questions or comments regarding this report.

Sincerely,

ALTON GEOSCIENCE

Eric R. Schaper

Project Hydrogeologist

cc:

Ms. Cherine Foutch - Mobil Oil Corporation

Mr. Lester Feldman - RWQCB - San Francisco Bay Region

Mr. Barton and Mrs. Bonnie Yates - Property Owner

Mr. Joe Ramia - Adjacent Property Owner

m:\...\mobil\04-h6j\q2.93



March 30, 1993

Mr. Ted Klink City of Pleasanton Fire Department P.O. Box 320 Pleasanton, California 94566-0802

30-0065-10

Subject:

Quarterly Ground Water Monitoring and Sampling Report

Former Mobil Station 04-H6J

1024 Main Street Pleasanton, California

Dear Mr. Klink:

The enclosed report presents the results of quarterly ground water monitoring and sampling performed January 22, 1993, by Alton Geoscience at former Mobil Station 04-H6J, 1024 Main Street, Pleasanton, California.

Please call if you have questions or comments regarding this report.

Sincerely,

ALTON GEOSCIENCE

Eric R. Schaper

Project Hydrogeologist

cc:


Ms. Cherine Foutch - Mobil Oil Corporation

Mr. Lester Feldman - RWQCB - San Francisco Bay Region

Mr. Barton and Mrs. Bonnie Yates - Property Owner

Mr. Joe Ramia - Adjacent Property Owner

f:\...\projects\0065\65qmar.cvr







Source: U.S.G.S. Map Dublin/Livermore Quadrangles California





SITE VICINITY MAP

U.S.G.S. Guaging Station

City of Pleasanton Monitoring Well

Kaiser Discharge to

Arroyo Valle

 \oplus

0

Former Mobil Station 04-H6J 1024 Main Street Pleasanton, California

FIGURE 1

7.5 Minute Series **ALTON GEOSCIENCE**

Project No. 31-0065

Pleasanton, California

LEGEND Ground water monitoring well Ground water elevation, in feet above mean sea level [NGVD-1929]

Ground water elevation contour line

1-4-WW-8*


MAIN STREET

SCALE (FEET)

General direction of ground water gradient

-⊕ ww-9

309.42



NOTES:

Contour lines are interpretive based on fluid level measurements collected January 22, 1993.

Contour interval = 2.0 foot.

* = Dry well.

** = perched ground water.



ALTON GEOSCIENCE Pleasanton, California GROUND WATER
ELEVATION CONTOUR MAP
January 22, 1993

Former Mobil Station 04-H6J 1024 Main Street Pleasanton, California

FIGURE 2

TABLE 1
Results of Ground Water Monitoring and Sampling
Former Mobil Service Station No. 10-H6J
1024 Main Street Pleasanton, California
Project No 30-065-05

Concentrations in parts per billion (ppb)

SAMPLE	DATE OF	CASING	DEPTH	GROUND	PRODUCT	*** *** ***	T D	_	_	_			Organic	Total	
ID	SAMPLING	ELEVATION	TO WATER	WATER ELEVATIO	THICKNESS N	TPH-G	TPH-D	B 	T	E	X	1,2-DCE	Lead	Lead	LAB
MW-1	04/12/90	348.03	43.57	304.46	0.00	3600		73	13	3	180	45	ND<10		SAL
MW-1	10/18/90	348.03	43.18	304.85	0.00	5000	ND<1000	700	360	170	480	54			SA
MW-1	08/06/91	348.03	38.65	309.38	0.00	2600		310	340	110	340	ND<25		ND<5.0	SAL
MW-1	01/08/92	348.03	38.68	309.35	0.00	2400		270	370	18	340	14	ND<50		SAL
MW-1	04/30/92	348.03	39.93	308.10	0.00	1300		150	120	12	160	4.3			SEQ
MW-1	07/31/92	348.03	43.05	304.98	0.00	ND<50		ND<0.5	ND<0.5	ND<0.5	ND<0.5				SEQ
MW-1	10/27/92	348.03	42.86	305.17	0.00	2700		320	310	84	310				SEQ
MW-1	01/22/93	348.03	34.88	313,15	0.00	2800	. 1	. 190	340	87	320		್ ಕರ್ಷ	i tha	SEQ
MW-2	04/12/90	348.45	44.14	304.31	0.00	64000		5500	7600	1900	7800	200	ND<10		SAL
MW-2	10/18/90	348.45	43.18	305.27	0.00	83000	10000	6800	9100	2400	11000	460			SAL
MW-2	08/06/91	348.45	39.19	309.26	0.00	160000		16000	25000	4300	19000	330		330	SEQ
MW-2	01/08/92	348.45	39.40	309.07	0.02										NA
MW-2	04/30/92	348.45	40.50	307.95	0.00	71000		9200	19000	3700	15000	420			SEQ
MW-2	07/31/92	348.45	43.64	304.93	0.15										NA
MW-2	10/27/92	348.45	43.53	304.92	TRACE										NA
MW-2	01/22/93	348.45	35.55	312.90	TRACE									**** 	NA
MW-3	04/12/90	347.97	23,18	324.79	0.00	2100		32	56	31	170	117	ND<10		SAL
MW-3	10/18/90	347.97	14.28	333.69	0.00	110	ND<1000	3	3	1	5	2			SAL
MW-3	08/06/91	347,97	DRY												NA
MW-3	01/08/92	347.97	32.36	315.61	0.00	680		8.9	26	8.5	72	5.7			SE
MW-3	04/30/92	347.97	DRY												NA
MW-3	07/31/92	347.97	DRY												NA
MW-3	10/27/92	347.97	DRY												NA
MW-3	01/22/93	347.97	27.30	320.67	0,00	2600	****	240	300	170	440				SEQ
MW-4	10/18/90	348.07	43.16	304.91	0.00	9600	2000	180	500	200	1200	9			SAL
MW-4	08/06/91	348.07	38.65	309.42	0.00	8600		320	420	220	650	ND<25		ND<5.0	SEQ
MW-4	01/08/92	348.07	38.65	309.42	0.00	3400		600	880	220	1100	9.2	ND<50		SEQ
MW-4	04/30/92	348.07	39.88	308.19	0.00	7200		650	1200	210	1200	ND<50			SEQ
MW-4	07/31/92	348.07	43.07	305,00	0.00	3800		320	340	120	360				SEQ
MW4	10/27/92	348.07	42.78	305,29	0.00	9000		440	750	190	900			***	SEQ
MW-4	01/22/93	348,07	34.76	313.31	0.00	12000	~ ~ ~ ~ ~	540	1200	320	1900	******		وكيكين فالمرازة	SEQ

•

TABLE 1
Results of Ground Water Monitoring and Sampling
Former Mobil Service Station No. 10—H6J
1024 Main Street Pleasanton, California
Project No 30—065—05

Concentrations in parts per billion (ppb)

SAMPLE	DATE OF	CASING	DEPTH	GROUND	PRODUCT					•			Organic	Total	
ID	SAMPLING	ELEVATION		WATER	THICKNESS	TPH-G	TPH-D	В	Т	Ε	X	1,2-DCE	Lead	Lead	LAB
			WATER	ELEVATIO	N										
MW-5	10/18/90	347.97	**												NA
MW-5	08/06/91	347.97	34.25												NA
MW-5	01/08/92	347.97	34.22												NA
MW-5	04/30/92	347.97	DRY												NA
MW-5	07/31/92	347.97	DRY												NA
MW-5	10/27/92	347.97	DRY												NA
MW-5	01/22/93	347.97	DRY		****										NA
MW-6	10/18/90	348.23	43.60	304.63	0.00	3000	ND<1000	1300	150	120	85	140			SAL
MW-6	08/06/91	348.23	39.07	309.16	0.00	1600		220	10	5.2	14	8.3		ND<5.0	SEQ
MW6	01/08/92	348,23	39.18	309.05	0.00	370		81	3.9	4.5	2.9	5.4	ND<50		SEQ
MW-6	04/30/92	348.23	40.46	307.77	0.00	610		180	8.4	6.8	3.3	7.0			SEQ
MW-6	07/31/92	348.23	43.61	304.62	0.00	9400		1500	1500	370	1100				SEQ
MW-6	10/27/92	348.23	43.68	304.55	0.00	850		27	ND<0.5	6	10				SEQ
MW-6	01/22/93	348.23	35.66	312.57	0.00	250		12	2.4	1.4	1,9				SEQ
MW-7	10/18/90	347.90	9.26	338.64	0.00	ND<50	ND<1000	0.3	0.5	ND<0.3	0.8	ND<0.5			SAL
MW-7	08/06/91	347.90	DRY												NA
MW-7	01/08/92	347.90	23.79	324,11	0.00	220		7.8	1.7	ND<0.3	0.55				SEQ
MW-7	04/30/92	347.90	DRY												NA
MW-7	07/31/92	347.90	DRY												NA
MW-7	10/27/92	347.90	DRY												NA
MW-7	01/22/93	347.90	DRY	ordi nati ni	e nam	i i i i i i i i i i i i i i i i i i i					<u></u> .				NA
MW-8	10/18/90	348.90	11.30	337.60	0.00	900	ND<1000	3	- 5	7	62	ND<0.5			SAL
MW-8	08/06/91	348.90	DRY												NA
MW-8	01/08/92	348.90	DRY												NA
MW-8	04/30/92	348.90	DRY												NA
MW-B	07/31/92	348.90	12.04	336.86	0.00	270 1		ND<0.5	ND<0.5	ND<0.5	1.3				SEQ
MW-8	10/27/92	348.90	DRY												NA.
MW-8	01/22/93	348.90	DRY		الإيمار تستس ار الإيا						\$3 444 .3				NA

•

TABLE 1 Results of Ground Water Monitoring and Sampling Former Mobil Service Station No. 10—H6J 1024 Main Street Pleasanton, California Project No 30—065—05

Concentrations in parts per billion (ppb)

Organic

Total

GROUND

DEPTH

SAMPLE DATE OF

CASING

PRODUCT

ID	SAMPLING	ELEVATION	TO WATER	WATER ELEVATIO	THICKNESS N	TPH-G	TPH-D	В	Ť	E	X	1,2-DCE	Lead	Lead	LAB
MW-9	02/04/92	348.53	43,54	304.99	0.00	16000		3000	740	1200	2500	68		ND<5.0	SEQ
MW-9	04/30/92	348.53	42.83	305.70	0.00	5600		1000	120	410	350	ND<50			SE(
MW-9	07/31/92	348.53	47.36	301.17	0.00	9300		1800	1900	620	940				SEQ
MW-9	10/27/92	348.53	48,32	300.21	0.00	13000		2400	1600	680	1100				SEQ
MW-9	01/22/93	348.53	39.11	309,42	0.00	5600		1200	200	510	350			usièle.	SEQ
EXPLAN	ATION OF A	BBREVIATIO	NS:					ND :r	not detected a	at or above	reported d	etection limit			
TPH-G	:total petrole	eum hydrocarb	ons quanti	fied as gaso	line			:r	not applicable	not analyz	sed .				
TPH-D	:total petrok	eum hydrocarb	ons quanti	fied as diese	ıl			* :r	reported by la	iboratory as	nongaso	line mixture			
TPH-D B	:total petrok :benzene	eum hydrocarb	ons quant	fied as diese	il				reported by la well inaccessi		nongaso	line mixture			
		eum hydrocarb	ons quant	fied as diese	·l			** :V		ble	non gaso	line mixture			
	:benzene	-	ons quant	fied as diese	ıl			** :v 1,2-DC:1	well inaccessi	ble ethane	-	line mixture			

APPENDIX A PROJECT BACKGROUND

PROJECT BACKGROUND

March 1989: A soil gas survey was conducted by Target Environmental Services (TES). Hydrocarbon vapors were detected in soil near the existing pump islands.

October 1989: Balch Petroleum removed three underground fuel storage tanks and an underground waste oil tank. Analysis of soil samples collected from the western boundary of the fuel tank cavity detected between 890 parts per million (ppm) and 2,400 ppm total petroleum hydrocarbons as gasoline (TPH-G). Following removal of the tanks approximately 260 yards of hydrocarbon-affected soil were excavated, sampled, aerated onsite, and subsequently removed for disposal.

June 1, 1990: Alton Geoscience submitted a site investigation report. Eight exploratory soil borings were drilled, three of which were subsequently converted to Monitoring Wells MW-1, MW-2, and MW-3. The geology of the site indicates the presence of two aquifers, separated by a difference in ground water elevations of approximately 20 feet. The highest hydrocarbon concentrations were detected in soil samples collected between 25 and 45 feet below grade with up to 3,500 ppm TPH-G.

January 15, 1991: Alton Geoscience submitted a supplemental site investigation report. Five additional monitoring wells MW-4 through MW-8 were installed. Two water bearing zones were encountered within 50 feet below grade (fbg), and appeared to be separated vertically and laterally by a less permeable clay. The ground water gradient of the upper water bearing zone was directed towards the northeast, and the lower to the northwest. Aquifer testing was performed on both water bearing zones. Adsorbed-phase hydrocarbons appeared limited to the vicinity of the former pump islands and north-northeast of the former underground fuel storage tanks.

August, 1991: Alton Geoscience supervised Earth Technology Corporation during a geotechnical survey using cone penetrometer test (CPT) methods and ground water sampling using a hydropunch tool. Nine CPT soundings were conducted and eight water samples collected. CPT results were used to help define the stratigraphy beneath the site. Results of CPT soundings and hydropunch sampling are summarized in the Alton Geoscience report dated July 31, 1992.

October 24 and 25, 1991: Alton Geoscience supervised Balch Petroleum during trenching operations beneath the location of the former pump islands. Analysis of soil samples collected during the excavation revealed the presence of hydrocarbon-affected soil. Approximately 100 yards of soil were excavated and stockpiled onsite.

August to November 1991: Alton Geoscience continuously monitored ground water levels from several wells using a data logger. Significant changes in ground water elevations were observed. Significant fluctuations in ground water elevations have been noted by Zone 7 in Monitoring Well 3S/1E 16P 5, located approximately 250 feet south of the site.

January 8, 1992: Trenches excavated by Balch Petroleum in October 1991 were backfilled by Balch Petroleum.

January 29 and 30, 1992: Alton Geoscience supervised Clear Heart Construction during drilling of MW-9 (SB-14) and SB-15 inside the former station building.

March 2 and 3, 1992: Alton Geoscience performed two constant rate pumping tests on MW-1 and MW-2. Pumping test results are presented in Alton Geoscience report dated July 31, 1992.

July 31, 1992: Alton Geoscience submitted Supplemental Site Investigation: Assessment and Remedial Investigation of Hydrocarbon-Affected Soil and Ground Water. The report concluded that adsorbed-phase hydrocarbons apparently originated from elbow junctions of the former product lines south of the western dispenser island and north of the former fuel tank cavity and possibly from the former fuel tanks. The migration of hydrocarbons in the vadose zone appears to have been controlled by lenses of coarser sediments within silty clays. The extent of dissolved-phase hydrocarbons in either the upper or lower aquifers has not been defined, however, liquid-phase hydrocarbons appear to be limited to the vicinity of MW-2.

APPENDIX B

ALTON GEOSCIENCE GENERAL FIELD PROCEDURES FOR MONITORING WELL SAMPLING

ALTON GEOSCIENCE GENERAL FIELD PROCEDURES FOR MONITORING WELL SAMPLING

Monitoring wells were inspected for the presence of free product using an electronic interface probe prior to purging. Before sampling, wells were purged of 3 to 4 casing volumes of water or until pH, temperature, and electroconductivity stabilized. Ground water samples were collected by lowering a 2-inch-diameter bottom-fill disposable polyethylene bailer below the air/water interface in the well. The samples were carefully transferred from the bailer to zero-headspace 40-milliliter and 1-liter glass containers fitted with Teflon-sealed caps. 40-milliliter samples were inverted to ensure entrapped air was not present. Each sample was labeled with sample number, well number, date, and sampler's initials, and remained on ice prior to and during transport to a California-certified laboratory for analysis. The samples were handled in accordance with proper chain of custody documentation. The purged water was pumped into barrels prior to disposal or recycling at an appropriate waste disposal facility.

APPENDIX C

ANALYTICAL METHODS, OFFICIAL LABORATORY REPORTS, AND CHAIN OF CUSTODY RECORD

ANALYTICAL METHODS, OFFICIAL LABORATORY REPORTS, AND CHAIN OF CUSTODY RECORD

This appendix includes copies of the official laboratory reports and chain of custody record for soil and ground water samples selected for laboratory analysis.

Laboratory analyses were performed by Sequoia Analytical, a California-certified laboratory (California Certification No. 1271).

Chemical analyses of soil and ground water samples were performed using standard test methods of the United States Environmental Protection Agency (EPA) and the California Department of Health Services (Cal-DHS).

Chain of custody protocol was followed for all samples. The chain of custody form(s) accompanies the samples from the sampling locality to the laboratory, providing a continuous record of possession prior to actual analysis.



Alton Geoscience

5870 Stoneridge Drive, Suite 6

Pleasanton, CA 94588 Attention: Eric Schaper Client Project ID: #

#30-0065-10 / Mobil #04 - H6J

Water

Analysis Method: EPA 5030/8015/8020 First Sample #: 301-0705 Sampled: Received:

Jan 22, 1993 Jan 27, 1993

Reported: Feb 2, 1993

TOTAL PURGEABLE PETROLEUM HYDROCARBONS with BTEX DISTINCTION

Analyte	Reporting Limit μg/L	Sample I.D. 301-0705 MW - 1	Sample I.D. 301-0706 MW - 3	Sample I.D. 301-0707 MW - 4	Sample I.D. 301-0708 MW - 6	Sample I.D. 301-0709 MW - 9	
Purgeable Hydrocarbons	50	2,800	2,600	12,000	250	5,600	
Benzene	0.5	190	240	540	12	1,200	
Toluene	0.5	340	300	1,200	2.4	200	
Ethyl Benzene	0.5	87	170	320	1.4	510	
Total Xylenes	0.5	320	440	1,900	1.9	350	
Chromatogram Pati	tern:	Gasoline	Gasoline	Gasoline	Gasoline	Gasoline	

Quality Control Data

Report Limit Multiplication Factor:	10	20	10	1.0	10
Date Analyzed:	1/28/93	1/28/93	1/28/93	1/29/93	1/28/93
Instrument Identification:	HP-5	HP-5	HP-5	HP-5	HP-5
Surrogate Recovery, %: (QC Limits = 70-130%)	105	107	102	108	111

Purgeable Hydrocarbons are quantitated against a fresh gasoline standard.

Analytes reported as N.D. were not detected above the stated reporting limit.

SEQUOIA ANALYTICAL

Scott A. Chieffo Project Manager

3010705.ALT <1>

FEB 3 1993

Alton Geoscience

Client Project ID: #30-0065-10 / Mobil #04 - H6J

5870 Stoneridge Drive, Suite 6 Pleasanton, CA 94588

Attention: Eric Schaper

QC Sample Group: 3010705-709

Reported: Feb 2, 1993

QUALITY CONTROL DATA REPORT

ANALVEE .			Fat. 1		
ANALYTE	_	7_1	Ethyl-	W. d	
	Benzene	Toluene	Benzene	Xylenes	
	rn.	EPA	EPA	EPA	
Method:	EPA	8015/8020	8015/8020	8015/8020	
	8015/8020	J.F.	J.F.	J.F.	
Analyst:	J.F.				
Reporting Units:	μg/L	μg/L	µg/L	μg/L	
Date Analyzed:	Jan 29, 1993	Jan 29, 1993	Jan 29, 1993	Jan 29, 1993	
QC Sample #:	Matrix Blank	Matrix Blank	Matrix Blank	Matrix Blank	
Sample Conc.:	N.D.	N.D.	N.D.	N.D.	
Spike Conc.					
Added:	20	20	20	60	
Added.	20	20	20	•	
Conc. Matrix					
Spike:	22	21	20	67	
•					
Matrix Spike					
% Recovery:	110	105	100	112	
Conc. Matrix					
Spike Dup.:	24	22	21	73	
opino bapii	≟ ₹		***	. —	
Matrix Spike					
Duplicate					
% Recovery:	120	110	105	122	
	· -				
Relative	2.2	4.0	4.0	0.5	
% Difference:	8.6	4.6	4.8	8.5	

Quality Assurance Statement: All standard operating procedures and quality control requirements have been met.

SEQUOIA ANALYTICAL

Scott A. Chieffo Project Manager

Conc. of M.S. - Conc. of Sample x 100 % Recovery: Spike Conc. Added

Relative % Difference: Conc. of M.S. - Conc. of M.S.D. x 100

(Conc. of M.S. + Conc. of M.S.D.) / 2

3010705.ALT <2>

Mobil Chain of Custody



Redwood City:
Concord:
Sacramento:

(415) 364-9600 (510) 686-9600 (916) 921-9600

Consulting Firm Name: ALTON	GEOSCIEN			04-H6			A Form Response			
Address: 5870 STONERID		STE.6	Mobil Site Address: 1024 MAINST, Pleasant B. Site Assessment							
City: PLEASANTON State:										
Telephone:(510) 734- 8134		į								
Project Contact: ERIC SCHAPER	li e		15 E 000(0)-l							
Turnaround Time: X Standard TAT (5	7_									
	Matrix # of scription Containers	Sequoia's Sample #	13 2 1 3 1 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1	A CONTRACTOR OF THE PARTY OF TH			Comments			
1-22-93	W Helpres.		×		13	019	705AB			
1-22-93	W 2		X				706 AB			
3. MW-4 1-22-93	W 2		× FEE	3 1993		 	707AB			
4. MW-6 1225	W 2		*	1		1-1-1	108 AB			
5. MW-9 1-22-93	W 2		X			W	707AB			
6.										
7.										
8.										
9.					 	-				
10.						<u></u>				
Relinquished By:	Date: 1-27-	93 Time: 1400	5 Received By	Mas or	Date:	1/27/23	Time: 1400			
Relinquished By:	Date:	Time:	Received By	<u>:</u>	Date:		Time:			
Relinquished By:	Date:	Time:	Received By	**	Date:		Time:			