

### 9100T-9 AHH: 34

October 8, 1991

Alameda County Dept. of Environmental Health Hazardous Materials Division 80 Swan Way, #200 Oakland, CA 94621

Attn: Mr. Ravi Arulanantham

Re: Geotechnical Work Plan 6301 Scarlett Court, Dublin

Dear Mr. Arulanantham:

Enclosed is the geotechnical work plan for the above referenced location. It should be self explanatory, but if you have any questions please call (510) 831-1957.

We have scheduled the drill rig for 0900 hrs on October 17, 1991. If this work plan meets with your approval, please FAX your authorization to proceed as soon as possible (510) 838-2151.

Cordially submitted,

Stephen R. Clark

Principal

Robert G. HEASMAN, V.P., DIREctor

C. C. BANCORP, INC

2900 South HARbor BLVd

SANTA ANA, CA. 92704

714-641-6078

714-979-4600

6301 SCARLETT Count, Dublin, G. APN 941-0550-16-2

The contract of the contract o

The second secon

and the second of the second o



# GROUND WATER GEOTECHNICAL INVESTIGATION WORK PLAN

6301 Scarlett Court Dublin, CA

October 8, 1991

prepared for


CCB Bancorp C/O Price Waterhouse 880 Douglas Street, Suite 620 Victoria, B.C



Alameda County Dept. of Environmental Health Hazardous Materials Division 80 Swan Way, #200 Oakland, CA 94621

Attn: Mr. Ravi Arulanantham

Re: Geotechnical Work Plan 6301 Scarlett Court, Dublin



#### INTRODUCTION

The above referenced location (refer to Figure 1) (hereafter referred to as the property or the subject site) has been recommended by the Alameda County Dept. of Environmental Health for geotechnical ground water monitoring. pH7 Environmental has been retained by BCC Bancorp, the property owner, to install one additional monitoring well and perform quarterly sampling. The purpose of the initial investigation will be to analyze shallow soil and ground water samples for potential contamination.

#### BACKGROUND

In August of 1991, one (1) underground fuel storage tank was removed from the subject site. Soil samples taken from the tank yielded non-detectable levels of analyzed components.

Concurrently with the tank removal project, waste oil contaminated soil was removed by Exceltech along the entire length of a french drain in front of the Vehicle Maintenance building. Two (2) sewer connections in front of the building were observed as probable dumping points for the oil. Based upon these observations, Mr. Arulanantham of the Alameda County Dept. of Environmental Health has recommended that a new monitoring well be installed and that the existing monitoring well be activated (refer to attachments - memo dated September 4, 1991).

#### BOREHOLE DRILLING, WELL CONSTRUCTION AND SOIL SAMPLING

In order to analyze shallow soil and ground water samples for potential contamination, one additional monitoring well will be installed under permit from Zone 7 of Alameda County Flood Control and Water Conservation District (refer to attachments). The general vector of the ground water gradient is thought to conform with the general down slope of the topography in a southwesterly direction. The new monitoring well (MW-2) will be installed within ten (10) ft of the westernmost sanitary sewer connection (refer to Figure 2). The existing monitoring well (MW-1) will be utilized to monitor the sanitary sewer connection on the east end of the building (refer to Figure 2).

The soil cuttings generated during drilling will be stockpiled on plastic and covered with plastic sheeting until receipt of the analytical results. Based on the analytical results, pH7 Environmental will provide recommendations to the owner on disposal or cleanup options for the soil cuttings. Disposal/cleanup of all cuttings will be the responsibility of the owner.

Drilling of monitoring well will be accomplished using a mobile drilling rig equipped with eight inch diameter hollow stem augers. The well will be extended to an estimated depth of twenty (20) feet, based upon the known depth to the standing water level at ten (10) feet.

During drilling, a geologist from pH7 Environmental, under the supervision of Mr. Dale Wilder, a Certified Engineering Geologist, will direct the field operations and log the soil samples as they are obtained using the Unified Soil Classification System. Soil samples will be collected at a maximum of five foot intervals in the unsaturated zone and at significant changes in lithology using a modified California sampler with brass sample tubes. The ends of the brass tubes will be covered with aluminum foil, then plastic end caps, and finally wrapped with a suitable tape. Samples will be screened in the field using a portable organic vapor analyzer to check for the presence of fuel compounds. Soil samples will then be immediately double plastic bagged to prevent possible dilution, and placed on ice or dry ice for transport to a DHS certified laboratory (Med-Tox in Pleasant Hill). Soil samples will be analyzed for Total Petroleum Hydrocarbons as Gasoline (TPHg) utilizing EPA Method 5030 GCFID, and BTEX utilizing EPA Method 8020. Formal chain-of-custody records shall be maintained.

The well will be extended ten (10) ft below the standing water level (refer to Figure 3). Two (2) inch diameter, factory threaded and slotted, Schedule 40 PVC casing and screen will rest on sand approximately one foot above the bottom of the hole. The ten (10) ft slotted interval will extend from the end cap to two (2) feet above the standing water level (SWL) to allow for seasonal fluctuations of the SWL. The #3 filter sand will extend two (2) ft above the slotted interval. A one foot bentonite seal will cap the filter sand, and the remaining annulus will be grouted to surface with neat Portland cement.

The top of the monitoring well will be enclosed in a locking field cover which in turn will be enclosed in a heavy duty, traffic cover with the top set slightly above grade to prevent surface infiltration, contamination, or vandalism.

### MONITORING WELL DEVELOPMENT, SAMPLING AND SAMPLE ANALYSES

Well development and sampling will be performed after well completion. The well will be developed by gentle mechanical pumping using a suction pump to remove suspended sediment and settle the sand pack. A minimum of 24 hours will be allowed to elapse in order to allow for the separation and accumulation of free product which will be measured using water and gasoline finding pastes. A water sample will be obtained after purging the well of three borehole volumes of water. Care will be taken during purging not to lower the water level in the monitoring well more than two to three feet in order to minimize potential aeration. The field parameters of pH, electrical conductivity, and temperature will be monitored, recorded and observed to stabilize during purging before the water is sampled. Water discharged during development and purging operations will be stored in 55 gallon drums on site until it can be disposed of properly. After analytical results of water samples, pH7 Environmental will provide recommendations for proper water disposal. Disposal of the purge waters is the financial responsibility of the property owner.



Water samples will collected using a clean Teflon bailer equipped with a flapper valve and cotton cord. The bailer will be decontaminated before sampling by washing in a trisodium phosphate solution followed by a distilled water rinse. The sample will be carefully decanted into a 40 ml volatile organic analysis (VOA) sample bottle provided by the laboratory, placed in a shipping cooler with ice, and transported to Med-Tox in Pleasant Hill, CA. Chain of custody procedures will be observed. Soil samples will be analyzed for Total Petroleum Hydrocarbons as Gasoline (TPHg) utilizing EPA Method 5030 GCFID, BTEX utilizing EPA Method 8020, and extractable hydrocarbons utilizing EPA Method 3550. Water samples will be collected in VOA vials with Teflon septum and analyzed utilizing EPA Methods 5030 GCFID for TPHg, Method 602 for BTEX, and Method 3510 for extractable hydrocarbons. Formal chain-of-custody records shall be maintained.

Sampling of both wells will be performed on a quarterly basis by pH7 Environmental for one year. At the end of that period, pH7 Environmental will negotiate with the property owner for an additional year of quarterly sampling to satisfy the requirements of the Alameda County Dept. of Environmental Health. A report of findings will be submitted to the Health Dept. on a quarterly basis.

#### SITE SAFETY PLAN

To date, no significant contamination has been detected on the subject site. The underground fuel storage tank has been removed and waste oil contaminated soil has been remediated. The new monitoring well is being installed to sample ground water potentially contaminated with waste oil, gasoline, or gasoline additives. Significant contamination is not expected during drilling or sampling. However, a brief site safety plan has been prepared (refer to attachments).

### REPORT PREPARATION

A report will be prepared following evaluation of the field drilling observations and analytical results. The report will include conclusions based on the data obtained along with graphic illustrations of the boring logs, and as-built well construction details.

### PROJECT SCHEDULE

In anticipation of the timely approval of this work plan, a drill rig has been scheduled for 0900 hrs on October 17, 1991. A well permit is currently in application status and will be obtained prior to commencement of field activities. The report by pH7 Environmental report will require approximately seven (7) days to complete following receipt of the final laboratory results. The drilling will be performed by Bay Area Exploration from Suisun, CA.

The work outlined in this Work Plan will commence upon written or verbal approval by the Alameda County Dept. of Environmental Health Hazardous Materials Division. Upon approval, a copy of this work plan will be forwarded to the Bay Area Regional Water Control Board (RWQCB) in Oakland.

Respectfully submitted,

Stephen R. Clark

Principal






Figure 1 Local Vicinity Map






Figure 2



# PROJECT: 6301 Scarlett Court, Dublin Alameda County Permit # Pending Drilled and constructed by: Bay Area Exploration, Suisun, CA (Well Permit Application Submitted 10/7/91) Designed by S. R. Clark Completion Date: October 19, 1991 (proposed) Construction of Monitoring Well MW-2 Water Tight Traffic Rated, Tamper Well Cap Proof Security Cover **Blank Casing** 2" Diameter Grout Bentonite Seal Borehole Wall (8" Diameter) - 10 SWL @ 10 ft Filter Pack (#3 Monterey Sand) Well Screen (2" Diameter, 0.01" Slots) 15 15 •Annular Space (minimum - 3 inches) Horizontal Not To Scale Bottom Plug 20



Figure 3

-env.health while: yellow -facility oink -files

RENE BROCHIER

# ALAMEDA COUNTY, DEPARTMENT OF ENVIRONMENTAL HEALTH

80 Swan Way, #200 Oakland, CA 94621

### Hazardous Materials Division Inspection Form

(415) 271-4320 banes

			Page 1
	Site ID#	Site Name	
	Site Address	630	
	city	ublin	Zip 94.568 Phone 532-7484
	MAX Amt. Stored > 5001t Hazardous Waste general	ted per mont	h? II. Business Plans, Acute Hazardous Materials III. Underground Tanks
-	The marked Items repres	ent violation	s of the Callf. Administration Code (CAC) or the Health & Safety Code (HS&C)
I.A		66471     66472     66508     66508     66493	Today I had a meetre with Mr. Rene E. Brochier and Bob
Manifesi	6. Records 7. Correct 8. Copy sent 9. Exception 10. Copies Recid	60492 66484 66492 66484 66492	Defley regarding this project.
Mic.	11. Treatment 12. On-site Disp. (H.S.&C.) 13. Ex Haz. Waste	66371 26189.5 66570	I was present at the Duslin Site this
In. Prevention	14. Communications 15. Aisle Space 14. Local Authority 17. Mointenance 18. Training  19. Prepared 20. Name List	67121 67124 67126 67120 67105	morning and inspected the remedial work.  Thave also carefully reviewed the final soil remediation report
kt   Sency	21. Copies 22. Emg. Coord. Ting. 23. Condition 24. Comparibility	67141 67144 67241 67242	preparted by Resna
Containers, Tank	25. Maintenance 26. Inspection 27. Buffer Zone 28. Tank inspection 29. Containment 30. Safe Storage 31. Freeboard	67243 67244 67246 67259 67245 67261 67257	The Tank results all Show N.D. for all the components analysed. Based on the Soil Core Sampling it appears at present, there is no
LB	TRANSPORTER (Title 22) 32_Applic_/Insurance33_Comp. Cert_/CHP Insp34_Contained	66428 66448 66465	Significant contamination left underneath the main building.
're Manifest	35. Vehicles 36. EPA ID #2 37. Correct 38. HW Delivery 39. Records	66465 66531 66541 66543 66544	to install a new monitary well and to activate the existing monitary
E JUO D	41. Recyclables		BERT DIFLEY, G.M.  Inspector: A. R. ananthan  Birchen Signature: De Mandanthan
		RENE	BROCHIER

white -env.health yellow -tacility -files

# ALAMEDA COUNTY, DEPARTMENT OF **ENVIRONMENTAL HEALTH**

80 Swan Way, #200 Oakland, CA 94621

(415) 271-4320

Hazar	dous Materials Division Inspection Form					
Site ID# Site Nar	no Old Lew Doty Chiller Today's Date 9,491					
Site Address	301 Scarlett Count EPA ID#					
city	Zip 94 Phone					
MAX Amt. Stored > 500lbs/55g/200cf? Y N Hazardous Waste generated per month?  — I. Hoz. Mot/Woste GENERATOR/TRANSPORTER  — II. Business Plans, Acute Hazardous Materials  — III. Underground Tanks						
The marked items represent violation	ns of the Calif. Administration Code (CAC) or the Health & Safety Code (HS&C)					
I.A GENERATOR (Title 22)  1. Waste ID	Comments:					
	Must as be monitered every 3 months					
	moniteur may be necessaux debend on the nortune and extent of Contamin					
011. Treciment	on the nortune du extent of Contamin					
13. Ex Haz. Waste 66570  14. Communications 67121  15. Alsie Space 67124  16. Local Authority 67126  17. Maintenance 67120  18. Training 67105	1. Based on the analytical results no further Soil removal is necessary					
19. Prepared 67140 20. Name Ust 67141 21. Copies 67141 22. Erng. Coord. Ting. 67144	2. Continue to moniter the two wells					
	3. If any further contamination is found ont this property this office will require further remediation					
.B TRANSPORTER (fittle 22) 32, Applic, final ronce 6642833, Comp. Cert./CHP Insp. 6644834, Containers 66465	Will TEGUTE THOUS TENUARISM					
38. Vehicles 6645  34. EPA ID 4s 66531  37. Correct 66541  38. HW Delivery 66543  39. Records 66544						
#						
Contact: ROCERT DIFLE	RENÉ BROCHIER A.R. Avilanunthen					
Title:	Rene Bushusignature:					



### ALAMEDA COUNTY FLOOD CONTROL AND WATER CONSERVATION DISTRICT

5997 PARKSIDE DRIVE

PLEASANTON, CALIFORNIA 94588

(415) 484-2600

### DRILLING PERMIT APPLICATION

FOR APPLICANT TO COMPLETE	FOR OFFICE USE
LOCATION OF PROJECT 630/ SCARLETT CT.  DUBLIN CA 94568	PERMIT NUMBER
	ESS/() (SI, NO. DELV
CLIENT  Name CCB BANCORP C/O PRICE WATREHOUSE, SUFE 6  Address BBO DOUGLAS ST Phone 604 383 4191  City VICTORIA B.C. Zip VBW 287	20 PERMIT CONDITIONS  Circled Permit Requirements Apply
APPLICANT Name pH7 ENDIRONMENTAL  Address 18211 Bounder Cyn RD Phone 510 831 1957 City SAN DAMON Zip 9458]  TYPE OF PROJECT Well Construction Geotechnical investigation Cathodic Protection General Water Supply Contamination Well Destruction  PROPOSED WATER SUPPLY WELL USE Domestic Industrial Other Municipal Irrigation  DRILLING METHOD: Mud Rotary Auger	A. GENERAL  1. A permit application should be submitted so as to arrive at the Zone 7 office five days prior to proposed starting date.  2. Submit to Zone 7 within 60 days after completion of permitted work the original Department of Water Resources Water Well Drillers Report or equivalent for well projects, or drilling logs and location sketch for geotechnical projects.  3. Permit is void if project not begun within 90 days of approval date.  B. WATER WELLS, INCLUDING PIEZOMETERS  1. Minimum surface seal thickness is two inches of cement grout placed by tremie.  2. Minimum seal depth is 50 feet for municipal and industrial wells or 20 feet for demestic and irrigation wells unless a lesser depth is
Cable Other  DRILLER'S LICENSE NO. 522/25 (C57)  WELL PROJECTS  Drill Hole Diameter 6 in. Maximum  Casing Diameter 2 in. Depth 25 ft.  Surface Seal Depth 7 ft. Number /  GEOTECHNICAL PROJECTS  Number of Borings Maximum  Hole Diameter in. Depth ft.	specially approved. Minimum seal depth for monitoring wells is the maximum depth practicable or 20 feet.  C. GEOTECHNICAL. Backfill bore hole with compacted cuttings or heavy bentonite and upper two feet with compacted material. In areas of known or suspected contamination, tremied cement grout shall be used in place of compacted cuttings.  D. CATHODIC. Fill hole above anode zone with concrete placed by tremie.  E. WELL DESTRUCTION. See attached.
ESTIMATED STARTING DATE  ESTIMATED COMPLETION DATE    o / 9/9/9/   hereby agree to comply with all requirements of this permit and Alameda County Ordinance No. 73-68.	ApprovedDate
APPLICANT'S AND PORT DETE 10/7/9/	5 199 1

### SITE SAFETY PLAN Geotechnical Ground Water Investigation 6301 Scarlett Court, Dublin

This Site Safety Plan establishes general safety requirements necessary to protect all persons and property involved in the remedial investigation at 6301 Scarlet Court, Dublin. This Site Safety Plan will be implemented immediately upon detection of significant contaminants. The expected contaminant is waste oil.

Health and Safety Coordinator for this project is Stephen Clark. Mr. Clark will be on-site during all field operations to verify adherence with the Site Safety Plan. He will coordinate all field activities with local and State Health & Safety representatives as needed.

Upon Site Safety Plan Implementation, the following agencies shall be immediately notified:

1.	Alameda County Dept. of Environmental Health Hazardous Materials Division	271-4320
2.	California Regional Water Quality Control Board San Francisco Bay Region	464-1255

3. Dublin Fire Department 911 or 881-8181

All site personnel and visitors must read this Site Safety Plan. No smoking, drinking or eating shall be allowed in work areas where contamination is suspected. All OSHA and EPA safety rules and regulations will apply.

All personnel should be alert for detectable chemical odors. Half-mask air purifying cartridge respirators will be used when a significant chemical contaminant odor is detected.

If a <u>significant</u> contaminant odor is noted, drilling should stop until the liquid can be identified and/or the potential hazard identified. Neoprene rubber gloves, chemical goggles, protective clothing, chemical-resistent safety boots, and a cartridge respirator, at a minimum, should be used by any personnel in an area of liquid pooling. All other non-essential personnel should leave the area until the potential hazard is evaluated. A qualified individual may be needed to evaluate an unforeseen occurrence.

All disposable clothing worn by on-site personnel will be placed in appropriate disposal containers at the end of each day. If any protective clothing is torn or otherwise damaged, thereby reducing its protective abilities, it will be replaced immediately and disposed of properly. Decontamination of personnel should be addressed.

Visitors entering the site do so at their own risk. Permission to enter a work area must be obtained from Mr. Clark. Their name and purpose should be noted in the field.

### **Emergency Procedures**

Stephen Clark shall be notified immediately of any injury or accident occurring at this site. A contingency plan for emergencies will be to contact one of the following emergency phone numbers if an injury requires off-site medical aid:

Fire and Police Departments	911
Ambulance	911
Chemical Spills	(800) 424-8802
Poison Control Center	(415) 476-6600 or (800) 523-2222
Community Hospital	(415) 847-3000