

**RECEIVED**

3:19 pm, Feb 28, 2008

Alameda County  
Environmental Health

**SUSTAINABLE STRATEGIES FOR GLOBAL LEADERS**

---

February 26, 2008  
DELTA Project: SJ8999S1X  
SAP: 135244

Mr. Jerry Wickham  
Alameda County Health Care Services Agency  
Environmental Health Services – Environmental Protection  
1131 Harbor Bay Parkway, Suite 250  
Alameda, California 94502-6577

**Re: FOURTH QUARTER 2007 GROUNDWATER MONITORING  
REPORT  
Shell-Branded Service Station  
8999 San Ramon Road  
Dublin, California**



Dear Mr. Wickham:

On behalf of Shell Oil Products (SHELL), Delta Consultants (DELTA) has prepared this *Fourth Quarter 2007 Groundwater Monitoring Report* for the above referenced site. The sampling activities at the site were conducted by Blaine Tech Services, Inc. under contract to SHELL and included static water level measurements. A DELTA staff member under the supervision of a California Registered Civil Engineer or a California Professional Geologist performed the data evaluation.

This quarterly report represents DELTA's professional opinions based upon the currently available information and is arrived at in accordance with currently acceptable professional standards. This report is based upon a specific scope of work requested by the client. The Contract between DELTA and its client outlines the scope of work, and only those tasks specifically authorized by that contract or outlined in this report were performed. This report is intended only for the use of DELTA's Client and anyone else specifically listed on this report. DELTA will not and cannot be liable for unauthorized reliance by any other third party. Other than as contained in this paragraph, DELTA makes no express or implied warranty as to the contents of this report.


Mr. Jerry Wickham  
Alameda County Health Care Services Agency  
February 26, 2008  
Page 2

If you have any questions regarding this site, please contact Mr. Richard Garlow (DELTA) at (408) 826-1880 or Mr. Denis Brown (SHELL) at (707) 865-0251.

Sincerely,  
**Delta Consultants**



Richard A. Garlow, M.S., P.G.  
Project Manager



Attachment: Fourth Quarter 2007 Groundwater Monitoring Report

cc: Denis Brown, Shell Oil Products US, Carson  
Carl Cox, C and J Cox Corporation, Pleasanton  
Colleen Winey, Zone 7 Water Agency, Livermore

## SHELL QUARTERLY STATUS REPORT

Station Address:	8999 San Ramon Road, Dublin, California
DELTA Project No.:	SJ8999S1X
SHELL Project Manager / Phone No.:	Denis Brown / (707) 865-0251
DELTA Site Manager / Phone No.:	Richard Garlow / (408) 826-1880
Primary Agency / Regulatory ID:	ACHCSA / Jerry Wickham
Other Agencies to Receive Copies:	Zone 7 Water Agency

**WORK PERFORMED THIS QUARTER (FOURTH - 2007):**

1. Quarterly groundwater monitoring and sampling. Submitted quarterly report.
2. Install additional wells

**WORK PROPOSED FOR NEXT QUARTER (FIRST - 2008):**

1. Quarterly groundwater monitoring and sampling. Submit quarterly report.
2. Complete well installation report

Current Phase of Project:	Site Assessment, Groundwater monitoring
Frequency of Sampling:	Quarterly
Frequency of Monitoring:	Quarterly
Is Separate Phase Hydrocarbon Present On-site (Well #'s):	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Cumulative SPH Recovered to Date:	NA
SPH Recovered This Quarter:	NA
Sensitive Receptor(s) and Respective Direction(s):	No municipal water supply wells were identified within a one-mile radius. A domestic drinking water well (25/1W-35L001) is located ~2,300 ft. southwest of the site.
Site Lithology:	Predominately clay with sand and sandy lean clays to a total depth of approximately 30 feet bg plus CPT data to 80 feet.
Current Remediation Techniques:	None
Permits for Discharge:	None
Approximate Depth to Groundwater:	28.39 feet (well MW-5) below top of well casing
Groundwater Gradient:	Not enough data to determine
Current Agency Correspondence:	NA
Site History:	
Case opening	August 2004
On-Site Assessment	July 2005
Off-Site Assessment	July 2006 -Present
Passive Remediation	Monitor Natural Attenuation

Active Remediation

Summary of Unusual Activity:

---

150 cubic yards of soil removed in 2004

---

All wells, except well MW-5, were dry. MW-5 contained insufficient water for sampling. No groundwater sampling.

---

**ATTACHED:**

- Table 1 – Well Concentrations
- Figure 1 – Site Location Map
- Figure 2 – Groundwater Elevation Map
- Figure 3 – Hydrocarbon Distribution in Groundwater Map
- Appendix A – Field Data Sheets
- Appendix B – Field Procedures

## TABLE

**Table 1**  
**WELL CONCENTRATIONS**  
**Shell Service Station**  
**8999 San Ramon Road**  
**Dublin, CA**

Well ID	Date	TPPH (ug/L)	TEPH (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE 8260 (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	TOC (MSL)	Depth to Water (ft.)	GW Elevation (MSL)
---------	------	----------------	----------------	-------------	-------------	-------------	-------------	------------------------	----------------	----------------	----------------	---------------	--------------	----------------------------	--------------------------

MW-1	5/9/2005	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20.93	NA
MW-1	5/19/2005	<5,000	160 a	<50	<50	<50	<100	1,400	<200	<200	<200	57,000	420.06	20.70	399.36
MW-1	8/15/2005	<5,000	<50	<50	<50	<50	<100	360	<200	<200	<200	56,000	420.06	23.98	396.08
MW-1	11/8/2005	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.06	NA	NA
MW-1	1/30/2006	585	438	<0.500	<0.500	<0.500	<0.500	15.6	<0.500	<0.500	<0.500	115,000	420.06	26.39	393.67
MW-1	5/19/2006	2,940	279 c	<0.500	<0.500	<0.500	<0.500	150	<0.500	0.940	<0.500	49,500	420.06	23.10	396.96
MW-1	8/24/2006	812	85.6 c	<0.500	<0.500	<0.500	<0.500	33.0	<0.500	0.890	<0.500	30,700	420.06	23.94	396.12
MW-1	11/2/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.06	NA	NA
MW-1	1/29/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.06	NA	NA
MW-1	6/5/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.06	NA	NA
MW-1	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.06	NA	NA
MW-1	11/30/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.06	NA	NA

MW-2	5/9/2005	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	20.72	NA
MW-2	5/19/2005	<500	<50	<5.0	<5.0	<5.0	<10	11	<20	<20	<20	4,200	418.88	21.26	397.62
MW-2	8/15/2005	<1,000	<50	<10	<10	<10	<20	<10	<40	<40	<40	7,500	418.88	25.33	393.55
MW-2	11/8/2005	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	418.88	NA	NA
MW-2	1/30/2006	<50.0	401	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	1,310	418.88	25.87	393.01
MW-2	5/19/2006	398	134 c	<0.500	<0.500	<0.500	<0.500	7.65	<0.500	<0.500	<0.500	4,910	418.88	21.75	397.13
MW-2	8/24/2006	<50.0	<46.9 c	<0.500	<0.500	<0.500	<0.500	2.82	<0.500	<0.500	<0.500	4,070	418.88	24.60	394.28
MW-2	11/2/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	418.88	NA	NA
MW-2	1/29/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	418.88	NA	NA
MW-2	6/5/2007	Insufficient water		NA	NA	NA	NA	NA	NA	NA	NA	NA	418.88	26.54	392.34
MW-2	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	418.88	NA	NA
MW-2	11/30/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	418.88	NA	NA

**Table 1**  
**WELL CONCENTRATIONS**  
**Shell Service Station**  
**8999 San Ramon Road**  
**Dublin, CA**

Well ID	Date	TPPH (ug/L)	TEPH (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE 8260 (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	TOC (MSL)	Depth to Water (ft.)	GW Elevation (MSL)
MW-3	5/9/2005	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	19.08	NA
MW-3	5/19/2005	<50	120 a	<0.50	<0.50	<0.50	<1.0	40	<2.0	<2.0	<2.0	6.5	417.24	19.08	398.16
MW-3	8/15/2005	<50	73	<0.50	<0.50	<0.50	<1.0	34	<2.0	<2.0	<2.0	<5.0	417.24	22.20	395.04
MW-3	11/8/2005	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	417.24	NA	NA
MW-3	1/30/2006	<50.0	412	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<10.0	417.24	23.64	393.60
MW-3	5/19/2006	<50.0	183 c	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<10.0	417.24	19.00	398.24
MW-3	8/24/2006	<50.0	214 c	<0.500	<0.500	<0.500	<0.500	3.11	<0.500	<0.500	<0.500	661	417.24	21.84	395.40
MW-3	11/2/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	417.24	NA	NA
MW-3	1/29/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	417.24	NA	NA
MW-3	6/5/2007	<50 f	230 c	<0.50	<1.0	<1.0	<1.0	0.38 g	<2.0	<2.0	<2.0	<10	417.24	23.80	393.44
MW-3	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	417.24	NA	NA
MW-3	11/30/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	417.24	NA	NA
MW-4	5/9/2005	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	19.77	NA
MW-4	5/19/2005	97	59 a	0.66	<0.50	<0.50	<1.0	4.8	<2.0	<2.0	<2.0	8.2	420.52	19.85	400.67
MW-4	8/15/2005	67	<50	<0.50	<0.50	<0.50	<1.0	0.86	<2.0	<2.0	<2.0	<5.0	420.52	23.34	397.18
MW-4	11/8/2005	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.52	NA	NA
MW-4	1/30/2006	<50.0	112	<0.500	<0.500	<0.500	<0.500	1.63	<0.500	<0.500	<0.500	<10.0	420.52	24.13	396.39
MW-4	5/19/2006	<50.0	<46.9 c	<0.500	<0.500	<0.500	<0.500	1.08	<0.500	<0.500	<0.500	<10.0	420.52	19.79	400.73
MW-4	8/24/2006	<50.0	<47.2 c	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	78.3	420.52	22.50	398.02
MW-4	11/2/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.52	NA	NA
MW-4	1/29/2007	<50	<50 c	<0.50	<0.50	<0.50	<1.0	<0.50	<2.0	<2.0	<2.0	<5.0	420.52	25.82	394.70
MW-4	6/5/2007	62 f	120 c	<0.50	<1.0	<1.0	<1.0	1.4	<2.0	<2.0	<2.0	<10	420.52	24.32	396.20
MW-4	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.52	NA	NA
MW-4	11/30/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	420.52	NA	NA



**Table 1**  
**WELL CONCENTRATIONS**  
**Shell Service Station**  
**8999 San Ramon Road**  
**Dublin, CA**

Well ID	Date	TPPH (ug/L)	TEPH (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE 8260 (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	TOC (MSL)	Depth to Water (ft.)	GW Elevation (MSL)
MW-5	8/21/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	416.88	25.25	391.63
MW-5	8/24/2006	<50.0	108 c	<0.500	<0.500	<0.500	<0.500	3.33	<0.500	<0.500	<0.500	21.0	416.88	25.70	391.18
MW-5	11/2/2006	<50	NA	<0.50	<0.50	<0.50	<1.0	<0.50	<2.0	<2.0	<2.0	<5.0	416.88	28.00	388.88
MW-5	1/29/2007	<50	66 c	<0.50	<0.50	<0.50	<1.0	<0.50	<2.0	<2.0	<2.0	<5.0	416.88	27.80	389.08
MW-5	6/5/2007	<50 f	2,200 c,e	<0.50	<1.0	<1.0	<1.0	0.56 g	<2.0	<2.0	<2.0	<10	416.88	27.72	389.16
MW-5	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	416.88	NA	NA
<b>MW-5</b>	<b>11/30/2007</b>	<b>Insufficient water</b>		<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>416.88</b>	<b>28.39</b>	<b>388.49</b>
MW-6	2/28/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	422.50	23.55	398.95
MW-6	3/3/2006	<50.0	104	<0.500	<0.500	<0.500	<0.500	4.93	<0.500	<0.500	<0.500	<10.0	422.50	23.30	399.20
MW-6	5/19/2006	<50.0	<46.9	<0.500	<0.500	<0.500	<0.500	5.76	<0.500	<0.500	<0.500	<10.0	422.50	20.31	402.19
MW-6	8/24/2006	<50.0	<47.2 c	<0.500	<0.500	<0.500	<0.500	0.870	<0.500	<0.500	<0.500	<10.0	422.50	23.69	398.81
MW-6	11/2/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	422.50	28.51	393.99
MW-6	1/29/2007	<50	<50 c	<0.50	<0.50	<0.50	<1.0	1.7	<2.0	<2.0	<2.0	<5.0	422.50	27.08	395.42
MW-6	6/5/2007	<50 f	97 c	<0.50	<1.0	<1.0	<1.0	1.1	<2.0	<2.0	<2.0	<10	422.50	25.77	396.73
MW-6	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	422.50	NA	NA
<b>MW-6</b>	<b>11/30/2007</b>	<b>Well dry</b>		<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>422.50</b>	<b>NA</b>	<b>NA</b>
MW-7	8/21/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.35	25.84	388.51
MW-7	8/24/2006	<50.0	<47.2 c	<0.500	<0.500	<0.500	<0.500	2.63	<0.500	<0.500	<0.500	751	414.35	26.21	388.14
MW-7	11/2/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.35	NA	NA
MW-7	1/29/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.35	NA	NA
MW-7	6/5/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.35	NA	NA
MW-7	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.35	NA	NA
<b>MW-7</b>	<b>11/30/2007</b>	<b>Well dry</b>		<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>414.35</b>	<b>NA</b>	<b>NA</b>

**Table 1**  
**WELL CONCENTRATIONS**  
**Shell Service Station**  
**8999 San Ramon Road**  
**Dublin, CA**

Well ID	Date	TPPH (ug/L)	TEPH (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE 8260 (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	TOC (MSL)	Depth to Water (ft.)	GW Elevation (MSL)
MW-8	8/21/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.54	23.02	391.52
MW-8	8/24/2006	110	74.5 c	<0.500	<0.500	<0.500	<0.500	4.62	<0.500	<0.500	<0.500	6,610	414.54	23.17	391.37
MW-8	11/2/2006	92	96 c	<0.50	<0.50	<0.50	<1.0	1.4	<2.0	<2.0	<2.0	2,300	414.54	27.69	386.85
MW-8	1/29/2007	<50	<50 c	<0.50	<0.50	<0.50	<1.0	0.51	<2.0	<2.0	<2.0	350	414.54	26.40	388.14
MW-8	6/5/2007	<50 f	120 c	<0.50	<1.0	<1.0	<1.0	0.48 g	<2.0	<2.0	<2.0	290	414.54	25.17	389.37
MW-8	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.54	NA	NA
MW-8	11/30/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	414.54	NA	NA
MW-9	8/21/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	412.69	27.75	384.94
MW-9	8/24/2006	<50.0	69.9 c,d	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	<0.500	86.8	412.69	28.35	384.34
MW-9	11/2/2006	<50	NA	<0.50	<0.50	<0.50	<1.0	<0.50	<2.0	<2.0	<2.0	<5.0	412.69	28.43	384.26
MW-9	1/29/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	412.69	NA	NA
MW-9	6/5/2007	Insufficient water		NA	NA	NA	NA	NA	NA	NA	NA	NA	412.69	28.72	383.97
MW-9	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	412.69	NA	NA
MW-9	11/30/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	412.69	NA	NA
MW-10	8/21/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	419.48	23.90	395.58
MW-10	8/24/2006	626	100 c	1.04	<0.500	1.22	<0.500	12.4	<0.500	<0.500	<0.500	5,740	419.48	24.02	395.46
MW-10	11/2/2006	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	419.48	28.50	390.98
MW-10	1/29/2007	91	<50 c	<0.50	<0.50	<0.50	<1.0	4.9	<2.0	<2.0	<2.0	1,900	419.48	27.30	392.18
MW-10	6/5/2007	82 f	150 c	<0.50	<1.0	<1.0	<1.0	1.3	<2.0	<2.0	<2.0	540	419.48	26.09	393.39
MW-10	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	419.48	NA	NA
MW-10	11/30/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	419.48	NA	NA
MW-11	8/21/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	409.69	NA	NA
MW-11	8/24/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	409.69	NA	NA

**Table 1**  
**WELL CONCENTRATIONS**  
**Shell Service Station**  
**8999 San Ramon Road**  
**Dublin, CA**

Well ID	Date	TPPH (ug/L)	TEPH (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE 8260 (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	TOC (MSL)	Depth to Water (ft.)	GW Elevation (MSL)
---------	------	----------------	----------------	-------------	-------------	-------------	-------------	------------------------	----------------	----------------	----------------	---------------	--------------	----------------------------	--------------------------

MW-11	11/2/2006	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	409.69	NA	NA
MW-11	1/29/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	409.69	NA	NA
MW-11	6/5/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	409.69	NA	NA
MW-11	8/27/2007	Well dry	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	409.69	NA	NA
<b>MW-11</b>	<b>11/30/2007</b>	<b>Well dry</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>NA</b>	<b>409.69</b>	<b>NA</b>	<b>NA</b>

Abbreviations:

TPPH = Total petroleum hydrocarbons as gasoline by modified EPA Method 8260B.

TEPH = Total petroleum hydrocarbons as diesel by modified EPA Method 8015.

BTEX = Benzene, toluene, ethylbenzene, xylenes by EPA Method 8260B.

MTBE = Methyl tertiary butyl ether

DIPE = Di-isopropyl ether, analyzed by EPA Method 8260B

ETBE = Ethyl tertiary butyl ether, analyzed by EPA Method 8260B

TAME = Tertiary amyl methyl ether, analyzed by EPA Method 8260B

TBA = Tertiary butyl alcohol or tertiary butanol, analyzed by EPA Method 8260B

TOC = Top of Casing Elevation

GW = Groundwater

ug/L = Parts per billion

MSL = Mean sea level

ft. = Feet

<n = Below detection limit

NA = Not applicable

**Table 1**  
**WELL CONCENTRATIONS**  
**Shell Service Station**  
**8999 San Ramon Road**  
**Dublin, CA**

Well ID	Date	TPPH (ug/L)	TEPH (ug/L)	B (ug/L)	T (ug/L)	E (ug/L)	X (ug/L)	MTBE 8260 (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	TOC (MSL)	Depth to Water (ft.)	GW Elevation (MSL)
---------	------	----------------	----------------	-------------	-------------	-------------	-------------	------------------------	----------------	----------------	----------------	---------------	--------------	----------------------------	--------------------------

Notes:

a = Hydrocarbon reported does not match the pattern of the laboratory's Diesel standard.

b = Quantity of unknown hydrocarbon(s) in sample based on gasoline.

c = Diesel with silica gel clean-up.

d = Insufficient sample available for reanalysis.

e = The sample chromatographic pattern for TPH does not match the chromatographic pattern of the specified standard. Quantitation of the unknown hydrocarbon(s)


f = Analyzed by EPA Method 8015B (M).

g = Analyte was detected at a concentration below the reporting limit and above the laboratory method detection limit. Reported value is estimated.

Site surveyed May 10, 2005 by Mid Coast Engineers.

Well MW-6 surveyed March 3, 2006 by Mid Coast Engineers.

## FIGURES




**GENERAL NOTES:**

Base Map from: 3-D TopoQuads DeLorme  
 Yarmouth, ME 04096 Source Data: USGS



QUADRANGLE LOCATION




**FIGURE 1**  
**SITE LOCATION MAP**

**SHELL-BRANDED SERVICE STATION**  
 8999 San Ramon Road  
 Dublin, California


PROJECT NO. SJ89-99S-1.2005	DRAWN BY V. F. 12/9/04
FILE NO. SJ89-99S-1.2004	PREPARED BY VF
REVISION NO.	REVIEWED BY





PROJECT NUMBER: SJ8999S1X  
 DRAWN BY: J.F.F.  
 CHECKED BY:  
 APPROVED BY:

SCALE IN FEET  
 0 20 40



MW-4			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-6			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-10			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-3			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-8			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-11			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA


MW-2			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-7			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-5			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-1			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA

MW-9			
TPH-g (µg/L)	BENZENE (µg/L)	MTBE (µg/L)	TBA (µg/L)
NA	NA	NA	NA



**LEGEND**

- MW-1 GROUNDWATER MONITORING WELL LOCATION AND DESIGNATION
- TPH-g TOTAL PETROLEUM HYDROCARBONS AS GASOLINE
- MTBE METHYL TERT-BUTYL ETHER
- TBA TERT-BUTYL ALCOHOL
- ND< NOT DETECTED ABOVE LIMIT NOTED
- µg/L MICROGRAMS PER LITER
- NA NOT ANALYZED

**DELTA CONSULTANTS**

SHELL OIL PRODUCTS U.S.  
 SHELL-BRANDED SERVICE STATION  
 DUBLIN, CALIFORNIA

**FIGURE 3  
 HYDROCARBON DISTRIBUTION IN  
 GROUNDWATER MAP  
 11/30/2007**

8999 SAN RAMON ROAD  
 DUBLIN, CALIFORNIA



**APPENDIX A**

**FIELD DATA SHEETS**

# SHELL WELLHEAD INSPECTION FORM

(FOR SAMPLE TECHNICIAN)

Site Address 8999 San Ramon Rd., Dublin Date 11/30/07  
 Job Number 071130-SCI Technician S. Chase Page 1 of 1

Well ID	Well Inspected - No Corrective Action Required	Well Box Meets Compliance Requirements "See Below"	Water Bailed From Wellbox	Cap Replaced	Lock Replaced	Well Not Inspected (explain in notes)	New Deficiency Identified	Previously Identified Deficiency Persists	Notes
MW-5	X	X			X				Water bailed from well box
MW-9	X	X							
MW-8	X	X							Water bailed from well box
MW-7	X	X							Water bailed from well box
MW-11	X	X							
MW-3	X	X							
MW-2	X	X							
MW-6	X	X							
MW-4	X	X							
MW-10	X	X							
MW-1	X	X							

\*Well box must meet all three criteria to be compliant: 1) WELL IS SECURABLE BY DESIGN (12" or less) 2) WELL IS MARKED WITH THE WORDS "MONITORING WELL" (12" or less) 3) WELL TAG IS PRESENT, SECURE, AND CORRECT

Notes: \_\_\_\_\_

### WELL GAUGING DATA

Project # 071130-5C1 Date 11/30/07 Client Shell

Site 8999 San Ramon Rl., Dublin

Well ID	Time	Well Size (in.)	Sheen / Odor	Depth to Immiscible Liquid (ft.)	Thickness of Immiscible Liquid (ft.)	Volume of Immiscibles Removed (ml)	Depth to water (ft.)	Depth to well bottom (ft.)	Survey Point: TOB, or TOO	Notes
MW-5	0752	4	NO / NO				28.39	28.48	↓	
MW-9	0758	4	NO / NO	* Dry Well			-	28.84		
MW-8	0810	4	NO / NO	* Dry Well			-	28.81		
MW-7	0815	4	NO / NO	* Dry Well			-	28.55		
MW-11	0830	2	NO / NO	* Dry Well			-	28.52		
MW-3	0845	4	NO / NO	* Dry Well			-	24.35		
MW-2	0850	4	NO / NO	* Dry Well			-	26.80		
MW-6	0856	4	NO / NO	* Dry Well			-	28.55		
MW-4	0905	4	NO / NO	* Dry Well			-	26.54		
MW-10	0910	4	NO / NO	* Dry Well			-	28.82		
MW-1	0915	4	NO / NO	* Dry Well			-	26.78		

### SHELL WELL MONITORING DATA SHEET

BTS #: <u>071130-5c1</u>	Site: <u>97565995</u>
Sampler: <u>S. Chase</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MA-1</u>	Well Diameter: 2 3 <u>(4)</u> 6 8
Total Well Depth (TD): <u>26.78</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method: <input type="checkbox"/> Bailer <input type="checkbox"/> Disposable Bailer <input type="checkbox"/> Positive Air Displacement <input type="checkbox"/> Electric Submersible	Waterra <input type="checkbox"/> Peristaltic <input checked="" type="checkbox"/> Extraction Pump Other: _____	Sampling Method: <input type="checkbox"/> Bailer <input type="checkbox"/> Disposable Bailer <input type="checkbox"/> Extraction Port <input type="checkbox"/> Dedicated Tubing Other: _____
--	--	---

	(Gals.) X	=	Gals.
I Case Volume	Specified Volumes		Calculated Volume

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius <sup>2</sup> * 0.163

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<u>* MA-1 is a dry well</u>						

Did well dewater? Yes No	Gallons actually evacuated:
Sampling Date:	Sampling Time: Depth to Water:
Sample I.D.:	Laboratory: STL Other _____
Analyzed for: TPH-G BTEX MTBE TPH-D Other:	
EB I.D. (if applicable): @ Time	Duplicate I.D. (if applicable):
Analyzed for: TPH-G BTEX MTBE TPH-D Other:	
D.O. (if req'd): Pre-purge: _____ mg/L	Post-purge: _____ mg/L
O.R.P. (if req'd): Pre-purge: _____ mV	Post-purge: _____ mV

### SHELL WELL MONITORING DATA SHEET

BTS #: <b>071130-5C1</b>	Site: <b>97565995</b>
Sampler: <b>S. Chase</b>	Date: <b>11/30/07</b>
Well I.D.: <b>MH-2</b>	Well Diameter: 2 3 <b>(4)</b> 6 8
Total Well Depth (TD): <b>26.80</b>	Depth to Water (DTW): <b>—</b>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <b>PVO</b> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <b>—</b>	

Purge Method: ~~Bailer~~ ~~Disposable Bailer~~ ~~Positive Air Displacement~~ ~~Electric Submersible~~ ~~Waterra~~ ~~Peristaltic~~ ~~Extraction Pump~~ Other \_\_\_\_\_

Sampling Method: ~~Bailer~~ ~~Disposable Bailer~~ ~~Extraction Port~~ ~~Dedicated Tubing~~ Other: \_\_\_\_\_

$\frac{\text{I Case Volume (Gals.)} \times \text{Specified Volumes}}{\text{Specified Volumes}} = \text{Calculated Volume Gals.}$	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>Well Diameter</th> <th>Multiplier</th> <th>Well Diameter</th> <th>Multiplier</th> </tr> <tr> <td>1"</td> <td>0.04</td> <td>4"</td> <td>0.65</td> </tr> <tr> <td>2"</td> <td>0.16</td> <td>6"</td> <td>1.47</td> </tr> <tr> <td>3"</td> <td>0.37</td> <td>Other</td> <td>radius<sup>2</sup> * 0.163</td> </tr> </table>	Well Diameter	Multiplier	Well Diameter	Multiplier	1"	0.04	4"	0.65	2"	0.16	6"	1.47	3"	0.37	Other	radius <sup>2</sup> * 0.163
Well Diameter	Multiplier	Well Diameter	Multiplier														
1"	0.04	4"	0.65														
2"	0.16	6"	1.47														
3"	0.37	Other	radius <sup>2</sup> * 0.163														

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<b>* MH-2 is a dry well</b>						

Did well dewater? Yes No	Gallons actually evacuated:
Sampling Date:	Sampling Time: Depth to Water:
Sample I.D.:	Laboratory: STL Other _____
Analyzed for: TPH-G BTEX MTBE TPH-D Other:	
EB I.D. (if applicable): @ Time	Duplicate I.D. (if applicable):
Analyzed for: TPH-G BTEX MTBE TPH-D Other:	
D.O. (if req'd): Pre-purge: _____ mg/L	Post-purge: _____ mg/L
O.R.P. (if req'd): Pre-purge: _____ mV	Post-purge: _____ mV

### SHELL WELL MONITORING DATA SHEET

BTS #: <u>071130-SC 1</u>	Site: <u>97565995</u>
Sampler: <u>S. Chase</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MW-3</u>	Well Diameter: 2 3 <u>(4)</u> 6 8 _____
Total Well Depth (TD): <u>24.35</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method: Bailer      Waterra      Sampling Method: Bailer  
 Disposable Bailer      Peristaltic      Disposable Bailer  
 Positive Air Displacement      Extraction Pump      Extraction Port  
 Electric Submersible      Other \_\_\_\_\_      Dedicated Tubing  
 Other: \_\_\_\_\_

\_\_\_\_\_ (Gals.) X \_\_\_\_\_ = \_\_\_\_\_ Gals.  
 1 Case Volume      Specified Volumes      Calculated Volume

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius <sup>2</sup> * 0.163

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<u>* MW-3 is a dry well</u>						

Did well dewater?    Yes    No      Gallons actually evacuated: \_\_\_\_\_

Sampling Date: \_\_\_\_\_      Sampling Time: \_\_\_\_\_      Depth to Water: \_\_\_\_\_

Sample I.D.: \_\_\_\_\_      Laboratory: STL    Other \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

EB I.D. (if applicable): \_\_\_\_\_ @ \_\_\_\_\_ Time      Duplicate I.D. (if applicable): \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV

### SHELL WELL MONITORING DATA SHEET

BTS #: <u>071130 - sc 1</u>	Site: <u>97565995</u>
Sampler: <u>S. Chase</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MA-4</u>	Well Diameter: 2 3 <u>4</u> 6 8
Total Well Depth (TD): <u>26.54</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method: Bailer  
 Disposable Bailer  
 Positive Air Displacement  
 Electric Submersible

Waters  
 Peristaltic  
 Extraction Pump  
 Other: \_\_\_\_\_

Sampling Method: Bailer  
 Disposable Bailer  
 Extraction Port  
 Dedicated Tubing

Other: \_\_\_\_\_

	(Gals.) X	=	Gals.
1 Case Volume	Specified Volumes	Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius <sup>2</sup> * 0.163

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<u>*MA-4 is a dry well</u>						

Did well dewater? Yes No      Gallons actually evacuated: \_\_\_\_\_

Sampling Date: \_\_\_\_\_      Sampling Time: \_\_\_\_\_      Depth to Water: \_\_\_\_\_

Sample I.D.: \_\_\_\_\_      Laboratory: STL Other: \_\_\_\_\_

Analyzed for: TPH-G BTEX MTBE TPH-D Other: \_\_\_\_\_

EB I.D. (if applicable): \_\_\_\_\_ @ \_\_\_\_\_ Time      Duplicate I.D. (if applicable): \_\_\_\_\_

Analyzed for: TPH-G BTEX MTBE TPH-D Other: \_\_\_\_\_

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV

**Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (800) 545-7558**

### SHELL WELL MONITORING DATA SHEET

BTS #: <b>071130-501</b>	Site: <b>97565995</b>
Sampler: <b>S. Chase</b>	Date: <b>11/30/07</b>
Well I.D.: <b>MW-5</b>	Well Diameter: 2 3 <b>4</b> 6 8
Total Well Depth (TD): <b>28.48</b>	Depth to Water (DTW): <b>28.39</b>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <b>PVC</b> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <b>-</b>	

Purge Method: Bailer      Water      Sampling Method: Bailer  
 Disposable Bailer      Peristaltic      Disposable Bailer  
 Positive Air Displacement      Extraction Pump      Extraction Port  
 Electric Submersible      Other \_\_\_\_\_      Dedicated Tubing  
 Other: \_\_\_\_\_

_____ (Gals.) X _____ = _____ Gals. 1 Case Volume      Specified Volumes      Calculated Volume	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>Well Diameter</th> <th>Multiplier</th> <th>Well Diameter</th> <th>Multiplier</th> </tr> <tr> <td>1"</td> <td>0.04</td> <td>4"</td> <td>0.65</td> </tr> <tr> <td>2"</td> <td>0.16</td> <td>6"</td> <td>1.47</td> </tr> <tr> <td>3"</td> <td>0.37</td> <td>Other</td> <td>radius<sup>2</sup> * 0.163</td> </tr> </table>	Well Diameter	Multiplier	Well Diameter	Multiplier	1"	0.04	4"	0.65	2"	0.16	6"	1.47	3"	0.37	Other	radius <sup>2</sup> * 0.163
Well Diameter	Multiplier	Well Diameter	Multiplier														
1"	0.04	4"	0.65														
2"	0.16	6"	1.47														
3"	0.37	Other	radius <sup>2</sup> * 0.163														

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<b>* Insufficient water to purge or sample</b>						

Did well dewater?    Yes    No      Gallons actually evacuated: \_\_\_\_\_

Sampling Date: \_\_\_\_\_      Sampling Time: \_\_\_\_\_      Depth to Water: \_\_\_\_\_

Sample I.D.: \_\_\_\_\_      Laboratory: STL    Other \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

EB I.D. (if applicable): \_\_\_\_\_ @ \_\_\_\_\_ Time      Duplicate I.D. (if applicable): \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV



### SHELL WELL MONITORING DATA SHEET

BTS #: <u>071130-521</u>	Site: <u>97565995</u>
Sampler: <u>S. Chase</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MN-6</u>	Well Diameter: 2 3 <u>(4)</u> 6 8
Total Well Depth (TD): <u>28.55</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method: Bailer      Waterra      Sampling Method: Bailer  
 Disposable Bailer      Peristaltic      Disposable Bailer  
 Positive Air Displacement      Extraction Pump      Extraction Port  
 Electric Submersible      Other \_\_\_\_\_      Dedicated Tubing

Other: \_\_\_\_\_

	(Gals.) X	=	Gals.
1 Case Volume	Specified Volumes		Calculated Volume

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius <sup>2</sup> * 0.163

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<u>* MN-6 is a dry well</u>						

Did well dewater?    Yes    No      Gallons actually evacuated:

Sampling Date:      Sampling Time:      Depth to Water:

Sample I.D.:      Laboratory:    STL    Other \_\_\_\_\_

Analyzed for:    TPH-G    BTEX    MTBE    TPH-D    Other:

EB I.D. (if applicable):      @      Duplicate I.D. (if applicable):

Analyzed for:    TPH-G    BTEX    MTBE    TPH-D    Other:

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV

### SHELL WELL MONITORING DATA SHEET

BTS #: <u>071130-SC1</u>	Site: <u>97565995</u>
Sampler: <u>S. Chase</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MU-7</u>	Well Diameter: 2 3 <u>4</u> 6 8
Total Well Depth (TD): <u>28.55</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method:  Bailer       Waterra      Sampling Method:  Bailer  
 Disposable Bailer       Peristaltic       Disposable Bailer  
 Positive Air Displacement       Extraction Pump       Extraction Port  
 Electric Submersible      Other: \_\_\_\_\_       Dedicated Tubing  
 Other: \_\_\_\_\_

	(Gals.) X _____ = _____ Gals.		
1 Case Volume	Specified Volumes	Calculated Volume	

Well Diameter	Multiplier	Well Diameter	Multiplier
1"	0.04	4"	0.65
2"	0.16	6"	1.47
3"	0.37	Other	radius <sup>2</sup> * 0.163

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<u>* MU-7 is a dry well</u>						

Did well dewater?  Yes  No      Gallons actually evacuated: \_\_\_\_\_

Sampling Date: \_\_\_\_\_      Sampling Time: \_\_\_\_\_      Depth to Water: \_\_\_\_\_

Sample I.D.: \_\_\_\_\_      Laboratory: STL Other: \_\_\_\_\_

Analyzed for: TPH-G BTEX MTBE TPH-D Other: \_\_\_\_\_

EB I.D. (if applicable): \_\_\_\_\_ @ \_\_\_\_\_ Time      Duplicate I.D. (if applicable): \_\_\_\_\_

Analyzed for: TPH-G BTEX MTBE TPH-D Other: \_\_\_\_\_

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV

**SHELL WELL MONITORING DATA SHEET**

BTS #: <u>071130-SC 1</u>	Site: <u>97565995</u>
Sampler: <u>S. Chase</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MH-8</u>	Well Diameter: 2 3 <u>(4)</u> 6 8
Total Well Depth (TD): <u>28.81</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method: Bailer      Waterra      Sampling Method: Bailer  
 Disposable Bailer      Peristaltic      Disposable Bailer  
 Positive Air Displacement      Extraction Pump      Extraction Port  
 Electric Submersible      Other: \_\_\_\_\_      Dedicated Tubing

$\frac{\text{Gals.}}{\text{Specified Volumes}} \times \text{I Case Volume} = \text{Calculated Volume Gals.}$	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>Well Diameter</th> <th>Multiplier</th> <th>Well Diameter</th> <th>Multiplier</th> </tr> <tr> <td>1"</td> <td>0.04</td> <td>4"</td> <td>0.65</td> </tr> <tr> <td>2"</td> <td>0.16</td> <td>6"</td> <td>1.47</td> </tr> <tr> <td>3"</td> <td>0.37</td> <td>Other</td> <td>radius<sup>2</sup> * 0.163</td> </tr> </table>	Well Diameter	Multiplier	Well Diameter	Multiplier	1"	0.04	4"	0.65	2"	0.16	6"	1.47	3"	0.37	Other	radius <sup>2</sup> * 0.163
Well Diameter	Multiplier	Well Diameter	Multiplier														
1"	0.04	4"	0.65														
2"	0.16	6"	1.47														
3"	0.37	Other	radius <sup>2</sup> * 0.163														

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<u>* MH-8 is a dry well</u>						

Did well dewater?    Yes    No      Gallons actually evacuated: \_\_\_\_\_

Sampling Date: \_\_\_\_\_    Sampling Time: \_\_\_\_\_    Depth to Water: \_\_\_\_\_

Sample I.D.: \_\_\_\_\_    Laboratory: STL    Other: \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

EB I.D. (if applicable): \_\_\_\_\_ @ \_\_\_\_\_ Time    Duplicate I.D. (if applicable): \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV

### SHELL WELL MONITORING DATA SHEET

BTS #: <u>071130-5C1</u>	Site: <u>97565995</u>
Sampler: <u>S. Chase</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MW-9</u>	Well Diameter: 2 3 <u>(4)</u> 6 8 _____
Total Well Depth (TD): <u>28.84</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method: ~~Bailer  
Disposable Bailer  
Positive Air Displacement  
Electric Submersible~~      ~~Water  
Peristaltic  
Extraction Pump  
Other \_\_\_\_\_~~      Sampling Method: ~~Bailer  
Disposable Bailer  
Extraction Port  
Dedicated Tubing  
Other: \_\_\_\_\_~~

$\frac{\text{(Gals.) X}}{\text{Specified Volumes}} = \frac{\text{Gals.}}{\text{Calculated Volume}}$	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>Well Diameter</th> <th>Multiplier</th> <th>Well Diameter</th> <th>Multiplier</th> </tr> <tr> <td>1"</td> <td>0.04</td> <td>4"</td> <td>0.65</td> </tr> <tr> <td>2"</td> <td>0.16</td> <td>6"</td> <td>1.47</td> </tr> <tr> <td>3"</td> <td>0.37</td> <td>Other</td> <td>radius<sup>2</sup> * 0.163</td> </tr> </table>	Well Diameter	Multiplier	Well Diameter	Multiplier	1"	0.04	4"	0.65	2"	0.16	6"	1.47	3"	0.37	Other	radius <sup>2</sup> * 0.163
Well Diameter	Multiplier	Well Diameter	Multiplier														
1"	0.04	4"	0.65														
2"	0.16	6"	1.47														
3"	0.37	Other	radius <sup>2</sup> * 0.163														

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<i>* MW-9 is a dry well</i>						

Did well dewater?    Yes    No	Gallons actually evacuated:		
Sampling Date:	Sampling Time:                      Depth to Water:		
Sample I.D.:	Laboratory:    STL    Other _____		
Analyzed for:    TPH-G    BTEX    MTBE    TPH-D    Other:			
EB I.D. (if applicable):                      @                      Time	Duplicate I.D. (if applicable):		
Analyzed for:    TPH-G    BTEX    MTBE    TPH-D    Other:			
D.O. (if req'd):    Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):    Pre-purge:	mV	Post-purge:	mV

**Blaine Tech Services, Inc. 1680 Rogers Ave., San Jose, CA 95112 (800) 545-7558**

### SHELL WELL MONITORING DATA SHEET

BTS #: <i>071130-SC1</i>	Site: <i>97565995</i>
Sampler: <i>S. Chase</i>	Date: <i>11/30/07</i>
Well I.D.: <i>MH-10</i>	Well Diameter: 2 3 <b>(4)</b> 6 8
Total Well Depth (TD): <i>28.82</i>	Depth to Water (DTW): <i>—</i>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <b>(PVC)</b> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <i>—</i>	

Purge Method: Bailer      Water      Sampling Method: Bailer  
 Disposable Bailer      Peristaltic      Disposable Bailer  
 Positive Air Displacement      Extraction Pump      Extraction Port  
 Electric Submersible      Other \_\_\_\_\_      Dedicated Tubing

$\frac{\text{_____ (Gals.)} \times \text{_____}}{\text{Specified Volumes}} = \text{_____ Gals.}$ 1 Case Volume      Calculated Volume	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>Well Diameter</th> <th>Multiplier</th> <th>Well Diameter</th> <th>Multiplier</th> </tr> <tr> <td>1"</td> <td>0.04</td> <td>4"</td> <td>0.65</td> </tr> <tr> <td>2"</td> <td>0.16</td> <td>6"</td> <td>1.47</td> </tr> <tr> <td>3"</td> <td>0.37</td> <td>Other</td> <td>radius<sup>2</sup> * 0.163</td> </tr> </table>	Well Diameter	Multiplier	Well Diameter	Multiplier	1"	0.04	4"	0.65	2"	0.16	6"	1.47	3"	0.37	Other	radius <sup>2</sup> * 0.163
Well Diameter	Multiplier	Well Diameter	Multiplier														
1"	0.04	4"	0.65														
2"	0.16	6"	1.47														
3"	0.37	Other	radius <sup>2</sup> * 0.163														

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<i>* MH-10 is a dry Well</i>						

Did well dewater?    Yes    No      Gallons actually evacuated: \_\_\_\_\_

Sampling Date: \_\_\_\_\_      Sampling Time: \_\_\_\_\_      Depth to Water: \_\_\_\_\_

Sample I.D.: \_\_\_\_\_      Laboratory: STL    Other \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

EB I.D. (if applicable): \_\_\_\_\_ @ \_\_\_\_\_ Time      Duplicate I.D. (if applicable): \_\_\_\_\_

Analyzed for: TPH-G    BTEX    MTBE    TPH-D    Other: \_\_\_\_\_

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV

### SHELL WELL MONITORING DATA SHEET

BTS #: <u>071130-SC1</u>	Site: <u>97565995</u>
Sampler: <u>S. Chate</u>	Date: <u>11/30/07</u>
Well I.D.: <u>MW-11</u>	Well Diameter: <u>2</u> 3 4 6 8
Total Well Depth (TD): <u>28.52</u>	Depth to Water (DTW): <u>—</u>
Depth to Free Product:	Thickness of Free Product (feet):
Referenced to: <u>PVC</u> Grade	D.O. Meter (if req'd): YSI HACH
DTW with 80% Recharge [(Height of Water Column x 0.20) + DTW]: <u>—</u>	

Purge Method: ~~Bailer~~  
~~Disposable Bailer~~  
~~Positive Air Displacement~~  
~~Electric Submersible~~

Water  
~~Peristaltic~~  
~~Extraction Pump~~  
 Other \_\_\_\_\_

Sampling Method: ~~Bailer~~  
~~Disposable Bailer~~  
~~Extraction Port~~  
~~Dedicated Tubing~~

Other: \_\_\_\_\_

$\frac{\text{Gals.} \times \text{Specified Volumes}}{\text{I Case Volume}} = \text{Calculated Volume Gals.}$	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>Well Diameter</th> <th>Multiplier</th> <th>Well Diameter</th> <th>Multiplier</th> </tr> <tr> <td>1"</td> <td>0.04</td> <td>4"</td> <td>0.65</td> </tr> <tr> <td>2"</td> <td>0.16</td> <td>6"</td> <td>1.47</td> </tr> <tr> <td>3"</td> <td>0.37</td> <td>Other</td> <td>radius<sup>2</sup> * 0.163</td> </tr> </table>	Well Diameter	Multiplier	Well Diameter	Multiplier	1"	0.04	4"	0.65	2"	0.16	6"	1.47	3"	0.37	Other	radius <sup>2</sup> * 0.163
Well Diameter	Multiplier	Well Diameter	Multiplier														
1"	0.04	4"	0.65														
2"	0.16	6"	1.47														
3"	0.37	Other	radius <sup>2</sup> * 0.163														

Time	Temp (°F)	pH	Cond. (mS or µS)	Turbidity (NTUs)	Gals. Removed	Observations
<i>* MW-11 is a dry well</i>						

Did well dewater? Yes No      Gallons actually evacuated: \_\_\_\_\_

Sampling Date: \_\_\_\_\_ Sampling Time: \_\_\_\_\_ Depth to Water: \_\_\_\_\_

Sample I.D.: \_\_\_\_\_ Laboratory: STL Other \_\_\_\_\_

Analyzed for: TPH-G BTEX MTBE TPH-D Other: \_\_\_\_\_

EB I.D. (if applicable): \_\_\_\_\_ @ \_\_\_\_\_ Time Duplicate I.D. (if applicable): \_\_\_\_\_

Analyzed for: TPH-G BTEX MTBE TPH-D Other: \_\_\_\_\_

D.O. (if req'd):	Pre-purge:	mg/L	Post-purge:	mg/L
O.R.P. (if req'd):	Pre-purge:	mV	Post-purge:	mV

**APPENDIX B**

**FIELD PROCEDURES**

BLAINE TECH SERVICES, INC.  
METHODS AND PROCEDURES  
FOR THE ROUTINE MONITORING OF  
GROUNDWATER WELLS AT SHELL SITES

Blaine Tech Services, Inc. performs environmental sampling and documentation as an independent third party. We specialize in groundwater monitoring assignments and intentionally limit the scope of our services to those centered on the generation of objective information.

To avoid conflicts of interest, Blaine Tech Services, Inc. personnel do not evaluate or interpret the information we collect. As a state licensed contractor (C-57 well drilling –water – 746684 ) performing strictly technical services, we do not make any professional recommendations and perform no consulting of any kind.

---

#### SAMPLING PROCEDURES OVERVIEW

##### SAFETY

All groundwater monitoring assignments performed for Shell comply with Shell's safety guidelines, 29 CFR 1910.120 and SB-198 Injury and Illness Prevention Program (IIPP). All Field Technicians receive the full 40-hour 29CFR 1910.120 OSHA SARA HAZWOPER course, medical clearance and on-the-job training prior to commencing any work on any Shell site.

##### INSPECTION AND GAUGING

Wells are inspected prior to evacuation and sampling. The condition of the wellhead is checked and noted according to a wellhead inspection checklist.

Standard measurements include the depth to water (DTW) and the total well depth (TD) obtained with industry standard electronic water level indicators that are graduated in increments of hundredths of a foot.

The water in each well is inspected for the presence of immiscibles. When free product is suspected, its presence is confirmed using an electronic interface probe (e.g. MMC). No samples are collected from a well containing over two-hundredths of a foot (0.02') of product.

##### EVACUATION

Depth to water measurements are collected by our personnel prior to purging and minimum purge volumes are calculated anew for each well based on the height of the water column and the diameter of the well. Expected purge volumes are never less than three case volumes and are set at no less than four case volumes in some jurisdictions.



Well purging devices are selected on the basis of the well diameter and the total volume to be evacuated. In most cases the well will be purged using an electric submersible pump (i.e. Grundfos) suspended near (but not touching) the bottom of the well.

#### PARAMETER STABILIZATION

Well purging completion standards include minimum purge volumes, but additionally require stabilization of specific groundwater parameters prior to sample collection. Typical groundwater parameters used to measure stability are electrical conductivity, pH, and temperature. Instrument readings are obtained at regular intervals during the evacuation process (no less than once per case volume).

Stabilization standards for routine quarterly monitoring of fuel sites include the following: Temperature is considered to have stabilized when successive readings do not fluctuate more than +/- 1 degree Celsius. Electrical conductivity is considered stable when successive readings are within 10%. pH is considered to be stable when successive readings remain constant or vary no more than 0.2 of a pH unit.

#### DEWATERED WELLS

Normal evacuation removes no less than three case volumes of water from the well. However, less water may be removed in cases where the well dewateres and does not immediately recharge.

#### MEASURING RECHARGE

Upon completion of well purging, a depth to water measurement is collected and notated to ensure that the well has recharged to within 80% of its static, pre-purge level prior to sampling.

Wells that do not immediately show 80% recharge or dewatered wells will be allowed a minimum of 2 hours to recharge prior to sampling. The water level at time of sampling will be noted.

#### PURGEWATER CONTAINMENT

All non-hazardous purgewater evacuated from each groundwater monitoring well is captured and contained in on-board storage tanks on the Sampling Vehicle and/or special water hauling trailers. Effluent from the decontamination of reusable apparatus (sounders, electric pumps and hoses etc.), consisting of groundwater combined with deionized water and non-phosphate soap, is also captured and pumped into effluent tanks.

Non-hazardous purgewater is transported under standard Bill of Lading documentation to a Blaine Tech Services, Inc. facility before being transported to a Shell approved disposal facility.

## SAMPLE COLLECTION DEVICES

All samples are collected using a stainless steel, Teflon or disposable bailers.

## SAMPLE CONTAINERS

Sample material is decanted directly from the sampling bailer into sample containers provided by the laboratory that will analyze the samples. The transfer of sample material from the bailer to the sample container conforms to specifications contained in the USEPA T.E.G.D. The type of sample container, material of construction, method of closure and filling requirements are specific to the intended analysis. Chemicals needed to preserve the sample material are commonly placed inside the sample containers by the laboratory or glassware vendor prior to delivery of the bottle to our personnel. The laboratory sets the number of replicate containers.

## TRIP BLANKS

Trip Blanks, if requested, are taken to the site and kept inside the sample cooler for the duration of the event. They are turned over to the laboratory for analysis with the samples from that site.

## DUPLICATES

Duplicates, if requested, may be collected at a site. The Field Technician uses their discretion in choosing the well at which the Duplicate is collected, typically one suspected of containing measurable contaminants. The Duplicate sample is labeled "DUP" and the time of collection is omitted from the COC, thus rendering the sample blind.

## SAMPLE STORAGE

All sample containers are promptly placed in food grade ice chests for storage in the field and transport (direct or via our facility) to the designated analytical laboratory. These ice chests contain quantities of restaurant grade ice as a refrigerant material. The samples are maintained in either an ice chest or a refrigerator until relinquished into the custody of the laboratory or laboratory courier.

## DOCUMENTATION CONVENTIONS

A label must be affixed to all sample containers. In most cases these labels are generated by our office personnel and are partially preprinted. Labels can also be hand written by our field personnel. The site is identified with the store number and site address, as is the particular groundwater well from which the sample is drawn (e.g. MW-1, MW-2, S-1 etc.). The time and date of sample collection along with the initials of the person who collects the sample are handwritten onto the label.

Chain of Custody records are created using client specific preprinted forms following USEPA specifications.

Bill of Lading records are contemporaneous records created in the field at the site where the non-hazardous purgewater is generated. Field Technicians use preprinted Bill of Lading forms.

## DECONTAMINATION

All equipment is brought to the site in clean and serviceable condition and is cleaned after use in each well and before subsequent use in any other well. Equipment is decontaminated before leaving the site.

The primary decontamination device is a commercial steam cleaner. The steam cleaner is de-tuned to function as a hot pressure washer that is then operated with high quality deionized water that is produced at our facility and stored onboard our sampling vehicle. Cleaning is facilitated by the use of proprietary fixtures and devices included in the patented workstation (U.S. Patent 5,535,775) that is incorporated in each sampling vehicle. The steam cleaner is used to decon reels, pumps and bailers.

Any sensitive equipment or parts (i.e. Dissolved Oxygen sensor membrane, water level indicator, etc.) that cannot be washed using the high pressure water, will be sprayed with a non-phosphate soap and deionized water solution and rinsed with deionized water.

## DISSOLVED OXYGEN READINGS

Dissolved Oxygen readings are taken pre- and/or post-purge using YSI meters (e.g. YSI Model 54, 58 or 95) or HACH field test kits.

The YSI meters are equipped with a stirring device that enables them to collect accurate in-situ readings. The probe/stirring devices are modified to allow downhole measurements to be taken from wells with diameters as small as two inches. The probe and reel is decontaminated between wells as described above. The meter is calibrated between wells as per the instructions in the operating manual. The probe and stirrer is lowered into the water column. The reading is allowed to stabilize prior to collection.

## OXYIDATON REDUCTION POTENTIAL READINGS

All readings are obtained with either Corning or Myron-L meters (e.g. Corning ORP-65 or a Myron-L Ultrameter GP). The meter is cleaned between wells as described above. The meter is calibrated at the start of each day according to the instruction manual.

## FERROUS IRON MEASUREMENTS

All field measurements are collected at time of sampling with a HACH test kit.