

May 5, 1992

General Electric Company Vallecitos Naclear, Çenter

Attention: Ravi Arulanantham Alameda County Department of Environmental Health Hazardous Materials Division 80 Swan Way, Room 200 Oakland, California 94621

Subject:

Workplan for bioremediation of approximately 10 cubic yards of soil containing diesel

fuel at the General Electric Company Vallecitos Nuclear Center, Pleasanton,

California.

Dear Mr. Arulanantham:

This letter presents a workplan to bioremediate a small volume of soil containing detectable diesel fuel. Approximately 10 cubic yards of soil was excavated during removal of diesel fuel tank piping at the "300 Area", General Electric Company Vallecitos Nuclear Center (GE-VNC). The soil is currently stored on site in 43 drums. Analytical test results of samples collected from the drums and excavated trench floor are given on Table 1 (attached). Analytical test results indicated total petroleum hydrocarbons (TPH)-as-diesel concentrations ranging from 61-to-13,000 ppm (parts per million) for the soil stored in these 55-gallon drums. Test results from samples taken from the excavation trench floor indicated non-detect for TPH-as-diesel at reporting limits of 1 ppm.

GE-VNC proposes to conduct on-site bioremediation of these soils to reduce the concentration of diesel hydrocarbons to below 100 ppm. Soil treatment will be conducted by our environmental consultant Science & Engineering Analysis Corporation (SEACOR). GE-VNC then proposes to reuse the soil on site as fill material. The following details specific work steps to be conducted:

TREATMENT AREA PREPARATION

A concrete pad approximately 15 feet by 40 feet will be used as the treatment area. The pad is walled on two sides with concrete blocks. The remaining two sides will be enclosed by the construction of berms using clean soil. The pad and the berms will then be lined with double layers of 6 mil plastic sheeting.

SOIL PLACEMENT AND PREPARATION

The diesel contaminated soil will be placed onto the treatment pad and spread out to a uniform thickness using a "bobcat" type mini tractor. The soil moisture will be brought up to approximately 60 percent capacity using clean water. Additionally, a special mixture of nutrients will be added and mixed into the soil. The soil will then be covered with two layers of 6 mil plastic sheeting so as to minimize hydrocarbon volatilization and prevent the infiltration of rain water into the soils.

SOIL TREATMENT AND SAMPLING

The soil will be uncovered and turned weekly using a "bobcat" type mini tractor. Additionally, moisture conditions will be checked and water added as necessary. A four part composite soil sample will be collected every three months for analysis of TPH-as-diesel by the DOHS-LUFT methodology until the soil reaches the cleanup objective of less than 100 ppm TPH. Soil treatment is anticipated to extend six months from project initialization.

REPORTING

Following successful completion of soil bioremediation, a final report will be prepared which details work conducted and contains the results of laboratory analysis of soil samples.

If you have any questions or require more information, please call myself at (510) 862-4345 or Paul Horton of SEACOR at (510) 686-9780.

Sincerely,

Susan A. Dahlin

Environmental Programs Engineer

Swan G. Dulli

TABLE 1
TPH (DIESEL) Concentration
"300 Area" GE-VNC

041077	CALCUTE	EDD.	DEDOCEMIA	TENNE Y	PECODIMINAL.
SAMPLE NUMBER	SAMPLE DATE	EPA METHOD	REPORTING LIMIT (ppm)	TPH (diesel) (ppm)	DESCRIPTION
DS-1	1/30/92	3550	1	61	DRUM NO. DS-1
DS-2	1/30/92	3550	1	160	DRUM NO. DS-2
DS-3	1/30/92	3550	1	450	DRUM NO. DS-3
DS-4	1/30/92	3550	1	710	DRUM NO. DS-4
DS-5	1/30/92	3550	1	210	DRUM NO. DS-5
DS-6	1/30/92	3550	1	170	DRUM NO. DS-6
DS-7	1/30/92	3550	1	430	DRUM NO. DS-7
DS-8	1/30/92	3550	1	250	DRUM NO. DS-8
DS-9	1/30/92	3550	11	560	DRUM NO. DS-9
DS-10	1/30/92	3550	1	210	DRUM NO. DS-10
DS-11	1/30/92	3550	1	130	DRUM NO. DS-11
DS-12	1/30/92	3550	1	760	DRUM NO. DS-12
DS-13	1/30/92	3550	1	360	DRUM NO. DS-13
DS-14	1/30/92	3550	1	720	DRUM NO. DS-14
DS-15	1/30/92	3550	1	480	DRUM NO. DS-15
DS-16	1/30/92	3550	11	490	DRUM NO. DS-16
DS-17	1/30/92	3550	11	430	DRUM NO. DS-17
DS-18	1/30/92	3550	1	250	DRUM NO. DS-18
DS-19	1/30/92	3550	11	250	DRUM NO. DS-19
C-1	1/30/92	3550	1	750	composite 8 drums
C-2	1/30/92	3550	1	900	composite 8 drums
C-3	1/30/92	3550	1	13000	composite 8 drums
RTS-1	1/30/92	3550	1	ND	trench floor
RTS-3	1/30/92	3550	1	ND	trench floor

white -env.health yellow -facility pink -files

ALAMEDA COUNTY, DEPARTMENT OF ENVIRONMENTAL HEALTH

80 Swan Way, #200 Oakland, CA 94621 (415) 271-4320

Hazardous Materials Division Inspection Form

Site ID# Site Non Site Address 6705 City Pleusantio				
MAX Amt. Stored > 500lbs/55g/200 Hazardous Waste generated per mor	ith? II. Business Plans, Acute Hazardous Materials III. Underground Tanks			
The marked items represent violation	ons of the Calif. Administration Code (CAC) or the Health & Safety Code (HS&C)			
1. Wigste ID 66471 2. EPA ID 66472 3. > 99 days 66608 4. Label dates 66693	About 60 feet of pipe attriched to a			
6. Records 664872 7. Correct 66484 8. Copy sent 66492 9. Exception 66484 10. Copies Rec'd 66472	Was removed. To truk Still the some dien left. The piper were about for feel below growne			
	The site sales is a min of the			
14. Communications 67121	any work was performed.			
19. Prepared 67140 20. Name Ust 67141 21. Copies 67141 22. Emg. Coord. Ting. 67144 23. Condition 67241	is on site awantry for analysis and duporal.			
24. Compartibility 67242 25. Maintenance 67243 26. Impaction 67244 27. Buffer Zone 67246 28. Tank Inspection 67259 29. Containment 67259 30. Safe Storage 67251 31. Freeboard 67257	Three Soil Samples (I feet below the pipe line) were taken and will be analyzed for BIXE, IPH(D) and one sample under the brunds will be analyzed for RB.			
B TRANSPORTER (Title 22) 32. Applic./Inturance	Please send Lab reports to this office.			
36. Vehicles 66465 36. UpA ID 4s 66531 37. Connect 66541 38. MW Delivery 66543 39. Récords 66544				
240. Name/ Covers 66645 41. Recyclobies 66600				
Comuch:	A. Dalilis Hal Programs Engineerinspector: A. Whileh Signature: Run Run Run Run Run Run Run Ru			