



RECEIVED

By Alameda County Environmental Health at 4:21 pm, Feb 19, 2013

30343 Canwood Street, Suite 200
Agoura Hills, CA 91301
p 818.206.5700 f 818.206.5715
platinum-energy.net

February 15, 2013

Mr. Keith Nowell
Alameda County Health Care Services Agency
1131 Harbor Bay Parkway, Suite 250
Alameda, CA 94502-6577

Subject: Quarterly Summary Report, Fourth Quarter 2012
Site: 76 Service Station No. 6277
15803 East 14th Street
San Leandro, California
Fuel Leak Case No. RO0002969

Dear Mr. Nowell;

I declare under penalty of perjury that to the best of my knowledge the information and/or recommendations contained in the attached report is/are true and correct.

If you have any questions or need additional information, please call:

Brian Whalen
Platinum Energy
30343 Canwood Street, Suite 200
Agoura Hills, Ca 91301
Tel: (818) 206-5704
Fax: (818) 206-5721
bwhalen@platinum-energy.net

Sincerely,

PLATINUM ENERGY

A handwritten signature in black ink, appearing to read "B Whalen", with a long horizontal flourish extending to the right.

BRIAN WHALEN

Attachment

Quarterly Summary Report, Fourth Quarter 2012

*76 Service Station No. 6277
15803 East 14th Street
San Leandro, California*

*Alameda County Health Care Services
Agency, Fuel Leak Case No. R00002969*

GeoTracker Global ID No. T0619718179

Antea Group Project No. I40256277

February 15, 2013

Prepared for:
Mr. Keith Nowell
Hazardous Materials Specialist
Alameda County Health Care
Services Agency
1131 Harbor Bay Parkway,
Suite 250
Alameda, CA 94502-6577

Prepared by:
Antea™ Group
11050 White Rock Road,
Suite 110
Rancho Cordova, CA 95670
+1 800 477 7411

Table of Contents

1.0	INTRODUCTION	1
1.1	Work Performed [Fourth Quarter 2012]	1
1.2	Work Proposed [First Quarter 2013].....	1
2.0	CURRENT PROJECT STATUS	1
2.1	Regulatory Correspondence.....	2
2.2	Remedial Activities.....	2
2.3	Groundwater Monitoring	2
2.3.1	Groundwater Flow Gradient and Direction	3
2.3.2	Groundwater Quality Data	3
2.3.3	Groundwater Contaminant Trends.....	4
2.3.4	Waste Disposal Summary	4
2.3.5	Quality Assurance / Quality Control	4
3.0	CONCLUSIONS AND RECOMMENDATIONS	5
4.0	REMARKS	6

Figures

Figure 1	Site Location Map
Figure 2	Site Plan
Figure 3	Groundwater Elevation Contour Map – November 14, 2012
Figure 4	Dissolved Phase TPHg Isoconcentration Map – November 14, 2012
Figure 5	Dissolved Phase MTBE Isoconcentration Map – November 14, 2012
Figure 6	Historical Groundwater Flow Directions

Tables

Table 1	Current Groundwater Gauging and Analytical Data
Table 2	Historical Groundwater Gauging and Analytical Data
Table 3	Historical Groundwater Gradient and Flow Direction Data

Appendices

Appendix A	Previous Investigation and Site History Summary
Appendix B	Antea Group Groundwater Sampling Procedures
Appendix C	Antea Group Groundwater Sampling Field Data Sheets
Appendix D	Certified Laboratory Analytical Report and Data Validation Form



1.0 INTRODUCTION

Antea™ Group is pleased to submit this *Quarterly Summary Report, Fourth Quarter 2012*, for the referenced site in San Leandro, CA (**Figure 1**). The subject site is currently an operating 76 service station located at 15803 East 14th Street in San Leandro, California (**Figure 1**). Station facilities include two, 12,000 gallon fuel underground storage tanks (USTs), a 520-gallon waste-oil UST, two dispenser islands, and a service station building, containing three service bays (**Figure 2**). A total of four groundwater monitoring wells are located at the site (**Figure 2**). Please refer to **Appendix A** for additional site information and for the history of environmental investigations and remedial actions.

This report summarizes the data obtained from the recent groundwater monitoring and sampling event conducted on November 14, 2012. Included herein are site figures and groundwater contaminant data tables and a discussion of trends. This report has received a technical review by Mr. Dennis Dettloff, California Professional Geologist No. 7480.

1.1 Work Performed [Fourth Quarter 2012]

1. Antea Group prepared and submitted the *Quarterly Summary Report, Third Quarter 2012*, dated October 19, 2012.
2. Antea Group conducted the fourth quarter 2012 groundwater monitoring and sampling event on November 14, 2012.

1.2 Work Proposed [First Quarter 2013]

1. Antea Group prepared and submitted the *Quarterly Summary Report, Fourth Quarter 2012* (contained herein) to the ACHCSA.
2. Antea Group will conduct the first quarter 2013 monitoring and sampling event.

2.0 CURRENT PROJECT STATUS

Current phase of project:	Quarterly Groundwater Monitoring
Local Oversight Program (LOP) – Lead agency for cleanup oversight:	Alameda County Health Care Services Agency Case No. RO0002969
Secondary agency(s):	None
Monitoring well gauging schedule:	Quarterly: MW-7 through MW-10
Monitoring well sampling schedule:	Quarterly: MW-7 through MW-10
Total number of monitoring/remediation wells:	Four
Range of well depths (total depth below ground surface, bgs):	Wells are set from 19 feet to 24 feet bgs.

Wells with historical measurable LNAPL (light non-aqueous phase liquid):	None
Historical depth to water range, in feet below top of casing (BTOC):	Min: 9.32 (MW-7, Q4 2012) Max: 10.86 (MW-10, Q4 2012)
Historical groundwater elevation range (ft) for wells MW-7 through MW-10:	Min: 25.04 (MW-7, Q3 2012) Max: 25.55 (MW-9, Q4 2011)
Local receptors:	See Appendix A
Current remediation technique	None

2.1 Regulatory Correspondence

Antea Group received a letter from the ACHCSA, dated November 16, 2012, indicating that the *Case Closure Petition* for this site had been reviewed and that the ACHCSA determined that the case meets the General and Media Specific criteria and is prepared to proceed with case closure and begin the public notification process and subsequent well decommissioning.

2.2 Remedial Activities

No remedial activities took place during the fourth quarter 2012.

2.3 Groundwater Monitoring

During the November 2012 groundwater monitoring and sampling event, four monitoring wells were gauged, purged, and sampled by Antea Group per standard sampling protocol (**Appendix B**). Copies of Antea Group's field data sheets are presented as **Appendix C**. The recent gauging and sampling data are summarized below and in **Table 1**.

Well gauging and sampling date:	November 14, 2012
Wells gauged:	MW-7 through MW-10
Wells sampled:	MW-7 through MW-10
Purge method:	3 well casing volumes via electric, submersible pump
Sample collection method:	Disposable bailers
Groundwater parameters measured (Appendix C):	Temperature, pH, Conductivity, Oxidation-reduction potential (ORP), Turbidity, Dissolved Oxygen (DO)
Wells with measurable LNAPL:	None
Current depth to water range (ft below top of casing (BTOC)):	Min: 9.32 (MW-7) Max: 10.86 (MW-10)
Current groundwater elevation range (ft):	Min: 25.14 (MW-10) Max: 25.28 (MW-7)
Change in water depths from previous event (average change for all gauged wells):	0.025 foot decrease

Groundwater flow direction and gradient in foot per foot (ft/ft):	West at 0.001 ft/ft
---	---------------------

2.3.1 Groundwater Flow Gradient and Direction

The fourth quarter 2012 groundwater monitoring and sampling event was performed by Antea Group on November 14, 2012. The average groundwater elevation was 25.22 feet above mean sea level. The average groundwater elevation increased 0.025 feet from the August 2012 event. Depth to groundwater in the site monitoring wells ranged from 9.32 feet (MW-7) to 10.86 feet (MW-10) BTOC during the current event. The groundwater flow direction and gradient were interpreted to be to the west at 0.001 ft/ft during the current event. A groundwater elevation contour map is presented on **Figure 3**.

2.3.2 Groundwater Quality Data

Groundwater samples collected during the fourth quarter 2012 monitoring and sampling event were submitted with chain-of-custody (COC) documentation to Kiff Analytical LLC (Kiff), a State of California National Environmental Laboratory Accreditation Program (NELAP) certified laboratory (Certification No. 08263CA). The complete analytical report and Antea Group's laboratory data validation checklist are presented as **Appendix D**. Groundwater samples were analyzed for the following:

- Total petroleum hydrocarbons as gasoline (TPHg), benzene, toluene, ethylbenzene, total xylenes (BTEX), methyl tertiary-butyl ether (MTBE), tertiary-butyl alcohol (TBA), di-isopropyl ether (DIPE), ethyl tertiary-butyl ether (ETBE), tertiary amyl-methyl ether (TAME), 1,2-dibromoethane (EDB), 1,2-dichloroethane (1,2-DCA), and ethanol by Environmental Protection Agency (EPA) Method 8260B.

Groundwater analytical results are presented in **Tables 1** (current) and **Table 2** (historical samples). The following ranges of contaminant concentrations were reported in the specified site wells groundwater samples collected on November 14, 2012. Only the reported contaminants are listed in the table below.

Constituents	Number of Reported Samples Above LRL of the Samples Collected	Minimum Reported Concentration, in µg/L (Sample ID)	Maximum Reported Concentration, in µg/L (Sample ID)
TPHg	4 of 4	160* (MW-10)	390* (MW-7)
Benzene	1 of 4	11 (MW-7)	11 (MW-7)
Toluene	1 of 4	0.68 (MW-7)	0.68 (MW-7)
Ethylbenzene	1 of 4	6.6 (MW-7)	6.6 (MW-7)
Total Xylenes	1 of 4	13 (MW-7)	13 (MW-7)
MTBE	4 of 4	2.8 (MW-9)	71 (MW-7)

Explanations:

µg/L = Micrograms per liter

LRL = Laboratory reporting limit

* TPHg result noted primary compounds not found in typical gasoline. Results are from tetrachloroethene (PCE) and trichloroethene (TCE).

2.3.3 Groundwater Contaminant Trends

During the fourth quarter 2012, analytical results from the samples collected from monitoring well MW-7 indicated that TPHg, benzene, toluene, ethylbenzene, total xylenes, and MTBE increased in concentration. Analytical results from the groundwater samples collected from monitoring well MW-8 indicated a decrease in TPHg and ethanol concentrations and an increase in MTBE concentration. Analytical results from the groundwater samples collected from monitoring well MW-9 indicated an increase in TPHg and MTBE concentrations and a decrease in ethanol concentration. Analytical results from the groundwater samples collected from monitoring wells MW-10 indicated an increase in TPHg and MTBE concentrations. Isoconcentration maps for TPHg and MTBE are presented on **Figures 4 and 5** and historical flow directions are presented on **Figure 6**.

2.3.4 Waste Disposal Summary

Water generated during well sampling and equipment cleaning was placed into a properly labeled 55-gallon Department of Transportation (DOT) approved steel drum and temporarily stored on-site. The waste was profiled using analytical results for the monitoring wells sampled during this groundwater sampling event. Subsequent to waste profiling, the waste will be transported off-site by Belshire Environmental Services to an approved disposal facility. Field procedures for purge water handling and disposal are included in **Attachment B**.

2.3.5 Quality Assurance / Quality Control

Antea Group's QA/QC measures included a detailed QA/QC data validation check on the Kiff analytical laboratory results for the November 2012 sampling event. Antea Group's laboratory data validation checklist and the Pace laboratory report are presented as **Appendix D**.

Laboratory QA/QC Performed:	Yes (validated by Antea Group)
Laboratory Data Qualifiers:	Yes (One*)
Are the data valid for their intended purpose?	Yes, the data are valid

* TPHg result noted primary compounds not found in typical gasoline. Results are from tetrachloroethene (PCE) and trichloroethene (TCE).

Based on a review of the laboratory's analytical report, including their QA/QC procedures and those implemented by Antea Group, we conclude that the laboratory data obtained during this groundwater sampling event are valid for their intended purpose.


3.0 CONCLUSIONS AND RECOMMENDATIONS

Based on the data obtained during site investigations conducted subsequent to the ATC investigation in 2007, when the environmental case was reopened and quarterly groundwater monitoring activities conducted since the installation of the four monitoring wells at the site, it appears that site conditions have remained consistent with conditions present when the site was granted closure in 2000. This appears to indicate that there has not been a new release since the site was granted closure. Therefore, Antea Group recommends that quarterly groundwater monitoring and sampling of the site monitoring wells be discontinued during SWRCB's review of the *Case Closure Petition* submitted by Antea Group on August 14, 2012.

4.0 REMARKS

The recommendations contained in this report represent Antea USA, Inc.'s professional opinions based upon the currently available information and are arrived at in accordance with currently accepted professional standards. This report is based upon a specific scope of work requested by the client. For any reports cited that were not generated by Delta or Antea Group, the data from those reports is used "as is" and is assumed to be accurate. Antea Group does not guarantee the accuracy of this data for the referenced work performed nor the inferences or conclusions stated in these reports. The contract between Antea USA, Inc. and its client outlines the scope of work, and only those tasks specifically authorized by that contract or outlined in this report were performed. This report is intended only for the use of Antea USA, Inc.'s client and anyone else specifically identified in writing by Antea USA, Inc. as a user of this report. Antea USA, Inc. will not and cannot be liable for unauthorized reliance by any other third party. Other than as contained in this paragraph, Antea USA, Inc. makes no express or implied warranty as to the contents of this report.

Prepared by:



Edward T. Weyrens, G.I.T.
Project Professional

Information, conclusions, and recommendations provided by Antea Group in this document regarding the site have been prepared under the supervision of and reviewed by the licensed professional whose signature appears below.

Licensed Approver:





2/15/13

Dennis S. Dettloff
Project Manager
California Registered Professional Geologist No. 7480

cc: GeoTracker (upload)

Figures

- Figure 1 Site Location Map
- Figure 2 Site Plan
- Figure 3 Groundwater Elevation Contour Map – November 14, 2012
- Figure 4 Dissolved Phase TPHg Isoconcentration Map – November 14, 2012
- Figure 5 Dissolved Phase MTBE Isoconcentration Map – November 14, 2012
- Figure 6 Historical Groundwater Flow Directions



SOURCE: USGS 7.5 MINUTE TOPOGRAPHIC MAP, SAN LEANDRO QUADRANGLE (1973)

FIGURE 1

SITE LOCATION MAP



76 SERVICE STATION NO. 6277
 15803 EAST 14TH STREET
 SAN LEANDRO, CALIFORNIA

PROJECT NO. I4256277	DRAWN BY JH 05/13/11
FILE NO. 6277-SiteLocator	PREPARED BY EW
REVISION NO.	REVIEWED BY



LEGEND:


- — — — — APPROXIMATE PROPERTY BOUNDARY
- x - x - FENCE
- - - - - FORMER EXCAVATION AREA
- ⊕ MONITORING WELL LOCATION (ANTEA GROUP 2011)



SITE PLAN ADAPTED FROM A SURVEY BY MORROW SURVEYING 2011 AND BASE MAPS DATED 1989 AND 2003 BY KEI AND 2007 BY ATC AND ASSOCIATES.


FIGURE 2
SITE PLAN

76 SERVICE STATION NO. 6277
15803 EAST 14TH STREET
SAN LEANDRO, CALIFORNIA

PROJECT NO. 14256277	PREPARED BY EW	DRAWN BY JH	
DATE 04/21/11	REVIEWED BY DD	FILE NAME 6277-SMS	


LEGEND:

- — — — — APPROXIMATE PROPERTY BOUNDARY
- x - x - FENCE
- - - - - FORMER EXCAVATION AREA
- ⊕ MONITORING WELL LOCATION (ANTEA GROUP 2011)
- (25.27') GROUNDWATER ELEVATION IN FEET ABOVE MEAN SEA LEVEL (ft/msl)
- 25.20' — GROUNDWATER ELEVATION CONTOUR LINE (ft/msl) — DASHED WHERE INFERRED (CONTOUR INTERVAL: 0.05 ft)
- ← 0.002 ft/ft GROUNDWATER FLOW DIRECTION AND HYDRAULIC GRADIENT (ft/ft)



SITE PLAN ADAPTED FROM A SURVEY BY MORROW SURVEYING 2011 AND BASE MAPS DATED 1989 AND 2003 BY KEI AND 2007 BY ATC AND ASSOCIATES.

FIGURE 3
GROUNDWATER ELEVATION CONTOUR MAP
 NOVEMBER 14, 2012
 76 SERVICE STATION NO. 6277
 15803 EAST 14TH STREET
 SAN LEANDRO, CALIFORNIA



PROJECT NO. 14256277	PREPARED BY EW	DRAWN BY JH
DATE 2/15/13	REVIEWED BY DD	FILE NAME 6277-SMS




LEGEND:

- — — — — APPROXIMATE PROPERTY BOUNDARY
- x - x - FENCE
- - - - - FORMER EXCAVATION AREA
- ⊕ MONITORING WELL LOCATION (ANTEA GROUP 2011)
- (160)* DISSOLVED PHASE TPHg ISOCONCENTRATION (µg/L)
- 50 — DISSOLVED PHASE TPHg ISOCONTOUR (µg/L)
-DASHED WHERE INFERRED


NOTES:

- TPHg = TOTAL PETROLEUM HYDROCARBONS AS GASOLINE
- µg/L = MICROGRAMS PER LITER
- * = PRIMARY COMPOUNDS NOT FOUND IN TYPICAL GASOLINE.



SITE PLAN ADAPTED FROM A SURVEY BY MORROW SURVEYING 2011 AND BASE MAPS DATED 1989 AND 2003 BY KEI AND 2007 BY ATC AND ASSOCIATES.

FIGURE 4
DISSOLVED PHASE TPHg ISOCONCENTRATION MAP
 NOVEMBER 14, 2012
 76 SERVICE STATION NO. 6277
 15803 EAST 14TH STREET
 SAN LEANDRO, CALIFORNIA





PROJECT NO. 14256277	PREPARED BY EW	DRAWN BY JH
DATE 2/15/13	REVIEWED BY DD	FILE NAME 6277-SMS



- LEGEND:**
- — — — — APPROXIMATE PROPERTY BOUNDARY
 - x - x - FENCE
 - - - - - FORMER EXCAVATION AREA
 - ⊕ MONITORING WELL LOCATION (ANTEA GROUP 2011)
 - (25) DISSOLVED PHASE MTBE ISOCONCENTRATION (μg/L)
 - 5.0 — DISSOLVED PHASE MTBE ISOCONTOUR (μg/L)
-DASHED WHERE INFERRED

- NOTES:**
- MTBE = METHYL TERTIARY BUTYL ETHER
 - μg/L = MICROGRAMS PER LITER
 - <0.50 = LESS THAN LABORATORY INDICATED REPORTING LIMITS




SITE PLAN ADAPTED FROM A SURVEY BY MORROW SURVEYING 2011 AND BASE MAPS DATED 1989 AND 2003 BY KEI AND 2007 BY ATC AND ASSOCIATES.

FIGURE 5
 DISSOLVED PHASE MTBE ISOCONCENTRATION MAP
 NOVEMBER 14, 2012
 76 SERVICE STATION NO. 6277
 15803 EAST 14TH STREET
 SAN LEANDRO, CALIFORNIA

PROJECT NO. 14256277	PREPARED BY EW	DRAWN BY JH
DATE 2/15/13	REVIEWED BY DD	FILE NAME 6277-SMS



Figure 6
Historical Groundwater Flow Directions
76 Service Station No. 6277
 15803 East 14th Street
 San leandro, California



Legend
 Concentric circles represent
 quarterly monitoring events
 Second Quarter 2011 through
 Fourth Quarter 2012 7 data
 points shown

■ Groundwater Flow Direction

Tables

Table 1	Current Groundwater Gauging and Analytical Data
Table 2	Historical Groundwater Gauging and Analytical Data
Table 3	Historical Groundwater Gradient and Flow Direction Data

**TABLE 1
CURRENT GROUND WATER GAUGING AND ANALYTICAL DATA
76 SERVICE STATION NO. 6277
15803 EAST 14TH STREET
SAN LEANDRO, CALIFORNIA**



Well I.D.	Date	GROUNDWATER GAUGING DATA				GROUNDWATER ANALYTICAL DATA												
		TOC Elevation (ft)	Depth to Water (ft)	LNAPL Thickness (ft)	Water Elevation* (ft)	TPHg (ug/L)	Benzene (ug/L)	Toluene (ug/L)	Ethylbenzene (ug/L)	Total Xylenes (ug/L)	MTBE (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	Ethanol (ug/L)	1,2-Dibromoethane (EDB) (ug/L)	1,2-Dichloroethane (ug/L)
MW-7	11/14/2012	34.60	9.32	NP	25.28	390*	11	0.68	6.6	13	71	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50
MW-8	11/14/2012	34.85	9.65	NP	25.20	190*	<0.50	<0.50	<0.50	<0.50	9.2	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50
MW-9	11/14/2012	35.09	9.82	NP	25.27	270*	<0.50	<0.50	<0.50	<0.50	2.8	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50
MW-10	11/14/2012	36.00	10.86	NP	25.14	160*	<0.50	<0.50	<0.50	<0.50	25	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50

Gauging Notes:
 TOC - Top of Casing
 ft - Feet
 NP - LNAPL not present
 LNAPL - Light non-aqueous phase liquid
 * - Corrected for LNAPL if present (assumes LNAPL specific gravity = 0.75)

Analytical Notes:
 < - Below the laboratory's indicated reporting limit
Bold - Above the laboratory's indicated reporting limit
 ug/L - micrograms/liter
 TPHg- Total petroleum hydrocarbons as gasoline
 MTBE- Methyl tertiary-butyl ether
 DIPE- Di-isopropyl ether
 ETBE- Ethyl tertiary-butyl ether
 TAME- Tertiary-amyl methyl ether
 TBA- Tertiary-butyl alcohol
 * - Primarily compounds not found in typical gasoline

**TABLE 2
HISTORICAL GROUNDWATER GAUGING AND ANALYTICAL DATA
76 SERVICE STATION NO. 6277
15803 EAST 14TH STREET
SAN LEANDRO, CALIFORNIA**



Well I.D.	Date	GROUNDWATER GAUGING DATA				GROUNDWATER ANALYTICAL DATA												
		TOC Elevation (ft)	Depth to Water (ft)	LNAPL Thickness (ft)	Water Elevation* (ft)	TPHg (ug/L)	Benzene (ug/L)	Toluene (ug/L)	Ethylbenzene (ug/L)	Total Xylenes (ug/L)	MTBE (ug/L)	DIPE (ug/L)	ETBE (ug/L)	TAME (ug/L)	TBA (ug/L)	Ethanol (ug/L)	1,2-Dibromoethane (EDB) (ug/L)	1,2-Dichloroethane (ug/L)
MW-7	4/18/2011	34.6	9.40	NP	25.20	2,420	22.4	12.4	11.3	449	152	<0.50	<0.50	<0.50	5.7	<250	<1.0	<1.0
	7/26/2011	34.6	9.43	NP	25.17	1,770	27.3	19	66.4	341	102	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	10/14/2011	34.6	9.37	NP	25.23	1,480	45.0	6.6	58.2	184	110	<0.50	<0.50	<0.50	23.0	<250	<1.0	<1.0
	2/22/2012	34.6	9.53	NP	25.07	655	14.9	1.7	16.3	38.8	112	<0.50	<0.50	<0.50	10.9	<250	<1.0	<1.0
	5/10/2012	34.6	9.43	NP	25.17	1,500	34.6	6.5	49.1	134	98.4	<0.50	<0.50	<0.50	14.5	<250	<1.0	<1.0
	8/14/2012	34.6	9.56	NP	25.04	270*	<0.50	<0.50	<0.50	0.72	63	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50
11/14/2012	34.6	9.32	NP	25.28	390*	11	0.68	6.6	13	71	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50	
MW-8	4/18/2011	34.85	9.40	NP	25.45	439	1.4	0.75	2.8	14.2	28.3	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	7/26/2011	34.85	9.42	NP	25.43	336 1n	4.0	<0.50	<0.50	<1.5	42.7	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	10/14/2011	34.85	9.35	NP	25.50	221 1n	2.2	<0.50	<0.50	<1.5	30.7	<0.50	<0.50	<0.50	5.5	<250	<1.0	<1.0
	2/22/2012	34.85	9.53	NP	25.32	308	<0.50	<0.50	<0.50	<1.5	45.9	<0.50	<0.50	<0.50	7.4	<250	<1.0	<1.0
	5/10/2012	34.85	9.50	NP	25.35	280 1n	1.8	<0.50	<0.50	<1.5	27.3	<0.50	<0.50	<0.50	11.7	<250	<1.0	<1.0
	8/14/2012	34.85	9.63	NP	25.22	260*	<0.50	<0.50	<0.50	<0.50	7.6	<0.50	<0.50	<0.50	<5.0	14	<0.50	<0.50
11/14/2012	34.85	9.65	NP	25.20	190*	<0.50	<0.50	<0.50	<0.50	9.2	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50	
MW-9	4/18/2011	35.09	9.55	NP	25.54	208 1n	<0.50	<0.50	<0.50	<1.5	1.6	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	7/26/2011	35.09	9.58	NP	25.51	176	<0.50	<0.50	<0.50	<1.5	1.7	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	10/14/2011	35.09	9.54	NP	25.55	154 1n	<0.50	<0.50	<0.50	<1.5	2.2	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	2/22/2012	35.09	9.81	NP	25.28	248	<0.50	<0.50	<0.50	<1.5	2.4	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	5/10/2012	35.09	9.65	NP	25.44	168 1n	<0.50	<0.50	<0.50	<1.5	1.8	<0.50	<0.50	<0.50	8.6	<250	<1.0	<1.0
	8/14/2012	35.09	9.74	NP	25.35	260*	<0.50	<0.50	<0.50	<0.50	2.6	<0.50	<0.50	<0.50	<5.0	5.4	<0.50	<0.50
11/14/2012	35.09	9.82	NP	25.27	270*	<0.50	<0.50	<0.50	<0.50	2.8	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50	
MW-10	4/18/2011	36	10.55	NP	25.45	513	<0.50	<0.50	6.9	40.0	14.9	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	7/26/2011	36	10.74	NP	25.26	169 1n	<0.50	<0.50	1.4	<1.5	22.9	<0.50	<0.50	<0.50	<5.0	<250	<1.0	<1.0
	10/14/2011	36	10.75	NP	25.25	141 1n	<0.50	<0.50	0.59	<1.5	29.7	<0.50	<0.50	<0.50	6.1	<250	<1.0	<1.0
	2/22/2012	36	10.78	NP	25.22	173	<0.50	<0.50	<0.50	<1.5	33.6	<0.50	<0.50	<0.50	5.3	<250	<1.0	<1.0
	5/10/2012	36	10.70	NP	25.30	118 1n	<0.50	<0.50	<0.50	<1.5	16.4	<0.50	<0.50	<0.50	6.4	<250	<1.0	<1.0
	8/14/2012	36	10.82	NP	25.18	150*	<0.50	<0.50	<0.50	<0.50	19	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50
11/14/2012	36	10.86	NP	25.14	160*	<0.50	<0.50	<0.50	<0.50	25	<0.50	<0.50	<0.50	<5.0	<5.0	<0.50	<0.50	

Gauging Notes:
 TOC - Top of Casing
 ft - Feet
 NP - LNAPL not present
 LNAPL - Light non-aqueous phase liquid
 * - Corrected for LNAPL if present (assumes LNAPL specific gravity = 0.75)

Analytical Notes:
 < - Below the laboratory's indicated reporting limit
Bold - Above the laboratory's indicated reporting limit
 ug/L - micrograms/liter
 TPHg- Total petroleum hydrocarbons as gasoline
 MTBE- Methyl tertiary-butyl ether
 DIPE- Di-isopropyl ether
 ETBE- Ethyl tertiary-butyl ether
 TAME- Tertiary-amyl methyl ether
 TBA- Tertiary-butyl alcohol
 1n - The TPHg result for this sample did not match the pattern of the laboratory standard for gasoline
 * - Primarily compounds not found in typical gasoline

TABLE 3
Historical Groundwater Gradient and Flow Direction Data

76 Service Station No. 6277
 15803 East 14th Street
 San Leandro, California

Site	Monitoring Date	Groundwater Gradient (feet per foot)	Groundwater Flow Direction															
			N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW
6277	04/18/11	0.003	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
	07/26/11	0.004	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0
	10/14/11	0.005	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	
	02/22/12	0.002	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	
	05/10/12	0.002	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	
	08/14/12	0.003	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	
	11/14/12	0.001	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	
0.003 Average			0	0	0	0	0	0	0	0	0	0	0	0	1	0	4	2

Explanation

NA = Not available

Number of Events = 6

Quarterly Summary Report, Fourth Quarter 2012
76 Service Station No. 6277
San Leandro, CA
Antea Group Project No. I40256277



Appendix A

Previous Investigation and Site History Summary

PREVIOUS INVESTIGATION AND SITE HISTORY SUMMARY

1969 - Reported site history indicates the site was first developed as a gas station from an empty lot in 1969.

March 1989 - Two 10,000-gallon gasoline USTs, one 550-gallon waste-oil UST, and the product piping were removed from the site during UST replacement activities. Kaprealian Engineering Inc. (KEI) advanced two exploratory borings designated as EB-1 and EB-2 at the site. The borings were advanced at the request of Alameda County to assess the possible presence of hydrocarbon impact to the soil in the vicinity of the proposed UST excavation.

The borings were advanced to depths of 10.5 feet below ground surface (bgs) and 13.5 feet bgs. Ground water was encountered in the borings at depths of 11 to 12 feet bgs. The analytical results of the soil samples were as follows:

- At a depth of 5 feet bgs soil samples analyzed for total petroleum hydrocarbons as gasoline (TPHg) ranged from below the laboratory's indicated reporting limit in boring EB-2 to 2.1 parts per million (ppm) in boring EB-1.
- At a depth of 10 feet bgs TPHg concentrations ranged from 200 ppm in boring EB-1 to 620 ppm in boring EB-2.

Based on results of this preliminary investigation, KEI recommended that the contractor excavate the existing UST excavation to a depth of approximately 13 feet bgs. Water was encountered in the fuel UST excavation at a depth of approximately 11 feet bgs, thus prohibiting the collection of any soil samples from immediately beneath the USTs.

Six soil samples, labeled SW1 through SW6, were collected from the sidewalls of the fuel UST pit at depths of approximately 1 foot above the water table; and one soil sample, labeled WO-1, was collected from beneath the waste-oil UST at a depth of about 10 feet bgs. Based on observations in the field, it was decided to excavate additional soil from three of the four excavation sidewalls.

March 14, 1989: Four trenches were installed to assess the limits of additional soil excavation needed. Four soil samples were then collected at depths of approximately 10 feet bgs. The soil analytical results were as follows:

- In the fuel UST excavation, TPHg concentrations ranged from 24 ppm to 150 ppm.
- A sample collected adjacent to the existing station building indicated that TPHg was present at a concentration of 3,500 ppm.
- The soil sample collected after excavating 2 feet of sidewall toward the station building indicated that TPHg was present at a concentration of 100 ppm.
- Soil sample (SW-2) contained TPHg at a concentration of 390 ppm.
- The soil sample collected from the waste-oil UST excavation (WO-1) contained total oil and grease (TOG) at a concentration of 280 ppm. A side wall sample, SW-7 collected after excavating 14 feet of sidewall contained TOG at a concentration of 41 ppm.

The analytical results of the water sample (W1) collected from the waste-oil/fuel UST excavation contained TPHg at a concentration of 19,000 parts per billion (ppb) and benzene at a concentration of 230 ppb.

March 23, 1989: KEI returned to the site for pipe trench soil sampling. Six soil samples, labeled P1 through P6, were collected from beneath the product lines at depths of approximately 3 to 3.5 feet below grade. The analytical results of the soil samples P1 through P6 collected from the pipe trenches indicated concentrations of TPHg ranging from 1.1 ppm to 6.8 ppm.

The fuel UST pit and the waste-oil UST pit were over-excavated in order to remove hydrocarbon-impacted soil. The majority of the hydrocarbon-impacted soil appeared to have been removed from the site, except for the capillary fringe in the vicinity of the former UST pit and the building.

May 24, 1989: Four two-inch diameter monitoring wells, MW-1 through MW-4 were installed at the site. The four wells were installed to depths ranging from 24.5 to 25 feet bgs. Ground water was encountered at depths ranging from 11 to 12 feet bgs during drilling.

July 1989: The monitoring and sampling program was initiated.

February 1990: Monitoring well MW-2 was destroyed on February 1 in preparation for additional soil excavation in the vicinity of this well. Soil was excavated to a depth of approximately 6 to 12 inches below the level of the groundwater, which was encountered at a depth of about 11.5 feet below grade. After additional excavation, four soil samples were collected from the sidewalls of the excavation, each approximately 6 to 12 inches above ground water. Soil excavation activities were terminated due to the close proximity of the former and new UST excavations and the site's property line.

The analytical results of three soil samples indicated that TPHg was present at concentrations ranging from 140 ppm to 1,100 ppm, while concentrations of total petroleum hydrocarbons as diesel (TPHd) ranged from below the laboratory's indicated reporting limits to 280 ppm. The analytical results also indicated Environmental Protection Agency (EPA) Method 8010 constituents and TOG from each of the four samples were below the laboratory's indicated reporting limits, except in sample SW11A which contained TOG at a concentration of 210 ppm.

Over-excavation in the vicinity of monitoring well MW-2 was completed in April of 1990. Monitoring well MW-2 was then replaced with a new monitoring well (MW-2A) in March 1991.

1991: Due to the regular occurrence of tetrachloroethene (PCE), trichloroethene (TCE) and 1,2-dichloroethane (1,2-DCA) in sampled groundwater, a review of records documenting historic site activities was performed in 1991 to assess whether there were any up-gradient sources contributing to the impacted groundwater at the site. The file review was conducted by KEI at the Regional Water Quality Control Board (RWQCB).

The review focused on three sites with monitoring wells located within a half mile of the station. The Okada property, located at 16109 Ashland Avenue, a former USA Petroleum station located at 15120 Hesperian Boulevard, and Kaufman and Broad, located at 1620 162nd Avenue, approximately 1,800 feet east-southeast of the site. The file review is outlined in Delta's *Addendum to Additional Site Assessment Work Plan*, dated April 3, 2009.

December 1992: A file review was conducted at the ACHCSA. Four sites with existing or former USTs were located in the vicinity of the site during the file review. These sites are as follows: 1.) Nayou Properties, 1500 Thrush Avenue; 2.) ABC Auto Repair, 15960 East 14th Street; 3. Petsas Property, 16035 East 14th Street, and; 4.) Speedee Oil Change, 15900 East 14th Street.

1991-1993: The California EPA, Department of Toxic Substances Control (DTSC), identified regional chlorinated solvent contamination of the upper aquifer in the San Leandro area.

1993: Based on the results of the site history research, site reconnaissance, and file review, and based upon the fact that no evidence of an on-site solvent source area in the vicinity of monitoring wells MW-3 and MW-4 was found, it was concluded that there was no likely on-site source of the halogenated volatile organic compound (HVOC) impact.

The potential of an off-site HVOC source is further supported by the fact that the highest HVOC concentrations have been reported in samples collected from monitoring wells MW-3 and MW-4, located on the up-gradient side of the site. HVOC concentrations reported in the groundwater samples collected from these monitoring wells are likely coming from a source (E.G. reaching sanitary sewer lines, etc.) up-gradient of the site.

March 1993: Monitoring wells MW-5 and MW-6 were installed on March 9, 1993. These wells were monitored monthly and sampled on a quarterly basis until 1996. Groundwater flow predominantly ranged from southwest to north during the course of the investigation. Chlorinated solvents have consistently been reported in up-gradient wells MW-3 and MW-4, and it appears that the chlorinated solvent impact at the site may be due to an unidentified source (or sources) located up-gradient of the site, or is part of a regional chlorinated solvent plume. The perimeter monitoring wells, MW-5 and MW-6, have historically shown a maximum concentration of 72 micrograms per liter ($\mu\text{g/L}$) of TPHg and below the laboratory's indicated reporting limits for benzene, toluene, ethylbenzene, and total xylenes (BTEX).

March 1997: An off-site investigation was conducted in March 1997 to assess any impacts in the down-gradient direction from monitoring well MW-1. Monitoring well MW-1 is the most down-gradient of the wells at the site and has historically contained the highest concentrations of petroleum hydrocarbons in groundwater throughout the duration of the site investigation.

Three direct push borings (EB-3, EB-4, and EB-5) were advanced through East 14th Street in a northerly transect from the site. The three borings were each advanced to total depths ranging from 11 to 15 feet below grade. Groundwater was encountered at depths ranging from 10.5 to 15 feet bgs during drilling. No reportable target compounds were identified in either soil or groundwater samples.

1998 – A *Case Closure Summary* was prepared by the Alameda County Environmental Protection Department. This document concluded that drinking water wells are not affected. It also documented the maximum contaminant concentrations – before and after cleanup as follows:

Contaminant	Soil (ppm)		Water (ppb)		
	Before	After	Before	After	
TPHg	3,500	1,100	19,000	510	
TPHd	ND	6.2	NA	NA	
Benzene	40	8	230	72	
Toluene	280	43	79	ND	
Xylenes	600	230	1,300	17	
Ethyl-benzene	100	37	ND	ND	
Methyl tert-butyl ether (MTBE)	NA	NA	NA	390	
TOG	7,700	1,300	NA	NA	
Heavy Metals	NA	NA	NA	NA	
Other HVOC	0.063	ND	TCE	4.4	ND
			PCE	110	950
			1,2-DCA	2.8	ND

The *Case Closure Summary* concluded that “there are no known municipal or residential water wells or surface water bodies within 750 feet down-gradient of the subject site that would be impacted by shallow groundwater from this site”.

December 2000: The ACHCSA issued a *Case Closure* letter dated December 26, 2000.

2003: Six groundwater monitoring wells (MW-1, MW-2A, and MW-3 through MW-6) destroyed. Groundwater was at 6-11 feet bgs.

September 2007: Six soil borings (ATC-1 through ATC-6) were advanced in the vicinity of the existing fuel and waste-oil USTs and dispensers on September 25 and 26, 2007. The borings were advanced to total depths of

approximately 20 feet bgs (ATC-2, ATC-3, ATC-4, and ATC-5) and 25 feet bgs (ATC-1 and ATC-6). Groundwater was initially encountered at depths ranging from 14 feet bgs to 24 feet bgs during drilling activities.

Groundwater samples were collected from each of the six borings. A duplicate groundwater sample designated as “Duplicate B-1” was collected from boring ATC-1. Photo ionization detector (PID) readings from the screened soil samples ranged from 1.4 ppm to 2,272 ppm. The analytical results from the ATC Investigation are outlined in Delta’s *Addendum to Additional Site Assessment Work Plan* dated April 3, 2009.

December 2009: Delta advanced six soil borings (B-1 through B-5, and B-7) to assess the extent of petroleum hydrocarbon impact to the soil and groundwater. The borings were advanced to total depths ranging from 24 to 32 feet bgs. First groundwater was encountered at depths ranging from 21 to 28.5 feet bgs during drilling activities.

Soil and groundwater samples were collected from each of the six borings. PID readings from the screened soil samples ranged from 0.2 ppm to 197 ppm. The analytical results indicated that TPHg was present in the soil at a maximum concentration of 603 mg/kg (B-1 at 12 feet) and in the groundwater at a maximum concentration of 2,110 µg/L (B-1). The analytical results from the December 2009 Investigation are outlined in Delta’s *Subsurface Soil and Groundwater Investigation Report* dated March 23, 2010.

April 5, 2011: Antea Group completed a site investigation consisting of the installation of four on-site monitoring wells (MW-7 through MW-10). The results of the investigation are presented in the *Site Investigation Report*, dated July 5, 2011.

SENSITIVE RECEPTORS

1991: The well survey performed by KEI focused on the area within a one-half mile radius of the subject site, and was based upon data obtained from the Alameda County Flood Control and Water Conservation District. The information revealed the presence of 15 producing wells designated as irrigation wells and had depths ranging from 20 to 440 feet bgs.

The Alameda County Flood Control and Water Conservation District records suggested that the status of many of the irrigation wells is unknown. In the 1991 survey, it was stated that “no producing wells that could possibly influence the groundwater flow direction at the subject site were located”. The closest irrigation well (148 feet deep) installed in 1949 was noted in the north corner of East 14th Street and 159th Avenue.

2008: This survey entailed a request to the California Department of Water Resources (DWR) office in Sacramento to provide well log records. DWR well log records were reviewed in order to assess the location of any water-supply wells in the vicinity of the subject site. Using the DWR well logs, a total of five wells had verifiable addresses within a half-mile radius of the site.

Stains and spills have been documented at the adjacent site to the east, SpeeDee Oil Change shop, located at 15900 East 14th Street, including staining from leaking automobiles, spills not cleaned up immediately, a spill migrating toward a storm drain inlet, a spill in the driveway not cleaned up, and a spill beneath the waste-oil UST was not appropriately addressed. Moreover, it is documented that solvents were used at this adjacent site in 1993 and based on that site history; it appears that solvents have been used at that site for decades.

Current Consultant: **Antea Group**

Quarterly Summary Report, Fourth Quarter 2012
76 Service Station No. 6277
San Leandro, CA
Antea Group Project No. I40256277



Appendix B

Antea Group Groundwater Sampling Procedures

FIELD METHODS AND PROCEDURES

The following section describes field procedures that are to be used by Antea Group personnel in the performance of the tasks involved with this project.

1.0 HEALTH AND SAFETY PLAN

Fieldwork performed by Antea Group and Antea Group's subcontractors at the site will be conducted according to guidelines established in a Site Health and Safety Plan (SHSP). The SHSP is a document that describes the hazards that may be encountered in the field and specifies protective equipment, work procedures and emergency information. A copy of the SHSP will be at the site and available for reference by appropriate parties during work at the site.

2.0 GROUNDWATER DEPTH ASSESSMENT

A water/product interface probe is used to assess the liquid-phase hydrocarbons (LPH) thickness, if present, and a water level indicator is used to measure the groundwater depth in monitoring wells that do not contain LPH. Depth to groundwater or LPH is measured from a datum point at the top of each monitoring well casing. The datum point is typically a notch cut in the north side of the casing edge. If a water level indicator is used, the tip is subjectively analyzed for LPH sheen.

3.0 SUBJECTIVE ANALYSIS OF GROUNDWATER

Prior to purging, a water sample is collected from the monitoring well for subjective assessment. The sample is retrieved by gently lowering a clean, disposable bailer to approximately one-half the bailer length past the air/liquid interface. The bailer is then retrieved and the sample contained within the bailer is examined for floating LPH and the appearance of a LPH sheen.

4.0 MONITORING WELL SAMPLING

Monitoring wells are purged using a pump or bailer until pH, temperature and conductivity of the purge water has stabilized and a minimum of three well volumes of water has been removed. The purge water is placed in 55-gallon drums and temporarily stored onsite pending evaluation of disposal options. If three well volumes cannot be removed in one-half an hour's time, the well is allowed to recharge to 80 percent of original level. After recharging, a groundwater sample is then removed from each of the wells using a pump or disposable bailer. The water sample is collected, labeled and handled according to the Quality Assurance Plan. Water generated during the monitoring event is disposed of according to the accepted regulatory method pertaining to the site.

5.0 QUALITY ASSURANCE PLAN

This section describes the field and analytical procedures to be followed by Antea Group throughout the investigation.

5.1 General Sample Collection and Handling Procedures

Proper collection and handling are essential to ensure the quality of a sample. Each sample will be collected in the appropriate container, preserved correctly for the intended analysis and stored, prior to analysis, for no longer than the maximum allowable holding time. Details on the procedures for collection and handling of soil samples from this project can be found in previous sections.

5.2 Sample Identification and Chain-of-Custody Procedures

Sample identification and chain-of-custody procedures ensure sample integrity and document sample possession from the time of collection to its ultimate disposal. Each sample container submitted for analysis will have a label affixed to identify the job number, sampler, date and time of sample collection and a sample number unique to that sample. During soil sampling, this information, in addition to a description of the sample, field measurements made, sampling methodology, names of on-site personnel and any other pertinent field observations will be recorded on the borehole log or in the field records.

Quarterly Summary Report, Fourth Quarter 2012
76 Service Station No. 6277
San Leandro, CA
Antea Group Project No. I40256277



Appendix C

Antea Group Groundwater Sampling Field Data Sheets

Antea Field Observations



Project: 256277 Weather: OVERCAST
Address: 15803 E. 14TH ST., SAN LEBANDO CA.
Date: S M T W T H F S 11/12
Recorded By: Jody Demello-Rice (916.402.3239)

Purpose: 4 Q GWMS

Notes: 0920 ARR ON SITE TALK TO OLIVIA @ 76 SCA.
CALL DENNIS D. THEN OPEN WELL CAPS.

0941 MW-9 OPENED

0943 MW-8 OPENED

0945 MW-10 OPENED

0947 MW-7 OPENED, THEN WENT TO PURCHASE ICE
FOR SAMPLES ACROSS THE STREET.

SET UP BOTTLES AND EQUIP FOR SAMPLE/GAUGING

1005 GAUGE MW-9, PURGE, 1030 SAMPLE - DECON.

1057 GAUGE MW-8, PURGE, 1118 SAMPLE - DECON.

1140 GAUGE MW-10, PURGE, 1205 SAMPLE - DECON.

1222 GAUGE MW-7, PURGE, 1244 SAMPLE - DECON.

TRANSFER INTO DROW AND CLEAN TRUCK, SECURE ICE
SAMPLES.

1255 CALL DENNIS D., LABEL DROW @ SW CORNER OF
76 SCA. BLDG. FINISH FN'S.

1310 DRT SITE TO LAB

Well-Head Inspection & Well Gauging Form

Antea Group Project No: I40256277

Site Address: 15803 East 14th Street, San Leandro CA

Weather: COOL OVERCAST

Field Technician: Jody Demello-Rice, Antea Group
 (Print Full Name & Company*)

Date: 11/4/12

Well Condition														
Sample Order	Field Point	Well Condition					Water in Well Box	Well Casing Dia.	Time Gauged	Depth to Water (Feet)	Depth to Bottom (Feet)	Depth to LNAPL (Feet)	LNAPL Thickness (Feet)	Comments
		Bolts	Seal	Lid Secure	Lock	Expanding Cap								
1	MW-9	G	G	G	G	G	N	2"	1005	20.40	23.80	NA		
2	MW-8	G	G	G	G	G	N	2"	1057	9.65	19.70	NA		
3	MW-10	G	G	G	G	G	N	2"	1140	10.86	19.70	NA		
4	MW-7	G	G	G	G	G	N	2"	1222	9.32	18.92	NA		

Notes: _____

**** All well caps opened at least 15 minutes or longer before gauging wells.**
CIRCLE ONE: YES or NO**



*Form provided by Antea Group

Note: Use G=good and P=poor for well condition

COP-ELT Groundwater Sampling Form

Facility Location:	15803 East 14th Str, San Leandro, CA 94577		
Station #:	140256277	Field Technician(s):	Jody DR
Well Identification:	MW-7	Date:	11/4/12
Well Diameter (in):	② 3 4 6 8	Depth to Water (DTW) (ft bgs):	9.32 @ 1222
Thickness of SPH (ft):	NA	Depth to SPH (ft bgs):	NA
Water Column Height(ft):	9.6	Total Depth of Well (ft bgs):	18.92

Purging Info and Calculations:

Purge Method:		Sample Method:	
Bailer (disposable) <input type="checkbox"/>	Bailer (Other) <input type="checkbox"/>	Bailer (disposable) <input checked="" type="checkbox"/>	Extraction port <input type="checkbox"/>
No Purge <input type="checkbox"/>	Submersible Pump <input checked="" type="checkbox"/>	Dedicated tubing <input type="checkbox"/>	
Vacuum Truck <input type="checkbox"/>	Peristaltic (low-flow) <input type="checkbox"/>	Other: _____	

Top of Screen: _____ If well is no-purge @XX feet, confirm water level is below the top of screen. Otherwise, well must be purged.

Water Column Height: _____ X Conversion Factor: _____ = Casing Volume (gal): 1.6

Casing Volume (gal): _____ X Specified Volumes: _____ = Calculated Purge (gal): 4.9

Water Column Height: _____ X (0.20 + DTW): _____ = DTW 80% Recharge (ft bgs): _____

Conversion Factors (gal/ft): 2" = 0.17 3" = 0.38 4" = 0.66 6" = 1.5 8" = 2.6 Other = radius² * 0.163

TORB

>1000

>1000

>1000

>1000

Time	Purge:					Water Characteristics:					Other:
	ORP	Temp (°C)	pH	Conductivity (mS)	DO mg/L	Val (Gal)					
Start Time: <u>1226</u>											
	<u>85.2</u>	<u>25.19</u>	<u>7.67</u>	<u>1252</u>	<u>0.47</u>	<u>0.25</u>					
	<u>78.6</u>	<u>21.53</u>	<u>7.58</u>	<u>1298</u>	<u>0.47</u>	<u>1.6</u>					
	<u>75.0</u>	<u>21.40</u>	<u>7.51</u>	<u>1291</u>	<u>0.42</u>	<u>3.2</u>					
	<u>74.1</u>	<u>21.37</u>	<u>7.50</u>	<u>1290</u>	<u>0.46</u>	<u>4.9</u>					
End Time: <u>1239</u>											

muddy

muddy

LT mud

"

Did Well dewater? Yes No Actual Purge volume (gal): 5

Other Comments: _____

Sample Info:

Sample ID: MW-7-2012130 Sample Date and Time: 11/4/12/1244

Sample Containers and Selected Analysis: Laboratory: KIFF

Purge Water Stored/Disposed of Where/How: Drum on-site

Signature: _____ Date: 11/4/12

QA Signature: _____ Date: _____



COP-ELT Groundwater Sampling Form

Facility Location: 15803 East 14th Str, San Leandro, CA 94577						
Station #: 140256277	Field Technician(s): Jody DR					
Well Identification: WW-9	Date: 11/4/12					
Well Diameter (in): 2 3 4 6 8	Depth to Water (DTW) (ft bgs): 982 @ P065					
Thickness of SPH (ft): NA	Depth to SPH (ft bgs): NA					
Water Column Height(ft): 14.00	Total Depth of Well (ft bgs): 23.90					
Purging Info and Calculations:						
Purge Method: <input type="checkbox"/> Bailer (disposable) <input type="checkbox"/> Bailer (Other) <input type="checkbox"/> No Purge <input type="checkbox"/> Vacuum Truck <input type="checkbox"/> Submersible Pump <input checked="" type="checkbox"/> Peristaltic (low-flow) <input type="checkbox"/> Other: _____						
Sample Method: <input checked="" type="checkbox"/> Bailer (disposable) <input type="checkbox"/> Extraction port <input type="checkbox"/> Dedicated tubing <input type="checkbox"/> Other: _____						
Top of Screen: _____ If well is no-purge @XX feet, confirm water level is below the top of screen. Otherwise, well must be purged.						
Water Column Height: 14.00	X Conversion Factor: 0.17 = Casing Volume (gal): 2.4					
Casing Volume (gal): 2.4	X Specified Volumes: 3 = Calculated Purge (gal): 7.2					
Water Column Height: _____	X (0.20 + DTW): _____ = DTW 80% Recharge (ft bgs): _____					
Conversion Factors (gal/ft): 2" = 0.17 3" = 0.38 4" = 0.66 6" = 1.5 8" = 2.6 Other = radius ² * 0.163						
Purge:						
Water Characteristics:						
Other:						
Time	ORP	Temp (°C)	pH	Conductivity (mS)	DO mg/L	Vol GAL
Start Time: 1010						
	189.1	19.61	6.06	1228	1.99	0.25
	139.4	20.73	6.63	1223	1.63	2.4
	111.7	20.71	6.84	1223	1.40	4.8
	97.2	20.70	7.00	1224	1.25	7.2
End Time: 1022						
Did Well dewater? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/>		Actual Purge volume (gal): 8 GAL				
Other Comments:						
Sample Info:						
Sample ID: NW-9-20121130	Sample Date and Time: 11/4/12/1030					
Sample Containers and Selected Analysis:	Laboratory: KIFF					
Purge Water Stored/Disposed of Where/How: Drum on site						
Signature: _____	Date: 11/4/12					
QA Signature: _____	Date: _____					

TURB
 > 1000
 > 1000
 > 1000
 > 1000

Muddy
 Muddy
 LT MUD
 LT MUD



COP-ELT Groundwater Sampling Form

Facility Location:	15803 East 14th Str, San Leandro, CA 94577		
Station #:	140256277	Field Technician(s):	Jody DR
Well Identification:	MW-8	Date:	11/4/12
Well Diameter (in):	2 3 4 6 8	Depth to Water (DTW) (ft bgs):	965 @ 1057
Thickness of SPH (ft):	NA	Depth to SPH (ft bgs):	NA
Water Column Height(ft):	10.05	Total Depth of Well (ft bgs):	1970

Purging Info and Calculations:

Purge Method:		Sample Method:	
Bailer (disposable) <input type="checkbox"/>	Bailer (Other) <input type="checkbox"/>	Bailer (disposable) <input checked="" type="checkbox"/>	Extraction port <input type="checkbox"/>
No Purge <input type="checkbox"/>	Submersible Pump <input checked="" type="checkbox"/>	Dedicated tubing <input type="checkbox"/>	
Vacuum Truck <input type="checkbox"/>	Peristaltic (low-flow) <input type="checkbox"/>		
Other: _____		Other: _____	

Top of Screen: _____ If well is no-purge @XX feet, confirm water level is below the top of screen. Otherwise, well must be purged.

Water Column Height: 10.05 X Conversion Factor: 0.17 = Casing Volume (gal): 1.7

Casing Volume (gal): 1.7 X Specified Volumes: 3 = Calculated Purge (gal): 5.2

Water Column Height: _____ X (0.20 + DTW): _____ = DTW 80% Recharge (ft bgs): _____

Conversion Factors (gal/ft): 2" = 0.17 3" = 0.38 4" = 0.66 6" = 1.5 8" = 2.6 Other = radius² * 0.163

Purge:	Water Characteristics:					Other:
---------------	-------------------------------	--	--	--	--	---------------

Time	ORP	Temp (°C)	pH	Conductivity (mS)	DO mg/L	VOL (GAL)
Start Time: <u>1102</u>						
	<u>50.3</u>	<u>22.3</u>	<u>7.64</u>	<u>1199</u>	<u>2.72</u>	<u>0.25</u>
	<u>44.9</u>	<u>22.45</u>	<u>7.62</u>	<u>1214</u>	<u>2.09</u>	<u>1.7</u>
	<u>41.4</u>	<u>22.30</u>	<u>7.59</u>	<u>1214</u>	<u>1.20</u>	<u>3.4</u>
	<u>35.7</u>	<u>22.30</u>	<u>7.57</u>	<u>1212</u>	<u>1.02</u>	<u>5.2</u>
End Time: <u>1114</u>						

Turb.
 >1000
 >1000
 >1000
 >1000

MWD
 LT MWD
 "
 "

Did Well dewater? Yes No Actual Purge volume (gal): 6.0

Other Comments: _____

Sample Info:

Sample ID:	MW-8-20121130	Sample Date and Time:	11/4/12/1108
Sample Containers and Selected Analysis:	Laboratory: <u>KIFF</u>		

Purge Water Stored/Disposed of Where/How: Drum on site

Signature: _____ Date: 11/4/12
 QA Signature: _____ Date: _____



COP-ELT Groundwater Sampling Form

Facility Location:	15803 East 14th Str, San Leandro, CA 94577		
Station #:	140256277	Field Technician(s):	Jody DR
Well Identification:	WW-10	Date:	11/4/12
Well Diameter (in):	② 3 4 6 8	Depth to Water (DTW) (ft bgs):	10.96 @ 1140
Thickness of SPH (ft):	NA	Depth to SPH (ft bgs):	NA
Water Column Height(ft):	8.84	Total Depth of Well (ft bgs):	19.70

Purging Info and Calculations:

Purge Method:		Sample Method:	
Bailer (disposable) <input type="checkbox"/>	Bailer (Other) <input type="checkbox"/>	Bailer (disposable) <input checked="" type="checkbox"/>	Extraction port <input type="checkbox"/>
No Purge <input type="checkbox"/>	Submersible Pump <input checked="" type="checkbox"/>	Dedicated tubing <input type="checkbox"/>	
Vacuum Truck <input type="checkbox"/>	Peristaltic (low-flow) <input type="checkbox"/>		
Other: _____		Other: _____	

Top of Screen: _____ If well is no-purge @XX feet, confirm water level is below the top of screen. Otherwise, well must be purged.

Water Column Height: 8.84 X Conversion Factor: 1.7 = Casing Volume (gal): 1.5

Casing Volume (gal): 1.5 X Specified Volumes: 3 = Calculated Purge (gal): 4.5

Water Column Height: _____ X (0.20 + DTW): _____ = DTW 80% Recharge (ft bgs): _____

Conversion Factors (gal/ft): 2" = 0.17 3" = 0.38 4" = 0.66 6" = 1.5 8" = 2.6 Other = radius² * 0.163

Purge:

Time	Water Characteristics:					Other:
	ORP	Temp (°C)	pH	Conductivity (mS)	DO mg/L	
Start Time: <u>1148</u>						<u>Vol(GAL)</u>
<u>>1000</u>	<u>82.2</u>	<u>25.30</u>	<u>7.71</u>	<u>1275</u>	<u>0.65</u>	<u>0.25</u>
<u>71000</u>	<u>77.5</u>	<u>21.43</u>	<u>7.64</u>	<u>1313</u>	<u>0.60</u>	<u>1.5</u>
<u>>1000</u>	<u>66.1</u>	<u>21.95</u>	<u>7.53</u>	<u>1321</u>	<u>0.82</u>	<u>3.0</u>
<u>>1000</u>	<u>56.7</u>	<u>21.47</u>	<u>7.46</u>	<u>1330</u>	<u>0.94</u>	<u>4.5</u>
End Time: <u>1200</u>						

Did Well dewater? Yes No Actual Purge volume (gal): ~~1.5~~ 4.5 5 GAL

Other Comments: _____

Sample Info:

Sample ID:	WW-10-20121130	Sample Date and Time:	11/4/12/1205
Sample Containers and Selected Analysis:	Laboratory: <u>KFF</u>		

Purge Water Stored/Disposed of Where/How: Drum outside

Signature: _____ Date: 11/4/12

QA Signature: _____ Date: _____

TOPS

>1000
71000
>1000
>1000

WDD
LT WDD
"
"





COP ELT CHAIN-OF-CUSTODY / Analytical Request Document

The Chain-of-Custody is a LEGAL DOCUMENT. All relevant fields must be completed and accurate.

4Q12 GW Event

Required Lab Information:			Required Project Information:			Required Invoice Information:					
Lab Name:	Kiff Analytical		Site ID #:	256277	Task:	WG_Q_201211		Send Invoice to:	Sandy Hayes		
Address:	2795 Second Street #300		AnteaGrp proj#:	I40256277		Address:	11050 White Rock Road Suite 110		Turn around time (days)		10
Davis, CA 95618			Site Address:	15803 East 14th Street		City/State:	Rancho Cordova CA 95670		Phone #:	916-503-1267	
Lab PM:	Scott Forbes		City:	San Leandro		State:	CA		Reimbursement project?	<input type="checkbox"/>	
Phone/Fax:	P: 530-297-4800 F: 530-297-4808		AG PM Name:	Dennis Dettloff		Send EDD to:	copeltdata@intelligentehs.com		Non-reimbursement project?	<input checked="" type="checkbox"/>	
Lab PM email:	SForbes@kiffanalytical.com		Phone/Fax:	P: 916-503-1261 F: 916-638-8385		CC Hardcopy report to:			Mark one	NJ Reduced Deliverable Package? <input type="checkbox"/>	
Applicable Lab Quote #:			AG PM Email:	Dennis.Dettloff@anteagroup.com		CC Hardcopy report to:			MA MCP Cert?	<input type="checkbox"/>	
									CT RCP Cert?	<input type="checkbox"/>	
									Mark One	<input type="checkbox"/>	
									Lab Project ID (lab use)		

ITEM #	SAMPLE ID One Character per box. (A-Z, 0-9 / -) Samples IDs MUST BE UNIQUE	Valid Matrix Codes MATRIX DRINKING WATER WP WATER W GROUND WATER WG SURFACE WATER WS WATER WTR WL WASTE WATER WW WATER GC WQ FREE PRODUCT LP SLUDGE SL SOIL SO RINSEATE SW WH OIL OL OTHER TA WIRE AW AMBIENT AIR AA SWP AND SA GSL GAS GS	MATRIX CODE	SAMPLE TYPE G-GRAB D-COMP	SAMPLE DATE	SAMPLE TIME	# OF CONTAINERS	FIELD FILTERED? (Y/N)	Preservatives									Requested Analyses	Comments/Lab Sample I.D.					
									Unpreserved	H ₂ SO ₄	HNO ₃	HCl	NaOH	Na ₂ S ₂ O ₃	Methanol	Other	TPH as Gasoline 8260			8260/MET/BECD/CK	8260 Ethanol	8260 1,2-DCA & EDB		
1	MW-10_20121130		WG		11/4/12	1205	3	N											X	X	X	X	7 Oxy's = DIPE, TBA, TAME, ETBE, 1-2DCA, EDB, and Ethanol	
2	MW-7_20121130		WG		}	1244	3	N											X	X	X	X		
3	MW-8_20121130		WG			1118	3	N												X	X	X		X
4	MW-9_20121130		WG			1030	3	N												X	X	X		X

Additional Comments/Special Instructions:			RELINQUISHED BY / AFFILIATION		DATE	TIME	ACCEPTED BY / AFFILIATION		DATE	TIME	Sample Receipt Conditions				
			<i>(Antea)</i>		11/4/12	1445	<i>(Antea)</i>						Y/N	Y/N	Y/N
													Y/N	Y/N	Y/N
													Y/N	Y/N	Y/N
Global ID: T0619718179			SHIPPING METHOD: (mark as appropriate)			SAMPLER NAME AND SIGNATURE									
			UPS COURIER FEDEX	PRINT Name of SAMPLER:											
			US MAIL	SIGNATURE of SAMPLER:		<i>(Signature)</i>		DATE Signed	11/4/12	TIME	1445	Temp in °C	Samples on Ice?	Sample intact?	Trip Blank?

Quarterly Summary Report, Fourth Quarter 2012
76 Service Station No. 6277
San Leandro, CA
Antea Group Project No. I40256277



Appendix D

Certified Laboratory Analytical Report and Data Validation Form

Is the Data Set Valid?

(circle)

Yes / No

Preservation Temperature

(if Known): 2.6 °C

Antea™ Group Laboratory Data Validation Sheet

Project/Client: 76 Service Station No. 6277 / COP-ELT

Project #: I40256277

Date of Validation: 2-13-13 **Date of Analysis:** 11-17-12

Sample Date: 11-14-12 **Completed By:** ETW

Signature: [Signature]

Circle
or
Highlight

 Yes / No

(below)

Analytical Lab Used and Report # (if any): Kiff #: 83247

1. Were the analyses the ones requested?
2. Do the sample number(s) on the chain-of-custody (COC) match the one(s) that appear on the laboratory data sheet?
3. Were samples prepared (extracted, filtered, etc.) within EPA holding times?
4. Once prepared/extracted, were the samples analyzed within the EPA holding times?
5. Were Laboratory blanks performed, if so, were they non-detect?
6. Are the units correct? (i.e., soil samples in mg/kg or ug/g, water samples mg/L, ug/L, and air samples in volume mg/m³, etc.)
7. Were appropriate Matrix Spike (MS) and Matrix Spike Duplicate (MSD) samples included in the laboratory batch sample?
8. In lieu of MS/ MSD, were surrogate spike (SS) or surrogate spike duplicate (SSD) samples included in the laboratory batch samples?
9. Were MS/ MSD (or SS/SSD) within the acceptable range of % recovery (i.e., approximately 80-120%, depending on the analyte)?
10. Were MS/MSD (or SS/SSD) values used to calculate Relative Percent Difference (RPD)?
11. Were Relative Percent Difference values within the acceptable range (i.e. ±25%)?

Yes / No

Yes / No

Yes / No

Yes / No

Yes / No

Yes / No

Yes / No

Yes / No

Yes / No

Yes / No

If any answer is no, explain why and what corrective action was taken (use additional sheet(s), as necessary:

Notes: THH₂ results for MW-7, MW-8, MW-9, and MW-10 are primarily compounds not found in typical gasoline

Laboratory Results


Dennis Dettloff
Antea Group
11050 White Rock Rd. Suite 110
Rancho Cordova, CA 95670

Subject : 4 Water Samples
Project Name : 256277
Project Number : I40256277

Dear Mr. Dettloff,

Chemical analysis of the samples referenced above has been completed. Summaries of the data are contained on the following pages. Sample(s) were received under documented chain-of-custody. US EPA protocols for sample storage and preservation were followed. Testing procedures comply with the 2003 NELAC and TNI 2009 standards. Laboratory results relate only to the samples tested. This report may be freely reproduced in full, but may only be reproduced in part with the express permission of Kiff Analytical, LLC. Kiff Analytical, LLC is certified by the State of California under the National Environmental Laboratory Accreditation Program (NELAP), lab # 08263CA. If you have any questions regarding procedures or results, please call me at 530-297-4800.

Sincerely,



Troy Turpen



Report Number : 83247

Date : 11/19/12

Analysis Summary

Attention : Dennis Dettloff
 Antea Group
 11050 White Rock Rd. Suite 110
 Rancho Cordova, CA 95670

Project Name :256277
 Project Number : I40256277

Sample Name			MW-10_20121130	MW-7_20121130	MW-8_20121130	MW-9_20121130				
Sample Date			11/14/12		11/14/12					
Analyte	Method	Units	MRL	Results	MRL	Results	MRL	Results	MRL	Results
Benzene	EPA 8260B	ug/L	0.50	ND	0.50	11	0.50	ND	0.50	ND
Ethylbenzene	EPA 8260B	ug/L	0.50	ND	0.50	6.6	0.50	ND	0.50	ND
Toluene	EPA 8260B	ug/L	0.50	ND	0.50	0.68	0.50	ND	0.50	ND
Total Xylenes	EPA 8260B	ug/L	0.50	ND	0.50	13	0.50	ND	0.50	ND
Diisopropyl ether (DIPE)	EPA 8260B	ug/L	0.50	ND	0.50	ND	0.50	ND	0.50	ND
Ethanol	EPA 8260B	ug/L	5.0	ND	5.0	ND	5.0	ND	5.0	ND
Ethyl-t-butyl ether (ETBE)	EPA 8260B	ug/L	0.50	ND	0.50	ND	0.50	ND	0.50	ND
Methyl-t-butyl ether (MTBE)	EPA 8260B	ug/L	0.50	25	0.50	71	0.50	9.2	0.50	2.8
Tert-Butanol	EPA 8260B	ug/L	5.0	ND	5.0	ND	5.0	ND	5.0	ND
Tert-amyl methyl ether (TAME)	EPA 8260B	ug/L	0.50	ND	0.50	ND	0.50	ND	0.50	ND
TPH as Gasoline	EPA 8260B	ug/L	50	160	50	390	50	190	50	270
1,2-Dibromoethane	EPA 8260B	ug/L	0.50	ND	0.50	ND	0.50	ND	0.50	ND
1,2-Dichloroethane	EPA 8260B	ug/L	0.50	ND	0.50	ND	0.50	ND	0.50	ND
1,2-Dichloroethane-d4 (Surr)	EPA 8260B	%		108		103		105		107
Toluene - d8 (Surr)	EPA 8260B	%		100		100		101		100

MRL = Method Reporting Limit

ND = Not Detected

Project Name : **256277**

Project Number : **I40256277**

Sample : **MW-10_20121130**

Matrix : Water

Lab Number : 83247-01

Sample Date :11/14/12

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
Toluene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
Methyl-t-butyl ether (MTBE)	25	0.50	ug/L	EPA 8260B	11/17/12 00:04
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 00:04
Ethanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 00:04
TPH as Gasoline	160	50	ug/L	EPA 8260B	11/17/12 00:04
(Note: Primarily compounds not found in typical Gasoline)					
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 00:04
1,2-Dichloroethane-d4 (Surr)	108		% Recovery	EPA 8260B	11/17/12 00:04
Toluene - d8 (Surr)	100		% Recovery	EPA 8260B	11/17/12 00:04

Project Name : **256277**

Project Number : **I40256277**

Sample : **MW-7_20121130**

Matrix : Water

Lab Number : 83247-02

Sample Date :11/14/12

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	11	0.50	ug/L	EPA 8260B	11/17/12 04:47
Toluene	0.68	0.50	ug/L	EPA 8260B	11/17/12 04:47
Ethylbenzene	6.6	0.50	ug/L	EPA 8260B	11/17/12 04:47
Total Xylenes	13	0.50	ug/L	EPA 8260B	11/17/12 04:47
Methyl-t-butyl ether (MTBE)	71	0.50	ug/L	EPA 8260B	11/17/12 04:47
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 04:47
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 04:47
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 04:47
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 04:47
Ethanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 04:47
TPH as Gasoline	390	50	ug/L	EPA 8260B	11/17/12 04:47
(Note: Primarily compounds not found in typical Gasoline)					
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 04:47
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 04:47
1,2-Dichloroethane-d4 (Surr)	103		% Recovery	EPA 8260B	11/17/12 04:47
Toluene - d8 (Surr)	100		% Recovery	EPA 8260B	11/17/12 04:47

Project Name : **256277**

Project Number : **I40256277**

Sample : **MW-8_20121130**

Matrix : Water

Lab Number : 83247-03

Sample Date :11/14/12

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
Toluene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
Methyl-t-butyl ether (MTBE)	9.2	0.50	ug/L	EPA 8260B	11/17/12 05:27
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 05:27
Ethanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 05:27
TPH as Gasoline	190	50	ug/L	EPA 8260B	11/17/12 05:27
(Note: Primarily compounds not found in typical Gasoline)					
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 05:27
1,2-Dichloroethane-d4 (Surr)	105		% Recovery	EPA 8260B	11/17/12 05:27
Toluene - d8 (Surr)	101		% Recovery	EPA 8260B	11/17/12 05:27

Project Name : **256277**

Project Number : **I40256277**

Sample : **MW-9_20121130**

Matrix : Water

Lab Number : 83247-04

Sample Date :11/14/12

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date/Time Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
Toluene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
Methyl-t-butyl ether (MTBE)	2.8	0.50	ug/L	EPA 8260B	11/17/12 06:10
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 06:10
Ethanol	< 5.0	5.0	ug/L	EPA 8260B	11/17/12 06:10
TPH as Gasoline	270	50	ug/L	EPA 8260B	11/17/12 06:10
(Note: Primarily compounds not found in typical Gasoline)					
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	11/17/12 06:10
1,2-Dichloroethane-d4 (Surr)	107		% Recovery	EPA 8260B	11/17/12 06:10
Toluene - d8 (Surr)	100		% Recovery	EPA 8260B	11/17/12 06:10

QC Report : Method Blank Data

Project Name : **256277**

Project Number : **I40256277**

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
Benzene	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
Ethylbenzene	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
Toluene	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
Total Xylenes	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
Diisopropyl ether (DIPE)	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
Ethanol	< 5.0	5.0	ug/L	EPA 8260B	11/16/12
Ethyl-t-butyl ether (ETBE)	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
Methyl-t-butyl ether (MTBE)	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
Tert-Butanol	< 5.0	5.0	ug/L	EPA 8260B	11/16/12
Tert-amyl methyl ether (TAME)	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
TPH as Gasoline	< 50	50	ug/L	EPA 8260B	11/16/12
1,2-Dibromoethane	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
1,2-Dichloroethane	< 0.50	0.50	ug/L	EPA 8260B	11/16/12
1,2-Dichloroethane-d4 (Surr)	101		%	EPA 8260B	11/16/12
Toluene - d8 (Surr)	100		%	EPA 8260B	11/16/12

Parameter	Measured Value	Method Reporting Limit	Units	Analysis Method	Date Analyzed
-----------	----------------	------------------------	-------	-----------------	---------------

QC Report : Matrix Spike/ Matrix Spike Duplicate

Project Name : 256277

Project Number : I40256277

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
1,2-Dibromoethane	83247-01	<0.50	40.0	39.6	43.8	41.3	ug/L	EPA 8260B	11/17/12	109	104	4.89	80-120	25
1,2-Dichloroethane	83247-01	<0.50	40.0	39.6	44.8	44.3	ug/L	EPA 8260B	11/17/12	112	112	0.147	75.7-122	25
Benzene	83247-01	<0.50	40.0	39.6	39.2	38.9	ug/L	EPA 8260B	11/17/12	98.0	98.2	0.225	80-120	25
Diisopropyl ether	83247-01	<0.50	39.4	39.0	41.6	41.1	ug/L	EPA 8260B	11/17/12	106	105	0.215	80-120	25
Ethanol	83247-01	<5.0	99.6	98.6	93.4	107	ug/L	EPA 8260B	11/17/12	93.8	109	14.8	55.1-159	25
Ethyl-tert-butyl ether	83247-01	<0.50	40.6	40.2	44.3	44.7	ug/L	EPA 8260B	11/17/12	109	111	2.01	76.5-120	25
Ethylbenzene	83247-01	<0.50	40.0	39.6	39.7	38.6	ug/L	EPA 8260B	11/17/12	99.2	97.6	1.67	80-120	25
Methyl-t-butyl ether	83247-01	25	40.1	39.7	72.1	69.0	ug/L	EPA 8260B	11/17/12	118	111	5.87	69.7-121	25
P + M Xylene	83247-01	<0.50	40.0	39.6	36.9	36.0	ug/L	EPA 8260B	11/17/12	92.2	90.9	1.41	76.8-120	25
Tert-Butanol	83247-01	<5.0	201	199	196	196	ug/L	EPA 8260B	11/17/12	97.3	98.4	1.12	80-120	25

QC Report : Matrix Spike/ Matrix Spike Duplicate

Project Name : **256277**Project Number : **I40256277**

Parameter	Spiked Sample	Sample Value	Spike Level	Spike Dup. Level	Spiked Sample Value	Duplicate Spiked Sample Value	Units	Analysis Method	Date Analyzed	Spiked Sample Percent Recov.	Duplicate Spiked Sample Percent Recov.	Relative Percent Diff.	Spiked Sample Percent Recov. Limit	Relative Percent Diff. Limit
Tert-amyl-methyl ether	83247-01	<0.50	40.4	40.0	43.2	44.4	ug/L	EPA 8260B	11/17/12	107	111	3.67	78.9-120	25
Toluene	83247-01	<0.50	40.0	39.6	39.3	38.4	ug/L	EPA 8260B	11/17/12	98.3	96.9	1.43	80-120	25

QC Report : Laboratory Control Sample (LCS)Project Name : **256277**Project Number : **I40256277**

Parameter	Spike Level	Units	Analysis Method	Date Analyzed	LCS Percent Recov.	LCS Percent Recov. Limit
1,2-Dibromoethane	40.0	ug/L	EPA 8260B	11/16/12	101	80-120
1,2-Dichloroethane	40.0	ug/L	EPA 8260B	11/16/12	109	75.7-122
Benzene	40.0	ug/L	EPA 8260B	11/16/12	99.7	80-120
Diisopropyl ether	39.4	ug/L	EPA 8260B	11/16/12	106	80-120
Ethanol	99.6	ug/L	EPA 8260B	11/16/12	102	55.1-159
Ethyl-tert-butyl ether	40.6	ug/L	EPA 8260B	11/16/12	108	76.5-120
Ethylbenzene	40.0	ug/L	EPA 8260B	11/16/12	101	80-120
Methyl-t-butyl ether	40.1	ug/L	EPA 8260B	11/16/12	102	69.7-121
P + M Xylene	40.0	ug/L	EPA 8260B	11/16/12	94.5	76.8-120
Tert-Butanol	201	ug/L	EPA 8260B	11/16/12	96.6	80-120
Tert-amyl-methyl ether	40.4	ug/L	EPA 8260B	11/16/12	104	78.9-120
Toluene	40.0	ug/L	EPA 8260B	11/16/12	99.0	80-120

